



UGC GENIE

CODEBASE SETUP GUIDE

Run UGC Genie locally or as a safe public demo

- Repository: <https://github.com/harshith-vaddiparth/UGC-dashboard>
- Live demo: <https://ugc-dashboard-jade.vercel.app>
- This guide separates real local Higgsfield execution from public-demo deployment.

1. PREREQUISITES

What you need

- Node.js 20+ and pnpm 10+.
- Higgsfield CLI authenticated locally for real generation.
- A standard OpenAI API key for prompt improvement.
- Git and an optional Vercel account for public deployment.

OPERATOR CHECK

Stop if the displayed runtime mode does not match the environment you intended to deploy. Correct boundaries matter more than a successful build.

2. INSTALL

Clone and boot

- `git clone https://github.com/harshith-vaddiparth/UGC-dashboard.git`
- `cd UGC-dashboard`
- `pnpm install`
- `cp .env.example .env.local`
- `pnpm dev -> open http://localhost:3000`

OPERATOR CHECK

Stop if the displayed runtime mode does not match the environment you intended to deploy. Correct boundaries matter more than a successful build.

3. LOCAL PROVIDERS

Enable real generation

- Run higgsfield auth login.
- Verify with higgsfield account status.
- Keep UGC_RUNTIME_MODE=local-cli.
- Add OPENAI_API_KEY for Improve prompt.
- Never commit .env.local or CLI session data.

OPERATOR CHECK

Stop if the displayed runtime mode does not match the environment you intended to deploy. Correct boundaries matter more than a successful build.

4. PUBLIC DEMO

Deploy safely to Vercel

- Set UGC_RUNTIME_MODE=public-demo.
- Set NEXT_PUBLIC_UGC_RUNTIME_MODE=public-demo.
- Do not copy the local Higgsfield session to cloud infrastructure.
- The public action becomes Run demo and consumes no credits.
- Deploy with vercel --prod or connect the GitHub repository.

OPERATOR CHECK

Stop if the displayed runtime mode does not match the environment you intended to deploy. Correct boundaries matter more than a successful build.

5. VERIFY

Prove the deployment works

- `pnpm lint`
- `pnpm build`
- Confirm the account card says Public demo.
- Confirm a forged `demo=false` request is still converted to demo mode.
- Run the complete demo and verify 100%, video playback, and download.

OPERATOR CHECK

Stop if the displayed runtime mode does not match the environment you intended to deploy. Correct boundaries matter more than a successful build.

6. PRODUCTIONIZE

What to replace before multi-user launch

- CLI runner -> direct Higgsfield API adapter.
- Local JSON -> PostgreSQL.
- Local uploads -> object storage.
- In-request execution -> durable queue and workers.
- Add authentication, organizations, authorization, rate limits, and spending controls.

OPERATOR CHECK

Stop if the displayed runtime mode does not match the environment you intended to deploy. Correct boundaries matter more than a successful build.

REFERENCE

Files and links

- Workflow UI: `components/workflow/workflow-studio.tsx`
- Executor: `lib/workflow/executor.ts`
- Higgsfield adapter: `lib/higgsfield/runner.ts`
- Public boundary: `app/api/workflows/route.ts`
- LinkedIn: <https://www.linkedin.com/in/harshith-vaddiparthy/>
- MIT licensed - fork, adapt, and commercialize under the license terms.

OPERATOR CHECK

Stop if the displayed runtime mode does not match the environment you intended to deploy. Correct boundaries matter more than a successful build.