


Section 11: Spring MVC - Building Spring Web Apps

0 / 8 | 26min

➤ Overview:


- Framework for building web applications in Java
- Based on Model-View-Controller design pattern.
- Leverages features of the core Spring Framework (IoC, DI).



Basically, we have an incoming request coming from a browser and it will encounter the Spring MVC front controller and it will actually delegate the request of to a Controller code that contains the business logic and then it will create a model and send back to the Front Controller and then it will pass the model to our View Template and View Template is like a JSP page or HTML page which will render the data and give as a response to the browser.

➤ Spring MVC Behind the Scenes:

Components of a Spring MVC Application



Spring MVC Front Controller:


- Front Controller known as *DispatcherServlet*.
 - Part of the Spring Framework.
 - Already developed by Spring Dev Team

This Front Controller will actually delegate the requests coming from browser to some other objects in our system.

- So as a developer we will create
 - **M**odel Objects
 - **V**iew Templates (like JSP page)
 - **C**ontroller Classes (Actual business logic)

Controller:


- Code created by developer
- Contains your business logic
 - Handle the request
 - Store/retrieve data (db, web service...)
 - Place data in model
- Send to appropriate view template



View Template:

Spring MVC is very flexible and there is many view template types. The model data comes to our JSP page and view template will read that data and display it. Other view Templates supported are Thymeleaf, Groovy, Velocity, Freemarker, etc.

- Spring MVC is flexible
- Supports many view templates
- Most common is **JSP + JSTL**
- Developer creates a page
- Displays data



JSP: Java Server Pages
JSTL: JSP Standard Tag Library

Development Environment Checkpoint:

We should have installed:

- ✓ Apache Tomcat
- ✓ Eclipse
- ✓ Connected Eclipse to Tomcat

Tomcat Version

- New version of Tomcat 10 was released to support Jakarta EE 9
 - Renamed packages: `javax.*` to `jakarta.*`
 - This is a breaking change for Java EE apps
- Spring 5 currently does not support the new package renaming Jakarta EE 9
- As a result, Spring 5 does not currently work on Tomcat 10
- Use **Tomcat 9** for your Spring 5 apps

February 2021

Spring Team is aware of this issue. You can track the status
<https://github.com/spring-projects/spring-framework/issues/25354>

Spring MVC Configuration:

Part 1: Add Configurations to file: WEB-INF/web.xml

- Configure Spring MVC Dispatcher Servlet.

Here we will add an entry for Spring Dispatcher Servlet or the Front Controller within `<servlet-name>` tag. And we don't need to do anything for Spring Dispatcher servlet as we will get it from spring jar files.

And then we will set up the initial parameter in which we tell where our spring context config file is located.

```
File: web.xml
<web-app>

  <servlet>
    <servlet-name>dispatcher</servlet-name>
    <servlet-class>org.springframework.web.servlet.DispatcherServlet</servlet-class>

    <init-param>
      <param-name>contextConfigLocation</param-name>
      <param-value>/WEB-INF/spring-mvc-demo-servlet.xml</param-value>
    </init-param>

    <load-on-startup>1</load-on-startup>
  </servlet>

</web-app>
```

- Set up URL mappings to Spring MVC Dispatcher Servlet


Next thing is we want to tell the Spring that for any URL pattern coming in, we like it to pass to our Dispatcher Servlet. We can give what ever pattern we want till we are consistent with it.



And the servlet-name while defining URL Pattern must matches with the servlet reference that we have set up above in step 1.


Part 2: Add configurations to File: WEB_INF/spring-mvc-demo-servlet.xml

- Add support for Spring component scanning.



- Also add Support for conversion, formatting and validation.

When we are using Spring MVC then it can perform formatting of form data and can also perform form validation and in order to get the support we need to add this into our configuration xml file.



- Finally Configure the Spring MVC View Resolver.

In the final step, we will tell the spring where to look for files to actually render the view for our application.


```
<!-- Step 5: Define Spring MVC view resolver -->
<bean
  class="org.springframework.web.servlet.view.InternalResourceViewResolver">
  <property name="prefix" value="/WEB-INF/view/" />
  <property name="suffix" value=".jsp" />
</bean>
```

When our app provides a “view” name, Spring MVC will


- ✓ Prepend the prefix
- ✓ Append the suffix to that view name automatically.



And we need to create this folder i.e., `/WEB_INF/view/` inside our project in Eclipse.




- ✚ During the Development on Eclipse, add the Spring framework jar file as well as JSTL jar files and it will automatically add those jars into our classpath of this project.



Now we are going to add two starter files inside the WEB-INF directory in our project.

Here spring-mvc-demo-servlet.xml is just our configuration file where we usually mention the Component scanning packages.



Section 12: Spring MVC - Creating Controllers and Views

1 / 15 | 46min

➤ Creating a Spring Home Controller and View:

Development Process:

- Create a Controller class

Annotate class with **@Controller**. And @Controller says that it's a Spring MVC controller and **@Controller inherits from @Component**, and Spring does the scanning for @Component then it does pick @Controller as they extend from @Component.


```
@Controller
public class HomeController {

}
```

- Define a controller method.

```
@Controller
public class HomeController {

    public String showMyPage() {
        ...
    }

}
```

- Add the Request Mapping to the Controller method.

```
@Controller
public class HomeController {

    @RequestMapping("/")
    public String showMyPage() {
        ...
    }

}
```

Annotation maps a path to a method name
That's why you can choose any method name

- Return View Name


```
@Controller
public class HomeController {

    @RequestMapping("/")
    public String showMyPage() {
        return "main-menu";
    }

}
```

View Name

Remember There is some magic that's going to happen in the background; Spring is going to take the information from it's configuration file and it will actually find the view page. So based on the config it is going to look into the prefix directory and it will use the view name and then it will append the suffix (*i.e.*, *“.jsp” in our case*)



- Develop the View Page.

```

File: /WEB-INF/view/main-menu.jsp

<html><body>


<h2>Spring MVC Demo - Home Page</h2>

</body></html>

```

➤ How to Read form Data with Spring MVC:

Here We will have only one Controller with two Request Mappings, where user will first ask for the form and then submit the data and later controller will process it and then show it on the JSP page.



Development Process:

1. Create Controller Class.
2. Show HTML form

2.1. Create controller method to show HTML form.

```
//need a controller method to show the initial HTML form
@RequestMapping("/showForm")
public String showForm() {
    return "helloworld-form";
}

//need a controller method to process the HTML form
@RequestMapping("/processForm")
public String processForm() {
    return "helloWorld";
}
```

2.2. Create View Page for HTML form.

File: helloworld-form.jsp

```
<form action="/processForm" method="GET">
    <input type="text" name="studentName" placeholder="What's your name?"/>
    <input type="submit"/>
</form>
```

3. Process HTML Form

3.1. Create Controller method to process HTML Form.

3.2. Develop View Page for Confirmation

File: helloWorld.jsp:

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
    <head>
        <meta charset="ISO-8859-1">
        <title>Insert title here</title>
    </head>
    <body>

        <h3>Hello world of Spring!</h3>

        Student Name: ${param.studentName}
    </body>
</html>
```

➤ Adding Data to Spring Model

So, the Spring model is just a container to your application data.

In our Controller we can put any type of data
Like String, objects, info from the Database, etc. and our View page (JSP) can access data from the **model**.

Passing Model to your Container:


Code Example-

1. We want to create a new method to process form data
2. Read the form data: Student's name
3. Convert the name to upper case
4. Add the uppercase version to the model.

In Spring MVC, when we create our controller method and we need to read our form data in controller then we pass any Http server request and it works like any Servlet Request and also, we can pass our model.

When we need to add something to the model then we call

model.addAttribute() and in the parameter we give model attribute name and then it's value (that's simply the name and value pair inside the addAttribute() method).



```
@RequestMapping("/processFormVersionTwo")
public String letsShoutDude(HttpServletRequest request, Model model) {

    // read the request parameter from the HTML form
    String theName = request.getParameter("studentName");

    // convert to uppercase
    theName = theName.toUpperCase();


    // create the message
    String result = "Yo! " + theName;

    // add message to the model
    model.addAttribute("message", result);

    return "helloworld";
}
```

The image shows a code snippet for a Spring MVC controller method. A blue callout bubble labeled "Name" points to the string "message" in the `addAttribute` method call. A red callout bubble labeled "Value" points to the `result` variable. A blue box with the text "You can give any attribute name" is also present. A red arrow points to the `addAttribute` method call.

And on the View Page (JSP) we can access the data from the model using the attribute name that has been set in the controller class.



And we can add any amount of data to the model, here is the example shown below:

```
// get the data
//
String result = ...
List<Student> theStudentList = ...
ShoppingCart theShoppingCart = ...

// add data to the model
//
model.addAttribute("message", result);

model.addAttribute("students", theStudentList);

model.addAttribute("shoppingCart", theShoppingCart);
```

Section 13: Spring MVC - Request Params and Request Mappings

6 / 6 | 17min

➤ Reading HTML Form Data with `@RequestParam` Annotation

Earlier we were getting the form data using `HttpServletRequest` and then we're using `getParameter("studentName")` but now we will read the form data i.e., "studentName" using `@RequestParam`.

Spring has this special annotation which will read the form data from request Parameters and then it will take that data and it will bind with the variable like here we have ***theName*** in our example.

And then we are good to perform rest of the operations on the form data which is inside the *theName* variable.

```
@RequestMapping("/processFormVersionTwo")
public String letsShoutDude(
    @RequestParam("studentName") String theName,
    Model model) {

    // now we can use the variable: theName
}
```

• Behind the scenes:

- Spring will read param from request: studentName
- Bind it to the variable: theName

➤ Controller Level Request Mapping:

Adding Request Mappings to controller:

- Serves as parent Mapping for Controller.
- All request Mappings on methods in the controller are relative.

Controller Request Mapping

```
@RequestMapping("/funny")
public class FunnyController {

    @RequestMapping("/showForm")
    public String showForm() {
        ...
    }

    @RequestMapping("/processForm")
    public String process(HttpServletRequest request, Model model) {
        ...
    }
}
```

Controller mapping: /funny/showForm, /funny/processForm

Method mapping

Here we will see the conflict that we can get when we have two request mappings with similar name.

This is the **error** we will get when we have the above-mentioned scenario;

```
root cause
java.lang.IllegalStateException: Ambiguous mapping. Cannot map 'sillyController' method
public java.lang.String com.luv2code.springdemo.mvc.SillyController.displayTheForm()
to {[/showForm]}: There is already 'helloWorldController' bean method
```

FAQ: How does "processForm" work for "/hello"?

Question: Can you please clarify how /hello is getting appended to the jsp file action for "processForm"?

Answer

You can use "**processForm**" because it is a relative path to the controller "/hello" request mapping. Here is how it works.

1. When you wish to view the form, the HTML link points to "hello/showForm". This calls the controller and it displays the form.

2. At this point the browser URL/path is: *http://localhost:8080/spring-mvc-demo/hello*

3. The HTML form uses "processForm" for the form action. Notice that it does not have a forward slash, as a result, this will be relative to the current browser URL. Since the current browser URL is

http://localhost:8080/spring-mvc-demo/hello

Then the actual form URL submission will send it to

http://localhost:8080/spring-mvc-demo/hello/processForm

The part in bold with map to the controller with top-level request mapping "/hello" and then map to request mapping in that class "/processForm"

The key here is **relative path of showing the form and then submitting to relative path.**



```
main-menu.jsp x helloworld-form.jsp
1 <%@ page language="java" contentType="text/html; charset=ISO-8859-1"
2   pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>Insert title here</title>
8 </head>
9 <body>
10 <h1>Spring MVC Demo - Home Page</h1>
11 <hr>
12 <a href="hello/showForm">Go To Form</a>
13 </body>
14 </html>
```

```

main-menu.jsp helloworld-form.jsp
1 <%@ page language="java" contentType="text/html; charset=ISO-8859-1"
2   pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6   <meta charset="ISO-8859-1">
7   <title>Insert title here</title>
8 </head>
9 <body>
10   <form action="processFormVersionThree" method="GET">
11     <input type="text" name="studentName" placeholder="What's your name?"/>
12     <input type="submit"/>
13   </form>
14 </body>
15 </html>

```

Section 14: Spring MVC - Form Tags and Data Binding

0 / 15 | 54min

➤ Spring MVC Form Tags Overview

Spring MVC has support for Form tags and these form tags are configurable and we can reuse them for a web page.

Data Binding

Spring MVC Form Tags support data binding.

It allows us to automatically set data and retrieve data from a Java objects and beans.

- Spring MVC Form tags:

Form Tag	Description
form:form	main form container
form:input	text field
form:textarea	multi-line text field
form:checkbox	check box
form:radio	radio buttons
form:select	drop down list
more ...	

We'll make use of normal JSP page and then we can simply drop the Spring MVC Form tags.

How to reference Spring MVC Form Tags?

Specify the Spring namespace at the beginning of the JSP file.

```
<%@ taglib prefix="form" uri="http://www.springframework.org/tags/form" %>
```


Once that's get setup, we can make use of Spring MVC form tag in our JSP page.

➤ Spring MVC Form Tag for TextField:

In our Spring Controller:

- We must add **model Attribute**.
- This is a bean that will actually hold form data and this will give us the support for data binding.

So, when we show the form, we need to add the model attribute and here we have Model parameter and model will pass the data between controllers and views.

In this example, we are giving the “*model name*” as “*student*” and then as value we’re giving the object of student type (empty object), that will get pass to the form so that form make up with Data Binding.

And our Form should use the name as given in model name i.e., *student* to reference the student Object.

Code snippet from Controller

```
@RequestMapping("/showForm")
public String showForm(Model theModel) {

    theModel.addAttribute("student", new Student());

    return "student-form";
}
```

Model is used to pass data between controllers and views

Code snippet from Controller

```
@RequestMapping("/showForm")
public String showForm(Model theModel) {

    theModel.addAttribute("student", new Student());

    return "student-form";
}
```

attribute name

value

Setting up HTML Form - Data Binding

```
<form:form action="processForm" modelAttribute="student">

    First name: <form:input type="text" />

    <br><br>

    Last name: <form:input type="text" />

    <br><br>

    <input type="submit" value="Submit" />

</form:form>
```

```
@RequestMapping("/showForm")
public String showForm(Model theModel) {

    theModel.addAttribute("student", new Student());

    return "student-form";
}
```

Last name:

Submit

```
First Name: <form:input path="firstName"/>
<br><br>
Last Name: <form:input path="lastName"/>
```

The Highlighted part is actually binding this from field with the property of the bean. When the form is first loaded what Spring MVC will do behind the scene is it will actually populate the form fields using getter methods of the Object property and if it returns null then the form will remain empty.

And when the form gets submitted Spring will call setter methods and it will use whatever data entered by the user into the form fields.

Handling Form Submission in the Controller:

We will make use of new Spring annotation called `@ModelAttribute`.

Code snippet from Controller

```
@RequestMapping("/processForm")
public String processForm(@ModelAttribute("student") Student theStudent) {
    // log the input data
    System.out.println("theStudent: " + theStudent.getLastName());
    return "student-confirmation";
}
```

attribute name

method parameter

Now that annotation will actually get the object using the Attribute name and pass it to the parameter **Student theStudent** and then we can use it in our controller method.


So, we don't need to do manually `request.getParameter` for each Form field and Spring will handle all that for us.

```
<html>
<body>
    The student is confirmed: ${student.firstName} ${student.lastName}
</body>
</html>
```


attribute name

attribute name

The student is confirmed: John Doe



➤ Spring MVC Form Tag – Drop Down List



Plain HTML

```
<select name="country">
  <option>Brazil</option>
  <option>France</option>
  <option>Germany</option>
  <option>India</option>
  ...
</select>
```

In the Spring MVC, Drop down list is represented by `<form:select>`

In `<form:select>`, we basically specify the path to the property of the Object and then we give the options in which value is the actual value that will get set using setter method of the property mentioned in the path attribute whereas label will be displayed on the view only.

Example:

Country:

```
<form:select path="country">
  <form:option value="Brazil" label="Brazil"/>
  <form:option value="France" label="France"/>
  <form:option value="Germany" label="Germany"/>
  <form:option value="India" label="India"/>
</form:select>
```


Country:

```
<form:select path="country">
  <form:option value="Brazil" label="Brazil" />
  <form:option value="France" label="France" />
  <form:option value="Germany" label="Germany" />
  <form:option value="India" label="India" />
</form:select>

<br><br>

<input type="submit" value="Submit" />
```

On submit, Spring will call `student.setCountry(...)`



Read the List of Countries from a Java class

1. Define `countryOptions` inside the class.

```

public class Student {

    String firstName;
    String lastName;
    String country;
    String favoriteLanguage;
    private LinkedHashMap<String, String> countryOptions;


    public Student() {
        //populate country options: used ISO country code
        countryOptions = new LinkedHashMap<String, String>();
        countryOptions.put("BR", "Brazil");
        // "BR" is key/code and "Brazil" is value/label
        countryOptions.put("FR", "France");
        countryOptions.put("DE", "Germany");
        countryOptions.put("IN", "India");
        countryOptions.put("US", "USA");
    }

    .
    .
    .
    .

    public LinkedHashMap<String, String> getCountryOptions() {
        return countryOptions;
    }
}

```

Here we will need only the getter method for `countryOptions`, as when form is loaded, Spring will call `student.getCountryOptions()` method, to load the drop down items into the list.



So, this way we're reading all the data from the Java class and we are not hardcoding it in the JSP page, and that Java class can read the data from the property file or from Database or external services.

FAQ: Use properties file to load country options:

Question:

How to use properties file to load country options

Answer:

This solution will show you how to place the country options in a properties file. The values will no longer be hard coded in the Java code.

1. **Create a properties file to hold the countries. It will be a name value pair. Country code is name. Country name is the value.**

New text file: WEB-INF/countries.properties

1. BR=Brazil
2. FR=France
3. CO=Colombia
4. IN=India

Note the location of the properties file is very important. It must be stored in

WEB-INF/countries.properties

2. Update header section for Spring config file

We are going to use a new set of Spring tags for <util>. As a result, you need to update the header information in the Spring config file.

File: spring-mvc-dmo-servlet.xml

Remove the previous header and add this.

```
1.      <?xml version="1.0" encoding="UTF-8"?>
2.  <beans xmlns="http://www.springframework.org/schema/beans"
3.        xmlns:context="http://www.springframework.org/schema/context"
4.        xmlns:mvc="http://www.springframework.org/schema/mvc"
5.        xmlns:util="http://www.springframework.org/schema/util"
6.        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
7.        xsi:schemaLocation="
8.            http://www.springframework.org/schema/beans
9.            http://www.springframework.org/schema/beans/spring-beans.xsd
10.       http://www.springframework.org/schema/context
11.       http://www.springframework.org/schema/context/spring-context.xsd
12.       http://www.springframework.org/schema/mvc
13.       http://www.springframework.org/schema/mvc/spring-mvc.xsd
14.       http://www.springframework.org/schema/util
15.       http://www.springframework.org/schema/util/spring-util.xsd">
```

3. Load the country options properties file in the Spring config file. Bean id: countryOptions

File: spring-mvc-demo-servlet.xml.

Add the following lines:

```
    <util:properties id="countryOptions"
location="classpath:../countries.properties" />
```

4.1 In StudentController.java, add the following import statement:

```
1. import java.util.Map;
```

4.2 Inject the properties values into your Spring Controller: StudentController.java

1. `@Value("#{countryOptions}")`
2. `private Map<String, String> countryOptions;`

5. Add the country options to the Spring MVC model. Attribute name: theCountryOptions

```
1. @RequestMapping("/showForm")
2. public String showForm(Model theModel) {
3.
4.     // create a student object Student
5.     Student theStudent = new Student();
6.
7.     // add student object to the model
8.     theModel.addAttribute("student", theStudent);
9.
10.    // add the country options to the model
11.    theModel.addAttribute("theCountryOptions", countryOptions);
12.
13.    return "student-form";
14. }
```

6. Update the JSP page, student-form.jsp, to use the new model attribute for the drop-down list: theCountryOptions

```
1. <form:select path="country">
2.   <form:options items="${theCountryOptions}" />
3. </form:select>
```

7. Remove all references to country option from your Student.java.

➤ Radio Buttons:



Code Example

Data binding

```
Java <form:radio button path="favoriteLanguage" value="Java" />
C# <form:radio button path="favoriteLanguage" value="C#" />
PHP <form:radio button path="favoriteLanguage" value="PHP" />
Ruby <form:radio button path="favoriteLanguage" value="Ruby" />
```

Spring MVC Tag for A Radio Button is represented by the tag `<form:radio button>`. And we need to have the setter methods in our class for the above mentioned property

Code Example

On submit, Spring will call
student.setFavoriteLanguage(...)

```
Java <form:radio button path="favoriteLanguage" value="Java" />
C# <form:radio button path="favoriteLanguage" value="C#" />
PHP <form:radio button path="favoriteLanguage" value="PHP" />
Ruby <form:radio button path="favoriteLanguage" value="Ruby" />
```


Inside the Student Java class add the property *favoriteLanguage*.

```
public class Student {  
    String firstName;  
    String lastName;  
    String country;  
    String favoriteLanguage;  
    .  
    . //getters and setters  
    .  
    .  
    public void setFavoriteLanguage(String favouriteLanguage) {  
        this.favoriteLanguage = favouriteLanguage;  
    }  
  
    public String getFavoriteLanguage() {  
        return favoriteLanguage;  
    }  
}
```

And update the confirmation page.

FAQ: How to populate radiobuttons with items from Java class?

FAQ: How to populate radiobuttons with items from Java class like we did with selectlist?

You can follow a similar approach that we used for the drop-down list.

Here are the steps

1. Set up the data in your Student class

Add a new field

```
1. private LinkedHashMap<String, String> favoriteLanguageOptions;
```

In your constructor, populate the data

```
1. // populate favorite language options  
2. favoriteLanguageOptions = new LinkedHashMap<>();  
3. // parameter order: value, display label  
4. //  
5. favoriteLanguageOptions.put("Java", "Java");  
6. favoriteLanguageOptions.put("C#", "C#");  
7. favoriteLanguageOptions.put("PHP", "PHP");  
8. favoriteLanguageOptions.put("Ruby", "Ruby");
```

Add getter method

```
1. public LinkedHashMap<String, String> getFavoriteLanguageOptions() {  
2.     return favoriteLanguageOptions;  
3. }
```

2. Reference the data in your form

Favorite Language:

```
<form:radiobuttons path="favoriteLanguage"
items="${student.favoriteLanguageOptions}" />
```

➤ Spring MVC form tags for Checkboxes:

A check box is represented by the tag `<form:checkbox>`



Operating Systems: Linux ☐ Mac OS ☐ MS Windows ☐

```
Linux <form:checkbox path="operatingSystems" value="Linux" />
Mac OS <form:checkbox path="operatingSystems" value="Mac OS" />
MS Windows <form:checkbox path="operatingSystems"
value="MS Windows" />
```

In Java code
Need to add support when user selects multiple options
Array of Strings
Add appropriate get/set methods

- Will update our *student-form.jsp*:

Operating Systems:

```
Linux <form:checkbox path="operatingSystems" value="Linux"/>
Windows <form:checkbox path="operatingSystems" value="Windows"/>
MAC OS <form:checkbox path="operatingSystems" value="MAC OS"/>

<br><br>
```

- Now update the *Student.java*

```
public class Student {
    String firstName;
    String lastName;
    String country;
    String favoriteLanguage;
```

```

ArrayList<String> operatingSystems;
private LinkedHashMap<String, String> countryOptions;
.
.
. //getters and setters and constructors
.
.

public ArrayList<String> getOperatingSystems() {
    return operatingSystems;
}

public void setOperatingSystems(ArrayList<String> operatingSystems) {
    this.operatingSystems = operatingSystems;
}
}

```

- Now we need to update the *student-confirmation.jsp* page

Add the **JSTL core tags** which will allow us to loop over the collections.

```

<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>

<br><br>

Operating Systems User used:

<ul>
    <c:forEach var="temp" items="${student.operatingSystems}">
        <li>${temp}</li>
    </c:forEach>
</ul>

```

“items:” will call the getter methods for *operatingSystems* property of the model object and it will display all the selected operating systems in the bullet points structure.


The screenshot shows a web browser window with the URL `http://localhost:8080/spring-mvc-demo/student/showForm`. The form contains the following elements:

- First Name:
- Last Name:
- Country:
- Favorite Language: Java ☐ C# ☐ PHP ☐ Ruby ☐
- Operating Systems: Linux ☐ Windows ☐ MAC OS ☐
- submit

We will get to look our student-from.jsp page on hitting the url:

<http://localhost:8080/spring-mvc-demo/student/showForm>

And the *student-confirmation.jsp* will look like, (after processing the form)



The Student name is : Anuj Kumar Singh

Country: US

Favorite Language: Java

Operating Systems User used:

- Linux
- MAC OS

Section 15: Spring MVC Form Validation - Applying Built-In Validation Rules

13 / 13 | 51min

➤ Spring Form Validation

We can use the Java's standard bean validation API.

It defines a metadata model and API for entity validation.

And this bean validation API is available for service side applications and also client-side applications.

For more information: <http://www.beanvalidation.org>


Spring and Validation

Spring version 4 or higher supports the Bean Validation API.

And it's actually the preferred method for validation when building Spring apps.

We will simply add the Validation JARs to our project and use specified annotations and we are ready to go.

Bean validation Features

Validation Feature	
	required
	validate length
	validate numbers
	validate with regular expressions
	custom validation

Annotation	Description
@NotNull	Checks that the annotated value is not null
@Min	Must be a number \geq value
@Max	Must be a number \leq value
@Size	Size must match the given size
@Pattern	Must match a regular expression pattern
@Future / @Past	Date must be in future or past of given date
others ...	

Our Road Map

1. Set up our development Environment
2. Require field
3. Validate number range: min, max
4. Validate using regular expression (regex)
5. Custom validation

• Setting up the development Environment:

Java's standard Bean validation API is only a specification, it's vendor independent and portable however, we still need an implementation.

So, this is where Hibernate team comes to the rescue! And they have a separate project for validation. Hibernate Validator is fully compliant with Java's standard bean validation API.

Website: <http://www.hibernate.org/validator>

About the versions!

1. Hibernate Validator 7 is based on Jakarta EE 9.
2. Jakarta EE is the community version of Java EE (rebranded, relicensed)
3. And Java EE is collection of enterprise API like servlets, JSP, JDBC, Enterprise java beans, Java Message Service, etc.
4. Allows innovation of Jakarta EE with community driven approach.
5. Jakarta EE does not replace Java EE.

Jakarta EE


1. At the moment main change with **Jakarta EE** is package renaming
2. *javax.** packages are renamed to *jakarta.**

What impact on Hibernate Validator?

- Hibernate Validator 7 is based on **Jakarta EE 9**
- Spring 5 is still based on some components of **Java EE (javax.*)**.
- Spring may use Jakarta EE components in the future but no news yet.

- As a result, Spring 5 is not compatible with Hibernate validator 7
- ✓ **Hibernate Validator 6.2** is compatible with Spring 5.
- ✓ **Hibernate Validator 6.2** has the same features as Hibernate Validator 7.


Download the Hibernate Validator 6.2 jar zip archive file from www.hibernate.org by going into the Validator section



- ✓ On opening the zip archive file, go to **dist** directory and then copy all the three jar files present in that directory and then paste the jar files in the lib directory in the webapps folder of our project.

spring_jar_sw > hibernate-validator-6.2.0.Final > dist			
Name	Date modified	Type	Size
lib	12/23/2020 5:44 PM	File folder	
hibernate-validator-6.2.0.Final	12/23/2020 5:42 PM	Executable Jar File	1,281 KB
hibernate-validator-annotation-processo...	12/23/2020 5:42 PM	Executable Jar File	134 KB
hibernate-validator-cdi-6.2.0.Final	12/23/2020 5:42 PM	Executable Jar File	41 KB

- ✓ And we will need some other required files as well which is present in **hibernate-validator-6.2.0.Final\dist\lib\required** and then copy them and paste into the webapps directory of our project.



hibernate-validator-6.2.0.Final > dist > lib > required			
Name	Date modified	Type	Size
classmate-1.5.1	12/23/2020 5:42 PM	Executable Jar File	67 KB
jakarta.el-3.0.3	12/23/2020 5:42 PM	Executable Jar File	233 KB
jakarta.validation-api-2.0.2	12/23/2020 5:42 PM	Executable Jar File	90 KB
jboss-logging-3.4.1.Final	12/23/2020 5:42 PM	Executable Jar File	60 KB

➤ Spring MVC Form Validation for Required Fields

In this example we will make the *Last Name* required for user to fill in.

The diagram illustrates the process of adding validation to a form. On the left, a form titled "Fill out the form. Asterisk (*) means required." contains two input fields: "First name:" and "Last name (*):", along with a "Submit" button. A blue arrow points to the right, where the same form is shown but with a red error message "is required" displayed next to the "Last name (*):" field, which is circled in yellow.

Development Process:

1. Add Validation rule to Customer Class
2. Display error messages on HTML Form
3. Perform Validation in the Customer Class
4. Update Confirmation Page

- Add validation rule to Customer Class

```
import javax.validation.constraints.NotNull;
import javax.validation.constraints.Size;

public class Customer {

    private String firstName;

    @NotNull(message="is required")
    @Size(min=1, message="is required")
    private String lastName;

    // getter/setter methods
}
```

Error message if validation fails

- Display the Error Message on HTML Form

Also add the reference for the Spring Form tag library.

```
<%@ taglib prefix="form" uri="http://www.springframework.org/tags/form" %>
```

With that add this **CSS styling** into the web page to show the error in red color

```
<head>
  <meta charset="ISO-8859-1">
  <title>Customer Registration Form</title>
  <style>
    .error {color:red}
  </style>
</head>
```




We will see the **error message** only if the validation gets fail.

✓ Perform Validation in the Customer Class

@Valid will perform the validation rules using the *Hiibernate Validator API* on the object that we are getting from the form and then the result of the Validation test will be placed in **theBindingResult**.

Here we are checking if the **bindingResult** is having any error then will return to the same customer-form or else simply send them to the Confirmation page/success page of our application.



✓ Update the Confirmation page

```

<html>
<head>
<meta charset="ISO-8859-1">
<title>Customer Confirmation</title>
</head>
<body>
    The Customer is confirmed: ${customer.firstName} ${customer.lastName}
    <br><br>
</body>
</html>

```

Special Note about BindingResult Parameter Order

When performing Spring MVC validation, the location of the *BindingResult* parameter is very important. In the method signature, **the BindingResult parameter must appear immediately after the model attribute**.

If you place it in any other location, Spring MVC validation will not work as desired. In fact, your validation rules will be ignored.

```
1.      @RequestMapping("/processForm")
2.      public String processForm(
3.          @Valid @ModelAttribute("customer") Customer theCustomer,
4.          BindingResult theBindingResult) {
5.          ...
6.      }
```

Here is the relevant section from the Spring Reference Manual

Defining @RequestMapping methods
@RequestMapping handler methods have a flexible signature and can choose from a range of supported controller method arguments and return values.

...

The `Errors` or `BindingResult` parameters have to follow the model object that is being bound immediately ...

Let's experiment and Break it up!


In `CustomerController.java`; let's add some logging message

```
@RequestMapping("/processForm")
public String processForm(@Valid @ModelAttribute("customer") Customer theCustomer,
    BindingResult theBindingResult) {

    System.out.println("Last Name: |"+ theCustomer.getLastName()+"|");

    if(theBindingResult.hasErrors()) {
        return "customer-form";
    }
    else
        return "customer-confirmation";
}
```


Now let's go to the customer-form.jsp on web page;
We will try to enter Whitespace in last Name TextField and the submit it to check whether our validation will allow it pass through or not and that why we have added that logging message into the controller method.



The screenshot shows a web browser window with the URL `http://localhost:8080/spring-mvc-demo/customer/processForm`. The page displays a form with the instruction "Fill out the form. Asterisk (*) means required." There are two text input fields: "First name: Bob" and "Last name (*):". The "Last name" field is empty and has a red "is required" message next to it. A "Submit" button is at the bottom. Below the browser window, there is a green button with the text "Enter whitespace ...".

Well, lastName field with **whitespace passes the validation** and let's check the logging message into the console.

So, how does it pass the validation as we have added @NotNull and @Size annotations?



The Solution is: **@InitBinder**

what we need to do is trim the whitespace from the input fields.

1. @InitBinder annotation works as a pre-processor
2. Every Web request that will come to our Controller, this annotation code will execute first
3. Therefore, we'll annotate a method with @InitBinder, then all requests coming in will get pre-processed.

So, we are going to use @InitBinder to trim the strings i.e., Remove the leading and trailing white space, and incase the string having just the whitespaces then we will trim it all the way to make it null object. This will actually resolve our validation issue.

Development Process:


1. Register the custom Editor in Controller and we will do that by using **@InitBinder**



Here, we're using the **StringTrimmerEditor** Class which is defined in Spring API, It's purpose is to trim Strings.

And in the constructor, we are keeping True Boolean value so that it can trim the String value to null. Once the **StringTrimmerEditor** Object is created then we're registering it to the **dataBinder** as a custom Editor. Actually, we are saying that every String class apply the StringTrimmerEditor.

- Now, All the incoming requests will pass through the method annotated with @InitBinder and it will resolve our issue of whitespace with Last Name textField.



Section 16: Spring MVC Form Validation - Validating Number Ranges and Regular Expressions

9 / 9 | 37min

➤ Validating a Number Range

Will use @Min and @Max.

What are we going to do here?

- Add a new Input Field on our form for: **freePasses**.
- User can only enter a range: 0 to 10.

Development Process

- Add Validation rule to Customer class

```
import javax.validation.constraints.Min;
import javax.validation.constraints.Max;

public class Customer {

    @Min(value=0, message="must be greater than or equal to zero")
    @Max(value=10, message="must be less than or equal to 10")
    private int freePasses;

    // getter/setter methods

}
```

New field

Message attribute is actually the error message that will generate if the validation failed.

- Display error messages on HTML form

File: customer-form.jsp


```
Free Passes (*): <form:input path="freePasses"/>
<form:errors path="freePasses" cssClass="error"/>
<br><br>
```

- Perform Validation in the Controller class

//nothing to do here, keep everything as it is

- Update Confirmation Page

File: customer-confirmation.jsp

```
<br><br>
Free Passes : ${customer.freePasses}
```

Fill out of the Form. Asterisk () means required*

First Name:

Last Name (*):

Free Passes (*): must be greater than or equal to 0

➤ Applying Regular Expressions

We're going to validate the postal code field.

Validation Process

- Add a new input field on your form for: Postal Code
- User can only enter 5 chars/digit neither more than that nor less than; hence we will write the regular expression for that.

✓ Adding the Validation rule to Customer class:

```
import javax.validation.constraints.Pattern;

public class Customer {

    @Pattern(regexp="^[a-zA-Z0-9]{5}", message="only 5 chars/digits")
    private String postalCode;

    // getter/setter methods

}
```

The "regular expression" pattern


✓ Display the Error message on HTML Form

```
<br><br>
Postal Code: <form:input path="postalCode"/>
<form:errors path="postalCode" cssClass="error"/>
<br><br>
```

✓ Update the Confirmation Page

```
<br><br>
Postal Code: ${customer.postalCode}
```


On running on server: So, Validation with Regular expression is working




➤ How to Integer Field Required?

Added @NotNull annotation will make sure that the *freePasses* field is required.

```
public class Customer {  
    @NotNull(message="is required")  
    @Min(value = 0,message = "must be greater than or equal to 0")  
    @Max(value = 10,message = "must be less than or equal to 10")  
    private int freePasses;  
    .  
    .  
    .  
    . //getters and setters  
    .  
}
```

Output we get is: root cause is **TypeConversion error** i.e., not able to convert String type into the primitive type of int. So, we need to make the Type **Integer** rather than int.



Fix:

```
@NotNull(message="is required")  
@Min(value = 0,message = "must be greater than or equal to 0")  
@Max(value = 10,message = "must be less than or equal to 10")  
private Integer freePasses;
```

We are using Integer wrapper class; it works because our @InitBinder annotated method StrimTrimEditor will actually trim the input to null if input is null or whitespace. And also update getters and setter in the class.

So, our aim of making field required has been met.

- Submitting some String value for the Integer type field freePasses, Let's see the output:

Fill out the form. Asterisk (*) means required.

First name:

Last name (*):

Free passes: Failed to convert property value of type [java.lang.String] to required type [java.lang.Integer] for property freePasses; nested exception is java.lang.NumberFormatException: For input string: "aklfjaklfjskjsdfa"

Postal Code:

Course Code:


Come on!

So, fix it, we will follow this Development Process:

1. Create custom error message ("Invalid Number")

We will create "resource" folder and within that we will put our *messages.properties* file

- *src/main/java/resources/messages.properties*



into the *messages.properties* file:



2. Load Custom messages resource in Spring config file.

Now we need to tell spring about our custom error message i.e., we will load this custom error message inside our spring config file.

Open the *spring-mvc-demo-servlet.xml* file, and add:

```
<!-- Load the custom Message resources -->
<bean id="messageSource"
class="org.springframework.context.support.ResourceBundleMessageSource">
<property name="basenames" value="resources/messages"></property>
</bean>
```

3. Run on Server:

The screenshot shows a web browser window with a form titled 'Fill out the'. The form has fields for 'First name', 'Last name (*)' (with value 'smith'), 'Free passes' (with value 'alkfjaskfjaslkfj'), 'Postal Code', and 'Course Code'. A 'Submit' button is at the bottom. The 'Free passes' field has a red error message 'Invalid number' next to it. A red arrow points to this message. The browser's developer console shows a message: '1 typeMismatch.customer.freePasses=Invalid number'.

Now let's see how we came up with text that we have written in *messages.properties* file.

So, we will add some logging message in our Controller method, in which we'll inspect the *bindingResult* Object:

```
@RequestMapping("/processForm")
public String processForm(@Valid @ModelAttribute("customer") Customer theCustomer,
BindingResult theBindingResult) {

    System.out.println("Last Name: |"+ theCustomer.getLastName()+"|");
    System.out.println("Binding Result: "+theBindingResult);
    System.out.println("\n\n\n\n");
    if(theBindingResult.hasErrors()) {
        return "customer-form";
    }
    else
        return "customer-confirmation";
}
```

Now on giving some random string into the *freePasses* field, check for the logging message that we got:

Customer Registration Form

http://localhost:8080/spring-mvc-demo/customer/processForm

Fill out of the Form. Asterisk (*) means required

First Name:

Last Name (*):

Free Passes (*): Invalid Number

Postal Code:

Logging Message:


Binding Result: org.springframework.validation.BeanPropertyBindingResult: 1 errors
 Field error in object 'customer' on field 'freePasses': rejected value [wjcbwbcw]; codes [typeMismatch.customer.freePasses,typeMismatch.freePasses,typeMismatch.java.lang.Integer,typeMismatch]; arguments [org.springframework.context.support.DefaultMessageSourceResolvable: codes [customer.freePasses,freePasses]; arguments []; default message [freePasses]]; default message [Failed to convert property value of type 'java.lang.String' to required type 'java.lang.Integer' for property 'freePasses'; nested exception is java.lang.NumberFormatException: For input string: "wjcbwbcw"]

Look at the highlighted part; where error codes are given:

Rejected Value: [wjcbwbcw], It is the value that we have given in the input text field

Codes:

[typeMismatch.customer.freePasses,typeMismatch.freePasses,typeMismatch.java.lang.Integer,typeMismatch]



So, we are overriding their default error code and we are providing our own custom message.

There is some other error codes mentioned in the array as well, basically error codes start with very specific error code from the left to very generic all the way to right in the array. Therefore, in this way we can use bindingResult to check the error codes and add our own custom message on unsuccessful validations.

Section 17: Spring MVC Form Validation - Creating Custom Validation Rules

8 / 8 | 31min

➤ Custom Validation with Spring MVC:

Here we will add our custom annotation.

Ex: Custom Business Rule that we need to add here for the Course Code field

So, here we want to start the course code form LUV and if user has written any other text then validation will give error by putting the message “**Course must start with LUV**”.

First name:

Last name:

Course Code: **Course code must start with LUV**

Custom Validation


- Spring MVC calls our Custom Validation
- Custom Validation returns Boolean value for pass/fail (true/false) based on the code user entered on the field/
- We will create our own custom Java Annotation @CourseCode



Development Process

1. Create custom Validation Rule

- Create @CourseCode annotation
- Create **CourseCodeConstraintValidator Class**, this is where we put own custom Logic for Validation and determine true or false as if value passes our validation or not.



```
@Constraint(validatedBy = CourseCodeConstraintValidator.class)
@Retention(RetentionPolicy.RUNTIME)
@Target({ ElementType.FIELD, ElementType.METHOD })
public @interface CourseCode {
```

- @Constraint with validatedBy property will actually contain the Helper class that has the business rule for validating the process.
- @Target basically says where can we apply this annotation like to a method or a field and here, we decided to put this annotation on method or on field.
- @Retention means how long we should retain it and we want to keep the annotation in the compiled java byte code so we can use it and intercept on it during runtime.

This annotation has two parameters i.e., “value” and “message”. So, we need to add some method declarations here inside the annotation.

```
//define the course code
public String value() default "LUV";
```

This means that the annotation has parameter called value and if user doesn't provide then we will use the default value of “LUV”

```
//define default error message
public String message() default "must start with LUV";
```

```
//define default groups
public Class<?>[] groups() default {};
```

```
//define default payloads
public Class<? extends Payload>[] payload() default {};
```

Payloads: provide custom details about validation failure (severity level, error code etc)

✓ Now CourseCodeConstraintValidator Helper class

```
public class CourseCodeConstraintValidator implements ConstraintValidator<CourseCode,
String>{

    private String coursePrefix;
```

```


@Override
public void initialize(CourseCode theCourseCode) {
    // TODO Auto-generated method stub
    coursePrefix = theCourseCode.value();
}

@Override
public boolean isValid(String theCode, ConstraintValidatorContext
theConstraintValidatorContext) {
    // TODO Auto-generated method stub
    boolean result = theCode.startsWith(coursePrefix);

    return result;
}
}

```

Code Explanation:



```

public class CourseCodeConstraintValidator
    implements ConstraintValidator<CourseCode, String> {

    private String coursePrefix;

    @Override
    public void initialize(CourseCode theCourseCode) {
        coursePrefix = theCourseCode.value();
    }
}

```

- `public void initialize(CourseCode theCourseCode)`



```

@Override
public void initialize(CourseCode theCourseCode) {
    coursePrefix = theCourseCode.value();
}

@Override
public boolean isValid(String theCode, ConstraintValidatorContext
theConstraintValidatorContext) {
    // TODO Auto-generated method stub
    return false;
}

```

`@CourseCode(value="LUV", message="must start with LUV")`
`private String courseCode;`

During initialization, it will get the actual value that passed in i.e., the prefix against which we want to validate in. This specially sets everything up, so our validator is up and running and now Spring MVC can actually use it for validation and then it takes us to another method `isValid()`.

- `public boolean isValid(String theCode, ConstraintValidatorContext theConstraintValidatorContext)`

This method will be called by Spring MVC at runtime it will say here is the data submitted by the form and check if it's valid? Spring MVC will pass the Form Data entered by the user in String theCode parameter and also pass the ConstraintValidatorContext which is just a helper class for additional error messages.



▪ **Business Rule:**

If the data (theCode) is not equal to null then we will check whether “*theCode*” start with the “coursePrefix” that is given in annotation’s **value** property and will return True/False based on that.

And incase **theCode** is empty i.e., **null** then we are simply returning **True**.

2. Add validation rule to Customer class
3. Display error message on HTML from

File: customer-form.jsp

```

<br><br>
Course Code: <form:input path="courseCode"/>
<form:errors path="courseCode" cssClass="error"/>
<br><br>

```

4. Update confirmation Page

File: customer-confirmation.jsp

```

<br><br>
Course Code : ${customer.courseCode}

```

Now it will work as per our Business Rule:

```

@CourseCode
private String courseCode;

```

Inside the Customer class

```

@Constraint(validatedBy = CourseCodeConstraintValidator.class)
@Retention(RetentionPolicy.RUNTIME)
@Target({ ElementType.FIELD, ElementType.METHOD })
public @interface CourseCode {

    //define the course code
    public String value() default "LUV";

    //define default error message
    public String message() default "must start with LUV";
}

```

http://localhost:8080/spring-mvc-demo/customer/processForm

Fill out of the Form. Asterisk (*) means required

First Name:

Last Name (*):

Free Passes (*):

Postal Code:

Course Code: must start with LUV

- ✓ Here `@CourseCode` will take default value and message that we have given while declaring the annotation.
- ✓ Below is the customized version of our `@CourseCode` annotation.

http://localhost:8080/spring-mvc-demo/customer/processForm

Fill out of the Form. Asterisk (*) means required

First Name:

Last Name (*):

Free Passes (*):

Postal Code:

Course Code: must start with TOPS

```
@CourseCode(value="TOPS", message="must start with TOPS")
private String courseCode;

public String getCourseCode() {
    return courseCode;
}

public void setCourseCode(String courseCode) {
    this.courseCode = courseCode;
}
```

Customize validation
Must start with "TOPS"

FAQ: Spring MVC Custom Validation - Possible to validate with multiple strings?

Spring MVC Custom Validation - FAQ: Is it possible to integrate multiple validation string in one annotation?

Question:

Is it possible to integrate multiple validation string in one annotation? For example, validate against both LUV and TOPS.

Answer:

Yes, you can do this. In your validation, you will make use of an array of strings.

Here's an overview of the steps.

1. Update CourseCode.java to use an array of strings

2. Update CourseCodeConstraintValidator.java to validate against array of strings

3. Update Customer.java to validate using array of strings

Detailed Steps

1. Update CourseCode.java to use an array of strings

Change the value entry to an array of Strings:

```
1.      // define default course code
2.      public String[] value() default {"LUV"};
```

Note the use of square brackets for the array of Strings. Also, the initialized value uses curly-braces for array data.

2. Update CourseCodeConstraintValidator.java to validate against array of strings

Change the field for coursePrefixes to an array

```
private String[] coursePrefixes;
```

Update the isValid(...) method to loop through the course prefixes. In the loop, check to see if the code matches any of the course prefixes.

```
1.      @Override
2.      public boolean isValid(String theCode,
3.                             ConstraintValidatorContext theConstraintValidatorContext) {
4.          boolean result = false;
5.
6.          if (theCode != null) {
7.
8.              //
9.              // loop thru course prefixes
10.             //
11.             // check to see if code matches any of the course prefixes
12.             //
13.             for (String tempPrefix : coursePrefixes) {
14.                 result = theCode.startsWith(tempPrefix);
15.
16.                 // if we found a match then break out of the loop
17.                 if (result) {
18.                     break;
19.                 }
20.             }
21.         }
22.         else {
23.             result = true;
24.         }
25.
26.         return result;
27.     }
```

3. Update Customer.java to validate using array of strings

```
1.      @CourseCode(value={"TOPS", "LUV"}, message="must start with TOPS or LUV")
2.      private String courseCode;
```

Note the use of curly braces.

Complete Source Code:

<https://gist.github.com/darbyluv2code/0275ddb6e70e085a10fd464e36a42739>

That's it. This provides a solution to integrate multiple validation string in one annotation. In this example, the code validates against both LUV and TOPS.

Below GitHub Repository contains all the discussed exercises:

<https://github.com/000GEV744/Spring-Git/tree/main/spring-mvc-demo>