# ES\_LPC1114 Errata sheet LPC1114 Rev. 2 — 15 November 2010

**Errata sheet** 

### **Document information**

Info	Content
Keywords	LPC1114 errata
Abstract	This errata sheet describes both the known functional problems and any deviations from the electrical specifications known at the release date of this document.
	Each deviation is assigned a number and its history is tracked in a table at the end of the document.





# **Revision history**

Rev	Date	Description
2	20101115	Added ADC.1.
		Added Rev. 'B'.
1	20100510	Initial version

# **Contact information**

For more information, please visit: <a href="http://www.nxp.com">http://www.nxp.com</a>

For sales office addresses, please send an email to: <a href="mailto:salesaddresses@nxp.com">salesaddresses@nxp.com</a>

# 1. Product identification

The LPC1114 devices typically have the following top-side marking:

LPC1114x

/xxx

XXXXXXX

xxYYWWxR[x]

The last letter in the last line (field 'R') will identify the device revision. This Errata Sheet covers the following revisions of the LPC1114:

Table 1. Device revision table

Revision identifier (R)	Revision description
'B'	Second device revision
'A'	Initial device revision

Field 'YY' states the year the device was manufactured. Field 'WW' states the week the device was manufactured during that year.

# 2. Errata overview

### Table 2. Functional problems table

Functional problems	Short description	Revision identifier	Detailed description
ADC.1	External sync inputs not operational	'A', 'B'	Section 3.1 on page 4

### Table 3. AC/DC deviations table

AC/DC deviations	Short description	Revision identifier	Detailed description
n/a	n/a	n/a	n/a

### Table 4. Errata notes

Note	Short description	Revision identifier	Detailed description
n/a	n/a	n/a	n/a

# 3. Functional problems detail

# 3.1 ADC.1: External sync inputs not operational

### Introduction:

In software-controlled mode (BURST bit is 0), the 10-bit ADC can start conversion by using the following options in the A/D Control Register:

26:24 START		When the BURST bit is 0, these bits control whether and when an A/D conversion is started:	0
	0x0	No start (this value should be used when clearing PDN to 0).	
	0x1	Start conversion now.	
	0x2	Start conversion when the edge selected by bit 27 occurs on PIO0_2/SSEL/CT16B0_CAP0.	
	0x3	Start conversion when the edge selected by bit 27 occurs on PIO1_5/DIR/CT32B0_CAP0.	
	0x4	Start conversion when the edge selected by bit 27 occurs on CT32B0_MAT0.	
	0x5	Start conversion when the edge selected by bit 27 occurs on CT32B0_MAT1.	
	0x6	Start conversion when the edge selected by bit 27 occurs on CT16B0_MAT0.	
	0x7	Start conversion when the edge selected by bit 27 occurs on CT16B0_MAT1.	

### **Problem:**

The external start conversion feature, AD0CR:START = 0x2 or 0x3, may not work reliably and ADC external trigger edges on PIO0\_2 or PIO1\_5 may be missed. The occurrence of this problem is peripheral clock (pclk) dependent. The probability of error (missing a ADC trigger from GPIO) is estimated as follows:

- For PCLK\_ADC = 100 MHz, probability error = 12 %
- For PCLK\_ADC = 50 MHz, probability error = 6 %
- For PCLK\_ADC = 12 MHz, probability error = 1.5 %

The probability of error is not affected by the frequency of ADC start conversion edges.

### Work-around:

In software-controlled mode (BURST bit is 0), the START conversion options (bits 26:24 set to 0x1 or 0x4 or 0x5 or 0x6 or 0x7) can be used. The user can also start a conversion by connecting an external trigger signal to a capture input pin (CAPx) from a Timer peripheral to generate an interrupt. The timer interrupt routine can then start the ADC conversion by setting the START bits (26:24) to 0x1. The trigger can also be generated from a timer match register.

# 4. AC/DC deviations detail

No known errata.



# 5. Errata notes

No known errata.

5 of 7

# 6. Legal information

## 6.1 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

### 6.2 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or

malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

# 6.3 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.



# **Errata sheet LPC1114**

# 7. Contents

1	Product identification
2	Errata overview 3
3	Functional problems detail 4
3.1	ADC.1: External sync inputs not operational 4 Introduction:
	Problem:
	Work-around:
4	AC/DC deviations detail 4
5	Errata notes 5
6	Legal information 6
6.1	Definitions
6.2	Disclaimers 6
6.3	Trademarks6
7	Contents 7

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.