Content borrowed from www.cs.columbia.edu/~junfeng/10sp-w4118/lectures/...

11/13/16 (1)

Paging

frames (= length)

16 bits 6 for frame # then have 2^6 frames each with 2^{10} words

process page = frame size

slide 37 – 41

each page table kept with process control block



say have 8 bit address space

have 8 frames (3 bits)

frames have $2^5 = 32$ words

~~but still need all of process in mem at once!~~

~~also internal frag on last block of process.~~

ex 8 bit logical address for process X



Segmentation like ~~paging with diff size frames~~

can have diff sized segments (like ~~frames in paging~~)

like paging logical address has 2 parts



diff is the segment table

has base & length

↑ like paging

↕ max size

- these segments map to blocks of memory
- no internal frag. (external though) best FA? first FA?
- ~~programmers~~ can control how process is segmented compilers (data, program)

  bit more complex than simple paging.

~~still all process in mem at once~~





	limit	base
0	1000	1400
1	400	6300
2	400	4300
3	1100	3200



also bits to determine read, write, dirty

stopped here 11/14/16 first class. I/O on mem.

11/13/16 ④

6 bit logical address 8 bit physical address

each frame is 16 bytes

① how many page table entries
② what if have 8 bit logical address?



③ how many physical pages? ($2^4=16$ in both cases)
④ how many logical (6 bits) $2^2=4$ (8 bits) $2^4=16$

---

add some bits to page table
valid bit: map to a valid physical page
read/write/execute bits

all checked by MMU on each mem access



can allocate from free-page-list. one page at a time from head of this list.