



2025 AEA Europe Regional

Mat Althuizen, Account Manager

TA245 Series USB Chargers

NEW

45-watt USB Chargers for 14-volt and 28-volt aircraft

Charging Technology

USB-C	Power Delivery 3.0 Programmable Power Supply 3.0 Qualcomm® Quick Charge™ 3.0 Battery Charging 1.2
USB-A	Qualcomm® Quick Charge™ 3.0 Battery Charging 1.2



TA245 Series USB Chargers

NEW

Smart Halo Lighting

- Charging status indication
 - Blue = On
 - Green = Charging
 - Yellow = Fault
- Adjustable brightness control

Configurations

- Dual USB-C (45 W / 45 W)
- Dual USB-C (45 W) / USB-A (36 W)
- Single USB-C (45 W)



Easy Panel Upgrade Cirrus SR Series

NEW

Easy Digital Standby and 100-watt USB Upgrade

- Custom Adapter Plate
- Dual 100 W USB-C PD / 15 W USB-A chargers
- SAM[®] Standby Attitude Module

New List Price

- \$5,550

**The ONLY TSO-certified USB chargers
compatible with Starlink[®] Mini**



New Panel



Legacy Panel

TS28 Emergency Battery Power Supply

NEW

**Power emergency lighting and critical equipment
in the event of electrical system failure**

Input Voltage	26.5 – 32 VDC
Output Power	24 VDC nominal, 3 amps max
Run Time	60 minutes @ 1A (28 Wh capacity)
Weight	1.7 lbs
Dimensions	5.5"L x 4.4"W x 1.5"H



Direct replacement for
Radiant Battery Power Supply CBS28-1
on Citation 550 / 560 / 680 / 680A / 700

TS28 Emergency Battery Power Supply

NEW

Technology

- Rechargeable, field-replaceable NiMH battery pack
- No memory effect

Maintenance

- 2-year cycle

Life Expectancy

- 4 – 6 years battery life




Direct replacement for
Radiant Battery Power Supply CBS28-1
on Citation 550 / 560 / 680 / 680A / 700

TS32 Emergency Battery Power Supply

COMING
SOON

**Power emergency lighting and critical equipment
in the event of electrical system failure**

Input Voltage	16 – 32 VDC
Output Power	6.2 VDC nominal, 7 amps max
Run Time	153 minutes @ 2.0A (32 Wh capacity)
Weight	1.9 lbs
Dimensions	10.8"L x 3.3"W x 2.0"H



Direct replacement for
Radiant RPS1-A / B and Bruce Industries
100865 power supplies

TS32 Emergency Battery Power Supply

COMING
SOON

Technology


- Rechargeable, field-replaceable NiMH battery pack
- No memory effect

Maintenance

- 2-year cycle

Life Expectancy

- 4 – 6 years battery life




Direct replacement for
Radiant RPS1-A / B and Bruce Industries
100865 power supplies

TS56 Emergency Battery Power Supply

COMING
SOON

**Power emergency lighting and critical equipment
in the event of electrical system failure**

Input Voltage	26 – 32 VDC
Output Power	24.6 VDC nominal, 3 amps max
Run Time	137 minutes @ 1A (56 Wh capacity)
Weight	2.9 lbs
Dimensions	9.1"L x 4.3"W x 2.4"H



Direct replacement for
Radiant Battery Power Supply 640-13595-00

TS56 Emergency Battery Power Supply

COMING
SOON

Technology


- Rechargeable, field-replaceable NiMH battery pack
- No memory effect

Maintenance

- 2-year cycle

Life Expectancy

- 6 – 8 years battery life



Direct replacement for
Radiant Battery Power Supply 640-13595-00



mcico.com

truebluepower.com