

Fine Tuning

```
In [1]: %matplotlib inline
import d2l
from mxnet import gluon, init, nd
from mxnet.gluon import data as gdata, loss as gloss, model_zoo
from mxnet.gluon import utils as gutils
import os
import zipfile
```

Hot Dog Recognition Dataset

Download the Data Set

```
In [2]: data_dir = '../data'
base_url = 'https://apache-mxnet.s3-accelerate.amazonaws.com/'
fname = gutils.download(
    base_url + 'gluon/dataset/hotdog.zip',
    path=data_dir, sha1_hash='fba480ffa8aa7e0febbb511d181409f899b9baa5')
with zipfile.ZipFile(fname, 'r') as z:
    z.extractall(data_dir)
```

Read the Dataset

```
In [3]: train_imgs = gdata.vision.ImageFolderDataset(
        os.path.join(data_dir, 'hotdog/train'))
        test_imgs = gdata.vision.ImageFolderDataset(
            os.path.join(data_dir, 'hotdog/test'))

        hotdogs = [train_imgs[i][0] for i in range(8)]
        not_hotdogs = [train_imgs[-i - 1][0] for i in range(8)]
        d2l.show_images(hotdogs + not_hotdogs, 2, 8, scale=1.4);
```

Image Augmentation

```
In [5]: # We specify the mean and variance of the three RGB channels to normalize the image channel.
normalize = gdata.vision.transforms.Normalize(
    [0.485, 0.456, 0.406], [0.229, 0.224, 0.225])

train_augs = gdata.vision.transforms.Compose([
    gdata.vision.transforms.RandomResizedCrop(224),
    gdata.vision.transforms.RandomFlipLeftRight(),
    gdata.vision.transforms.ToTensor(),
    normalize])

test_augs = gdata.vision.transforms.Compose([
    gdata.vision.transforms.Resize(256),
    gdata.vision.transforms.CenterCrop(224),
    gdata.vision.transforms.ToTensor(),
    normalize])
```

Model

Download Pre-trained Models

```
In [6]: pretrained_net = model_zoo.vision.resnet18_v2(pretrained=True)  
pretrained_net.output
```

Initialize Model for Fine Tuning

```
In [8]: finetune_net = model_zoo.vision.resnet18_v2(classes=2)
finetune_net.features = pretrained_net.features
finetune_net.output.initialize(init.Xavier())
# The model parameters in output will be updated using a learning rate ten times greater.
finetune_net.output.collect_params().setattr('lr_mult', 10)
```

Fine Tune

```
In [9]: def train_fine_tuning(net, learning_rate, batch_size=128, num_epochs=5):
        train_iter = gdata.DataLoader(
            train_imgs.transform_first(train_augs), batch_size, shuffle=True)
        test_iter = gdata.DataLoader(
            test_imgs.transform_first(test_augs), batch_size)
        ctx = d2l.try_all_gpus()
        net.collect_params().reset_ctx(ctx)
        net.hybridize()
        loss = gloss.SoftmaxCrossEntropyLoss()
        trainer = gluon.Trainer(net.collect_params(), 'sgd', {
            'learning_rate': learning_rate, 'wd': 0.001})
        d2l.train(train_iter, test_iter, net, loss, trainer, ctx, num_epochs)
```

Train

```
In [10]: train_fine_tuning(finetune_net, 0.01)
```

```
training on [gpu(0), gpu(1)]  
epoch 1, loss 3.3067, train acc 0.690, test acc 0.921, time 16.9 sec  
epoch 2, loss 0.3924, train acc 0.902, test acc 0.919, time 12.3 sec  
epoch 3, loss 0.2863, train acc 0.919, test acc 0.911, time 12.4 sec  
epoch 4, loss 0.4881, train acc 0.877, test acc 0.936, time 12.4 sec  
epoch 5, loss 0.2394, train acc 0.923, test acc 0.870, time 12.5 sec
```


Train from Scratch

```
In [11]: scratch_net = model_zoo.vision.resnet18_v2(classes=2)
scratch_net.initialize(init=init.Xavier())
train_fine_tuning(scratch_net, 0.1)
```

```
training on [gpu(0), gpu(1)]
epoch 1, loss 0.6512, train acc 0.708, test acc 0.795, time 12.4 sec
epoch 2, loss 0.3935, train acc 0.830, test acc 0.781, time 12.4 sec
epoch 3, loss 0.4056, train acc 0.820, test acc 0.828, time 12.5 sec
epoch 4, loss 0.3863, train acc 0.831, test acc 0.781, time 12.5 sec
epoch 5, loss 0.3592, train acc 0.842, test acc 0.830, time 12.4 sec
```