## Visualise all the things



# VISUALISE ALL THE THINGS

BUILDING DASHBOARD WIDGETS FOR MISP

CIRCL / TEAM MISP PROJECT

HTTP://WWW.MISP-PROJECT.ORG/ TWITTER: @MISPPROJECT


**NSPA** 



VISUALISE ALL THE THINGS CIRCL / TEAM MISP PROJEC

### DASHBOARD IN MISP

- User configurable simple dashboard interface
- Visualise, aggregate and track data important to you
- Brand new feature, still undergoing reworks



Visualise all the things

└─ Dashboard in MISP



#### THE INTERNALS OF AWIDGET

- **Backend** for the widget, full access to all MISP internals
- Load, convert, format to be represented via view widgets
- Widget metadata size, name, description, behaviours
- Only main function required to be implemented: handler()
- Optional: checkPermissions() for ACL
- Accepts **user configuration** for which a template can be provided
- Located in /var/www/MISP/app/Lib/Dashboard/
- Custom widgets can be placed in /var/www/MISP/app/Lib/Dashboard/Custom/

Visualise all the things

2022

☐ The internals of awidget

· Backend for the widget, full access to all MISP internals m Load, convert, format to be represented via view widgets

■ Located in /var/www/MISP/app/Lib/Dashboard/

Custom widgets can be placed in

#### THE VIEW LAYER OF A WIDGET

- View files are included by default and reusable
- Currently we have a small but growing list of views
  - ► BarChart
  - ► SimpleList
  - ► WorldMap
- Converts the data passed by the Widget logic to HTML
- Located in /var/www/MISP/view/Elements/dashboard/Widgets/

Visualise all the things

2022-08-03

└─The view layer of a widget

IEW LAYER OF A WIDGET

■ View files are included by default and reusable
■ Currently we have a small but growing list of views

arChart implo list

➤ SimpleList
➤ WorldMap

Converts the data passed by the Widget logic to HTMI
 Located in

/var/www/MISP/view/Elements/dashboard

### WIDGET BEHAVIOURS

- Widgets can additionally be tied to certain **behaviours**:
  - ► Caching
    - Executions of the widget logic are cached
    - Separate caches for each organisation in addition to site admins
    - Cache duration is controlled by the widget logic
  - ► Refresh
    - Widgets can be set to refresh after x seconds
  - ► Both of these should be used with special care in regards to the use of **system resources**

Visualise all the things

2022

-Widget behaviours

ET BEHAVIOURS

Widgets can additionally be tied to certain behaviours:
 Caching
 Structions of the widget logic are cached
 Separate caches for each organisation in addition to sit admins
 scache duration is controlled by the widget logic.

Widgets can be set to refresh after x seconds
 Both of these should be used with special care in the use of system resources

## EXERCISE MODULE: SIMPLE WHOAMI

- Let's start with a skeleton
- Create /var/www/MISP/app/Lib/Dashboard/Custom/WhoamiWidget.php
- MISP will parse anything ending with Widget.php in this directory

Visualise all the things

2022

Exercise module: simple Whoami

EXERCISE MODULE: SIMPLE WHOAMI

■ Let's start with a skeleton ■ Create /var/www/MISP/app/Lib/Dashboard/Cus-

MISP will parse anything ending with Widget.php in the directory

### **EXERCISE MODULE: SIMPLE WHOAMI**

```
2 class MispWhoamiWidget
    public $title = 'Whoami';
    public $render = 'SimpleList';
    public $width = 2;
    public $height = 2;
    public $params = array();
    public $description = 'Shows information about the
        currently logged in user.';
    public $cacheLifetime = false;
    public $autoRefreshDelay = 3;
    public function handler($user, $options = array())
      $data = arrav();
      return $data;
```

1 <?php

Visualise all the things

-Exercise module: simple Whoami

#### META INFORMATION

- **\$title**: The name of the widget
- **\$description**: A description of the widget
- **\$render**: The view element to use in rendering the widget
- \$width & \$height: Default relative dimensions
- **\$params**: Configuration array with explanations for each key
- \$cacheLifetime: The lifetime of the caches in seconds (false disables it)
- \$autoRefreshDelay: The time in seconds between each refresh (false disables it)

yisualise all the things

2022-08-03

-Meta information

META INFORMATION

otte: The name of the widget description: A description of the widget

# \$render: The view element to use in rendering the widget

m \$width & \$height: Default relative dimensions

m \$cacheLifetime: The lifetime of the caches in seconds (false disables it)

 \$autoRefreshDelay: The time in seconds between each refresh (false disables it)

### THE HANDLER

```
public function handler($user, $options = array())
     $this->Log = ClassRegistry::init('Log');
     $entries = $this->Log->find('all', array(
       'recursive' => -1,
       'conditions' => array(
         'action' => 'login', 'user_id' => $user['id']
       'order' => 'id desc',
       'limit' => 5,
       'fields' => array('created', 'ip')
12
     foreach ($entries as &$entry) {
       $entry = $entry['Log']['created'] . ' --- ' .
14
15
         empty($entry['Log']['ip']) ?
16
         'IP not logged' :
          $entry['Log']['ip']
18
19
20
     return arrav(
       array('title' => 'Email', 'value' => $user['email']),
22
23
       array(
         'title' => 'Role', 'value' => $user['Role']['name']
25
26
       arrav(
         'title' => 'Organisation',
28
         'value' => $user['Organisation']['name']
29
       array(
         'title' => 'IP', 'value' => $ SERVER['REMOTE ADDR']
32
       array('title' => 'Last logins', 'value' => $entries)
34
35 }
```

າ Visualise all the things

└─The handler

2022-

THE HANDLER

THE CONTROL OF THE PROPERTY OF TH

### **RESULT**

#### 

Visualise all the things

Visualise all the things

Result

