

# AN INTRODUCTION TO CYBERSECURITY INFORMATION SHARING

MISP - THREAT SHARING

CIRCL / TEAM MISP PROJECT

MISP PROJECT

<https://www.misp-project.org/>

MISP PROJECT



**MISP**  
Threat Sharing

- Data sharing in MISP
- Data models for the Data layer
- Data models for the Context layer

## ■ Data layer

- ▶ The raw data itself as well as element to link them together
- ▶ Indicators, Observables and means to contextually link them
- ▶ MISP terminology: Event, Attributes, misp-objects, ...

## ■ Context layer

- ▶ As important as the data layer, allow triage, false-positive management, risk-assessment and prioritisation
- ▶ Latches on the data layer, usually referencing threat intelligence, concepts, knowledge base and vocabularies
- ▶ Tags, Taxonomies, Galaxies, ...

# DATA SHARING IN MISP

# SHARING IN MISP: DISTRIBUTION


MISP offers granular distribution settings:

- Organisation only
- This community
- Connected communities
- All communities
- Distribution lists - aka **Sharing groups**

Sharing Group						
Id	11					
Uuid	5e4b73c-05dc-4586-840f-5848a5c39e14					
Name	Banking sector in Europe					
Releasability	Banks located in Europe					
Description	Everything banking					
Selectable	✓					
Created by	Training					
Organisations				Instances		
Name	Local	Extend		Name	Url	All orgs
Training	✓	✓		Local Instance	https://lgloska.eu	✗
A-FUNKY-HUNGARIAN-BANK.hu	✓	✓		https://lgloska.eu	https://lgloska.eu	✗
AFB	✓	✗				
Italian Bank	✓	✗				
NCSC-NL	✗	✗				

At multiple levels: **Events, Attributes, Objects** (and their **Attributes**) and **Galaxy-clusters**

# SHARING IN MISP: DISTRIBUTION



# DATA LAYER

## ■ Data layer

- ▶ **Events** are encapsulations for contextually linked information
- ▶ **Attributes** are individual data points, which can be indicators or supporting data.
- ▶ **Objects** are custom templated Attribute compositions
- ▶ **Object references** are the relationships between individual building blocks
- ▶ **Shadow Attributes/Proposal** are suggestions made by users to modify an existing *attribute*
- ▶ **Sightings** are a means to convey that a data point has been seen
- ▶ **Event reports** are supporting materials for analysts to describe *events, processes, etc*

















# DATA LAYER: EVENTS


**Events** are encapsulations for contextually linked information

**Purpose:** Group datapoints and context together. Acting as an envelop, it allows setting distribution and sharing rules for itself and its children.

**Usecase:** Encode incidents / events / reports / ...

## IoT malware - Gafgyt.Gen28 (active) - 20190220 - 20190222

Event ID	178
UUID	5c6d21e5-bb60-47b7-b892-42e6950d2111 
Creator org	<a href="#">CIRCL</a>
Owner org	<a href="#">Training</a>
Creator user	andras.kiody@circl.lu
Tags	 <a href="#">tip:white</a>  <a href="#">osint:source-type="automatic-collection"</a>  <a href="#">circl:incident-classification="malware"</a>   <a href="#">adversary:infrastructure-action="take-down"</a>   
Date	2019-02-20
Threat Level	 Low
Analysis	Completed
Distribution	All communities  
Info	IoT malware - Gafgyt.Gen28 (active) - 20190220 - 20190222
Published	<b>Yes</b> (2020-11-28 07:53:39)
#Attributes	2601 (296 Objects)
First recorded change	2019-02-20 09:46:24
Last change	2020-10-10 07:36:28
Modification map	
Sightings	0 (0) - restricted to own organisation only 



# DATA LAYER: EVENTS

---

```
1 {  
2   "date": "2019-02-20",  
3   "info": "IoT malware — Gafgyt.Gen28 (active)",  
4   "uuid": "5c6d21e5-bb60-47b7-b892-42e6950d2111",  
5   "analysis": "2",  
6   "timestamp": "1602315388",  
7   "distribution": "3",  
8   "sharing_group_id": "0",  
9   "threat_level_id": "3",  
10  "extends_uuid": "",  
11  "Attribute": [...],  
12  "Object": [...],  
13  "EventReport": [...],  
14  "Tag": [...],  
15  "Galaxy": [...]  
16 }
```


---

# DATA LAYER: ATTRIBUTES


**Attributes** are individual data points, indicators or supporting data

**Purpose:** Individual data point. Can be an indicator or supporting data.

**Usecase:** Domain, IP, link, sha1, attachment, ...

« previous   next »   view all												
+ 			Filters: <b>All</b> File Network Financial Proposal Correlation									
Date	Org	Category	Type	Value	Comment	Related Events	IDS	Distribution	Actions			
2016-02-23		Network activity	domain	microsoft.com			No	Inherit	✖ 🔍 🗑			
2016-02-23		Network activity	domain	google.com		25	No	Inherit	✖ 🔍 🗑			
2016-02-23		Network activity	domain	circ.lju			No	Inherit	✖ 🔍 🗑			
2016-02-23		Network activity	ip-src	23.100.122.175	Derived from microsoft.com via the dns enrichment module.		No	Inherit	🔍 🗑			

# DATA LAYER: EVENT BUILDING BLOCKS - RAW DATA



# DATA LAYER: ATTRIBUTES

```
1 {  
2     "type": "url",  
3     "category": "Network activity",  
4     "to_ids": true,  
5     "uuid": "5c6d24bd-d094-4dd6-a1b6-4fa3950d2111",  
6     "event_id": "178",  
7     "distribution": "5",  
8     "sharing_group_id": "o",  
9     "timestamp": "1550656701",  
10    "comment": "Delivery point for the malware",  
11    "object_id": "o",  
12    "object_relation": null,  
13    "first_seen": null,  
14    "last_seen": null,  
15    "value": "ftp://185.135.80.163/",  
16    "Tag": [...]  
17    "Galaxy": [...]  
18 }
```

# DATA LAYER: MISP OBJECTS


**Objects** are custom templated Attribute compositions

**Purpose:** Groups Attributes that are intrinsically linked together

**Usecase:** File, person, credit-card, x509, device, ...

■	2018-03-27	Name: file ✓		
		References: 1 ✓ +		
□	2018-03-27	Payload delivery	filename: putty.exe	+
			filename	
□	2018-03-27	Other	size-in-bytes: 774200	+
			size-in-bytes	
□	2018-03-27	Other	entropy: 6.7264597226	+
			float	
□	2018-03-27	Payload delivery	md5: b6c12d88eeb910784d75a5e4df954001	+
			md5	
□	2018-03-27	Payload delivery	sha1: 5ef9515e8fd92a254dd2dcdd9c4b50afa8007b8f	+
			sha1	
□	2018-03-27	Payload delivery	sha256: 81de431987304676134138705fc1c21188ad7f27edf6b77a6551aa693194485e	+
			sha256	
□	2018-03-27	Payload delivery	sha512: e174ecf4fffb36d30c2cc66b37f82877d421244c924d5c9f39f2e0f37d85332b7d107d5ac5bd19cb7ffdcdbdd8b506d488faa30664ef610f62f3970c163cca76	+
			sha512	
□	2018-03-27	Payload delivery	malware-sample: putty.exe	+

# DATA LAYER: EVENT BUILDING BLOCKS - DATA COMPOSITION





# DATA LAYER: MISP OBJECTS


```
1 {  
2   "name": "elf-section",  
3   "meta-category": "file",  
4   "description": "Object describing a sect...",  
5   "template_uuid": "ca271f32-1234-4e87-b240-6b6e882de5de",  
6   "template_version": "4",  
7   "uuid": "ab5f0c85-5623-424c-bc03-d79841700d74",  
8   "timestamp": "1550655984",  
9   "distribution": "5",  
10  "sharing_group_id": "0",  
11  "comment": "",  
12  "first_seen": null,  
13  "last_seen": null,  
14  "ObjectReference": [],  
15  "Attribute": [...]  
16 }
```

# DATA LAYER: OBJECT REFERENCES

**Object references** are the relationships between individual building blocks

**Purpose:** Allows to create relationships between entities, thus creating a graph where they are the edges and entities are the nodes.


**Usecase:** Represent behaviours, similarities, affiliation, ...



# DATA LAYER: OBJECT REFERENCES

```
1 {  
2   "uuid": "5c6d21f9-0384-4bd2-b256-40de950d2111",  
3   "timestamp": "1602318569",  
4   "object_id": "1024",  
5   "source_uuid": "23275e05-c202-460e-aadf-819c417fb326",  
6   "referenced_uuid": "ab5foc85-5623-424c-bc03-d79841700d74",  
7   "referenced_type": "1",  
8   "relationship_type": "included-in",  
9   "comment": "Section 0 of ELF"  
10 }
```

# DATA LAYER: EVENT BUILDING BLOCKS - CONTEXT




# DATA LAYER: SIGHTINGS

**Sightings** are a means to convey that a data point has been seen

**Purpose:** Allows to add temporality to the data.

**Usecase:** Record activity or occurrence, perform IoC expiration, ...



The screenshot shows a table titled "Events" with three rows. Each row has a checkbox (all checked), a status (all "No"), and a "No Inherit" label. A tooltip is displayed over the first row, showing "Sightings" and "CIRCL: 2 (2017-03-19 16:17:59)". Below the table, there are some statistics: "(2/0/0)" and "(0/0/0)".

Events		
<input checked="" type="checkbox"/>	No	No Inherit
<input checked="" type="checkbox"/>	No	No Inherit
<input checked="" type="checkbox"/>	No	No Inherit

(2/0/0)

(0/0/0)


```
1 {  
2   "org_id": "1",  
3   "date_sighting": "1573722432",  
4   "uuid": "5dcd1940-5de8-4462-93dd-12a2a5e38e14",  
5   "source": "",  
6   "type": "o",  
7   "attribute_uuid": "5da97b59-9650-4be2-9443-2194a5e38e14"  
8 }
```

# DATA LAYER: EVENT REPORTS


**Event reports** are supporting data for analysis to describe events, processes, ect

**Purpose:** Supporting data point to describe events or processes

**Usecase:** Encode reports, provide more information about the Event, ...



# DATA LAYER: EVENT BUILDING BLOCKS - COLLABORATION & INTELLIGENCE



# DATA LAYER: EVENT REPORTS


---

```
1 {  
2   "uuid": "076e240b-5a76-4a8b-9eab-cfff551993dd",  
3   "event_id": "2127",  
4   "name": "Event report (1607362986)",  
5   "content": "...",  
6   "distribution": "5",  
7   "sharing_group_id": "o",  
8   "timestamp": "1607362986"  
9 }
```

---



# DATA LAYER: EVENT BUILDING BLOCKS - FULL



# CONTEXT LAYER

## ■ Context layer

- ▶ **Tags** are free-text labels attached to events/attributes and can come from **Taxonomies**
  - Android Malware, C2, ...
- ▶ **Taxonomies** are a set of common classification allowing to express the same vocabulary among a distributed set of users and organisations
  - `tlp:green, false-positive:risk="high", admiralty-scale:information-credibility="2"`

## ■ Context layer

- ▶ **Galaxies** are container composed of **Galaxy-clusters** that belongs to the same family
  - Similar to what **Events** are to **Attributes**
  - Country, Threat actors, Botnet, ...
- ▶ **Galaxy-clusters** are knowledge base items coming from **Galaxies**.
  - Basically a taxonomy with additional meta-information
  - `misp-galaxy:threat-actor="APT 29",`  
`misp-galaxy:country="luxembourg"`

# CONTEXT LAYER: TAGS

## Simple free-text labels

TLP AMBER

TLP:AMBER

Threat tlp:Amber

tlp-amber

tlp::amber

tlp:amber





```
1 {  
2   "name": "Android malware",  
3   "colour": "#22681c",  
4   "exportable": true,  
5   "numerical_value": null,  
6 }
```

# CONTEXT LAYER: TAXONOMIES

Simple label standardised on common set of vocabularies

**Purpose:** Enable efficient classification globally understood, easing consumption and automation.

**Usecase:** Provide classification such as: TLP, Confidence, Source, Workflows, Event type, ...

<input type="checkbox"/> Tag	Events	Attributes	Tags
<input type="checkbox"/> workflow:state="complete"	11	0	workflow:state="complete" 
<input type="checkbox"/> workflow:state="draft"	0	0	workflow:state="draft" 
<input type="checkbox"/> workflow:state="incomplete"	55	10	workflow:state="incomplete" 
<input type="checkbox"/> workflow:state="ongoing"	0	0	workflow:state="ongoing" 

# CONTEXT LAYER: TAXONOMIES

```
1 {
2   "Taxonomy": {
3     "namespace": "admiralty-scale",
4     "description": "The Admiralty Scale or Ranking (also called
5       the NATO System)...",
6     "version": "6",
7     "exclusive": false ,
8   },
9   "entries": [
10    {
11      "tag": "admiralty-scale:information-credibility=\"1\"",
12      "expanded": "Information Credibility: Confirmed by other
13        sources",
14      "numerical_value": 100,
15      "exclusive_predicate": true ,
16    },
17    ...
18  ]
19 }
```

# CONTEXT LAYER: GALAXIES

## Collections of galaxy clusters



### Threat Actor galaxy

Galaxy ID	8
Name	Threat Actor
Namespace	misp
UUID	698774c7-8022-42c4-917f-8d6e4f06ada3
Description	Threat actors are characteristics of malicious actors (or adversaries) representing a cyber attack threat including presumed intent and historically observed behaviour.
Version	3

[← previous](#) [next →](#)

All Default Custom 0 My Clusters Deleted View Fork Tree View Galaxy Relationships											
ID	Published	Value	Synonyms	Owner Org	Creator Org	Default	Activity	#Events	#Relations	Description	Distribution
7059	N/A	APT 29	Dukes, Group 100, Cozy Duke, EuroAPT, CozyBear, CozyCar, Cozer, Office Markhouse	MISP	MISP	✓	<div></div>	0	0 0 0	A 2015 report by F-Secure describe APT29 as: 'The Dukes are a well-resourced, highly dedicated and organized cyberespionage group that we believe has been working for the Russian Federation since at least 2008 to collect intelligence in support of foreign and security policy decision-making. The Dukes show unusual confidence in their ability to continue successfully compromising their	All communities



# CONTEXT LAYER: GALAXY CLUSTERS

Knowledge base items including a description, links, synonyms, meta-information and relationships

**Purpose:** Enable description of complex high-level information for classification

**Usecase:** Extensively describe elements such as threat actors, countries, technique used, ...

## Threat Actor :: APT 29

Cluster ID	2805
Name	APT 29
Parent Galaxy	Threat Actor
Description	A 2015 report by F-Secure describe APT29 as: "The Dukes are a well-resourced, highly dedicated and organized cyberespionage group that we believe has been working for the Russian Federation..."
Published	No
Default	Yes
Version	190
UUID	b2056ff0-00b9-482e-b11c-c771daa5f28a
Collection UUID	7cdf1317-a673-4474-84ec-4f1754947823
Source	MISP Project
Authors	Alexandre Dulaioy, Florian Roth, Thomas Schreck, Timo Steffens, Various
Distribution	All communities
Owner Organisation	<a href="#">MISP</a>
Creator Organisation	<a href="#">MISP</a>
Connector tag	misp-galaxy-threat-actor="APT 29"
Events	0
Forked From	
Forked By	

# CONTEXT LAYER: GALAXY CLUSTERS

## Galaxy cluster elements: Tabular view

Tabular view JSON view		
Key ↓	Value	Actions
attribution-confidence	50	
cfr-suspected-state-sponsor	Russian Federation	
cfr-suspected-victims	United States	
cfr-suspected-victims	China	
cfr-suspected-victims	New Zealand	

## Galaxy cluster elements: JSON view

Tabular view JSON view + Add JSON as cluster's elements		
<pre>{   "attribution-confidence": [     "50"   ],   "cfr-suspected-state-sponsor": [     "Russian Federation"   ],   "cfr-suspected-victims": [     "United States",     "China",     "New Zealand",     "Ukraine",   ] }</pre>		

# CONTEXT LAYER: GALAXY CLUSTERS

```
1 {  
2   "uuid": "5edaoa53-1d98-4d01-ae06-4odaoa0002of",  
3   "type": "fellowship-characters",  
4   "value": "Aragorn wielding Anduril",  
5   "tag_name": "misp-galaxy:fellowship-characters=\"c3fe907a-6a36  
6     -4cd1-9456-dcdf35c3f907\"",  
7   "description": "The Aragorn character wielding Anduril",  
8   "source": "Middle-earth universe by J. R. R. Tolkien",  
9   "authors": null,  
10  "version": "1591347795",  
11  "distribution": "o",  
12  "sharing_group_id": null,  
13  "default": false,  
14  "extends_uuid": "5edao117-1e14-4boa-9e26-34aff331dc3b",  
15  "extends_version": "1591345431",  
16  "GalaxyElement": [...],  
17  "GalaxyClusterRelation": [...]  
18 }
```

# CONTEXT LAYER: GALAXIES & GALAXY CLUSTERS

- MISP integrates MITRE's Adversarial Tactics, Techniques, and Common Knowledge (ATT&CK) and similar **Galaxy Matrix**
- MISP terminology of these matrixes: **Galaxy Matrix**

Enterprise Attack - Attack Pattern										
Initial access	Execution	Persistence	Privilege escalation	Defense evasion	Credential access	Discovery	Lateral movement	Collection	Exfiltration	Command and control
Spearfishing Attachment	Scripting	Screensaver	File System Permissions Weakness	Process Hollowing	Secured Memory	Password Policy Discovery	AppleScript	Data from Information Repositories	Exfiltration Over Alternative Protocol	Standard Application Layer Protocol
Spearfishing via Service	Command-Line Interface	Login Item	AppCert DLLs	Code Signing	Input Capture	System Network Configuration Discovery	Distributed Component Object Model	Data from Removable Media	Exfiltration Over Command and Control Channel	Communication Through Removable Media
Trusted Relationship	User Execution	Trap	Application Shimming	Rootkit	Bash History	Process Discovery	Pass the Hash	Man in the Browser	Data Compressed	Custom Command and Control Protocol
Replication Through Removable Media	Regsvcs/Regasm	System Firmware	Scheduled Task	NTFS File Attributes	Exploitation for Credential Access	Network Share Discovery	Exploitation of Remote Services	Data Staged	Automated Exfiltration	Multi-Stage Channels
Exploit Public-Facing Application	Trusted Developer Utilities	Registry Run Keys / Start Folder	Startup Items	Exploitation for Defense Evasion	Private Keys	Peripheral Device Discovery	Remote Desktop Protocol	Screen Capture	Scheduled Transfer	Remote Access Tools
Spearfishing Link	Windows Management Instrumentation	LC_LOAD_DYLIB Addition	New Service	Network Share Connection Removal	Brute Force	Account Discovery	Pass the Ticket	Email Collection	Data Encrypted	Uncommonly Used Port
Valid Accounts	Service Execution	LSASS Driver	Sudo Caching	Process Doppelganging	Password Filter DLL	System Information Discovery	Windows Remote Management	Clipboard Data	Exfiltration Over Other Network Medium	Multilayer Encryption
Supply Chain Compromise	CMSTP	Rccommon	Process Injection	Disabling Security Tools	Two-Factor Authentication Interception	System Network Connections Discovery	Windows Admin Shares	Video Capture	Exfiltration Over Physical Medium	Domain Fronting
Drive-by Compromise	Control Panel Items	Authentication Package	Bypass User Account Control	Timestamp	LLMNR/NBT-NS Poisoning	Network Service Scanning	Remote Services	Audio Capture	Data Transfer Size Limits	Data Obfuscation
Hardware Additions	Dynamic Data Exchange	Component Firmware	Extra Window Memory Injection	Modify Registry	Credentials in Files	File and Directory Discovery	Taint Shared Content	Data from Network Shared Drive		Connection Proxy
	Source	Windows Management Instrumentation Event Subscription	Setuid and Setgid	Indicator Removal from Tools	Forced Authentication	Security Software Discovery	Application Deployment Software	Data from Local System		Commonly Used Port
	Space after Filename	Change Default File	Launch Daemon	Hidden Window	Keychain	System Service Discovery	Third-party Software	Automated Collection		Data Encoding

# GALAXY JSON MATRIX-LIKE

```
1 {
2   "description": "Universal Development and Security Guidelines as
   Applicable to Election Technology.",
3   "icon": "map",
4   "kill_chain_order": {           \\Tab in the matrix
5     "example-of-threats": [       \\Column in the matrix
6       "setup | party/candidate-registration",
7       "setup | electoral-rolls",
8       "campaign | campaign-IT",
9       "all-phases | governement-IT",
10      "voting | election-technology",
11      "campaign/public-communication | media/press"
12    ]
13  },
14  "name": "Election guidelines",
15  "namespace": "misp",
16  "type": "guidelines",
17  "uuid": "c1dco3b2-89b3-42a5-9d41-782ef726435a",
18  "version": 1
19 }
```

# CLUSTER JSON MATRIX-LIKE

```
1 {
2     "description": "DoS or overload of party/campaign
3     registration, causing them to miss the deadline",
4     "meta": {
5         "date": "March 2018.",
6         "kill_chain": [ \\Define in which column the cluster should be placed
7             "example-of-threats:setup | party/candidate-registration"
8         ],
9         "refs": [
10             "https://www.ria.ee/sites/default/files/content-editors/
11             kuberturve/cyber_security_of_election_technology.pdf"
12         ]
13     },
14     "uuid": "154c6186-a007-4460-a029-ea23163448fe",
15     "value": "DoS or overload of party/campaign registration,
16             causing them to miss the deadline"
```

# EXPRESSING RELATION BETWEEN CLUSTERS

- Cluster can be related to one or more clusters using default relationships from MISP objects and a list of tags to classify the relation.

---

```
1      "related": [  
2      {  
3          "dest-uuid": "5ce5392a-3a6c-4e07-9df3-9b6a9159ac45",  
4          "tags": [  
5              "estimative-language:likelihood-probability=\"likely\""  
6          ],  
7          "type": "similar"  
8      }  
9  ],  
10     "uuid": "oca45163-e223-4167-b1af-f088ed14a93d",  
11     "value": "Putter Panda"
```

---

- Supported by the grant 2018-LU-IA-0148



**Co-financed by the European Union**

Connecting Europe Facility