mail\_to\_misp





# MAIL\_TO\_MISP

CONNECT YOUR MAIL INFRASTRUCTURE TO MISP TO

CIRCL / TEAM MISP PROJECT

HTTP://www.misp-project.org/ Twitter: @MISPProject

**NSPA** 



## **CONTEXT**

- You receive emails with IoC's inside
- How to create an event out of it?
- Create event manually and copy paste
- → This works once or twice
- Forwarding the email would be nice
- $\blacksquare$   $\rightarrow$  mail\_to\_misp

mail\_to\_misp

### Wor receive emails with InC's inside
### wor create an event out of it?
### Context

### Context
### Context
### In The Incident Inciden

### FEATURES: EMAIL HANDLING

- Extraction of URLs and IP addresses and port numbers
- Extraction of hostnames from URLs
- Extraction of hashes (MD5, SHA1, SHA256)
- DNS expansion
- Subject filters
- Refanging of URLs ('hxxp://...')
- ... and more

mail\_to\_misp ■ DNS expansion Subject filters Features: Email handling ■ Refanging of URLs ('hxxp://...') ... and more

2022-08

# FEATURES: SUPPORT MISP FEATURES

- Add tags automatically
- Ignore 'whitelisted' domains
- Configurable list of attributes not to enable the IDS flag
- DNS expansion
- Automatically create 'external analysis' links based on filter list (e.g. VirusTotal, malwr.com)
- Automatically filter out attributes that are on a server side warning list
- Support for value sighting
- ... and more

က္ mail\_to\_misp

-Features: Support MISP features

# Add tags automatically

■ Configurable list of attributes not to enable the IDS flag

■ Support for value sighting

... and more

#### **IMPLEMENTATION**

### Legacy

- ightharpoonup Email ightarrow Apple Mail ightharpoonup Mail rule ightharpoonup Apple Script o AppleScript o mail\_to\_misp o PyMISP o MISP
- ► Email  $\rightarrow$  Thunderbird  $\rightarrow$  Mail rule  $\rightarrow$  filterscript  $\rightarrow$  $thunderbird\_wrapper \rightarrow mail\_to\_misp \rightarrow PyMISP \rightarrow MISP$
- Postfix and others
  - ► Email → mail\_to\_misp

က္က mail\_to\_misp thunderbird\_wrapper → mail\_to\_misp → PyMISP → MISP -Implementation Postfix and others

2022-

#### INSTALLATION

- mail\_to\_misp
  - 1. git clone
     git://github.com/MISP/mail to misp.git
  - 2. Install dependencies See Github site
- MTA (Postfix or alike)
  - 1. Setup a new email address in the aliases file (e.g.
     /etc/aliases)
     misp\_handler: "|/path/to/mail\_to\_misp.py -"
  - 2. Rebuild the DB sudo newaliases
  - 3. Configure mail\_to\_misp\_config.py

```
misp_url = 'http://127.o.o.1/'
misp_key = 'ssjPWClud36Z8XHgsiCVI7SaL1XsMTyfEsN45tTe'
misp_verifycert = True
body_config_prefix = 'm2m'
...
```

# EXERCISE: MAIL\_2\_MISP.PY

#### Bonus:

```
https://github.com/MISP/mail to misp test
./ mail_to_misp.py -r mail_to_misp_test/simple_forward.eml
```

#### ■ Bonus: Fake-SMTPD spamtrap

```
./fake_smtp.py
telnet 127.0.0.1 2526
   Trying 127.0.0.1...
   Connected to 127.0.0.1.
   Escape character is '^]'.
   220 misp Python SMTP 1.1
   helo misp
   250 misp
   mail from: mikel
   250 OK
   rcpt to: m2m
   250 OK
   data
   354 End data with <CR><LF>. <CR><LF>
```

mail\_to\_misp -Exercise: mail\_2\_misp.py

2022-