

# MISP CLI

AUTOMATE ALL THE THINGS

CIRCL / TEAM MISP PROJECT



NSPA

2022-08-03

MISP CLI

MISP CLI

AUTOMATE ALL THE THINGS

CIRCL / TEAM MISP PROJECT



NSPA

- The MISP API is great for remotely executing administrative tasks
- But sometimes we want to simplify the process / avoid having to deal with authentication
- MISP also has an extensive CLI sub-system for this reason

### └─ MISP CLI functionalities

- The MISP API is great for remotely executing administrative tasks
- But sometimes we want to simplify the process / avoid having to deal with authentication
- MISP also has an extensive CLI sub-system for this reason

# TYPES OF OBJECTIVES FOR THE SCRIPTS

- Automating recurring tasks
- Recovery from loss of access
- Updates / initialisation
- Background worker management

2022-08-03

MISP CLI

└ Types of objectives for the scripts

- Automating recurring tasks
- Recovery from loss of access
- Updates / initialisation
- Background worker management

■ <https://path.to.your.misp/events/automation>

## Administering the background workers via the API.

You can start/stop and view the background workers via the API.

Add worker: `http://localhost:5001/servers/startWorker/[queue_name]`

Stop worker: `http://localhost:5001/servers/stopWorker/[worker_pid]`

Get worker info: `http://localhost:5001/servers/getWorkers`

## Administering MISP via the CLI

Certain administrative tasks are exposed to the API, these help with maintaining and configuring MISP in an automated way / via external tools.:

Get Setting: `MISP/app/Console/cake Admin getSetting [setting]`

Set Setting: `MISP/app/Console/cake Admin setSetting [setting] [value]`

Get Authkey: `MISP/app/Console/cake Admin getAuthkey [email]`

Set Baseurl: `MISP/app/Console/cake Admin setBaseurl [baseurl]`

Change Password: `MISP/app/Console/cake Admin setPassword [email] [new_password] [--override_password_change]`

Clear Bruteforce Entries: `MISP/app/Console/cake Admin clearBruteforce [user_email]`

Run Database Update: `MISP/app/Console/cake Admin updateDatabase`

Update All JSON Structures: `MISP/app/Console/cake Admin updateJSON`

Update Galaxy Definitions: `MISP/app/Console/cake Admin updateGalaxies`

Update Taxonomy Definitions: `MISP/app/Console/cake Admin updateTaxonomies`

Update Object Templates: `MISP/app/Console/cake Admin updateObjectTemplates`

Update Warninglists: `MISP/app/Console/cake Admin updateWarningLists`

└─ CLI documentation

■ <https://path.to.your.misp/events/automation>

## Administering the background workers via the API.

You can start/stop and view the background workers via the API.

Add worker: `http://localhost:5001/servers/startWorker/[queue_name]`

Stop worker: `http://localhost:5001/servers/stopWorker/[worker_pid]`

Get worker info: `http://localhost:5001/servers/getWorkers`

## Administering MISP via the CLI

Certain administrative tasks are exposed to the API, these help with maintaining and configuring MISP in an automated way / via external tools.:

Get Setting: `MISP/app/Console/cake Admin getSetting [setting]`

Set Setting: `MISP/app/Console/cake Admin setSetting [setting] [value]`

Get Authkey: `MISP/app/Console/cake Admin getAuthkey [email]`

Set Baseurl: `MISP/app/Console/cake Admin setBaseurl [baseurl]`

Change Password: `MISP/app/Console/cake Admin setPassword [email] [new_password] [--override_password_change]`

Clear Bruteforce Entries: `MISP/app/Console/cake Admin clearBruteforce [user_email]`

Run Database Update: `MISP/app/Console/cake Admin updateDatabase`

Update All JSON Structures: `MISP/app/Console/cake Admin updateJSON`

Update Galaxy Definitions: `MISP/app/Console/cake Admin updateGalaxies`

Update Taxonomy Definitions: `MISP/app/Console/cake Admin updateTaxonomies`

Update Object Templates: `MISP/app/Console/cake Admin updateObjectTemplates`

Update Warninglists: `MISP/app/Console/cake Admin updateWarningLists`

`/var/www/MISP/app/Console/cake [Shell] [Command]  
[parameters]`

■ Example:

- ▶ `/var/www/MISP/app/Console/cake Password "andras.iklody@gmail.com" "Nutella"`
- ▶ Change password to "Nutella" for my user
- ▶ Some shells are single use and don't need a command parameter

■ Also used by the background processing

■ Automation is meant to be used via cron jobs

### Usage

```
/var/www/MISP/app/Console/cake [Shell] [Command]  
[parameters]  
■ Example:  
  ▶ /var/www/MISP/app/Console/cake Password  
    "andras.iklody@gmail.com" "Nutella"  
  ▶ Change password to "Nutella" for my user  
  ▶ Some shells are single use and don't need a command  
    parameter  
■ Also used by the background processing  
■ Automation is meant to be used via cron jobs
```

- Edit crontab of www-data user
- `crontab -u www-data -e`
- `0 3,9,15,21 * * *`  
`/var/www/MISP/app/Console/cake Server pull 1`  
`30 full`
- Pull server ID #30 as user #1 every 6 hours
- `@hourly /var/www/MISP/app/Console/cake Server`  
`cacheFeed 1 csv full`
- Cache all csv feeds as user #1 every hour

2022-08-03

MISP CLI

└ Automation via crontab

AUTOMATION VIA CRONTAB

```
■ Edit crontab of www-data user
■ crontab -u www-data -e
■ 0 3,9,15,21 * * *
  /var/www/MISP/app/Console/cake Server pull 1
  30 full
■ Pull server ID #30 as user #1 every 6 hours
■ @hourly /var/www/MISP/app/Console/cake Server
  cacheFeed 1 csv full
■ Cache all csv feeds as user #1 every hour
```