

MISP Objects

MISP Objects

Introduction	1
Funding and Support	2
MISP objects	3
ail-leak	3
android-permission	4
annotation	7
asn	8
av-signature	9
bank-account	10
cap-alert	13
cap-info	16
cap-resource	19
coin-address	19
cookie	20
course-of-action	21
cowrie	22
credential	24
credit-card	25
ddos	26
diameter-attack	27
domain-ip	28
elf	28
elf-section	31
email	33
fail2ban	35
file	35
geolocation	37
gtp-attack	38
http-request	39
ip-port	41
ja3	41
legal-entity	42
macho	43
macho-section	43
microblog	44
mutex	45
netflow	46
passive-dns	47

paste	49
pe	50
pe-section	51
person	52
phone	54
r2graphity	56
regex	58
registry-key	59
report	61
rtir	61
sandbox-report	62
sb-signature	63
ss7-attack	64
stix2-pattern	66
suricata	66
target-system	67
timesketch-timeline	67
timestamp	68
tor-node	68
transaction	70
url	71
victim	72
virustotal-report	74
vulnerability	75
whois	76
x509	77
yabin	78
yara	79
Relationships	79

Introduction



The MISP threat sharing platform is a free and open source software helping information sharing of threat intelligence including cyber security indicators, financial fraud or counter-terrorism information. The MISP project includes multiple sub-projects to support the operational requirements of analysts and improve the overall quality of information shared.

MISP objects are used in MISP (starting from version 2.4.80) system and can be used by other information sharing tool. MISP objects are in addition to MISP attributes to allow advanced combinations of attributes. The creation of these objects and their associated attributes are based on real cyber security use-cases and existing practices in information sharing. The objects are just shared like any other attributes in MISP even if the other MISP instances don't have the template of the object. The following document is generated from the machine-readable JSON describing the [MISP objects](#).

Funding and Support

The MISP project is financially and resource supported by [CIRCL Computer Incident Response Center Luxembourg](#).



A CEF (Connecting Europe Facility) funding under CEF-TC-2016-3 - Cyber Security has been granted from 1st September 2017 until 31th August 2019 as **Improving MISP as building blocks for next-generation information sharing**.



Co-financed by the European Union

Connecting Europe Facility

If you are interested to co-fund projects around MISP, feel free to get in touch with us.

MISP objects

ail-leak

An information leak as defined by the AIL Analysis Information Leak framework..



ail-leak is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
origin	text	The link where the leak is (or was) accessible at first-seen.	—
original-date	datetime	When the information available in the leak was created. It's usually before the first-seen.	✓
duplicate_number	counter	Number of known duplicates.	—
sensor	text	The AIL sensor uuid where the leak was processed and analysed.	—
raw-data	attachment	Raw data as received by the AIL sensor compressed and encoded in Base64.	✓
type	text	Type of information leak as discovered and classified by an AIL module. ['Credential', 'CreditCards', 'Mail', 'Onion', 'Phone', 'Keys']	—

Object attribute	MISP attribute type	Description	Disable correlation
text	text	A description of the leak which could include the potential victim(s) or description of the leak.	✓
last-seen	datetime	When the leak has been accessible or seen for the last time.	✓
first-seen	datetime	When the leak has been accessible or seen for the first time.	✓
duplicate	text	Duplicate of the existing leaks.	—

android-permission

A set of android permissions - one or more permission(s) which can be linked to other objects (e.g. malware, app)..



android-permission is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
permission	text	Android permission ['ACCESS_CHECKIN_PROPERTIES', 'ACCESS_COARSE_LOCATION', 'ACCESS_FINE_LOCATION', 'ACCESS_LOCATION_EXTRA_COMMANDS', 'ACCESS_NETWORK_STATE', 'ACCESS_NOTIFICATION_POLICY', 'ACCESS_WIFI_STATE', 'ACCOUNT_MANAGER', 'ADD_VOICEMAIL', 'ANSWER_PHONE_CALLS', 'BATTERY_STATS', 'BIND_ACCESSIBILITY_SERVICE', 'BIND_APPWIDGET', 'BIND_AUTOFILL_SERVICE', 'BIND_CARRIER_MESSAGING_SERVICE', 'BIND_CHOOSER_TARGET_SERVICE', 'BIND_CONDITION_PROVIDER_SERVICE', 'BIND_DEVICE_ADMIN', 'BIND_DREAM_SERVICE', 'BIND_INCALL_SERVICE', 'BIND_INPUT_METHOD', 'BIND_MIDI_DEVICE_SERVICE', 'BIND_NFC_SERVICE', 'BIND_NOTIFICATION_LISTENER_SERVICE', 'BIND_PRINT_SERVICE', 'BIND_QUICK_SETTINGS_TILE', 'BIND_REMOTEVIEWS', 'BIND_SCREENING_SERVICE', 'BIND_TELECOM_CONNECTIONS']	—

Object attribute	MISP attribute type	Description	Disable correlation
comment	comment	Comment about the set of android permission(s)	—

annotation

An annotation object allowing analysts to add annotations, comments, executive summary to a MISP event, objects or attributes..



annotation is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
modification-date	datetime	Last update of the annotation	—
creation-date	datetime	Initial creation of the annotation	—
format	text	Format of the annotation ['text', 'markdown', 'asciidoc', 'MultiMarkdown', 'GFM', 'pandoc', 'Fountain', 'CommonWork', 'kramdown-rfc2629', 'rfc7328', 'Extra']	✓
ref	link	Reference(s) to the annotation	—

'CHANGE_WIFI_MULTICAST_STATE',
'CHANGE_WIFI_STATE',
'CLEAR_APP_CACHE',
'CONTROL_LOCATION_UPDATES',
'DELETE_CACHE_FILES',
'DELETE_PACKAGES',
'DIAGNOSTIC',
'DISABLE_KEYGUARD',
'DUMP',
'EXPAND_STATUS_BAR',
'FACTORY_TEST',

Object attribute	MISP attribute type	Description	Disable correlation
type	text	Type of the annotation ['Annotation', 'Executive Summary', 'Introduction', 'Conclusion', 'Disclaimer', 'Keywords', 'Acknowledgement', 'Other', 'Copyright', 'Authors', 'Logo']	✓
text	text	Raw text of the annotation	—

asn

Autonomous system object describing an autonomous system which can include one or more network operators management an entity (e.g. ISP) along with their routing policy, routing prefixes or alike..



asn is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
asn	AS	Autonomous System Number	—
import	text	The inbound IPv4 routing policy of the AS in RFC 2622 – Routing Policy Specification Language (RPSL) format	—
mp-import	text	The inbound IPv4 or IPv6 routing policy of the AS in RFC 4012 – Routing Policy Specification Language next generation (RPSLng), section 4.5. format	—

Object attribute	MISP attribute type	Description	Disable correlation
subnet-announced	ip-src	Subnet announced	—
export	text	The outbound routing policy of the AS in RFC 2622 – Routing Policy Specification Language (RPSL) format	—
mp-export	text	This attribute performs the same function as the export attribute above. The difference is that mp-export allows both IPv4 and IPv6 address families to be specified. The export is described in RFC 4012 – Routing Policy Specification Language next generation (RPSLng), section 4.5. format	—
last-seen	datetime	Last time the ASN was seen	✓
description	text	Description of the autonomous system	—
first-seen	datetime	First time the ASN was seen	✓
country	text	Country code of the main location of the autonomous system	—

av-signature

Antivirus detection signature.



av-signature is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

'SET_WALLPAPER',
'SET_WALLPAPER_HINTS',
'SIGNAL_PERSISTENT_PROCESSES',
'STATUS_BAR',
'SYSTEM_ALERT_WINDOW',
'TRANSMIT_IR',
'UNINSTALL_SHORTCUT',
'UPDATE_DEVICE_STAT

Object attribute	MISP attribute type	Description	Disable correlation
signature	text	Name of detection signature	—
software	text	Name of antivirus software	✓
text	text	Free text value to attach to the file	✓
datetime	datetime	Datetime	✓

bank-account

An object describing bank account information based on account description from goAML 4.0..



bank-account is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
institution-name	text	Name of the bank or financial organisation.	✓
beneficiary-comment	text	Comment about the final beneficiary.	✓
swift	bic	SWIFT or BIC as defined in ISO 9362.	✓
institution-code	text	Institution code of the bank.	✓
iban	iban	IBAN of the bank account.	—
personal-account-type	text	Account type. ['A - Business', 'B - Personal Current', 'C - Savings', 'D - Trust Account', 'E - Trading Account', 'O - Other']	✓

Object attribute	MISP attribute type	Description	Disable correlation
client-number	text	Client number as seen by the bank.	—
aba-rtn	aba-rtn	ABA routing transit number	—
comments	text	Comments about the bank account.	✓
date-balance	datetime	When the balance was reported.	✓
account-name	text	A field to freely describe the bank account details.	—
currency-code	text	Currency of the account. ['USD', 'EUR']	✓
non-banking-institution	boolean	A flag to define if this account belong to a non-banking organisation. If set to true, it's a non-banking organisation.	✓
branch	text	Branch code or name	✓
opened	datetime	When the account was opened.	✓
text	text	A description of the bank account.	✓
balance	text	The balance of the account after the suspicious transaction was processed.	✓
closed	datetime	When the account was closed.	✓

Object attribute	MISP attribute type	Description	Disable correlation
report-code	text	Report code of the bank account. ['CTR Cash Transaction Report', 'STR Suspicious Transaction Report', 'EFT Electronic Funds Transfer', 'IFT International Funds Transfer', 'TFR Terror Financing Report', 'BCR Border Cash Report', 'UTR Unusual Transaction Report', 'AIF Additional Information File – Can be used for example to get full disclosure of transactions of an account for a period of time without reporting it as a CTR.', 'IRI Incoming Request for Information – International', 'ORI Outgoing Request for Information – International', 'IRD Incoming Request for Information – Domestic', 'ORD Outgoing Request for Information – Domestic']	✓
account	bank-account-nr	Account number	–
beneficiary	text	Final beneficiary of the bank account.	✓
status-code	text	Account status at the time of the transaction processed. ['A - Active', 'B - Inactive', 'C - Dormant']	✓

cap-alert

Common Alerting Protocol Version (CAP) alert object.



cap-alert is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
note	text	The text describing the purpose or significance of the alert message.	✓
status	text	The code denoting the appropriate handling of the alert message. ['Actual', 'Exercise', 'System', 'Test', 'Draft']	—
incident	text	The group listing naming the referent incident(s) of the alert message. (1) Used to collate multiple messages referring to different aspects of the same incident. (2) If multiple incident identifiers are referenced, they SHALL be separated by whitespace. Incident names including whitespace SHALL be surrounded by double-quotes.	✓
sent	datetime	The time and date of the origination of the alert message.	✓

Object attribute	MISP attribute type	Description	Disable correlation
identifier	text	The identifier of the alert message in a number or string uniquely identifying this message, assigned by the sender.	✓
addresses	text	The group listing of intended recipients of the alert message. (1) Required when <scope> is “Private”, optional when <scope> is “Public” or “Restricted”. (2) Each recipient SHALL be identified by an identifier or an address. (3) Multiple space-delimited addresses MAY be included. Addresses including whitespace MUST be enclosed in double-quotes.	✓
scope	text	The code denoting the intended distribution of the alert message. ['Public', 'Restricted', 'Private']	✓

Object attribute	MISP attribute type	Description	Disable correlation
references	text	The group listing identifying earlier message(s) referenced by the alert message. (1) The extended message identifier(s) (in the form sender,identifier,sent) of an earlier CAP message or messages referenced by this one. (2) If multiple messages are referenced, they SHALL be separated by whitespace.	✓
source	text	The text identifying the source of the alert message. The particular source of this alert; e.g., an operator or a specific device.	✓
msgType	text	The code denoting the nature of the alert message. ['Alert', 'Update', 'Cancel', 'Ack', 'Error']	✓
restriction	text	The text describing the rule for limiting distribution of the restricted alert message.	✓
code	text	The code denoting the special handling of the alert message.	✓

Object attribute	MISP attribute type	Description	Disable correlation
sender	text	The identifier of the sender of the alert message which identifies the originator of this alert. Guaranteed by assigner to be unique globally; e.g., may be based on an Internet domain name.	✓

cap-info

Common Alerting Protocol Version (CAP) info object.



cap-info is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
senderName	text	The text naming the originator of the alert message.	✓
description	text	The text describing the subject event of the alert message.	✓
eventCode	text	A system-specific code identifying the event type of the alert message.	✓
responseType	text	The code denoting the type of action recommended for the target audience. ['Shelter', 'Evacuate', 'Prepare', 'Execute', 'Avoid', 'Monitor', 'Assess', 'AllClear', 'None']	✓

Object attribute	MISP attribute type	Description	Disable correlation
language	text	The code denoting the language of the info sub-element of the alert message.	✓
web	link	The identifier of the hyperlink associating additional information with the alert message.	✓
severity	text	The code denoting the severity of the subject event of the alert message. ['Extreme', 'Severe', 'Moderate', 'Minor', 'Unknown']	✓
category	text	The code denoting the category of the subject event of the alert message. ['Geo', 'Met', 'Safety', 'Security', 'Rescue', 'Fire', 'Health', 'Env', 'Transport', 'Infra', 'CBRNE', 'Other']	✓
event	text	The text denoting the type of the subject event of the alert message.	✓
certainty	text	The code denoting the certainty of the subject event of the alert message. For backward compatibility with CAP 1.0, the deprecated value of “Very Likely” SHOULD be treated as equivalent to “Likely”. ['Likely', 'Possible', 'Unlikely', 'Unknown']	✓

Object attribute	MISP attribute type	Description	Disable correlation
audience	text	The text describing the intended audience of the alert message.	✓
instruction	text	The text describing the recommended action to be taken by recipients of the alert message.	✓
urgency	text	The code denoting the urgency of the subject event of the alert message. ['Immediate', 'Expected', 'Future', 'Past', 'Unknown']	✓
expires	datetime	The expiry time of the information of the alert message.	✓
effective	datetime	The effective time of the information of the alert message.	✓
parameter	text	A system-specific additional parameter associated with the alert message.	✓
onset	datetime	The expected time of the beginning of the subject event of the alert message.	✓
headline	text	The text headline of the alert message.	✓
contact	text	The text describing the contact for follow-up and confirmation of the alert message.	✓

cap-resource

Common Alerting Protocol Version (CAP) resource object.



cap-resource is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
uri	link	The identifier of the hyperlink for the resource file.	—
derefUri	attachment	The base-64 encoded data content of the resource file.	✓
size	text	The integer indicating the size of the resource file.	✓
digest	sha1	The code representing the digital digest (“hash”) computed from the resource file (OPTIONAL).	—
resourceDesc	text	The text describing the type and content of the resource file.	✓
contentType	mime-type	The identifier of the MIME content type and sub-type describing the resource file.	✓

coin-address

An address used in a cryptocurrency.



coin-address is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
text	text	Free text value	✓
address	btc	Address used as a payment destination in a cryptocurrency	—
last-seen	datetime	Last time this payment destination address has been seen	✓
first-seen	datetime	First time this payment destination address has been seen	✓
symbol	text	The (uppercase) symbol of the cryptocurrency used. Symbol should be from https://coinmarketcap.com/all/views/all/ ['BTC', 'ETH', 'BCH', 'XRP', 'MIOTA', 'DASH', 'BTG', 'LTC', 'ADA', 'XMR', 'ETC', 'NEO', 'NEM', 'EOS', 'XLM', 'BCC', 'LSK', 'OMG', 'QTUM', 'ZEC', 'USDT', 'HSR', 'STRAT', 'WAVES', 'PPT']	✓

cookie

An HTTP cookie (web cookie, browser cookie) is a small piece of data that a server sends to the user's web browser. The browser may store it and send it back with the next request to the same server. Typically, it's used to tell if two requests came from the same browser — keeping a user logged-in, for example. It remembers stateful information for the stateless HTTP protocol. (as defined by the Mozilla foundation..



cookie is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
cookie-value	text	Value of the cookie (if splitted)	—
type	text	Type of cookie and how it's used in this specific object. ['Session management', 'Personalization', 'Tracking', 'Exfiltration', 'Malicious Payload', 'Beaconing']	—
text	text	A description of the cookie.	✓
cookie	cookie	Full cookie	—
cookie-name	text	Name of the cookie (if splitted)	—

course-of-action

An object describing a specific measure taken to prevent or respond to an attack..



course-of-action is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
cost	text	The estimated cost of applying the course of action. ['High', 'Medium', 'Low', 'None', 'Unknown']	✓
stage	text	The stage of the threat management lifecycle that the course of action is applicable to. ['Remedy', 'Response']	✓

Object attribute	MISP attribute type	Description	Disable correlation
name	text	The name used to identify the course of action.	✓
efficacy	text	The estimated efficacy of applying the course of action. ['High', 'Medium', 'Low', 'None', 'Unknown']	✓
type	text	The type of the course of action. ['Perimeter Blocking', 'Internal Blocking', 'Redirection', 'Redirection (Honey Pot)', 'Hardening', 'Patching', 'Eradication', 'Rebuilding', 'Training', 'Monitoring', 'Physical Access Restrictions', 'Logical Access Restrictions', 'Public Disclosure', 'Diplomatic Actions', 'Policy Actions', 'Other']	✓
impact	text	The estimated impact of applying the course of action. ['High', 'Medium', 'Low', 'None', 'Unknown']	✓
description	text	A description of the course of action.	✓
objective	text	The objective of the course of action.	✓

cowrie

Cowrie honeypot object template.



cowrie is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
password	text	Password	—
input	text	Input of the session	—
username	text	Username related to the password(s)	—
sensor	text	Cowrie sensor name	✓
isError	text	isError	✓
macCS	text	SSH MAC supported in the session	✓
message	text	Message of the cowrie honeypot	✓
src_ip	ip-src	Source IP address of the session	—
eventid	text	Eventid of the session in the cowrie honeypot	✓
dst_ip	ip-dst	Destination IP address of the session	✓
session	text	Session id	—
encCS	text	SSH symmetric encryption algorithm supported in the session	✓
src_port	port	Source port of the session	✓
keyAlgs	text	SSH public-key algorithm supported in the session	✓

Object attribute	MISP attribute type	Description	Disable correlation
dst_port	port	Destination port of the session	✓
system	text	System origin in cowrie honeypot	✓
compCS	text	SSH compression algorithm supported in the session	✓
timestamp	datetime	When the event happened	✓
protocol	text	Protocol used in the cowrie honeypot	✓

credential

Credential describes one or more credential(s) including password(s), api key(s) or decryption key(s)..



credential is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
password	text	Password	—
username	text	Username related to the password(s)	—
format	text	Format of the password(s) ['clear-text', 'hashed', 'encrypted', 'unknown']	—
notification	text	Mention of any notification(s) towards the potential owner(s) of the credential(s) ['victim-notified', 'service-notified', 'none']	—

Object attribute	MISP attribute type	Description	Disable correlation
type	text	Type of password(s) ['password', 'api-key', 'encryption-key', 'unknown']	—
text	text	A description of the credential(s)	✓
origin	text	Origin of the credential(s) ['bruteforce-scanning', 'malware-analysis', 'memory-analysis', 'network-analysis', 'leak', 'unknown']	—

credit-card

A payment card like credit card, debit card or any similar cards which can be used for financial transactions..



credit-card is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
expiration	datetime	Maximum date of validity	—
issued	datetime	Initial date of validity or issued date.	—
name	text	Name of the card owner.	—
comment	comment	A description of the card.	—
card-security-code	text	Card security code (CSC, CVD, CVV, CVC and SPC) as embossed or printed on the card.	—

Object attribute	MISP attribute type	Description	Disable correlation
cc-number	cc-number	credit-card number as encoded on the card.	—
version	text	Version of the card.	—

ddos

DDoS object describes a current DDoS activity from a specific or/and to a specific target. Type of DDoS can be attached to the object as a taxonomy.



ddos is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
ip-dst	ip-dst	Destination IP (victim)	—
protocol	text	Protocol used for the attack ['TCP', 'UDP', 'ICMP', 'IP']	—
ip-src	ip-src	IP address originating the attack	—
last-seen	datetime	End of the attack	✓
dst-port	port	Destination port of the attack	—
total-bps	counter	Bits per second	—
total-pps	counter	Packets per second	—
domain-dst	domain	Destination domain (victim)	—
text	text	Description of the DDoS	✓
first-seen	datetime	Beginning of the attack	✓

Object attribute	MISP attribute type	Description	Disable correlation
src-port	port	Port originating the attack	—

diameter-attack

Attack as seen on diameter authentication against a GSM, UMTS or LTE network.



diameter-attack is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
SessionId	text	Session-ID.	—
Destination-Realm	text	Destination-Realm.	—
IdrFlags	text	IDR-Flags.	✓
category	text	Category. ['Cat0', 'Cat1', 'Cat2', 'Cat3', 'CatSMS']	✓
text	text	A description of the attack seen.	✓
first-seen	datetime	When the attack has been seen for the first time.	✓
Origin-Host	text	Origin-Host.	—
Destination-Host	text	Destination-Host.	—
CmdCode	text	A decimal representation of the diameter Command Code.	✓
Username	text	Username (in this case, usually the IMSI).	—
Origin-Realm	text	Origin-Realm.	—

Object attribute	MISP attribute type	Description	Disable correlation
ApplicationId	text	Application-ID is used to identify for which Diameter application the message is applicable. Application-ID is a decimal representation.	—

domain-ip

A domain and IP address seen as a tuple in a specific time frame..



domain-ip is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
ip	ip-dst	IP Address	—
last-seen	datetime	Last time the tuple has been seen	✓
text	text	A description of the tuple	✓
domain	domain	Domain name	—
first-seen	datetime	First time the tuple has been seen	✓

elf

Object describing a Executable and Linkable Format.



elf is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
os_abi	text	Header operating system application binary interface (ABI) [AIX, 'ARM', 'AROS', 'C6000_ELFABI', 'C6000_LINUX', 'CLOUDABI', 'FENIXOS', 'FREEBSD', 'GNU', 'HPUX', 'HURD', 'IRIX', 'MODESTO', 'NETBSD', 'NSK', 'OPENBSD', 'OPENVMS', 'SOLARIS', 'STANDALONE', 'SYSTEMV', 'TRU64']	✓
text	text	Free text value to attach to the ELF	✓

Object attribute	MISP attribute type	Description	Disable correlation
arch	text	Architecture of the ELF file ['None', 'M32', 'SPARC', 'i386', 'ARCH_68K', 'ARCH_88K', 'IAMCU', 'ARCH_860', 'MIPS', 'S370', 'MIPS_RS3_LE', 'PARISC', 'VPP500', 'SPARC32PLUS', 'ARCH_960', 'PPC', 'PPC64', 'S390', 'SPU', 'V800', 'FR20', 'RH32', 'RCE', 'ARM', 'ALPHA', 'SH', 'SPARCV9', 'TRICORE', 'ARC', 'H8_300', 'H8_300H', 'H8S', 'H8_500', 'IA_64', 'MIPS_X', 'COLDFIRE', 'ARCH_68HC12', 'MMA', 'PCP', 'NCPU', 'NDR1', 'STARCORE', 'ME16', 'ST100', 'TINYJ', 'x86_64', 'PDSP', 'PDP10', 'PDP11', 'FX66', 'ST9PLUS', 'ST7', 'ARCH_68HC16', 'ARCH_68HC11', 'ARCH_68HC08', 'ARCH_68HC05', 'SVX', 'ST19', 'VAX', 'CRIS', 'JAVELIN', 'FIREPATH', 'ZSP', 'MMIX', 'HUANY', 'PRISM', 'AVR', 'FR30', 'D10V', 'D30V', 'V850', 'M32R', 'MN10300', 'MN10200', 'PJ', 'OPENRISC', 'ARC_COMPACT', 'XTENSA', 'VIDEOCORE', 'TMM_GPP', 'NS32K', 'TPC', 'SNP1K', 'ST200', 'IP2K', 'MAX', 'CR', 'F2MC16', 'MSP430', 'BLACKFIN', 'SE_C33', 'SEP', 'ARCA', 'UNICORE', 'EXCESS', 'DXP', 'ALTERA_NIOS2', 'CRX', 'XGATE', 'C166',	✓

Object attribute	MISP attribute type	Description	Disable correlation
type	text	Type of ELF ['CORE', 'DYNAMIC', 'EXECUTABLE', 'HIPROC', 'LOPROC', 'NONE', 'RELOCATABLE']	—
entrypoint-address	text	Address of the entry point	✓
number-sections	counter	Number of sections	✓

elf-section

Object describing a section of an Executable and Linkable Format.



elf-section is a MISP object available in MISP JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—
entropy	float	Entropy of the whole section	✓
name	text	Name of the section	✓
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—
text	text	Free text value to attach to the section	✓

Object attribute	MISP attribute type	Description	Disable correlation
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—
size-in-bytes	size-in-bytes	Size of the section, in bytes	✓
flag	text	Flag of the section ['ALLOC', 'EXCLUDE', 'EXECINSTR', 'GROUP', 'HEX_GPREL', 'INFO_LINK', 'LINK_ORDER', 'MASKOS', 'MASKPROC', 'MERGE', 'MIPS_ADDR', 'MIPS_LOCAL', 'MIPS_MERGE', 'MIPS_NAMES', 'MIPS_NODUPES', 'MIPS_NOSTRIP', 'NONE', 'OS_NONCONFORMING', 'STRINGS', 'TLS', 'WRITE', 'XCORE_SHF_CP_SECTION']	✓

Object attribute	MISP attribute type	Description	Disable correlation
type	text	Type of the section ['NULL', 'PROGBITS', 'SYMTAB', 'STRTAB', 'RELA', 'HASH', 'DYNAMIC', 'NOTE', 'NOBITS', 'REL', 'SHLIB', 'DYNSYM', 'INIT_ARRAY', 'FINI_ARRAY', 'PREINIT_ARRAY', 'GROUP', 'SYMTAB_SHNDX', 'LOOS', 'GNU_ATTRIBUTES', 'GNU_HASH', 'GNU_VERDEF', 'GNU_VERNEED', 'GNU_VERSYM', 'HIOS', 'LOPROC', 'ARM_EXIDX', 'ARM_PREEMPTMAP', 'HEX_ORDERED', 'X86_64_UNWIND', 'MIPS_REGINFO', 'MIPS_OPTIONS', 'MIPS_ABIFLAGS', 'HIPROC', 'LOUSER', 'HIUSER']	✓
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—
md5	md5	[Insecure] MD5 hash (128 bits)	—

email

Email object describing an email with meta-information.



email is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
from	email-src	Sender email address	—
to-display-name	email-dst-display-name	Display name of the receiver	—
from-display-name	email-src-display-name	Display name of the sender	—
mime-boundary	email-mime-boundary	MIME Boundary	—
return-path	text	Message return path	—
send-date	datetime	Date the email has been sent	✓
to	email-dst	Destination email address	—
header	email-header	Full headers	—
message-id	email-message-id	Message ID	—
attachment	email-attachment	Attachment	—
screenshot	attachment	Screenshot of email	—
eml	attachment	Full EML	—
cc	email-dst	Carbon copy	—
reply-to	email-reply-to	Email address the reply will be sent to	—
email-body	email-body	Body of the email	—
x-mailer	email-x-mailer	X-Mailer generally tells the program that was used to draft and send the original email	—
subject	email-subject	Subject	—

Object attribute	MISP attribute type	Description	Disable correlation
thread-index	email-thread-index	Identifies a particular conversation thread	—

fail2ban

Fail2ban event.



fail2ban is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
attack-type	text	Type of the attack	✓
failures	counter	Amount of failures that lead to the ban.	✓
logfile	attachment	Full logfile related to the attack.	✓
sensor	text	Identifier of the sensor	✓
processing-timestamp	datetime	Timestamp of the report	✓
banned-ip	ip-src	IP Address banned by fail2ban	—
victim	text	Identifier of the victim	✓
logline	text	Example log line that caused the ban.	✓

file

File object describing a file with meta-information.



file is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—
entropy	float	Entropy of the whole file	✓
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—
tlsh	tlsh	Fuzzy hash by Trend Micro: Locality Sensitive Hash	—
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—
text	text	Free text value to attach to the file	✓
filename	filename	Filename on disk	✓
authentihash	authentihash	Authenticode executable signature hash	—
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—
certificate	x509-fingerprint-sha1	Certificate value if the binary is signed with another authentication scheme than authenticode	—
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—

Object attribute	MISP attribute type	Description	Disable correlation
mimetype	mime-type	Mime type	✓
malware-sample	malware-sample	The file itself (binary)	—
size-in-bytes	size-in-bytes	Size of the file, in bytes	✓
path	text	Path of the filename complete or partial	✓
state	text	State of the file ['Malicious', 'Harmless', 'Signed', 'Revoked', 'Expired', 'Trusted']	✓
pattern-in-file	pattern-in-file	Pattern that can be found in the file	—
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—
md5	md5	[Insecure] MD5 hash (128 bits)	—

geolocation

An object to describe a geographic location..



geolocation is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
country	text	Country.	—
latitude	float	The latitude is the decimal value of the latitude in the World Geodetic System 84 (WGS84) reference.	✓
address	text	Address.	—

Object attribute	MISP attribute type	Description	Disable correlation
zipcode	text	Zip Code.	—
altitude	float	The altitude is the decimal value of the altitude in the World Geodetic System 84 (WGS84) reference.	—
longitude	float	The longitude is the decimal value of the longitude in the World Geodetic System 84 (WGS84) reference	✓
region	text	Region.	—
last-seen	datetime	When the location was seen for the last time.	✓
text	text	A generic description of the location.	✓
first-seen	datetime	When the location was seen for the first time.	✓
city	text	City.	—

gtp-attack

GTP attack object as seen on a GSM, UMTS or LTE network.



gtp-attack is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
GtpInterface	text	GTP interface. ['S5', 'S11', 'S10', 'S8', 'Gn', 'Gp']	✓
GtpImei	text	GTP IMEI (International Mobile Equipment Identity).	—

Object attribute	MISP attribute type	Description	Disable correlation
PortSrc	port	Source port.	✓
GtpServingNetwork	text	GTP Serving Network.	✓
text	text	A description of the GTP attack.	✓
GtpMsisdn	text	GTP MSISDN.	—
first-seen	datetime	When the attack has been seen for the first time.	✓
PortDest	text	Destination port.	✓
GtpVersion	text	GTP version ['0', '1', '2']	✓
ipSrc	ip-src	IP source address.	—
GtpImsi	text	GTP IMSI (International mobile subscriber identity).	—
GtpMessageType	text	GTP defines a set of messages between two associated GSNs or an SGSN and an RNC. Message type is described as a decimal value.	✓
ipDest	ip-dst	IP destination address.	—

http-request

A single HTTP request header.



http-request is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
basicauth-password	text	HTTP Basic Authentication Password	—
method	http-method	HTTP Method invoked (one of GET, POST, PUT, HEAD, DELETE, OPTIONS, CONNECT)	✓
url	url	Full HTTP Request URL	—
uri	uri	Request URI	—
user-agent	user-agent	The user agent string of the user agent	—
text	text	HTTP Request comment	✓
content-type	other	The MIME type of the body of the request	—
cookie	text	An HTTP cookie previously sent by the server with Set-Cookie	—
proxy-password	text	HTTP Proxy Password	—
referrer	other	This is the address of the previous web page from which a link to the currently requested page was followed	—
host	hostname	The domain name of the server	—
proxy-user	text	HTTP Proxy Username	—
basicauth-user	text	HTTP Basic Authentication Username	—

ip-port

An IP address (or domain or hostname) and a port seen as a tuple (or as a triple) in a specific time frame..



ip-port is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
domain	domain	Domain	—
ip	ip-dst	IP Address	—
src-port	port	Source port	—
hostname	hostname	Hostname	—
last-seen	datetime	Last time the tuple has been seen	✓
text	text	Description of the tuple	✓
first-seen	datetime	First time the tuple has been seen	✓
dst-port	port	Destination port	✓

ja3

JA3 is a new technique for creating SSL client fingerprints that are easy to produce and can be easily shared for threat intelligence. Fingerprints are composed of Client Hello packet; SSL Version, Accepted Ciphers, List of Extensions, Elliptic Curves, and Elliptic Curve Formats. <https://github.com/salesforce/ja3>.



ja3 is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
ip-dst	ip-dst	Destination IP address	—
ip-src	ip-src	Source IP Address	—

Object attribute	MISP attribute type	Description	Disable correlation
last-seen	datetime	Last seen of the SSL/TLS handshake	✓
ja3-fingerprint-md5	md5	Hash identifying source	—
description	text	Type of detected software ie software, malware	—
first-seen	datetime	First seen of the SSL/TLS handshake	✓

legal-entity

An object to describe a legal entity..



legal-entity is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
legal-form	text	Legal form of an entity.	—
name	text	Name of an entity.	—
phone-number	phone-number	Phone number of an entity.	—
registration-number	text	Registration number of an entity in the relevant authority.	—
text	text	A description of the entity.	✓
commercial-name	text	Commercial name of an entity.	—
business	text	Business area of an entity.	—

macho

Object describing a file in Mach-O format..



macho is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
text	text	Free text value to attach to the Mach-O file	✓
type	text	Type of Mach-O ['BUNDLE', 'CORE', 'DSYM', 'DYLIB', 'DYLIB_STUB', 'DYLINKER', 'EXECUTE', 'FVMLIB', 'KEXT_BUNDLE', 'OBJECT', 'PRELOAD']	—
entrypoint-address	text	Address of the entry point	✓
number-sections	counter	Number of sections	✓
name	text	Binary's name	—

macho-section

Object describing a section of a file in Mach-O format..



macho-section is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—
entropy	float	Entropy of the whole section	✓
name	text	Name of the section	✓

Object attribute	MISP attribute type	Description	Disable correlation
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—
text	text	Free text value to attach to the section	✓
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—
size-in-bytes	size-in-bytes	Size of the section, in bytes	✓
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—
md5	md5	[Insecure] MD5 hash (128 bits)	—

microblog

Microblog post like a Twitter tweet or a post on a Facebook wall..



microblog is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
url	url	Original URL location of the microblog post	—

Object attribute	MISP attribute type	Description	Disable correlation
username	text	Username who posted the microblog post	—
modification-date	datetime	Last update of the microblog post	—
removal-date	datetime	When the microblog post was removed	—
post	text	Raw post	—
creation-date	datetime	Initial creation of the microblog post	—
username-quoted	text	Username who are quoted into the microblog post	—
type	text	Type of the microblog post ['Twitter', 'Facebook', 'LinkedIn', 'Reddit', 'Google+', 'Instagram', 'Forum', 'Other']	✓
link	url	Link into the microblog post	—

mutex

Object to describe mutual exclusion locks (mutex) as seen in memory or computer program.



mutex is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
operating-system	text	Operating system where the mutex has been seen ['Windows', 'Unix']	—
description	text	Description	—

Object attribute	MISP attribute type	Description	Disable correlation
name	text	name of the mutex	—

netflow

Netflow object describes an network object based on the Netflowv5/v9 minimal definition.



netflow is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
ip-protocol-number	size-in-bytes	IP protocol number of this flow	✓
last-packet-seen	datetime	Last packet seen in this flow	—
icmp-type	text	ICMP type of the flow (if the traffic is ICMP)	✓
src-port	port	Source port of the netflow	—
dst-as	AS	Destination AS number for this flow	—
flow-count	counter	Flows counted in this flow	✓
ip-dst	ip-dst	IP address destination of the netflow	—
first-packet-seen	datetime	First packet seen in this flow	—
ip-src	ip-src	IP address source of the netflow	—
dst-port	port	Destination port of the netflow	—
byte-count	counter	Bytes counted in this flow	✓

Object attribute	MISP attribute type	Description	Disable correlation
packet-count	counter	Packets counted in this flow	✓
src-as	AS	Source AS number for this flow	—
direction	text	Direction of this flow ['Ingress', 'Egress']	✓
tcp-flags	text	TCP flags of the flow	✓
ip_version	counter	IP version of this flow	✓
protocol	text	Protocol used for this flow ['TCP', 'UDP', 'ICMP', 'IP']	—

passive-dns

Passive DNS records as expressed in draft-dulaunoy-dnsop-passive-dns-cof-01.



passive-dns is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
time_first	datetime	First time that the unique tuple (rrname, rrtype, rdata) has been seen by the passive DNS	✓
zone_time_first	datetime	First time that the unique tuple (rrname, rrtype, rdata) record has been seen via master file import	✓

Object attribute	MISP attribute type	Description	Disable correlation
rrtype	text	Resource Record type as seen by the passive DNS. ['A', 'AAAA', 'CNAME', 'PTR', 'SOA', 'TXT', 'DNAME', 'NS', 'SRV', 'RP', 'NAPTR', 'HINFO', 'A6']	✓
text	text	Description of the passive DNS record.	✓
sensor_id	text	Sensor information where the record was seen	✓
time_last	datetime	Last time that the unique tuple (rrname, rrtype, rdata) record has been seen by the passive DNS	✓
origin	text	Origin of the Passive DNS response	✓
zone_time_last	datetime	Last time that the unique tuple (rrname, rrtype, rdata) record has been seen via master file import.	✓
count	counter	How many authoritative DNS answers were received at the Passive DNS Server's collectors with exactly the given set of values as answers.	✓
rdata	text	Resource records of the queried resource	—
rrname	text	Resource Record name of the queried resource.	—

Object attribute	MISP attribute type	Description	Disable correlation
bailiwick	text	Best estimate of the apex of the zone where this data is authoritative	✓

paste

Paste or similar post from a website allowing to share privately or publicly posts..



paste is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
url	url	Link to the original source of the paste or post.	—
origin	text	Original source of the paste or post. ['pastebin.com', 'pastebin.com_pro', 'pastie.org', 'slexy.org', 'gist.github.com', 'codepad.org', 'safebin.net', 'hastebin.com', 'ghostbin.com']	—
last-seen	datetime	When the paste has been accessible or seen for the last time.	✓
paste	text	Raw text of the paste or post	—
title	text	Title of the paste or post.	—
first-seen	datetime	When the paste has been accessible or seen for the first time.	✓

pe

Object describing a Portable Executable.



pe is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
pehash	pehash	Hash of the structural information about a sample. See https://www.usenix.org/legacy/event/leet09/tech/full_papers/wicherski/wicherski_html/	—
number-sections	counter	Number of sections	✓
file-description	text	FileDescription in the resources	✓
product-name	text	ProductName in the resources	✓
text	text	Free text value to attach to the PE	✓
lang-id	text	Lang ID in the resources	✓
product-version	text	ProductVersion in the resources	✓
imphash	imphash	Hash (md5) calculated from the import table	—
company-name	text	CompanyName in the resources	✓
file-version	text	FileVersion in the resources	✓

Object attribute	MISP attribute type	Description	Disable correlation
impfuzzy	impfuzzy	Fuzzy Hash (ssdeep) calculated from the import table	—
internal-filename	filename	InternalFilename in the resources	✓
type	text	Type of PE ['exe', 'dll', 'driver', 'unknown']	✓
compilation-timestamp	datetime	Compilation timestamp defined in the PE header	—
entrypoint-address	text	Address of the entry point	✓
entrypoint-section-at-position	text	Name of the section and position of the section in the PE	✓
original-filename	filename	OriginalFilename in the resources	✓
legal-copyright	text	LegalCopyright in the resources	✓

pe-section

Object describing a section of a Portable Executable.



pe-section is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—
entropy	float	Entropy of the whole section	✓

Object attribute	MISP attribute type	Description	Disable correlation
name	text	Name of the section ['.rsrc', '.reloc', '.rdata', 'data', '.text']	✓
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—
text	text	Free text value to attach to the section	✓
characteristic	text	Characteristic of the section ['read', 'write', 'executable']	—
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—
size-in-bytes	size-in-bytes	Size of the section, in bytes	✓
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—
md5	md5	[Insecure] MD5 hash (128 bits)	—

person

An object which describes a person or an identity..



person is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
gender	gender	The gender of a natural person. ['Male', 'Female', 'Other', 'Prefer not to say']	✓
first-name	first-name	First name of a natural person.	✓
place-of-birth	place-of-birth	Place of birth of a natural person.	✓
passport-number	passport-number	The passport number of a natural person.	—
last-name	last-name	Last name of a natural person.	—
nationality	nationality	The nationality of a natural person.	✓
redress-number	redress-number	The Redress Control Number is the record identifier for people who apply for redress through the DHS Travel Redress Inquiry Program (DHS TRIP). DHS TRIP is for travelers who have been repeatedly identified for additional screening and who want to file an inquiry to have erroneous information corrected in DHS systems.	—
alias	text	Alias name or known as.	—

Object attribute	MISP attribute type	Description	Disable correlation
text	text	A description of the person or identity.	✓
date-of-birth	date-of-birth	Date of birth of a natural person (in YYYY-MM-DD format).	—
middle-name	middle-name	Middle name of a natural person.	—
identity-card-number	identity-card-number	The identity card number of a natural person.	—
passport-expiration	passport-expiration	The expiration date of a passport.	✓
passport-country	passport-country	The country in which the passport was issued.	✓
mothers-name	text	Mother name, father, second name or other names following country's regulation.	—
title	text	Title of the natural person such as Dr. or equivalent.	✓
social-security-number	text	Social security number	—

phone

A phone or mobile phone object which describe a phone..



phone is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
imei	text	International Mobile Equipment Identity (IMEI) is a number, usually unique, to identify 3GPP and iDEN mobile phones, as well as some satellite phones.	—
imsi	text	A usually unique International Mobile Subscriber Identity (IMSI) is allocated to each mobile subscriber in the GSM/UMTS/EPS system. IMSI can also refer to International Mobile Station Identity in the ITU nomenclature.	—
first-seen	datetime	When the phone has been accessible or seen for the first time.	✓
gummei	text	Globally Unique MME Identifier (GUMMEI) is composed from MCC, MNC and MME Identifier (MMEI).	—
text	text	A description of the phone.	✓
last-seen	datetime	When the phone has been accessible or seen for the last time.	✓

Object attribute	MISP attribute type	Description	Disable correlation
guti	text	Globally Unique Temporary UE Identity (GUTI) is a temporary identification to not reveal the phone (user equipment in 3GPP jargon) composed of GUMMEI and the M-TMSI.	—
tmsi	text	Temporary Mobile Subscriber Identities (TMSI) to visiting mobile subscribers can be allocated.	—
serial-number	text	Serial Number.	—
msisdn	text	MSISDN (pronounced as /'em es ai es di en/ or misden) is a number uniquely identifying a subscription in a GSM or a UMTS mobile network. Simply put, it is the mapping of the telephone number to the SIM card in a mobile/cellular phone. This abbreviation has a several interpretations, the most common one being Mobile Station International Subscriber Directory Number.	—

r2graphity

Indicators extracted from files using radare2 and graphml.



r2graphity is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
callbacks	counter	Amount of callbacks (functions started as thread)	✓
not-referenced-strings	counter	Amount of not referenced strings	✓
gml	attachment	Graph export in G>raph Modelling Language format	✓
referenced-strings	counter	Amount of referenced strings	✓
dangling-strings	counter	Amount of dangling strings (string with a code cross reference, that is not within a function. Radare2 failed to detect that function.)	✓
ratio-string	float	Ratio: amount of referenced strings per kilobyte of code section	✓
total-functions	counter	Total amount of functions in the file.	✓
total-api	counter	Total amount of API calls	✓
ratio-api	float	Ratio: amount of API calls per kilobyte of code section	✓
miss-api	counter	Amount of API call reference that does not resolve to a function offset	✓
text	text	Description of the r2graphity object	✓

Object attribute	MISP attribute type	Description	Disable correlation
get-proc-address	counter	Amount of calls to GetProcAddress	✓
ratio-functions	float	Ratio: amount of functions per kilobyte of code section	✓
r2-commit-version	text	Radare2 commit ID used to generate this object	✓
unknown-references	counter	Amount of API calls not ending in a function (Radare2 bug, probalby)	✓
memory-allocations	counter	Amount of memory allocations	✓
refsglobalvar	counter	Amount of API calls outside of code section (glob var, dynamic API)	✓
shortest-path-to-create-thread	counter	Shortest path to the first time the binary calls CreateThread	✓
create-thread	counter	Amount of calls to CreateThread	✓
callback-average	counter	Average size of a callback	✓
local-references	counter	Amount of API calls inside a code section	✓
callback-largest	counter	Largest callback	✓

regexp

An object describing a regular expression (regex or regexp). The object can be linked via a relationship to other attributes or objects to describe how it can be represented as a regular expression..



regex is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
regex-type	text	Type of the regular expression syntax. ['PCRE', 'PCRE2', 'POSIX BRE', 'POSIX ERE']	✓
regex	text	regex	—
type	text	Specify which type corresponds to this regex. ['hostname', 'domain', 'email-src', 'email-dst', 'email-subject', 'url', 'user-agent', 'regkey', 'cookie', 'uri', 'filename', 'windows-service-name', 'windows-scheduled-task']	✓
comment	comment	A description of the regular expression.	—

registry-key

Registry key object describing a Windows registry key with value and last-modified timestamp.



registry-key is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
data	text	Data stored in the registry key	—

Object attribute	MISP attribute type	Description	Disable correlation
root-keys	text	Root key of the Windows registry (extracted from the key) ['HKCC', 'HKCR', 'HKCU', 'HKDD', 'HKEY_CLASSES_ROOT', 'HKEY_CURRENT_CONFIG', 'HKEY_CURRENT_USER', 'HKEY_DYN_DATA', 'HKEY_LOCAL_MACHINE', 'HKEY_PERFORMANCE_DATA', 'HKEY_USERS', 'HKLM', 'HKPD', 'HKU']	✓
name	text	Name of the registry key	—
data-type	text	Registry value type ['REG_NONE', 'REG_SZ', 'REG_EXPAND_SZ', 'REG_BINARY', 'REG_DWORD', 'REG_DWORD_LITTLE_ENDIAN', 'REG_DWORD_BIG_ENDIAN', 'REG_LINK', 'REG_MULTI_SZ', 'REG_RESOURCE_LIST', 'REG_FULL_RESOURCE_DESCRIPTOR', 'REG_RESOURCE_REQUIREMENTS_LIST', 'REG_QWORD', 'REG_QWORD_LITTLE_ENDIAN']	✓
last-modified	datetime	Last time the registry key has been modified	—
key	regkey	Full key path	—

Object attribute	MISP attribute type	Description	Disable correlation
hive	text	Hive used to store the registry key (file on disk)	✓

report

Metadata used to generate an executive level report.



report is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
summary	text	Free text summary of the report	—
case-number	text	Case number	—

rtir

RTIR - Request Tracker for Incident Response.



rtir is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
queue	text	Queue of the RTIR ticket ['incident', 'investigations', 'blocks', 'incident reports']	—
ip	ip-dst	IPs automatically extracted from the RTIR ticket	—
classification	text	Classification of the RTIR ticket	—
ticket-number	text	ticket-number of the RTIR ticket	—

Object attribute	MISP attribute type	Description	Disable correlation
subject	text	Subject of the RTIR ticket	—
constituency	text	Constituency of the RTIR ticket	—
status	text	Status of the RTIR ticket ['new', 'open', 'stalled', 'resolved', 'rejected', 'deleted']	—

sandbox-report

Sandbox report.



sandbox-report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
results	text	Freetext result values	✓
raw-report	text	Raw report from sandbox	✓
web-sandbox	text	A web sandbox where results are publicly available via an URL ['malwr', 'hybrid-analysis']	✓
score	text	Score	✓
sandbox-type	text	The type of sandbox used ['on-premise', 'web', 'saas']	✓
permalink	link	Permalink reference	—

Object attribute	MISP attribute type	Description	Disable correlation
on-premise-sandbox	text	The on-premise sandbox used ['cuckoo', 'symantec-cas-on-premise', 'bluecoat-maa', 'trendmicro-deep-discovery-analyzer', 'fireeye-ax', 'vmray', 'joe-sandbox-on-premise']	✓
saas-sandbox	text	A non-on-premise sandbox, also results are not publicly available ['forticloud-sandbox', 'joe-sandbox-cloud', 'symantec-cas-cloud']	✓

sb-signature

Sandbox detection signature.



sb-signature is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
signature	text	Name of detection signature - set the description of the detection signature as a comment	—
software	text	Name of Sandbox software	✓
text	text	Additional signature description	✓
datetime	datetime	Datetime	✓

ss7-attack

SS7 object of an attack seen on a GSM, UMTS or LTE network via SS7 logging..



ss7-attack is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
MapSmscGT	text	MAP SMSC. Phone number.	—
MapImsi	text	MAP IMSI. Phone number starting with MCC/MNC.	—
MapGsmcfGT	text	MAP GSMSCF GT. Phone number.	—
SccpCdGT	text	Signaling Connection Control Part (SCCP) CdGT - Phone number.	—
MapApplicationContext	text	MAP application context in OID format.	✓
MapGmlc	text	MAP GMLC. Phone number.	—
MapMsisdn	text	MAP MSISDN. Phone number.	—
MapOpCode	text	MAP operation codes - Decimal value between 0-99.	✓
MapSmsTP-DCS	text	MAP SMS TP-DCS.	✓
MapSmsText	text	MAP SMS Text. Important indicators in SMS text.	—
MapSmsTP-OA	text	MAP SMS TP-OA. Phone number.	—

Object attribute	MISP attribute type	Description	Disable correlation
MapSmsTypeNumber	text	MAP SMS TypeNumber.	✓
MapSmsTP-PID	text	MAP SMS TP-PID.	✓
SccpCdSSN	text	Signaling Connection Control Part (SCCP) - Decimal value between 0-255.	✓
MapVlrGT	text	MAP VLR GT. Phone number.	—
SccpCgSSN	text	Signaling Connection Control Part (SCCP) - Decimal value between 0-255.	✓
SccpCdPC	text	Signaling Connection Control Part (SCCP) CdPC - Phone number.	—
MapUssdContent	text	MAP USSD Content.	—
text	text	A description of the attack seen via SS7 logging.	✓
MapUssdCoding	text	MAP USSD Content.	✓
first-seen	datetime	When the attack has been seen for the first time.	✓
MapMscGT	text	MAP MSC GT. Phone number.	—
Category	text	Category ['Cat0', 'Cat1', 'Cat2.1', 'Cat2.2', 'Cat3.1', 'Cat3.2', 'Cat3.3', 'CatSMS', 'CatSpoofing']	✓
MapVersion	text	Map version. ['1', '2', '3']	✓

Object attribute	MISP attribute type	Description	Disable correlation
SccpCgGT	text	Signaling Connection Control Part (SCCP) CgGT - Phone number.	—
SccpCgPC	text	Signaling Connection Control Part (SCCP) CgPC - Phone number.	—

stix2-pattern

An object describing a STIX pattern. The object can be linked via a relationship to other attributes or objects to describe how it can be represented as a STIX pattern..



stix2-pattern is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
stix2-pattern	stix2-pattern	STIX 2 pattern	—
version	text	Version of STIX 2 pattern. ['stix 2.0']	—
comment	comment	A description of the stix2-pattern.	—

suricata

An object describing a Suricata rule along with its version and context.



suricata is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
suricata	suricata	Suricata rule.	—
ref	link	Reference to the Suricata rule such as origin of the rule or alike.	—

Object attribute	MISP attribute type	Description	Disable correlation
version	text	Version of the Suricata rule depending where the suricata rule is known to work as expected.	—
comment	comment	A description of the Suricata rule.	—

target-system

Description about an targeted system, this could potentially be a compromised internal system.



target-system is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
targeted_ip_of_system	ip-src	Targeted system IP address	✓
targeted_machine	target-machine	Targeted system	✓
timestamp_seen	datetime	Registered date and time	✓

timesketch-timeline

A timesketch timeline object based on mandatory field in timesketch to describe a log entry..



timesketch-timeline is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
timestamp_desc	text	Text explaining what type of timestamp is it	—
message	text	Informative message of the event	—

Object attribute	MISP attribute type	Description	Disable correlation
datetime	datetime	When the log entry was seen	—
timestamp	timestamp-microsec	When the log entry was seen in microseconds since Unix epoch	—

timestamp

A generic timestamp object to represent time including first time and last time seen. Relationship will then define the kind of time relationship..



timestamp is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
precision	text	Timestamp precision represents the precision given to first_seen and/or last_seen in this object. ['year', 'month', 'day', 'hour', 'minute', 'full']	✓
last-seen	datetime	First time that the linked object or attribute has been seen.	✓
text	text	Description of the time object.	✓
first-seen	datetime	First time that the linked object or attribute has been seen.	✓

tor-node

Tor node (which protects your privacy on the internet by hiding the connection between users Internet address and the services used by the users) description which are part of the Tor network at a time..



tor-node is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
nickname	text	router's nickname.	—
version_line	text	versioning information reported by the node.	—
flags	text	list of flag associated with the node.	—
fingerprint	text	router's fingerprint.	—
last-seen	datetime	When the Tor node designed by the IP address has been seen for the last time.	✓
text	text	Tor node comment.	✓
first-seen	datetime	When the Tor node designed by the IP address has been seen for the first time.	✓
address	ip-src	IP address of the Tor node seen.	—
version	text	parsed version of tor, this is None if the relay's using a new versioning scheme.	—
published	datetime	router's publication time. This can be different from first-seen and last-seen.	✓
description	text	Tor node description.	✓
document	text	Raw document from the consensus.	✓

transaction

An object to describe a financial transaction..



transaction is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
teller	text	Person who conducted the transaction.	—
to-country	text	Target country of a transaction.	—
transmode-comment	text	Comment describing transmode-code, if needed.	—
location	text	Location where the transaction took place.	—
amount	text	The value of the transaction in local currency.	—
transmode-code	text	How the transaction was conducted.	—
transaction-number	text	A unique number identifying a transaction.	—
authorized	text	Person who authorized the transaction.	—
text	text	A description of the transaction.	✓
from-country	text	Origin country of a transaction.	—
date-posting	datetime	Date of posting, if different from date of transaction.	—

Object attribute	MISP attribute type	Description	Disable correlation
from-funds-code	text	Type of funds used to initiate a transaction. [A Deposit', 'C Currency exchange', 'D Casino chips', 'E Bank draft', 'F Money order', 'G Traveler's cheques', 'H Life insurance policy', 'I Real estate', 'J Securities', 'K Cash', 'O Other', 'P Cheque']	✓
to-funds-code	text	Type of funds used to finalize a transaction. [A Deposit', 'C Currency exchange', 'D Casino chips', 'E Bank draft', 'F Money order', 'G Traveler's cheques', 'H Life insurance policy', 'I Real estate', 'J Securities', 'K Cash', 'O Other', 'P Cheque']	✓
date	datetime	Date and time of the transaction.	—

url

url object describes an url along with its normalized field (like extracted using faup parsing library) and its metadata..



url is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
url	url	Full URL	—
credential	text	Credential (username, password)	—
tld	text	Top-Level Domain	✓

Object attribute	MISP attribute type	Description	Disable correlation
domain	domain	Full domain	—
last-seen	datetime	Last time this URL has been seen	✓
text	text	Description of the URL	—
domain_without_tld	text	Domain without Top-Level Domain	—
scheme	text	Scheme ['http', 'https', 'ftp', 'gopher', 'sip']	✓
resource_path	text	Path (between hostname:port and query)	—
fragment	text	Fragment identifier is a short string of characters that refers to a resource that is subordinate to another, primary resource.	—
first-seen	datetime	First time this URL has been seen	✓
host	hostname	Full hostname	—
subdomain	text	Subdomain	✓
query_string	text	Query (after path, preceded by '?')	—
port	port	Port number	✓

victim

Victim object describes the target of an attack or abuse..



victim is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
email	target-email	The email address(es) of the user targeted.	—
node	target-machine	Name(s) of node that was targeted.	—
sectors	text	The list of sectors that the victim belong to ['agriculture', 'aerospace', 'automotive', 'communications', 'construction', 'defence', 'education', 'energy', 'engineering', 'entertainment', 'financial services', 'government national', 'government regional', 'government local', 'government public services', 'healthcare', 'hospitality leisure', 'infrastructure', 'insurance', 'manufacturing', 'mining', 'non profit', 'pharmaceuticals', 'retail', 'technology', 'telecommunications', 'transportation', 'utilities']	—
name	target-org	The name of the department(s) or organisation(s) targeted.	—
roles	text	The list of roles targeted within the victim.	—

Object attribute	MISP attribute type	Description	Disable correlation
classification	text	The type of entity being targeted. ['individual', 'group', 'organization', 'class', 'unknown']	✓
user	target-user	The username(s) of the user targeted.	—
regions	target-location	The list of regions or locations from the victim targeted. ISO 3166 should be used.	—
ip-address	ip-dst	IP address(es) of the node targeted.	—
description	text	Description of the victim	—
external	target-external	External target organisations affected by this attack.	—

virustotal-report

VirusTotal report.



virustotal-report is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
last-submission	datetime	Last Submission	—
comment	text	Comment related to this hash	—
first-submission	datetime	First Submission	—
community-score	text	Community Score	✓
permalink	link	Permalink Reference	—

Object attribute	MISP attribute type	Description	Disable correlation
detection-ratio	text	Detection Ratio	✓

vulnerability

Vulnerability object describing a common vulnerability enumeration which can describe unpublished, under review or embargo vulnerability for software, equipments or hardware..



vulnerability is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
created	datetime	First time when the vulnerability was discovered	✓
vulnerable_configuration	text	The vulnerable configuration is described in CPE format	—
modified	datetime	Last modification date	✓
summary	text	Summary of the vulnerability	—
published	datetime	Initial publication date	✓
state	text	State of the vulnerability. A vulnerability can have multiple states depending of the current actions performed. ['Published', 'Embargo', 'Reviewed', 'Vulnerability ID Assigned', 'Reported', 'Fixed']	✓
text	text	Description of the vulnerability	—

Object attribute	MISP attribute type	Description	Disable correlation
references	link	External references	—
id	vulnerability	Vulnerability ID (generally CVE, but not necessarily). The id is not required as the object itself has an UUID and the CVE id can updated later.	—

whois

Whois records information for a domain name or an IP address..



whois is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
creation-date	datetime	Initial creation of the whois entry	✓
expiration-date	datetime	Expiration of the whois entry	✓
domain	domain	Domain of the whois entry	—
text	text	Full whois entry	✓
registrant-email	whois-registrant-email	Registrant email address	—
registrant-name	whois-registrant-name	Registrant name	—
nameserver	hostname	Nameserver	✓
registrar	whois-registrar	Registrar of the whois entry	—
registrant-phone	whois-registrant-phone	Registrant phone number	—

Object attribute	MISP attribute type	Description	Disable correlation
modification-date	datetime	Last update of the whois entry	✓
registrant-org	whois-registrant-org	Registrant organisation	—
comment	text	Comment of the whois entry	—
ip-address	ip-src	IP address of the whois entry	—

x509

x509 object describing a X.509 certificate.



x509 is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
x509-fingerprint-sha256	x509-fingerprint-sha256	Secure Hash Algorithm 2 (256 bits)	—
pubkey-info-algorithm	text	Algorithm of the public key	—
x509-fingerprint-md5	x509-fingerprint-md5	[Insecure] MD5 hash (128 bits)	—
validity-not-before	datetime	Certificate invalid before that date	—
x509-fingerprint-sha1	x509-fingerprint-sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—
issuer	text	Issuer of the certificate	—
text	text	Free text description of the certificate	—
validity-not-after	datetime	Certificate invalid after that date	—

Object attribute	MISP attribute type	Description	Disable correlation
serial-number	text	Serial number of the certificate	—
pubkey-info-exponent	text	Exponent of the public key	—
pubkey-info-modulus	text	Modulus of the public key	—
pem	text	Raw certificate in PEM format (Unix-like newlines)	—
is_ca	boolean	CA certificate	—
version	text	Version of the certificate	—
dns_names	text	DNS names	—
self_signed	boolean	Self-signed certificate	—
pubkey-info-size	text	Length of the public key (in bits)	—
raw-base64	text	Raw certificate base64 encoded (DER format)	—
subject	text	Subject of the certificate	—

yabin

yabin.py generates Yara rules from function prologs, for matching and hunting binaries. ref: <https://github.com/AlienVault-OTX/yabin>.



yabin is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
yara-hunt	yara	Wide yara rule generated from -yh.	✓

Object attribute	MISP attribute type	Description	Disable correlation
whitelist	comment	Whitelist name used to generate the rules.	—
version	comment	yabin.py and regex.txt version used for the generation of the yara rules.	—
yara	yara	Yara rule generated from -y.	✓
comment	comment	A description of Yara rule generated.	—

yara

An object describing a YARA rule along with its version..



yara is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
context	text	Context where the YARA rule can be applied ['all', 'disk', 'memory', 'network']	—
version	text	Version of the YARA rule depending where the yara rule is known to work as expected. ['3.7.1']	—
yara	yara	YARA rule.	—
comment	comment	A description of the YARA rule.	—

Relationships

Default type of relationships in MISP objects.

Relationships are part of MISP object and available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Name of relationship	Description	Format
derived-from	The information in the target object is based on information from the source object.	['misp', 'stix-2.0']
duplicate-of	The referenced source and target objects are semantically duplicates of each other.	['misp', 'stix-2.0']
related-to	The referenced source is related to the target object.	['misp', 'stix-2.0']
connected-to	The referenced source is connected to the target object.	['misp', 'stix-1.1']
contains	The references source is containing the target object.	['misp', 'stix-1.1']
resolved-to	The referenced source is resolved to the target object.	['misp', 'stix-1.1']
attributed-to	This referenced source is attributed to the target object.	['misp', 'stix-2.0']
targets	This relationship describes that the source object targets the target object.	['misp', 'stix-2.0']
uses	This relationship describes the use by the source object of the target object.	['misp', 'stix-2.0']
indicates	This relationships describes that the source object indicates the target object.	['misp', 'stix-2.0']
mitigates	This relationship describes a source object which mitigates the target object.	['misp', 'stix-2.0']
variant-of	This relationship describes a source object which is a variant of the target object	['misp', 'stix-2.0']
impersonates	This relationship describe a source object which impersonates the target object	['misp', 'stix-2.0']
authored-by	This relationship describes the author of a specific object.	['misp']
located	This relationship describes the location (of any type) of a specific object.	['misp']

Name of relationship	Description	Format
included-in	This relationship describes an object included in another object.	['misp']
analysed-with	This relationship describes an object analysed by another object.	['misp']
claimed-by	This relationship describes an object claimed by another object.	['misp']
communicates-with	This relationship describes an object communicating with another object.	['misp']
dropped-by	This relationship describes an object dropped by another object.	['misp']
drops	This relationship describes an object which drops another object	['misp']
executed-by	This relationship describes an object executed by another object.	['misp']
affects	This relationship describes an object affected by another object.	['misp']
beacons-to	This relationship describes an object beaconing to another object.	['misp']
abuses	This relationship describes an object which abuses another object.	['misp']
exfiltrates-to	This relationship describes an object exfiltrating to another object.	['misp']
identifies	This relationship describes an object which identifies another object.	['misp']
intercepts	This relationship describes an object which intercepts another object.	['misp']
calls	This relationship describes an object which calls another objects.	['misp']
detected-as	This relationship describes an object which is detected as another object.	['misp']

Name of relationship	Description	Format
followed-by	This relationship describes an object which is followed by another object. This can be used when a time reference is missing but a sequence is known.	['misp']
preceding-by	This relationship describes an object which is preceded by another object. This can be used when a time reference is missing but a sequence is known.	['misp']
triggers	This relationship describes an object which triggers another object.	['misp']
vulnerability-of	This relationship describes an object which is a vulnerability of another object.	['cert-eu']
works-like	This relationship describes an object which works like another object.	['cert-eu']
seller-of	This relationship describes an object which is selling another object.	['cert-eu']
seller-on	This relationship describes an object which is selling on another object.	['cert-eu']
trying-to-obtain-the-exploit	This relationship describes an object which is trying to obtain the exploit described by another object	['cert-eu']
used-by	This relationship describes an object which is used by another object.	['cert-eu']
affiliated	This relationship describes an object which is affiliated with another object.	['cert-eu']
alleged-founder-of	This relationship describes an object which is the alleged founder of another object.	['cert-eu']
attacking-other-group	This relationship describes an object which attacks another object.	['cert-eu']
belongs-to	This relationship describes an object which belongs to another object.	['cert-eu']

Name of relationship	Description	Format
business-relations	This relationship describes an object which has business relations with another object.	['cert-eu']
claims-to-be-the-founder-of	This relationship describes an object which claims to be the founder of another object.	['cert-eu']
cooperates-with	This relationship describes an object which cooperates with another object.	['cert-eu']
former-member-of	This relationship describes an object which is a former member of another object.	['cert-eu']
successor-of	This relationship describes an object which is a successor of another object.	['cert-eu']
has-joined	This relationship describes an object which has joined another object.	['cert-eu']
member-of	This relationship describes an object which is a member of another object.	['cert-eu']
primary-member-of	This relationship describes an object which is a primary member of another object.	['cert-eu']
administrator-of	This relationship describes an object which is an administrator of another object.	['cert-eu']
is-in-relation-with	This relationship describes an object which is in relation with another object,	['cert-eu']
provide-support-to	This relationship describes an object which provides support to another object.	['cert-eu']
regional-branch	This relationship describes an object which is a regional branch of another object.	['cert-eu']
similar	This relationship describes an object which is similar to another object.	['cert-eu']
subgroup	This relationship describes an object which is a subgroup of another object.	['cert-eu']
suspected-link	This relationship describes an object which is suspected to be linked with another object.	['misp']

Name of relationship	Description	Format
same-as	This relationship describes an object which is the same as another object.	['misp']
creator-of	This relationship describes an object which is the creator of another object.	['cert-eu']
developer-of	This relationship describes an object which is a developer of another object.	['cert-eu']
uses-for-recon	This relationship describes an object which uses another object for recon.	['cert-eu']
operator-of	This relationship describes an object which is an operator of another object.	['cert-eu']
overlaps	This relationship describes an object which overlaps another object.	['cert-eu']
owner-of	This relationship describes an object which owns another object.	['cert-eu']
publishes-method-for	This relationship describes an object which publishes method for another object.	['cert-eu']
recommends-use-of	This relationship describes an object which recommends the use of another object.	['cert-eu']
released-source-code	This relationship describes an object which released source code of another object.	['cert-eu']
released	This relationship describes an object which release another object.	['cert-eu']