## FreeRDP User Manual

Marc-André Moreau

February 17, 2013

# Contents

1	Intr	oduction	2
	1.1	Help	2
	1.2	Authentication	4
		1.2.1 Credentials Prompt	6

## Chapter 1

## Introduction

### 1.1 Help

```
FreeRDP - A Free Remote Desktop Protocol Implementation
See www.freerdp.com for more information
Usage: ./client/X11/xfreerdp [file] [options] [/v:<server>[:port]]
Syntax:
/flag (enables flag)
/option:<value> (specifies option with value)
+toggle -toggle (enables or disables toggle, where '/' is a synonym of '+')
/v:<server>[:port]
                        Server hostname
/port:<number>
                        Server port
/w:<width>
                        Width
/h:<height>
                       Height
/size:<width>x<height> Screen size
                        Fullscreen mode
/bpp:<depth>
                        Session bpp (color depth)
/kbd:0x<layout id> or <layout name> Keyboard layout
                       List keyboard layouts
/kbd-list
/kbd-type:<type id>
                        Keyboard type
/kbd-subtype:<subtype id>
                           Keyboard subtype
/kbd-fn-key:<function key count>
                                    Keyboard function key count
                        Admin (or console) session
/admin
/multimon
                        Multi-monitor
```

```
/workarea
                        Work area
/t:<title>
                        Window title
+decorations (default:off) Window decorations
                        Addin
/a
/vc
                        Static virtual channel
/dvc
                        Dynamic virtual channel
/u:[<domain>\\]<user> or <user>[@<domain>] Username
                        Password
/p:<password>
/d:<domain>
                        Domain
/g:<gateway>[:port]
                        Gateway Hostname
/gu:[<domain>\\]<user> or <user>[@<domain>] Gateway username
                        Gateway password
/gp:<password>
/gd:<domain>
                        Gateway domain
/app: | | <alias > or <executable path > Remote application program
/app-name:<app name>
                        Remote application name for user interface
/app-icon:<icon path>
                        Remote application icon for user interface
/app-cmd:<parameters>
                        Remote application command-line parameters
/app-file:<file name>
                        File to open with remote application
/app-guid:<app guid>
                        Remote application GUID
+compression (default:off) Compression
/shell
                        Alternate shell
/shell-dir
                        Shell working directory
/audio-mode
                        Audio output mode
/mic
                        Audio input (microphone)
/network
                        Network connection type
+clipboard (default:off)
                            Redirect clipboard
+fonts (default:off)
                        Smooth fonts (cleartype)
+aero (default:off)
                        Desktop composition
+window-drag (default:off) Full window drag
+menu-anims (default:off)
                            Menu animations
                        Themes
-themes (default:on)
-wallpaper (default:on) Wallpaper
/gdi:<sw|hw>
                        GDI rendering
/rfx
                        RemoteFX
/rfx-mode:<image|video> RemoteFX mode
/frame-ack:<number>
                        Frame acknowledgement
/nsc
                        NSCodec
                        JPEG codec
/jpeg
/jpeg-quality:<percentage> JPEG quality
-nego (default:on)
                        protocol security negotiation
/sec:<rdp|tls|nla|ext>
                        force specific protocol security
-sec-rdp (default:on)
                        rdp protocol security
-sec-tls (default:on)
                        tls protocol security
-sec-nla (default:on)
                        nla protocol security
+sec-ext (default:off) nla extended protocol security
/cert-name:<name>
                        certificate name
```

```
/cert-ignore
                        ignore certificate
/pcb:<blob>
                        Preconnection Blob
/pcid:<id>
                        Preconnection Id
                        Hyper-V console (use port 2179, disable negotiation)
/vmconnect:<vmid>
-authentication (default:on)
                                authentication (hack!)
                            encryption (hack!)
-encryption (default:on)
-grab-keyboard (default:on) grab keyboard
-mouse-motion (default:on) mouse-motion
/parent-window:<window id> Parent window id
-bitmap-cache (default:on) bitmap cache
-offscreen-cache (default:on) offscreen bitmap cache
-glyph-cache (default:on) glyph cache
/codec-cache:<rfx|nsc|jpeg> bitmap codec cache
-fast-path (default:on) fast-path input/output
+async-input (default:off) asynchronous input
+async-update (default:off) asynchronous update
/version
                        print version
/help
                        print help
Examples:
xfreerdp connection.rdp /p:Pwd123! /f
xfreerdp /u:CONTOSO\\JohnDoe /p:Pwd123! /v:rdp.contoso.com
xfreerdp /u:JohnDoe /p:Pwd123! /w:1366 /h:768 /v:192.168.1.100:4489
xfreerdp /u:JohnDoe /p:Pwd123! /vmconnect:C824F53E-95D2-46C6-9A18-23A5BB403532 /v:192.168.1
Clipboard Redirection: +clipboard
Drive Redirection: /a:drive,home,/home
Smartcard Redirection: /a:smartcard, <device>
Printer Redirection: /a:printer, <device>, <driver>
Serial Port Redirection: /a:serial, <device>
Parallel Port Redirection: /a:parallel, <device>
Printer Redirection: /a:printer, <device>, <driver>
```

#### 1.2 Authentication

Audio Input Redirection: /dvc:audin,sys:alsa Audio Output Redirection: /vc:rdpsnd,sys:alsa

Multimedia Redirection: /dvc:tsmf,sys:alsa

USB Device Redirection: /dvc:urbdrc,id,dev:054c:0268

Sample Values:

• User: JohnDoe

• Domain: CONTOSO

Password: Password123!Server: rdp.contoso.com

There simplest, unambiguous way of passing credentials at the command-line is with /u, /d and /p. The domain name is only needed if you connect using domain credentials:

```
xfreerdp /u:JohnDoe /d:CONTOSO /p:Password123! /v:rdp.contoso.com
```

The domain name can also be passed in the username using the same notation accepted by mstsc:

```
xfreerdp /u:CONTOSO\JohnDoe /p:Password123! /v:rdp.contoso.com
```

While the above notation is shorter, it has an unpractical side effect: the backslash is often, but not always, interpreted as an escape character. To avoid the problem, make sure the shell does not interpret the backslash as an escape character:

```
xfreerdp /u:CONTOSO\\JohnDoe /p:Password123! /v:rdp.contoso.com
xfreerdp "/u:CONTOSO\JohnDoe" /p:Password123! /v:rdp.contoso.com
```

From experience, most Linux shells will require such handling of the backslash character. However, there are certain cases like the Eclipse launcher which do not require it.

Alternatively, the User Principal Name (UPN) notation can be used:

```
xfreerdp /u:JohnDoe@CONTOSO /p:Password123! /v:rdp.contoso.com
```

This notation does not have the drawbacks of the backslash character, but introduces a potential conflict with usernames containing the '@' symbol and no domain name. This is frequently the case with the new Windows 8 Microsoft Accounts (a.k.a. Windows Live Accounts) which correspond to an email address. To work work around the ambiguity, precede the user name "john.doe@live.com" with a backslash:

xfreerdp /u:\john.doe@live.com /p:Password123! /v:rdp.contoso.com

Be careful to properly handle the backslash character as previously instructed.

Passwords entered as command-line arguments could potentially be seen by other users on the same system, so they are automatically hidden:

```
awake@workstation:~$ ps aux | grep freerdp
awake 22506 0.0 0.1 2502620 10236 s002 S+ 11:10pm 0:01.00 xfreerdp /u:Jo
```

#### 1.2.1 Credentials Prompt

If you omit entering credentials at the command-line, FreeRDP may prompt you for credentials depending on the negotiated protocol security level.

#### **Protocol Security**

RDP protocol security is confusing for many users because it strongly affects the way credentials can be prompted. There are three main security levels that can be negotiated:

- RDP Security (old encryption, old authentication)
- TLS Security (TLS encryption, old authentication)
- NLA Security (TLS encryption, NLA authentication)

**Old Authentication** The old RDP authentication mechanism is very simple: the server presents the client with the Winlogon GUI, and the user can either automatically or manually enter the credentials. If you enter credentials prior to connecting to a server with the old authentication, they will be automatically on connection, saving you the trouble of typing them manually.

Old RDP authentication may be practical in the sense that you can get a remote Winlogon GUI without being authenticated on the server. This is however a design flaw which makes the RDP server vulnerable to a DDOS attack: since significant resources need to be allocated for the Winlogon GUI without being authenticated, a distributed denial of service attack could be performed by simply launching multiple unauthenticated connections. This is exactly why it is no longer possible to obtain such a GUI prior to authentication with newer security levels.

Network Level Authentication (NLA) Network Level Authentication (NLA) is required by default with servers starting with Windows Vista. With NLA, authentication is the very first thing that occurs over the wire, such that the server will only allocate resources and present a graphical interface to

authenticated clients. It is also much more secure and provides strong defense mechanisms against Man-in-the-Middle (MITM) attacks.

When NLA is negotiated, the complete credentials are needed at connection time, which is why FreeRDP will prompt for the missing information:

xfreerdp /u:JohnDoe /d:CONTOSO /v:rdp.contoso.com connected to rdp.contoso.com  $\,$ 

Password: