

Expires in six months

January 10, 2002

**Multiple Signalling Gateway Support  
for  
Signalling User Adaptation Layers  
<draft-bidulock-sigtran-multisg-00.ps>**

## **Status of this Memo**

This document is an Internet-Draft and is in full conformance with all provisions of Section 10 or RFC 2026. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as 'work in progress'.

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

To learn the current status of any Internet-Draft, please check the Directories on [ftp.is.co.za](ftp://ftp.is.co.za) (Africa), [ftp.nordu.net](ftp://ftp.nordu.net) (Europe), [ftp.munnari.oz.au](ftp://ftp.munnari.oz.au) (Pacific Rim), [ftp.ietf.org](ftp://ftp.ietf.org) (US East Coast), or [ftp.isi.edu](ftp://ftp.isi.edu) (US West Coast).

## **Abstract**

This Internet-Draft describes **Load Selection** for Signalling User Adaptation Protocols [M3UA, SUA, TUA], which permits an Application Server Processes (ASP) to indicate its placement within an Application Server and permits an Signalling Gateway (SG) to distribute traffic over ASPs in Application Servers under Application Server Process (ASP) control.

## **1. Introduction**

### **1.1. Scope**

This Internet-Draft provides parameters and procedures in extension to the parameters and procedures of the Signalling User Adaptation Layers (UAs) [M3UA, SUA, TUA], for the purpose of supporting Application Servers interworking with multiple Signalling Gateways to the SS7 Network.

UA implementations with **Multiple SG Support** are intended to be compatible with UA implementations not supporting this configuration.

**MULTI-SG** is only applicable to Signalling Gateway (SG)-Application Server Process (ASP) configurations in which ASP are supporting Application Server (AS) connectivity to an SS7 network via multiple SGs.<sup>1</sup> **MULTI-SG** is not applicable to configurations of IPSPs working in a point-to-point network without relay points.<sup>2</sup>

### **1.2. Terminology**

**Multiple SG Support (MULTI-SG)** supplements the terminology used in the UA documents [M3UA, SUA, TUA] by adding the following terms:

*Multiple SG Support (MULTI-SG)* – the parameters and procedures provided in this document.

*Signalling User Adaptation Layer (UA)* – one or more of the Stream Control Transmission Protocol (SCTP) [RFC 2960] SS7 Signalling User Adaptation Layers [M3UA, SUA, TUA] supporting the concept of a *Routing Context*.

---

<sup>1</sup> This is commonly referred to within the SIGTRAN WG as the "backhaul" case.

<sup>2</sup> This is commonly referred to within the SIGTRAN WG as the "peer-to-peer" case.

### 1.3. Overview

**MULTI-SG** provides procedures in addition to the UA procedures<sup>3</sup> that provides for seamless interworking of SS7 Network Management with Application Server Processes (ASPs) supporting Application Servers (AS) to multiple Signalling Gateways (SGs). **MULTI-SG** procedures provide support for the following functions not provided for in the existing UA documents:

- Support for fail-over of SCTP associations between Signalling Gateways (SGs).
- Support for rerouting of traffic destined to Signalling Endpoints (SEP) in SS7 Network between Signalling Gateways (SGs).
- Support for seamless interworking with SS7 Changeback [Q.704] procedures towards the SS7 Network for rerouting of traffic between SGs for eliminating message mis-sequencing across the interworking point between the SS7 and IP networks.

**MULTI-SG** supplements the procedures for the diversion of traffic during fail-over or restoration of ASPs, SGPs and IPSPs already provided for in "*Correlation Id and Heartbeat Procedures (CORID) Supporting Lossless Fail-Over between SCTP Associations*" [CORID]. The benefits of **MULTI-SG** can, nevertheless, be supported independent from **CORID** [CORID]

#### 1.3.1. Multiple SGs

No procedures are described which provide for reduction of message loss, duplication or mis-sequencing in multiple SG configurations in the existing UA procedures.

##### 1.3.1.1. Fail-over of routesets between SGs

##### 1.3.1.2. Redirection of routesets between SGs

### 1.4. Sample Configurations




Figure 1. Example (A) Sample Multiple-SG Configuration

A typical Example (A) configuration multiple Signalling Gateways is illustrated in Figure 1. In this configuration a number of Application Server Processes (ASPs) serving a number of Application Servers (ASs) are connected to two Signalling Gateways (SGs). The SGs appear as mated SS7 Signalling Transfer Points (STPs) [Q.705] to the SS7 Network. Traffic originating at Signalling Endpoints (SEP) in the SS7 network and directed toward SEP in the IP network (i.e., Application Servers) is loadshared over the STPs by the Signalling Link Selection (SLS) [Q.704] value associated with each message. Traffic originating at the SEP in the IP network (i.e., AS) is loadshared over the SGs in the same fashion.

<sup>3</sup> See Section 4 of M3UA, SUA and TUA [M3UA, SUA, TUA].

## 2. Conventions

The keywords **MUST**, **MUST NOT**, **REQUIRED**, **SHALL**, **SHALL NOT**, **SHOULD**, **SHOULD NOT**, **RECOMMENDED**, **NOT RECOMMENDED**, **MAY**, and **OPTIONAL**, when they appear in this document, are to be interpreted as described in [RFC 2119].

## 3. Protocol Elements

### 3.1. Parameters

### 3.2. Messages

## 4. Procedures

### 4.1. AS and ASP State Maintenance

#### 4.1.1. ASP State

#### 4.1.2. AS State

#### 4.1.3. ASP Up Procedures

#### 4.1.4. ASP Down Procedures

#### 4.1.5. ASP Active Procedures

#### 4.1.6. ASP Inactive Procedures

#### 4.1.7. Notify Procedures

## 5. Examples

## 6. Security

**Load Selection** does not introduce any new security risks or considerations that are not already inherent in the UA [M3UA, SUA, TUA] Please see the "Security" sections of M3UA, SUA and TUA [M3UA, SUA, TUA] for security considerations and recommendations that are applicable to each of these UAs.

## 7. IANA Considerations

## Acknowledgments

The authors would like to thank for their valuable comments and suggestions.

## Notes

## References

- M3UA. G. Sidebottom, J. Pastor-Balbes, I. Rytina, G. Mousseau, L. Ong, H. J. Schwarzbauer, K. Gradischnig, K. Morneault, M. Kalla, N. Glaude, B. Bidulock and N. Glaude, "SS7 MTP3-User Adaptation Layer (M3UA)," <draft-ietf-sigtran-m3ua-10.txt>, Internet Engineering Task Force - Signalling Transport Working Group (November, 2001). Work In Progress.
- SUA. J. Loughney, G. Sidebottom, G. Mousseau, S. Lorusso, L. Coene, G. Verwimp, J. Keller, F. E. Gonzalez, W. Sully, S. Furniss and B. Bidulock, "SS7 SCCP-User Adaptation Layer (SUA)," <draft-ietf-sigtran-sua-09.txt>, Internet Engineering Task Force - Signalling Transport Working Group (June 15, 2001). Work In Progress.
- TUA. B. Bidulock, "SS7 TCAP-User Adaptation Layer (TUA)," <draft-bidulock-sigtran-tua-00.txt>, Internet Engineering Task Force - Signalling Transport Working Group (January 2002). Work In Progress.
- RFC 2960.  
R. Stewart, Q. Xie, K. Morneault, C. Sharp, H. J. Schwarzbauer, T. Taylor, I. Rytina, H. Kalla, L. Zhang and V. Paxson, "Stream Control Transmission Protocol (SCTP)," RFC 2960, The Internet Society (February 2000).

Q.704. ITU, "Message Transfer Part – Signalling Network Functions and Messages," ITU-T Recommendation Q.704, ITU-T Telecommunication Standardization Sector of ITU, Geneva (March 1993). (Previously "CCITT Recommendation")

CORID.

B. Bidulock, "Correlation Id and Heartbeat Procedures Supporting Lossless Fail-Over," <draft-bidulock-sigtran-corid-00.txt>, Internet Engineering Task Force - Signalling Transport Working Group (January 2002). Work In Progress.

Q.705. ITU, "Signalling System No. 7 – Signalling Network Structure," ITU-T Recommendation Q.705, ITU-T Telecommunication Standardization Sector of ITU, Geneva (March 1993). (Previously "CCITT Recommendation")

RFC 2119.

S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels," RFC 2119 - BCP 14, Internet Engineering Task Force (March 1997).

## Author's Addresses

Brian Bidulock  
OpenSS7 Corporation  
4701 Preston Park Boulevard  
Suite 424  
Plano, TX 75093  
USA

Phone: +1-972-839-4489  
Email: [bidulock@openss7.org](mailto:bidulock@openss7.org)  
URL: <http://www.openss7.org/>

This Internet draft expires July, 2002.

## List of Illustrations

Figure 1 Example (A) Sample Multiple-SG Configuration .....	2
---	---

## Table of Contents

1 Introduction .....	1
1.1 Scope .....	1
1.2 Terminology .....	1
1.3 Overview .....	2
1.3.1 Multiple SGs .....	2
1.4 Sample Configurations .....	2
2 Conventions .....	3
3 Protocol Elements .....	3
3.1 Parameters .....	3
3.2 Messages .....	3
4 Procedures .....	3
4.1 AS and ASP State Maintenance .....	3
4.1.1 ASP State .....	3
4.1.2 AS State .....	3
4.1.3 ASP Up Procedures .....	3
4.1.4 ASP Down Procedures .....	3
4.1.5 ASP Active Procedures .....	3
4.1.6 ASP Inactive Procedures .....	3
4.1.7 Notify Procedures .....	3
5 Examples .....	3
6 Security .....	3
7 IANA Considerations .....	3

## Copyright Statement

**Copyright © The Internet Society (2002). All Rights Reserved.**

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedure for copyrights defined in the Internet Standards process must be followed, or as required to translate into languages other than English.

The limited permission granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and **THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.**