



eXpress

0.90 BETA

<http://bio.math.berkeley.edu/eXpress>

Generated by Doxygen 1.7.3

Sat Oct 8 2011 22:41:37

Contents

1	Class Index	1
1.1	Class Hierarchy	1
2	Class Index	3
2.1	Class List	3
3	Class Documentation	5
3.1	BAMParser Class Reference	5
3.1.1	Detailed Description	5
3.1.2	Constructor & Destructor Documentation	6
3.1.2.1	BAMParser	6
3.1.2.2	~BAMParser	6
3.1.3	Member Function Documentation	6
3.1.3.1	header	6
3.1.3.2	next_fragment	6
3.1.3.3	trans_index	6
3.2	BAMWriter Class Reference	7
3.2.1	Detailed Description	7
3.2.2	Constructor & Destructor Documentation	7
3.2.2.1	BAMWriter	7
3.2.2.2	~BAMWriter	8
3.2.3	Member Function Documentation	8
3.2.3.1	write_fragment	8
3.3	BiasBoss Class Reference	8
3.3.1	Detailed Description	8
3.3.2	Constructor & Destructor Documentation	9
3.3.2.1	BiasBoss	9
3.3.3	Member Function Documentation	9
3.3.3.1	append_output	9
3.3.3.2	get_transcript_bias	9
3.3.3.3	to_string	10
3.3.3.4	update_expectations	10
3.3.3.5	update_observed	10
3.4	Bundle Class Reference	10
3.4.1	Detailed Description	11
3.4.2	Constructor & Destructor Documentation	11
3.4.2.1	Bundle	11
3.4.3	Member Function Documentation	11
3.4.3.1	counts	11

3.4.3.2	incr_counts	12
3.4.3.3	size	12
3.4.3.4	transcripts	12
3.5	BundleTable Class Reference	12
3.5.1	Detailed Description	13
3.5.2	Constructor & Destructor Documentation	13
3.5.2.1	BundleTable	13
3.5.2.2	~BundleTable	13
3.5.3	Member Function Documentation	13
3.5.3.1	bundles	13
3.5.3.2	create_bundle	14
3.5.3.3	merge	14
3.5.3.4	size	14
3.6	FLD Class Reference	14
3.6.1	Detailed Description	15
3.6.2	Constructor & Destructor Documentation	15
3.6.2.1	FLD	15
3.6.3	Member Function Documentation	15
3.6.3.1	add_val	15
3.6.3.2	append_output	16
3.6.3.3	max_val	16
3.6.3.4	mean	16
3.6.3.5	pdf	16
3.6.3.6	to_string	16
3.6.3.7	tot_mass	17
3.7	FragHit Struct Reference	17
3.7.1	Detailed Description	18
3.7.2	Member Function Documentation	18
3.7.2.1	length	18
3.7.2.2	pair_status	18
3.7.3	Member Data Documentation	18
3.7.3.1	left	18
3.7.3.2	left_first	19
3.7.3.3	mapped_trans	19
3.7.3.4	mate_l	19
3.7.3.5	name	19
3.7.3.6	right	19
3.7.3.7	seq_l	19
3.7.3.8	seq_r	19
3.7.3.9	trans_id	20
3.8	Fragment Class Reference	20
3.8.1	Detailed Description	20
3.8.2	Constructor & Destructor Documentation	20
3.8.2.1	~Fragment	20
3.8.3	Member Function Documentation	21
3.8.3.1	add_map_end	21
3.8.3.2	hits	21
3.8.3.3	name	21
3.8.3.4	num_hits	21
3.9	FrequencyMatrix Class Reference	22

3.9.1	Detailed Description	22
3.9.2	Constructor & Destructor Documentation	22
3.9.2.1	FrequencyMatrix	22
3.9.2.2	FrequencyMatrix	22
3.9.3	Member Function Documentation	23
3.9.3.1	arr	23
3.9.3.2	increment	23
3.9.3.3	increment	23
3.9.3.4	operator()	23
3.9.3.5	operator()	24
3.9.3.6	row	24
3.10	Globals Struct Reference	24
3.10.1	Detailed Description	25
3.11	MismatchTable Class Reference	25
3.11.1	Detailed Description	25
3.11.2	Constructor & Destructor Documentation	26
3.11.2.1	MismatchTable	26
3.11.3	Member Function Documentation	26
3.11.3.1	activate	26
3.11.3.2	append_output	26
3.11.3.3	log_likelihood	26
3.11.3.4	to_string	27
3.11.3.5	update	27
3.12	Parser Class Reference	27
3.12.1	Detailed Description	28
3.12.2	Member Function Documentation	28
3.12.2.1	header	28
3.12.2.2	next_fragment	28
3.12.2.3	trans_index	29
3.13	ParseThreadSafety Struct Reference	29
3.13.1	Detailed Description	29
3.13.2	Member Data Documentation	29
3.13.2.1	mut	29
3.13.2.2	next_frag	30
3.14	PosWeightTable Class Reference	30
3.14.1	Detailed Description	30
3.14.2	Constructor & Destructor Documentation	31
3.14.2.1	PosWeightTable	31
3.14.3	Member Function Documentation	31
3.14.3.1	append_output	31
3.14.3.2	get_weight	31
3.14.3.3	get_weight	31
3.14.3.4	increment_expected	32
3.14.3.5	increment_expected	32
3.14.3.6	increment_observed	32
3.14.3.7	increment_observed	33
3.15	SAMParser Class Reference	33
3.15.1	Detailed Description	33
3.15.2	Constructor & Destructor Documentation	34
3.15.2.1	SAMParser	34

3.15.3	Member Function Documentation	34
3.15.3.1	header	34
3.15.3.2	next_fragment	34
3.15.3.3	trans_index	34
3.16	SAMWriter Class Reference	35
3.16.1	Detailed Description	35
3.16.2	Constructor & Destructor Documentation	36
3.16.2.1	SAMWriter	36
3.16.2.2	~SAMWriter	36
3.16.3	Member Function Documentation	36
3.16.3.1	write_fragment	36
3.17	SeqWeightTable Class Reference	36
3.17.1	Detailed Description	37
3.17.2	Constructor & Destructor Documentation	37
3.17.2.1	SeqWeightTable	37
3.17.3	Member Function Documentation	37
3.17.3.1	append_output	37
3.17.3.2	get_weight	37
3.17.3.3	increment_expected	38
3.17.3.4	increment_observed	38
3.17.3.5	to_string	38
3.18	ThreadedMapParser Class Reference	39
3.18.1	Detailed Description	39
3.18.2	Constructor & Destructor Documentation	39
3.18.2.1	ThreadedMapParser	39
3.18.2.2	~ThreadedMapParser	39
3.18.3	Member Function Documentation	40
3.18.3.1	threaded_parse	40
3.18.3.2	trans_index	40
3.19	Transcript Class Reference	40
3.19.1	Detailed Description	41
3.19.2	Constructor & Destructor Documentation	41
3.19.2.1	Transcript	41
3.19.3	Member Function Documentation	42
3.19.3.1	add_mass	42
3.19.3.2	bundle	42
3.19.3.3	bundle	42
3.19.3.4	effective_length	42
3.19.3.5	est_effective_length	42
3.19.3.6	id	43
3.19.3.7	incr_uniq_counts	43
3.19.3.8	length	43
3.19.3.9	log_likelihood	43
3.19.3.10	mass	44
3.19.3.11	mass_var	44
3.19.3.12	name	44
3.19.3.13	seq	44
3.19.3.14	tot_counts	44
3.19.3.15	unbiased_effective_length	45
3.19.3.16	uniq_counts	45

3.19.3.17	update_transcript_bias	45
3.20	TranscriptTable Class Reference	45
3.20.1	Detailed Description	46
3.20.2	Constructor & Destructor Documentation	46
3.20.2.1	TranscriptTable	46
3.20.2.2	~TranscriptTable	47
3.20.3	Member Function Documentation	47
3.20.3.1	covar_size	47
3.20.3.2	get_covar	47
3.20.3.3	get_trans	47
3.20.3.4	merge_bundles	48
3.20.3.5	num_bundles	48
3.20.3.6	output_results	48
3.20.3.7	size	48
3.20.3.8	threaded_bias_update	49
3.20.3.9	update_covar	49
3.21	Writer Class Reference	49
3.21.1	Detailed Description	50
3.21.2	Member Function Documentation	50
3.21.2.1	write_fragment	50

Chapter 1

Class Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

BiasBoss	8
Bundle	10
BundleTable	12
FLD	14
FragHit	17
Fragment	20
FrequencyMatrix	22
Globals	24
MismatchTable	25
Parser	27
BAMParser	5
SAMPParser	33
ParseThreadSafety	29
PosWeightTable	30
SeqWeightTable	36
ThreadedMapParser	39
Transcript	40
TranscriptTable	45
Writer	49
BAMWriter	7
SAMWriter	35

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

BAMParser	5
BAMWriter	7
BiasBoss	8
Bundle	10
BundleTable	12
FLD	14
FragHit	17
Fragment	20
FrequencyMatrix	22
Globals	24
MismatchTable	25
Parser	27
ParseThreadSafety	29
PosWeightTable	30
SAMParser	33
SAMWriter	35
SeqWeightTable	36
ThreadedMapParser	39
Transcript	40
TranscriptTable	45
Writer	49


Chapter 3

Class Documentation

3.1 BAMParser Class Reference

```
#include <mapparser.h>
```

Inheritance diagram for BAMParser:



Public Member Functions

- [BAMParser](#) (BamTools::BamReader *reader)
- [~BAMParser](#) ()
- const std::string [header](#) () const
- const TransIndex & [trans_index](#) () const
- bool [next_fragment](#) ([Fragment](#) &f)

3.1.1 Detailed Description

The [BAMParser](#) class fills [Fragment](#) objects by parsing an input file in BAM format.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 85 of file mapparser.h.

3.1.2 Constructor & Destructor Documentation

3.1.2.1 `BAMParser::BAMParser (BamTools::BamReader * reader)`

[BAMParser](#) constructor sets the reader

Definition at line 178 of file mapparser.cpp.

3.1.2.2 `BAMParser::~~BAMParser ()` `[inline]`

[BAMParser](#) destructor deletes the reader

Definition at line 118 of file mapparser.h.

3.1.3 Member Function Documentation

3.1.3.1 `const std::string BAMParser::header () const` `[inline, virtual]`

a member function that returns a string version of the header

Returns

string version of the header

Implements [Parser](#).

Definition at line 124 of file mapparser.h.

3.1.3.2 `bool BAMParser::next_fragment (Fragment & f)` `[virtual]`

a member function that loads all mappings of the next fragment

Parameters

<i>f</i>	the empty Fragment to add mappings to
----------	---

Returns

true if more reads remain in the BAM file, false otherwise

Implements [Parser](#).

Definition at line 200 of file mapparser.cpp.

3.1.3.3 `const TransIndex& BAMParser::trans_index () const` `[inline, virtual]`

a member function that returns the transcript-to-index map

Returns

the transcript-to-index map

Implements [Parser](#).

Definition at line 130 of file mapparser.h.


The documentation for this class was generated from the following files:

- src/mapparser.h
- src/mapparser.cpp

3.2 BAMWriter Class Reference

```
#include <mapparser.h>
```

Inheritance diagram for BAMWriter:



Public Member Functions

- [BAMWriter](#) (BamTools::BamWriter *writer)
- [~BAMWriter](#) ()
- void [write_fragment](#) ([Fragment](#) &f)

3.2.1 Detailed Description

The [BAMWriter](#) class writes [Fragment](#) objects back to file (in BAM format) with per-mapping probabilistic assignments.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 146 of file mapparser.h.

3.2.2 Constructor & Destructor Documentation

3.2.2.1 BAMWriter::BAMWriter (BamTools::BamWriter * *writer*)

[BAMWriter](#) constructor stores a pointer to the BAM file

Definition at line 256 of file mapparser.cpp.

3.2.2.2 BAMWriter::~~BAMWriter ()

[BAMWriter](#) destructor flushes and deletes the Bamtools::BamWriter

Definition at line 257 of file mapparser.cpp.

3.2.3 Member Function Documentation

3.2.3.1 void BAMWriter::write_fragment ([Fragment](#) & *f*) [virtual]

a member function that writes all mappings of the fragment to the ouput file in BAM format along with their probabilities in the "PH" field

Parameters

<i>f</i>	the processed Fragment to output
----------	--

Implements [Writer](#).

Definition at line 263 of file mapparser.cpp.

The documentation for this class was generated from the following files:

- src/mapparser.h
- src/mapparser.cpp

3.3 BiasBoss Class Reference

```
#include <biascorrection.h>
```

Public Member Functions

- [BiasBoss](#) (double alpha)
- void [update_expectations](#) (const [Transcript](#) &trans)
- void [update_observed](#) (const [FragHit](#) &hit, double mass)
- double [get_transcript_bias](#) (std::vector< double > &start_bias, std::vector< double > &end_bias, const [Transcript](#) &trans) const
- std::string [to_string](#) () const
- void [append_output](#) (std::ofstream &outfile) const

3.3.1 Detailed Description

The [BiasBoss](#) class keeps track of sequence-specific and positional bias. It allows for the bias associated with a given fragment end to be calculated, and for the bias parameters to be updated based on additional observations. All stored and returned values are in log space.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 208 of file biascorrection.h.

3.3.2 Constructor & Destructor Documentation**3.3.2.1 BiasBoss::BiasBoss (double *alpha*)**

[BiasBoss](#) Constructor

Parameters

<i>alpha</i>	a double specifying the strength of the uniform prior (logged pseudo-counts for each paramater)
--------------	---

Definition at line 218 of file biascorrection.cpp.

3.3.3 Member Function Documentation**3.3.3.1 void BiasBoss::append_output (std::ofstream & *outfile*) const**

a member function that outputs the positional and sequence-specific bias parameter matrices

Parameters

<i>outfile</i>	the file to append to
----------------	-----------------------

3.3.3.2 double BiasBoss::get_transcript_bias (std::vector< double > & *start_bias*, std::vector< double > & *end_bias*, const Transcript & *trans*) const

a member function that returns the 5' and 3' bias values at each position in a given transcript based on the current bias parameters

Parameters

<i>start_bias</i>	a vector containing the logged bias for each 5' start site in the transcript
<i>end_bias</i>	a vector containing the logged bias for each 3' end site in the transcript
<i>trans</i>	the transcript for which to calculate the logged bias

Returns

the product of the average 5' and 3' bias (logged)

Definition at line 284 of file biascorrection.cpp.

3.3.3.3 string BiasBoss::to_string () const

a member function that returns a string containing the observed positional nucleotide probabilities (non-logged) in column-major order (A,C,G,T)

Returns

the string representation of the observed probabilities

Definition at line 313 of file biascorrection.cpp.

3.3.3.4 void BiasBoss::update_expectations (const Transcript & *trans*)

a member function that updates the expectation parameters (sequence-specific and positional) assuming uniform expression of and accross the transcript's sequence

Parameters

<i>trans</i>	the transcript to measure expected counts from
--------------	--

Definition at line 225 of file biascorrection.cpp.

3.3.3.5 void BiasBoss::update_observed (const FragHit & *hit*, double *mass*)

a member function that updates the observed parameters (sequence-specific and positional) given a fragment mapping to a transcript and its logged probabilistic assignment

Parameters

<i>hit</i>	the fragment hit (alignment)
<i>mass</i>	the logged probability of the mapping, which is the amount to update the observed counts by

Definition at line 245 of file biascorrection.cpp.

The documentation for this class was generated from the following files:

- src/biascorrection.h
- src/biascorrection.cpp

3.4 Bundle Class Reference

```
#include <bundles.h>
```

Public Member Functions

- [Bundle](#) ([Transcript](#) *trans)
- void [incr_counts](#) (size_t incr_amt=1)
- size_t [size](#) () const
- std::vector< [Transcript](#) * > & [transcripts](#) ()
- size_t [counts](#) () const

3.4.1 Detailed Description

The [Bundle](#) class keeps track of a group of transcripts that have shared ambiguous (multi-mapped) reads. Besides storing the transcript, it keeps track of the number of observed fragments, the total fragment mass, and the next fragment mass (which it also updates).

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 26 of file bundles.h.

3.4.2 Constructor & Destructor Documentation

3.4.2.1 [Bundle::Bundle](#) ([Transcript](#) * *trans*)

[Bundle](#) Constructor.

Parameters

<i>trans</i>	a pointer to the initial Transcript object in the bundle
<i>fmt</i>	a pointer to the (global) FragMassTable

Definition at line 15 of file bundles.cpp.

3.4.3 Member Function Documentation

3.4.3.1 [size_t Bundle::counts](#) () const `[inline]`

a member function that returns the total number of observed fragments mapped to transcripts in the bundle

Returns

the total number of fragments mapped to transcripts in the bundle

Definition at line 70 of file bundles.h.

3.4.3.2 void Bundle::incr_counts (size_t *incr_amt* = 1)

a member function that increases the total bundle observed fragment counts by a given amount

Parameters

<i>incr_amt</i>	the amount to increase the counts by
-----------------	--------------------------------------

Definition at line 19 of file bundles.cpp.

3.4.3.3 size_t Bundle::size () const [inline]

a member function that returns the number of transcripts in the bundle

Returns

the number of transcripts in the bundle

Definition at line 58 of file bundles.h.

3.4.3.4 std::vector<Transcript*>& Bundle::transcripts () [inline]

a member function that returns a reference to the vector of pointers to transcripts in the bundle

Returns

reference to the vector pointing to bundle transcripts

Definition at line 64 of file bundles.h.

The documentation for this class was generated from the following files:

- src/bundles.h
- src/bundles.cpp

3.5 BundleTable Class Reference

```
#include <bundles.h>
```

Public Member Functions

- [BundleTable](#) ()
- [~BundleTable](#) ()

- `const BundleSet & bundles () const`
- `size_t size () const`
- `Bundle * create_bundle (Transcript *trans)`
- `Bundle * merge (Bundle *b1, Bundle *b2)`

3.5.1 Detailed Description

The `BundleTable` class keeps track of the `Bundle` objects for a given run. It has the ability to create, delete, and merge bundles. It also keeps track of the transcript covariances, since these are related to bundles in that all covariances outside of a bundle are nonzero.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 84 of file `bundles.h`.

3.5.2 Constructor & Destructor Documentation

3.5.2.1 `BundleTable::BundleTable ()` `[inline]`

`BundleTable` constructor.

Definition at line 96 of file `bundles.h`.

3.5.2.2 `BundleTable::~~BundleTable ()`

`BundleTable` destructor. Deletes all `Bundle` objects.

Definition at line 24 of file `bundles.cpp`.

3.5.3 Member Function Documentation

3.5.3.1 `const BundleSet& BundleTable::bundles () const` `[inline]`

a member function that returns the set of current `Bundle` objects

Returns

a reference to the `unordered_set` containing all current `Bundle` objects

Definition at line 107 of file `bundles.h`.

3.5.3.2 `Bundle * BundleTable::create_bundle (Transcript * trans)`

a member function that creates a new bundle, initially with only the single given [Transcript](#)

Parameters

<i>trans</i>	a pointer to the only Transcript initially contained in the Bundle
--------------	--

Returns

a pointer to the new [Bundle](#) object

Definition at line 32 of file bundles.cpp.

3.5.3.3 `Bundle * BundleTable::merge (Bundle * b1, Bundle * b2)`

a member function that merges two [Bundle](#) objects into one the Transcripts are all move to the larger bundles and the other is deleted

Parameters

<i>b1</i>	a pointer to one of the Bundle objects to merge
<i>b2</i>	a pointer to the other Bundle object to merge

Returns

a pointer to the merged [Bundle](#) object

Definition at line 39 of file bundles.cpp.

3.5.3.4 `size_t BundleTable::size () const` `[inline]`

a member function that returns the size of the set of current [Bundle](#) objects, which is the current number of bundles

Returns

the current number of bundles

Definition at line 114 of file bundles.h.

The documentation for this class was generated from the following files:

- src/bundles.h
- src/bundles.cpp

3.6 FLD Class Reference

```
#include <fld.h>
```

Public Member Functions

- [FLD](#) (double *alpha*, size_t *max_val*, size_t *mean*, size_t *std_dev*)
- size_t [max_val](#) () const
- double [mean](#) () const
- void [add_val](#) (size_t *len*, double *mass*)
- double [pdf](#) (size_t *len*) const
- double [tot_mass](#) () const
- std::string [to_string](#) () const
- void [append_output](#) (std::ofstream &*outfile*) const

3.6.1 Detailed Description

The [FLD](#) class keeps track of the observed fragment length distribution. It starts with a Gaussian prior with parameters specified by the arguments. A small "Gaussian" kernel is added for each observation. All mass values and probabilities are stored and returned in log space (except in [to_string](#)).

Definition at line 21 of file `fld.h`.

3.6.2 Constructor & Destructor Documentation

3.6.2.1 FLD::FLD (double *alpha*, size_t *max_val*, size_t *mean*, size_t *std_dev*)

[FLD](#) Constructor

Parameters

<i>alpha</i>	double that sets the average pseudo-counts (logged)
<i>max_val</i>	an integer that sets the maximum allowable FragHit length
<i>mean</i>	a size_t for the mean of the prior gaussian dist
<i>std_dev</i>	a size_t for the std dev of the prior gaussian dist

Definition at line 21 of file `fld.cpp`.

3.6.3 Member Function Documentation

3.6.3.1 void FLD::add_val (size_t *len*, double *mass*)

a member function that updates the distribution based on a new [FragHit](#) observation

Parameters

<i>len</i>	an integer for the observed FragHit length
<i>mass</i>	a double for the mass (logged) of the observed FragHit

Definition at line 46 of file `fld.cpp`.

3.6.3.2 void FLD::append_output (std::ofstream & *outfile*) const

a member function that appends the [FLD](#) parameters to the end of the given file

Parameters

<i>outfile</i>	the file to append to
----------------	-----------------------

3.6.3.3 size_t FLD::max_val () const

a member function that returns the maximum allowed [FragHit](#) length

Returns

max allowed [FragHit](#) length

Definition at line 41 of file fld.cpp.

3.6.3.4 double FLD::mean () const

a member function that returns the mean [FragHit](#) length

Returns

mean observed [FragHit](#) length

Definition at line 74 of file fld.cpp.

3.6.3.5 double FLD::pdf (size_t *len*) const

a member function that returns the (logged) probability of a given [FragHit](#) length

Parameters

<i>len</i>	an integer for the FragHit length to return the probability of
------------	--

Returns

(logged) probability of observing the given [FragHit](#) length

Definition at line 62 of file fld.cpp.

3.6.3.6 string FLD::to_string () const

a member function that returns a string containing the current distribution

Returns

space-separated string of probabilities ordered from length 0 to max_val (non-logged)

Definition at line 79 of file fld.cpp.

3.6.3.7 double FLD::tot_mass () const

a member function that returns the (logged) number of observed FragHits (including pseudo-counts)

Returns

number of observed fragments

Definition at line 69 of file fld.cpp.

The documentation for this class was generated from the following files:

- src/fld.h
- src/fld.cpp

3.7 FragHit Struct Reference

```
#include <fragments.h>
```

Public Member Functions

- int [length](#) () const
- PairStatus [pair_status](#) () const

Public Attributes

- std::string [name](#)
- TransID [trans_id](#)
- Transcript * [mapped_trans](#)
- std::string [seq_l](#)
- std::string [seq_r](#)
- int [left](#)
- int [right](#)
- int [mate_l](#)
- bool [left_first](#)
- double **probability**
- BamTools::BamAlignment **bam_l**
- BamTools::BamAlignment **bam_r**
- std::string **sam_l**
- std::string **sam_r**

3.7.1 Detailed Description

The [FragHit](#) struct stores the information for a single (multi-)mapping of a fragment.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 37 of file fragments.h.

3.7.2 Member Function Documentation

3.7.2.1 `int FragHit::length () const` `[inline]`

a member function returning the length of the fragment according to this mapping note, that this result will be invalid if the fragment is single-end

Returns

int length of fragment mapping

Definition at line 95 of file fragments.h.

3.7.2.2 `PairStatus FragHit::pair_status () const` `[inline]`

a member function returning whether the mapping is PAIRED, LEFT_ONLY, or RIGHT_ONLY LEFT_ONLY denotes that the single read is not reverse complemented => its left end is the left fragment end RIGHT_ONLY denotes that the single read is reverse complemented => its right end is the right fragment end

Returns

PairStatus the pair status of the mapping

Definition at line 106 of file fragments.h.

3.7.3 Member Data Documentation

3.7.3.1 `int FragHit::left`

a public int containing the 0-based leftmost coordinate mapped to in the transcript valid only if PairStatus is PAIRED or LEFT_ONLY

Definition at line 68 of file fragments.h.

3.7.3.2 bool FragHit::left_first

a public bool specifying that the "right" (second according to SAM flag) is reverse complemented when true and the "left" (first according to SAM flag) is reverse complemented when false in other words, the "left" read is truly left of the "right" read in transcript coordinate space when true

Definition at line 88 of file fragments.h.

3.7.3.3 Transcript* FragHit::mapped_trans

a public pointer to the transcript mapped to

Definition at line 52 of file fragments.h.

3.7.3.4 int FragHit::mate_l

a public int containing the left position for the mate of the first read read in from the SAM file 0 if single-end fragment this is temporarily used to help find the mate, but is not important later on

Definition at line 81 of file fragments.h.

3.7.3.5 std::string FragHit::name

a public string for the SAM "Query Template Name" (fragment name)

Definition at line 42 of file fragments.h.

3.7.3.6 int FragHit::right

a public int containing the position following the 0-based rightmost coordinate mapped to in the transcript valid only if PairStatus is PAIRED or RIGHT_ONLY

Definition at line 74 of file fragments.h.

3.7.3.7 std::string FragHit::seq_l

a public string containing the "left" read sequence (first according to SAM flag)

Definition at line 57 of file fragments.h.

3.7.3.8 std::string FragHit::seq_r

a public string containing the "right" read sequence (second according to SAM flag)

Definition at line 62 of file fragments.h.

3.7.3.9 TransID `FragHit::trans_id`

a public TransID for the transcript mapped to

Definition at line 47 of file `fragments.h`.

The documentation for this struct was generated from the following file:

- `src/fragments.h`

3.8 Fragment Class Reference

```
#include <fragments.h>
```

Public Member Functions

- [~Fragment](#) ()
- bool [add_map_end](#) ([FragHit](#) *f)
- const std::string [name](#) () const
- const size_t [num_hits](#) () const
- const std::vector< [FragHit](#) * > & [hits](#) () const

3.8.1 Detailed Description

The [Fragment](#) class stores information for all multi-mappings of a single fragment. By design, only paired-end mappings of paired-end reads will be accepted. All mappings of single-end reads will be accepted.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 131 of file `fragments.h`.

3.8.2 Constructor & Destructor Documentation

3.8.2.1 `Fragment::~~Fragment` ()

[Fragment](#) destructor deletes all [FragHit](#) objects pointed to by the [Fragment](#)

Definition at line 14 of file `fragments.cpp`.

3.8.3 Member Function Documentation

3.8.3.1 `bool Fragment::add_map_end (FragHit * f)`

a member function that adds a new [FragHit](#) (single read at this point) to the [Fragment](#) if it is the first [FragHit](#), it sets the [Fragment](#) name and is added to `_open_mates`, if the fragment is not paired, it is added to `_frag_hits`, otherwise, `add_open_mate` is called

Parameters

<i>f</i>	the FragHit to be added
----------	---

Definition at line 27 of file `fragments.cpp`.

3.8.3.2 `const std::vector<FragHit*>& Fragment::hits () const` `[inline]`

a member function that returns [FragHit](#) multi-mappings of the fragment

Returns

a vector containing pointers to the [FragHit](#) multi-mappings

Definition at line 188 of file `fragments.h`.

3.8.3.3 `const std::string Fragment::name () const` `[inline]`

a member function that returns the SAM "Query Template Name" (fragment name)

Returns

the string SAM "Query Template Name" (fragment name)

Definition at line 176 of file `fragments.h`.

3.8.3.4 `const size_t Fragment::num_hits () const` `[inline]`

a member function that returns the number of multi-mappings for the fragment

Returns

number of multi-mappings for fragment

Definition at line 182 of file `fragments.h`.

The documentation for this class was generated from the following files:

- `src/fragments.h`
- `src/fragments.cpp`

3.9 FrequencyMatrix Class Reference

```
#include <frequencymatrix.h>
```

Public Member Functions

- [FrequencyMatrix](#) ()
- [FrequencyMatrix](#) (size_t m, size_t n, double alpha)
- double [operator\(\)](#) (size_t i, size_t j) const
- double [operator\(\)](#) (size_t k) const
- void [increment](#) (size_t i, size_t j, double incr_amt)
- void [increment](#) (size_t k, double incr_amt)
- double [arr](#) (size_t k) const
- double [row](#) (size_t i) const

3.9.1 Detailed Description

The [FrequencyMatrix](#) class keeps track of the frequency parameters in order to allow for constant-time probability look-ups and updates. The table is rectangular to allow for multiple distributions to be stored in one [FrequencyMatrix](#). Rows are distributions. All values are stored and returned in log space.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 24 of file frequencymatrix.h.

3.9.2 Constructor & Destructor Documentation

3.9.2.1 [FrequencyMatrix::FrequencyMatrix](#) () [inline]

dummy constructor

Definition at line 51 of file frequencymatrix.h.

3.9.2.2 [FrequencyMatrix::FrequencyMatrix](#) (size_t m, size_t n, double alpha)

[FrequencyMatrix](#) constructor initializes the matrix based on the log of the given pseudo-counts

Parameters

<i>m</i>	a size_t specifying the number of distributions (rows)
<i>n</i>	a size_t specifying the number of values in each distribution (columns)
<i>alpha</i>	a double specifying the initial pseudo-counts (m*log(alpha))

Definition at line 16 of file frequencymatrix.cpp.

3.9.3 Member Function Documentation

3.9.3.1 double FrequencyMatrix::arr (size_t *k*) const [inline]

a member function that returns the raw value stored at a given position of the flattened matrix

Parameters

<i>k</i>	the array position
----------	--------------------

Returns

a double specifying the raw value stored at the given position of the flattened matrix

Definition at line 96 of file frequencymatrix.h.

3.9.3.2 void FrequencyMatrix::increment (size_t *i*, size_t *j*, double *incr_amt*)

a member function to increase the mass of a given position in the matrix

Parameters

<i>i</i>	the distribution (row)
<i>j</i>	the value (column)
<i>incr_amt</i>	the logged amount to increase the mass by

Definition at line 37 of file frequencymatrix.cpp.

3.9.3.3 void FrequencyMatrix::increment (size_t *k*, double *incr_amt*)

a member function to increase the mass of a given position in the flattened matrix

Parameters

<i>k</i>	the array position
<i>incr_amt</i>	the logged amount to increase the mass by

Definition at line 45 of file frequencymatrix.cpp.

3.9.3.4 double FrequencyMatrix::operator() (size_t *k*) const

a member function to extract the logged probability of a given position in the flattened matrix

Parameters

k	the array position
-----	--------------------

Returns

a double specifying the logged probability of the given position in the flattened matrix

Definition at line 31 of file frequencymatrix.cpp.

3.9.3.5 double FrequencyMatrix::operator() (size_t i , size_t j) const

a member function to extract the logged probability of a given position in the matrix

Parameters

i	the distribution (row)
j	the value (column)

Returns

a double specifying the logged probability of the given value in the given distribution

Definition at line 24 of file frequencymatrix.cpp.

3.9.3.6 double FrequencyMatrix::row (size_t i) const [inline]

a member function that returns the raw row sum

Parameters

i	the distribution (row)
-----	------------------------

Returns

a double specifying the raw row sum for the given distribution

Definition at line 103 of file frequencymatrix.h.

The documentation for this class was generated from the following files:

- src/frequencymatrix.h
- src/frequencymatrix.cpp

3.10 Globals Struct Reference

```
#include <main.h>
```


Public Attributes

- [FLD](#) * **fld**
- [MismatchTable](#) * **mismatch_table**
- [BiasBoss](#) * **bias_table**

3.10.1 Detailed Description

a struct for holding pointers to the global parameter tables (bias_table, mismatch_table, fld)

Definition at line 26 of file main.h.

The documentation for this struct was generated from the following file:

- src/main.h

3.11 MismatchTable Class Reference

```
#include <mismatchmodel.h>
```

Public Member Functions

- [MismatchTable](#) (double alpha)
- void [activate](#) (bool active=true)
- double [log_likelihood](#) (const [FragHit](#) &f) const
- void [update](#) (const [FragHit](#) &, double mass)
- std::string [to_string](#) () const
- void [append_output](#) (std::ofstream &outfile) const

3.11.1 Detailed Description

The [MismatchTable](#) class is used to store and update mismatch (error) parameters using a first-order Markov model based on nucleotide and position in a ride and to return likelihoods of mismatches in given reads. All values are stored and returned in log space.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 24 of file mismatchmodel.h.

3.11.2 Constructor & Destructor Documentation

3.11.2.1 MismatchTable::MismatchTable (double *alpha*)

[MismatchTable](#) constructor initializes the model parameters using the specified (non-logged) pseudo-counts.

Parameters

<i>alpha</i>	a double containing the non-logged pseudo-counts for parameter initialization
--------------	---

Definition at line 18 of file mismatchmodel.cpp.

3.11.3 Member Function Documentation

3.11.3.1 void MismatchTable::activate (bool *active* = true) [inline]

member function that 'activates' the table to allow its values to be used in calculating log-likelihoods when it is sufficiently burned-in

Parameters

<i>active</i>	a boolean specifying whether to activate (true) or deactivate (false)
---------------	---

Definition at line 59 of file mismatchmodel.h.

3.11.3.2 void MismatchTable::append_output (std::ofstream & *outfile*) const

a member function that outputs the final model parameters in a tab-separated file the file has 1 row for each read position and the parameters are in columns indexed as (ref, prev, obs) in base 4 with A,C,G,T encoded as 0,1,2,3.

Parameters

<i>file</i>	stream to append to
-------------	---------------------

Definition at line 85 of file biascorrection.cpp.

3.11.3.3 double MismatchTable::log_likelihood (const FragHit & *f*) const

member function returns the log likelihood of mismatches in the mapping given the current error model paramaters

Parameters

<i>f</i>	the fragment mapping to calculate the log likelihood for
----------	--

Returns

the log likelihood of the mapping based on mismatches

Definition at line 25 of file mismatchmodel.cpp.

3.11.3.4 string MismatchTable::to_string () const

member function that returns a string containing a collapsed confusion matrix based on the model parameters for the first read

Returns

a space-separated string for the flattened, collapsed confusion matrix in row-major format (observed value as rows)

Definition at line 113 of file mismatchmodel.cpp.

3.11.3.5 void MismatchTable::update (const FragHit & f, double mass)

member function that updates the error model parameters based on a mapping and its (logged) mass

Parameters

<i>f</i>	the fragment mapping
<i>mass</i>	the logged mass to increase the parameters by

Definition at line 72 of file mismatchmodel.cpp.


The documentation for this class was generated from the following files:

- src/mismatchmodel.h
- src/biascorrection.cpp
- src/flc.cpp
- src/mismatchmodel.cpp

3.12 Parser Class Reference

```
#include <mapparser.h>
```

Inheritance diagram for Parser:



Public Member Functions

- virtual const std::string [header](#) () const =0
- virtual const TransIndex & [trans_index](#) () const =0
- virtual bool [next_fragment](#) ([Fragment](#) &f)=0

3.12.1 Detailed Description

The [Parser](#) class is an abstract class that can be a [SAMParse](#)r or [BAMParse](#)r. It fills [Fragment](#) objects by parsing an input file in SAM/BAM format.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 33 of file mapparser.h.

3.12.2 Member Function Documentation

3.12.2.1 virtual const std::string Parser::header () const [pure virtual]

a member function that returns a string version of the header

Returns

string version of the header

Implemented in [BAMParse](#)r, and [SAMParse](#)r.

3.12.2.2 virtual bool Parser::next_fragment ([Fragment](#) &f) [pure virtual]

a member function that loads all mappings of the next fragment

Parameters

<i>f</i>	the empty Fragment to add mappings to
----------	---

Returns

true if more reads remain in the SAM/BAM file/stream, false otherwise

Implemented in [BAMParse](#)r, and [SAMParse](#)r.

3.12.2.3 `virtual const TransIndex& Parser::trans_index () const` `[pure virtual]`

a member function that returns the transcript-to-index map

Returns

the transcript-to-index map

Implemented in [BAMParser](#), and [SAMPParser](#).

The documentation for this class was generated from the following file:

- `src/mapparser.h`

3.13 ParseThreadSafety Struct Reference

```
#include <mapparser.h>
```

Public Attributes

- [Fragment](#) * `next_frag`
- `boost::mutex` `mut`
- `boost::condition_variable` `cond`
- `bool` `frag_clean`

3.13.1 Detailed Description

The [ParseThreadSafety](#) struct stores objects to allow for parsing to safely occur on a separate thread from processing.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 277 of file `mapparser.h`.

3.13.2 Member Data Documentation

3.13.2.1 `boost::mutex` `ParseThreadSafety::mut`

FIX

Definition at line 287 of file `mapparser.h`.

3.13.2.2 `Fragment* ParseThreadSafety::next_frag`

a pointer to the next [Fragment](#) to be processed by the main thread

Definition at line 282 of file `mapparser.h`.

The documentation for this struct was generated from the following file:

- `src/mapparser.h`

3.14 `PosWeightTable` Class Reference

```
#include <biascorrection.h>
```

Public Member Functions

- [PosWeightTable](#) (const std::vector< size_t > &len_bins, const std::vector< double > &pos_bins, double alpha)
- const std::vector< size_t > & **len_bins** () const
- const std::vector< double > & **pos_bins** () const
- void [increment_expected](#) (size_t len, double pos)
- void [increment_expected](#) (size_t l, size_t p)
- void [increment_observed](#) (size_t len, double pos, double normalized_mass)
- void [increment_observed](#) (size_t l, size_t p, double normalized_mass)
- double [get_weight](#) (size_t len, double pos) const
- double [get_weight](#) (size_t l, size_t p) const
- void [append_output](#) (std::ofstream &outfile) const

3.14.1 Detailed Description

The [PosWeightTable](#) class keeps track of fractional position bias parameters in log space. It allows for the bias associated with a given fractional position to be calculated, and for the bias parameters to be updated based on additional fragment observations.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 101 of file `biascorrection.h`.

3.14.2 Constructor & Destructor Documentation

3.14.2.1 `PosWeightTable::PosWeightTable (const std::vector< size_t > & len_bins, const std::vector< double > & pos_bins, double alpha)`

[PosWeightTable](#) Constructor

Parameters

<i>len_bins</i>	a vector of unsigned integers specifying the bin ranges for transcript lengths
<i>pos_bins</i>	a vector of doubles specifying the bin ranges for fractional positions
<i>alpha</i>	a double specifying the strength of the uniform prior (logged pseudo-counts for each paramater)

Definition at line 123 of file biascorrection.cpp.

3.14.3 Member Function Documentation

3.14.3.1 `void PosWeightTable::append_output (std::ofstream & outfile) const`

a member function that outputs the fractional position probabilities in matrix format with length bins as rows and fractional position bins as columns

Parameters

<i>outfile</i>	the file to append to
----------------	-----------------------

3.14.3.2 `double PosWeightTable::get_weight (size_t len, double pos) const`

a member function that return the bias weight (logged) of a fractional transcript position

Parameters

<i>len</i>	the transcript length
<i>pos</i>	the fractional transcript position

Returns

the logged bias weight for the fractional transcript position

Definition at line 156 of file biascorrection.cpp.

3.14.3.3 `double PosWeightTable::get_weight (size_t l, size_t p) const`

a member function that return the bias weight (logged) of a fractional transcript position bin

Parameters

<i>l</i>	the transcript length bin
<i>p</i>	the fractional transcript position bin

Returns

the logged bias weight for the fractional transcript position

Definition at line 55 of file biascorrection.cpp.

3.14.3.4 void PosWeightTable::increment_expected (size_t *l*, size_t *p*)

a member function that increments the expected counts for the given fractional position bin by 1 (logged)

Parameters

<i>l</i>	the transcript length bin
<i>p</i>	the fractional transcript position bin

Definition at line 137 of file biascorrection.cpp.

3.14.3.5 void PosWeightTable::increment_expected (size_t *len*, double *pos*)

a member function that increments the expected counts for the given fractional position by 1 (logged)

Parameters

<i>len</i>	the transcript length
<i>pos</i>	the fractional transcript position

Definition at line 130 of file biascorrection.cpp.

3.14.3.6 void PosWeightTable::increment_observed (size_t *len*, double *pos*, double *normalized_mass*)

a member function that increments the observed counts for the given fragment position by some mass (logged)

Parameters

<i>len</i>	the transcript length
<i>pos</i>	the fractional transcript position
<i>normalized_mass</i>	the mass (logged probabilistic assignment) of the fragment normalized by its estimated expression

Definition at line 143 of file biascorrection.cpp.

3.14.3.7 `void PosWeightTable::increment_observed (size_t l, size_t p, double normalized_mass)`

a member function that increments the observed counts for the given fragment position bin by some mass (logged)

Parameters

<i>l</i>	the transcript length bin
<i>p</i>	the fractional transcript position bin
<i>normalized_-mass</i>	the mass (logged probabilistic assignment) of the fragment normalized by its estimated expression

Definition at line 44 of file biascorrection.cpp.


The documentation for this class was generated from the following files:

- src/biascorrection.h
- src/biascorrection.cpp

3.15 SAMParser Class Reference

```
#include <mapparser.h>
```

Inheritance diagram for SAMParser:



Public Member Functions

- [SAMParser](#) (std::istream *in)
- const std::string [header](#) () const
- const TransIndex & [trans_index](#) () const
- bool [next_fragment](#) ([Fragment](#) &f)

3.15.1 Detailed Description

The [SAMParser](#) class fills [Fragment](#) objects by parsing an input in SAM format. The input may come from a file or stdin.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 181 of file mapparser.h.

3.15.2 Constructor & Destructor Documentation**3.15.2.1 SAMParser::SAMParser (std::istream * *in*)**

[SAMParser](#) constructor removes the header, and parses the first line

Definition at line 274 of file mapparser.cpp.

3.15.3 Member Function Documentation**3.15.3.1 const std::string SAMParser::header () const [inline, virtual]**

a member function that returns a string version of the header

Returns

string version of the header

Implements [Parser](#).

Definition at line 219 of file mapparser.h.

3.15.3.2 bool SAMParser::next_fragment (Fragment & *f*) [virtual]

a member function that loads all mappings of the next fragment when the next fragment is reached, the current alignment is left in the `_frag_buff` for the next call

Parameters

<i>f</i>	the empty Fragment to add mappings to
----------	---

Returns

true if more reads remain in the SAM file, false otherwise

Implements [Parser](#).

Definition at line 322 of file mapparser.cpp.

3.15.3.3 const TransIndex& SAMParser::trans_index () const [inline, virtual]

a member function that returns the transcript-to-index map

Returns

the transcript-to-index map

Implements [Parser](#).

Definition at line 225 of file mapparser.h.


The documentation for this class was generated from the following files:

- src/mapparser.h
- src/mapparser.cpp

3.16 SAMWriter Class Reference

```
#include <mapparser.h>
```

Inheritance diagram for SAMWriter:

**Public Member Functions**

- [SAMWriter](#) (std::ostream *out)
- [~SAMWriter](#) ()
- void [write_fragment](#) ([Fragment](#) &f)

3.16.1 Detailed Description

The [SAMWriter](#) class writes [Fragment](#) objects back to file (in SAM format) with per-mapping probabilistic assignments.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 243 of file mapparser.h.

3.16.2 Constructor & Destructor Documentation

3.16.2.1 SAMWriter::SAMWriter (std::ostream * out)

[SAMWriter](#) constructor stores a pointer to the output stream

Definition at line 410 of file mapparser.cpp.

3.16.2.2 SAMWriter::~SAMWriter ()

[SAMWriter](#) destructor flushes and deletes output stream

Definition at line 411 of file mapparser.cpp.

3.16.3 Member Function Documentation

3.16.3.1 void SAMWriter::write_fragment (Fragment & f) [virtual]

a member function that writes all mappings of the fragment to the output file in SAM format along with their probabilities in the "PH" field

Parameters

<i>f</i>	the processed Fragment to output
----------	--

Implements [Writer](#).

Definition at line 417 of file mapparser.cpp.

The documentation for this class was generated from the following files:

- src/mapparser.h
- src/mapparser.cpp

3.17 SeqWeightTable Class Reference

```
#include <biascorrection.h>
```

Public Member Functions

- [SeqWeightTable](#) (size_t window_size, double alpha)
- void [increment_expected](#) (char c)
- void [increment_observed](#) (std::string &seq, double normalized_mass)
- double [get_weight](#) (const std::string &seq, int i) const
- std::string [to_string](#) () const
- void [append_output](#) (std::ofstream &outfile) const

3.17.1 Detailed Description

The [SeqWeightTable](#) class keeps track of sequence-specific bias parameters. It allows for the bias associated with a given sequence to be calculated, and for the bias parameters to be updated based on additional observations. All values stored in log space.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 29 of file biascorrection.h.

3.17.2 Constructor & Destructor Documentation

3.17.2.1 SeqWeightTable::SeqWeightTable (*size_t window_size*, *double alpha*)

[SeqWeightTable](#) Constructor

Parameters

<i>window_size</i>	an unsigned integer specifying the size of the bias window surrounding fragment ends
<i>alpha</i>	a double specifying the strength of the uniform prior (logged pseudo-counts for each paramater)

Definition at line 29 of file biascorrection.cpp.

3.17.3 Member Function Documentation

3.17.3.1 void SeqWeightTable::append_output (*std::ofstream & outfile*) const

a member function that outputs the positional nucleotide probabilities in matrix format with nucleotides (A,C,G,T) as rows and window position as columns

Parameters

<i>outfile</i>	the file to append to
----------------	-----------------------

3.17.3.2 double SeqWeightTable::get_weight (*const std::string & seq*, *int i*) const

a member function that calculates the bias weight (logged) of a bias window

Parameters

<i>seq</i>	the transcript sequence the fragment hits to
------------	--

<i>i</i>	the fragment end point (the central point of the bias window)
----------	---

Returns

the bias weight for the bias window which is the product of the individual nucleotide bias weights

3.17.3.3 void SeqWeightTable::increment_expected (char *c*)

a member function that increments the expected counts for the given nucleotide by 1 (logged)

Parameters

<i>c</i>	a char representing a nucleotide that has been observed in the transcriptome
----------	--

Definition at line 34 of file biascorrection.cpp.

3.17.3.4 void SeqWeightTable::increment_observed (std::string & *seq*, double *normalized_mass*)

a member function that increments the observed counts for the given fragment sequence by some mass (logged)

Parameters

<i>seq</i>	a string of nucleotides in the bias window for the sequenced fragment end
<i>normalized_mass</i>	the mass (logged probabilistic assignment) of the fragment normalized by its estimated expression

3.17.3.5 string SeqWeightTable::to_string () const

a member function that returns a string containing the positional nucleotide probabilities in column-major order (A,C,G,T)

Returns

the string representation of the positional nucleotide probabilities

Definition at line 68 of file biascorrection.cpp.

The documentation for this class was generated from the following files:

- src/biascorrection.h
- src/biascorrection.cpp

3.18 ThreadedMapParser Class Reference

```
#include <mapparser.h>
```

Public Member Functions

- [ThreadedMapParser](#) (std::string input_file, std::string output_file)
- [~ThreadedMapParser](#) ()
- void [threaded_parse](#) ([ParseThreadSafety](#) *thread_safety, [TranscriptTable](#) *trans_table)
- const [TransIndex](#) & [trans_index](#) ()

3.18.1 Detailed Description

The [ThreadedMapParser](#) class is meant to be run on as a separate thread from the main processing. Once started, this thread will read input from a file or stream in SAM/BAM format, parse, and collect read alignments into fragment alignments, and fragment alignments into fragments, which are placed on a buffer for the processing thread. Once the processing thread copies the fragment address from the buffer, the parser is unlocked to load the next fragment. The process stops when EOF is reached

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 306 of file mapparser.h.

3.18.2 Constructor & Destructor Documentation

3.18.2.1 [ThreadedMapParser::ThreadedMapParser](#) (std::string *input_file*, std::string *output_file*)

[ThreadedMapParser](#) constructor determines what format the input is in and initializes the correct parser.

Definition at line 51 of file mapparser.cpp.

3.18.2.2 [ThreadedMapParser::~~ThreadedMapParser](#) ()

[ThreadedMapParser](#) destructor deletes the parser and writer (if it exists).

Definition at line 109 of file mapparser.cpp.

3.18.3 Member Function Documentation

3.18.3.1 void ThreadedMapParser::threaded_parse (ParseThreadSafety * *thread_safety*, TranscriptTable * *trans_table*)

a member function that drives the parse thread when all valid mappings of a fragment have been parsed, its mapped transcripts are found and the information is passed in a [Fragment](#) object to the processing thread through the [ParseThreadSafety](#) struct

Parameters

<i>thread_safety</i>	a pointer to the struct containing shared locks and data with the processing thread
<i>trans_table</i>	a pointer to the table of Transcript objects to lookup the mapped transcripts

Definition at line 116 of file mapparser.cpp.

3.18.3.2 const TransIndex& ThreadedMapParser::trans_index () [inline]

a member function that returns the transcript-to-index map

Returns

the transcript-to-index map

Definition at line 342 of file mapparser.h.

The documentation for this class was generated from the following files:

- src/mapparser.h
- src/mapparser.cpp

3.19 Transcript Class Reference

```
#include <transcripts.h>
```

Public Member Functions

- [Transcript](#) (const size_t id, const std::string &name, const std::string &seq, double alpha, const [Globals](#) *globs)
- const std::string & [name](#) () const
- TransID [id](#) () const
- const std::string & [seq](#) () const
- size_t [length](#) () const
- double [mass](#) () const
- double [mass_var](#) () const
- double [est_counts](#) () const

- double **est_counts_var** () const
- size_t **tot_counts** () const
- size_t **uniq_counts** () const
- **Bundle** * **bundle** ()
- void **bundle** (**Bundle** *b)
- void **add_mass** (double p, double mass)
- void **add_prob_count** (double p)
- void **incr_uniq_counts** (size_t incr_amt=1)
- double **log_likelihood** (const **FragHit** &frag) const
- double **effective_length** () const
- double **est_effective_length** () const
- double **unbiased_effective_length** () const
- void **update_transcript_bias** ()

3.19.1 Detailed Description

The **Transcript** class is used to store objects for the transcripts being mapped to. Besides storing basic information about the object (id, length), it also stores a mass based on the number of fragments mapping to the object. To help with updating this number, it returns the likelihood that a given fragment originated from it. These values are stored and returned in log space.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 41 of file transcripts.h.

3.19.2 Constructor & Destructor Documentation

3.19.2.1 Transcript::Transcript (const size_t *id*, const std::string & *name*, const std::string & *seq*, double *alpha*, const Globals * *globs*)

Transcript Constructor

Parameters

<i>name</i>	a string that stores the transcript name
<i>seq</i>	a string that stores the transcript sequence
<i>alpha</i>	a double that specifies the initial pseudo-counts (non-logged)
<i>globs</i>	a pointer to the struct containing pointers to the global parameter tables (bias_table, mismatch_table, fld)

Definition at line 24 of file transcripts.cpp.

3.19.3 Member Function Documentation

3.19.3.1 void Transcript::add_mass (double *p*, double *mass*)

a member function that increases the expected fragment counts and variance by a given (logged) fragment mass

Parameters

<i>p</i>	a double for the (logged) probability that the fragment was generated by this transcript
<i>mass</i>	a double specifying the (logged) mass of the fragment being mapped

Definition at line 42 of file transcripts.cpp.

3.19.3.2 void Transcript::bundle (Bundle * *b*) [inline]

a member function that set the [Bundle](#) this [Transcript](#) is a member of

Parameters

<i>b</i>	a pointer to the Bundle to set this Transcript as a member of
----------	---

Definition at line 205 of file transcripts.h.

3.19.3.3 Bundle* Transcript::bundle () [inline]

a member function that returns the [Bundle](#) this [Transcript](#) is a member of

Returns

a pointer to the [Bundle](#) this transcript is a member of

Definition at line 199 of file transcripts.h.

3.19.3.4 double Transcript::effective_length () const

a member function that calculates and returns the effective length of the transcript (non-logged)

Returns

the effective length of the transcript calculated as $\tilde{l} = \sum_{l=1}^{L(t)} \sum_{i=1}^{L(l)} D(l) b_5[i] * b_3[i+l]$

Definition at line 112 of file transcripts.cpp.

3.19.3.5 double Transcript::est_effective_length () const

a member function that calculates and returns the estimated effective length of the transcript (non-logged) using the avg bias

Returns

the estimated effective length of the transcript calculated as $\tilde{l} = \bar{bias} \sum_{l=1}^{L(t)} D(l)(L(t) - l + 1)$

Definition at line 93 of file transcripts.cpp.

3.19.3.6 TransID Transcript::id () const [inline]

a member function that returns the transcript id

Returns

TransID transcript ID

Definition at line 153 of file transcripts.h.

3.19.3.7 void Transcript::incr_uniq_counts (size_t incr_amt = 1) [inline]

a member function that increases the ccount of fragments uniquely mapped to this transcript

Parameters

<i>incr_amt</i>	a size_t to increase the counts by
-----------------	------------------------------------

Definition at line 221 of file transcripts.h.

3.19.3.8 size_t Transcript::length () const [inline]

a member function that returns the transcript length

Returns

transcript length

Definition at line 164 of file transcripts.h.

3.19.3.9 double Transcript::log_likelihood (const FragHit & frag) const

a member function that returns (a value proportional to) the log likelihood the given fragment originated from this transcript

Parameters

<i>frag</i>	a FragHit to return the likelihood of being originated from this transcript
-------------	---

Returns

(a value proportional to) the log likelihood the given fragment originated from this

transcript

Definition at line 59 of file transcripts.cpp.

3.19.3.10 `double Transcript::mass () const` [inline]

a member function that returns the current (logged) fragment mass

Returns

logged mass

Definition at line 170 of file transcripts.h.

3.19.3.11 `double Transcript::mass_var () const` [inline]

a member function that returns the current (logged) variance

Returns

logged mass variance

Definition at line 176 of file transcripts.h.

3.19.3.12 `const std::string& Transcript::name () const` [inline]

a member function that returns the transcript name

Returns

string containing transcript name

Definition at line 147 of file transcripts.h.

3.19.3.13 `const std::string& Transcript::seq () const` [inline]

a member function that returns the transcript sequence

Returns

string containing transcript sequence

Definition at line 158 of file transcripts.h.

3.19.3.14 `size_t Transcript::tot_counts () const` [inline]

a member function that returns the current count of fragments mapped to this transcript (uniquely or ambiguously)

Returns

total fragment count

Definition at line 187 of file transcripts.h.

3.19.3.15 double Transcript::unbiased_effective_length () const

a member function that calculates and returns the effective length of the transcript (non-logged) ignoring bias and using the prior [FLD](#) distribution

Returns

the effective length of the transcript calculated as $\tilde{l} = \sum_{l=1}^{L(t)} D_{prior}(l)(L(t) - l + 1)$

Definition at line 107 of file transcripts.cpp.

3.19.3.16 size_t Transcript::uniq_counts () const [inline]

a member function that returns the current count of fragments uniquely mapped to this transcript

Returns

unique fragment count

Definition at line 193 of file transcripts.h.

3.19.3.17 void Transcript::update_transcript_bias ()

a member function that causes the transcript bias to be re-calculated by the `_bias_table` based on current parameters

Definition at line 136 of file transcripts.cpp.

The documentation for this class was generated from the following files:

- `src/transcripts.h`
- `src/transcripts.cpp`

3.20 TranscriptTable Class Reference

```
#include <transcripts.h>
```

Public Member Functions

- [TranscriptTable](#) (const std::string &trans_fasta_file, const TransIndex &trans_index, double alpha, const [Globals](#) *globs)

- [~TranscriptTable](#) ()
- [Transcript * get_trans](#) (TransID id)
- [size_t size](#) () const
- [void update_covar](#) (TransID trans1, TransID trans2, double covar)
- [double get_covar](#) (TransID trans1, TransID trans2)
- [size_t covar_size](#) () const
- [Bundle * merge_bundles](#) ([Bundle *b1](#), [Bundle *b2](#))
- [size_t num_bundles](#) ()
- [void threaded_bias_update](#) ()
- [void output_results](#) (std::string output_dir, size_t tot_counts, bool output_varcov, bool multi_iteration)

3.20.1 Detailed Description

The [TranscriptTable](#) class is used to keep track of the [Transcript](#) objects for a run. The constructor parses a fasta file to generate the [Transcript](#) objects and store them in a map that allows them to be looked up based on their string id.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 272 of file transcripts.h.

3.20.2 Constructor & Destructor Documentation

3.20.2.1 [TranscriptTable::TranscriptTable](#) (const std::string & *trans_fasta_file*, const TransIndex & *trans_index*, double *alpha*, const Globals * *globs*)

[TranscriptTable](#) Constructor

Parameters

<i>trans_fasta_file</i>	a string storing the path to the fasta file from which to load transcripts
<i>trans_index</i>	the transcript-to-index map
<i>alpha</i>	a double that specifies the initial pseudo-counts for each bp of the transcripts (non-logged)
<i>globs</i>	a pointer to the struct containing pointers to the global parameter tables (bias_table, mismatch_table, fld)

Definition at line 144 of file transcripts.cpp.

3.20.2.2 TranscriptTable::~~TranscriptTable ()

[TranscriptTable](#) Destructor deletes all of the transcript objects in the table

Definition at line 202 of file transcripts.cpp.

3.20.3 Member Function Documentation

3.20.3.1 size_t TranscriptTable::covar_size () const [inline]

a member function that returns the number of pairs of transcripts with non-zero covariance

Returns

the number of transcript pairs with non-zero covariance

Definition at line 359 of file transcripts.h.

3.20.3.2 double TranscriptTable::get_covar (TransID *trans1*, TransID *trans2*)

a member function that returns the covariance between two transcripts these returned value will be the log of the negative of the true value

Parameters

<i>trans1</i>	one of the transcripts in the pair
<i>trans2</i>	the other transcript in the pair

Returns

the log of the negative of the pair's covariance

Definition at line 244 of file transcripts.cpp.

3.20.3.3 Transcript * TranscriptTable::get_trans (TransID *id*)

a member function that returns a pointer to the transcript with the given id

Parameters

<i>id</i>	of the transcript queried
-----------	---------------------------

Returns

pointer to the transcript wit the given id

Definition at line 226 of file transcripts.cpp.

3.20.3.4 Bundle * TranscriptTable::merge_bundles (Bundle * *b1*, Bundle * *b2*)

a member function that merges the given Bundles

Parameters

<i>b1</i>	a pointer to the first Bundle to merge
<i>b2</i>	a pointer to the second Bundle to merge

Returns

a pointer to the merged [Bundle](#)

Definition at line 258 of file transcripts.cpp.

3.20.3.5 size_t TranscriptTable::num_bundles ()

a member function that returns the number of bundles in the partition

Returns

the number of bundles in the partition

Definition at line 267 of file transcripts.cpp.

3.20.3.6 void TranscriptTable::output_results (std::string *output_dir*, size_t *tot_counts*, bool *output_varcov*, bool *multi_iteration*)

a member function that outputs the final expression data in a file called 'results.xprs' and (optionally) the variance-covariance matrix in 'varcov.xprs' in the given output directory

Parameters

<i>output_dir</i>	the directory to output the expression file to
<i>tot_counts</i>	the total number of observed mapped fragments
<i>output_varcov</i>	boolean specifying whether to also output the variance-covariance matrix
<i>multi_iteration</i>	boolean specifying whether multiple rounds were run, which affects count normalization

Definition at line 343 of file transcripts.cpp.

3.20.3.7 size_t TranscriptTable::size () const [inline]

a member function that returns the number of transcripts in the table

Returns

number of transcripts in the table

Definition at line 335 of file transcripts.h.

3.20.3.8 void TranscriptTable::threaded_bias_update ()

a member function for driving a thread that continuously updates the transcript bias values

Definition at line 273 of file transcripts.cpp.

3.20.3.9 void TranscriptTable::update_covar (TransID *trans1*, TransID *trans2*, double *covar*)

a member function that increases the covariance between two transcripts by the specified (logged) amount these values are stored positive even though they are negative

Parameters

<i>trans1</i>	one of the transcripts in the pair
<i>trans2</i>	the other transcript in the pair
<i>covar</i>	a double specifying the (logged) amount to increase the pair's covariance by

Definition at line 231 of file transcripts.cpp.


The documentation for this class was generated from the following files:

- src/transcripts.h
- src/transcripts.cpp

3.21 Writer Class Reference

```
#include <mapparser.h>
```

Inheritance diagram for Writer:



Public Member Functions

- virtual void [write_fragment](#) ([Fragment](#) &f)=0

3.21.1 Detailed Description

The [Writer](#) class is an abstract class than can be a [SAMWriter](#) or [BAMWriter](#). It writes [Fragment](#) objects back to file (in SAM/BAM format) with per-mapping probabilistic assignments.

Author

Adam Roberts

Date

2011 Artistic License 2.0

Definition at line 65 of file mapparser.h.

3.21.2 Member Function Documentation

3.21.2.1 virtual void Writer::write_fragment ([Fragment & f](#)) [pure virtual]

a member function that writes all mappings of the fragment to the ouptut file along with their probabilities in the "PH" field

Parameters

<i>f</i>	the processed Fragment to output
----------	--

Implemented in [BAMWriter](#), and [SAMWriter](#).

The documentation for this class was generated from the following file:

- src/mapparser.h

Index

- ~BAMParser
 - BAMParser, 6
- ~BAMWriter
 - BAMWriter, 7
- ~BundleTable
 - BundleTable, 13
- ~Fragment
 - Fragment, 20
- ~SAMWriter
 - SAMWriter, 36
- ~ThreadedMapParser
 - ThreadedMapParser, 39
- ~TranscriptTable
 - TranscriptTable, 46
- activate
 - MismatchTable, 26
- add_map_end
 - Fragment, 21
- add_mass
 - Transcript, 42
- add_val
 - FLD, 15
- append_output
 - BiasBoss, 9
 - FLD, 15
 - MismatchTable, 26
 - PosWeightTable, 31
 - SeqWeightTable, 37
- arr
 - FrequencyMatrix, 23
- BAMParser, 5
 - ~BAMParser, 6
 - BAMParser, 6
 - header, 6
 - next_fragment, 6
 - trans_index, 6
- BAMWriter, 7
 - ~BAMWriter, 7
 - BAMWriter, 7
- write_fragment, 8
- BiasBoss, 8
 - append_output, 9
 - BiasBoss, 9
 - get_transcript_bias, 9
 - to_string, 10
 - update_expectations, 10
 - update_observed, 10
- Bundle, 10
 - Bundle, 11
 - counts, 11
 - incr_counts, 12
 - size, 12
 - transcripts, 12
- bundle
 - Transcript, 42
- bundles
 - BundleTable, 13
- BundleTable, 12
 - ~BundleTable, 13
 - bundles, 13
 - BundleTable, 13
 - create_bundle, 13
 - merge, 14
 - size, 14
- counts
 - Bundle, 11
- covar_size
 - TranscriptTable, 47
- create_bundle
 - BundleTable, 13
- effective_length
 - Transcript, 42
- est_effective_length
 - Transcript, 42
- FLD, 14
 - add_val, 15
 - append_output, 15

- FLD, 15
- max_val, 16
- mean, 16
- pdf, 16
- to_string, 16
- tot_mass, 17
- FragHit, 17
 - left, 18
 - left_first, 18
 - length, 18
 - mapped_trans, 19
 - mate_l, 19
 - name, 19
 - pair_status, 18
 - right, 19
 - seq_l, 19
 - seq_r, 19
 - trans_id, 19
- Fragment, 20
 - ~Fragment, 20
 - add_map_end, 21
 - hits, 21
 - name, 21
 - num_hits, 21
- FrequencyMatrix, 22
 - arr, 23
 - FrequencyMatrix, 22
 - increment, 23
 - operator(), 23, 24
 - row, 24
- get_covar
 - TranscriptTable, 47
- get_trans
 - TranscriptTable, 47
- get_transcript_bias
 - BiasBoss, 9
- get_weight
 - PosWeightTable, 31
 - SeqWeightTable, 37
- Globals, 24
- header
 - BAMParser, 6
 - Parser, 28
 - SAMParser, 34
- hits
 - Fragment, 21
- id
 - Transcript, 43
- incr_counts
 - Bundle, 12
- incr_uniq_counts
 - Transcript, 43
- increment
 - FrequencyMatrix, 23
- increment_expected
 - PosWeightTable, 32
 - SeqWeightTable, 38
- increment_observed
 - PosWeightTable, 32
 - SeqWeightTable, 38
- left
 - FragHit, 18
- left_first
 - FragHit, 18
- length
 - FragHit, 18
 - Transcript, 43
- log_likelihood
 - MismatchTable, 26
 - Transcript, 43
- mapped_trans
 - FragHit, 19
- mass
 - Transcript, 44
- mass_var
 - Transcript, 44
- mate_l
 - FragHit, 19
- max_val
 - FLD, 16
- mean
 - FLD, 16
- merge
 - BundleTable, 14
- merge_bundles
 - TranscriptTable, 47
- MismatchTable, 25
 - activate, 26
 - append_output, 26
 - log_likelihood, 26
 - MismatchTable, 26
 - to_string, 27
 - update, 27
- mut
 - ParseThreadSafety, 29

- name
 - FragHit, 19
 - Fragment, 21
 - Transcript, 44
- next_frag
 - ParseThreadSafety, 29
- next_fragment
 - BAMParser, 6
 - Parser, 28
 - SAMParser, 34
- num_bundles
 - TranscriptTable, 48
- num_hits
 - Fragment, 21
- operator()
 - FrequencyMatrix, 23, 24
- output_results
 - TranscriptTable, 48
- pair_status
 - FragHit, 18
- Parser, 27
 - header, 28
 - next_fragment, 28
 - trans_index, 28
- ParseThreadSafety, 29
 - mut, 29
 - next_frag, 29
- pdf
 - FLD, 16
- PosWeightTable, 30
 - append_output, 31
 - get_weight, 31
 - increment_expected, 32
 - increment_observed, 32
 - PosWeightTable, 31
- right
 - FragHit, 19
- row
 - FrequencyMatrix, 24
- SAMParser, 33
 - header, 34
 - next_fragment, 34
 - SAMParser, 34
 - trans_index, 34
- SAMWriter, 35
 - ~SAMWriter, 36
- SAMWriter, 36
 - write_fragment, 36
- seq
 - Transcript, 44
- seq_l
 - FragHit, 19
- seq_r
 - FragHit, 19
- SeqWeightTable, 36
 - append_output, 37
 - get_weight, 37
 - increment_expected, 38
 - increment_observed, 38
 - SeqWeightTable, 37
 - to_string, 38
- size
 - Bundle, 12
 - BundleTable, 14
 - TranscriptTable, 48
- threaded_bias_update
 - TranscriptTable, 49
- threaded_parse
 - ThreadedMapParser, 40
- ThreadedMapParser, 39
 - ~ThreadedMapParser, 39
 - threaded_parse, 40
 - ThreadedMapParser, 39
 - trans_index, 40
- to_string
 - BiasBoss, 10
 - FLD, 16
 - MismatchTable, 27
 - SeqWeightTable, 38
- tot_counts
 - Transcript, 44
- tot_mass
 - FLD, 17
- trans_id
 - FragHit, 19
- trans_index
 - BAMParser, 6
 - Parser, 28
 - SAMParser, 34
 - ThreadedMapParser, 40
- Transcript, 40
 - add_mass, 42
 - bundle, 42
 - effective_length, 42
 - est_effective_length, 42

- id, [43](#)
- incr_uniq_counts, [43](#)
- length, [43](#)
- log_likelihood, [43](#)
- mass, [44](#)
- mass_var, [44](#)
- name, [44](#)
- seq, [44](#)
- tot_counts, [44](#)
- Transcript, [41](#)
- unbiased_effective_length, [45](#)
- uniq_counts, [45](#)
- update_transcript_bias, [45](#)
- transcripts
 - Bundle, [12](#)
- TranscriptTable, [45](#)
 - ~TranscriptTable, [46](#)
 - covar_size, [47](#)
 - get_covar, [47](#)
 - get_trans, [47](#)
 - merge_bundles, [47](#)
 - num_bundles, [48](#)
 - output_results, [48](#)
 - size, [48](#)
 - threaded_bias_update, [49](#)
 - TranscriptTable, [46](#)
 - update_covar, [49](#)
- unbiased_effective_length
 - Transcript, [45](#)
- uniq_counts
 - Transcript, [45](#)
- update
 - MismatchTable, [27](#)
- update_covar
 - TranscriptTable, [49](#)
- update_expectations
 - BiasBoss, [10](#)
- update_observed
 - BiasBoss, [10](#)
- update_transcript_bias
 - Transcript, [45](#)
- write_fragment
 - BAMWriter, [8](#)
 - SAMWriter, [36](#)
 - Writer, [50](#)
- Writer, [49](#)
 - write_fragment, [50](#)