


# Open Source Rover: Head Assembly Instructions

Authors: Michael Cox, Eric Junkins, Olivia Lofaro



**Jet Propulsion Laboratory**  
California Institute of Technology

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not constitute or imply its endorsement by the United States Government or the Jet Propulsion Laboratory, California Institute of Technology. ©2018 California Institute of Technology. Government sponsorship acknowledged.

---

## Contents

<b>1</b>	<b>3D printing</b>	<b>3</b>
<b>2</b>	<b>Machining/Fabrication</b>	<b>4</b>
2.1	Cutting the PVC Pipe . . . . .	4
<b>3</b>	<b>Mechanical Assembly</b>	<b>5</b>

### 1 3D printing

There are a few components that need to be 3D printed to make the head assembly. You can find the STL files necessary for these prints in the Mechanical/Head Assembly/3D Printed Parts folder of the repository. Based on difficulties we've seen with printing these pieces, we've also included a few different orientations of "printing pads" to help with thermal contraction as shown in Figure 1. These pads help hold the corners down and reduce the warping of the pieces.




Figure 1: Printing Pads

If you do not have a 3D printer there are a number of online 3D printing services available, an example of which can be found at:



- <https://www.makexyz.com/>

(If you decide to use a 3D printing service, we recommend sending them the files *without* the printing pads.)

## 2 Machining/Fabrication

### 2.1 Cutting the PVC Pipe












**Table 1: Parts/Tools Necessary**

Item	Ref	Qty	Image	Item	Ref	Qty	Image
2" PCV Pipe	S29	1		Vice or V-Clamps			
HackSaw or Band-saw							

Take the PVC pipe **S29** (this will be the "neck" of the rover) and cut it to your desired length. For reference, we cut our "neck" PVC pipe to be roughly 6 inches long.

### 3 Mechanical Assembly

**Table 2: Parts/Tools Necessary**

Item	Ref	Qty	Image	Item	Ref	Qty	Image
Head Left Back		1		#6-32x3/8" Button Head Screw	B2	4	
Head Right Back		1		#4-40x1/4" Button Head Screw	B8	12	
Head Left Side		1		#4-40 Locking Hex Nut	B12	4	
Head Right Side		1		LED Matrix	E8	1	
Bore Clamping Hub for 1" PVC	S24	1		Allen Key Set			
PVC Pipe	S29A	1		5/16 Wrench			
Logic Shifter PCB		1					

1. **Insert the LED matrix into the head:** Start by taking the LED Matrix **E8** and inserting it on the ledges in the left and right sides of the 3D printed head. Screw together the two sides of the head using screws **B8**.<sup>1</sup>

<sup>1</sup>The size of the holes should be such that you can use a hex key to "thread" the 3D printed holes. If it is too tight, you can use a drill/file to very slightly open up the hole




Figure 2: Inserting LED Matrix

2. **Attach the PVC Clamping Hub:** Attach the 1 Inch PVC Clamping Hub **S24** to the bottom of the head using screws **B2**.




Figure 3: Attach the PVC Clamping Hub

3. **Mounting the Logic Shifter PCB:** Attach the Logic Shifter PCB to the support

structure in the 3D printed head using screws **B8** and hex nuts **B12**.




Figure 4: Mounting the Logic Shifter PCB

4. **Connecting to back plane:** Attach the two back pieces together using screws **B8**.




Figure 5: Back Plane connecting

5. **Attaching the Back plane:** Attach the back plane to the rest of the head structure using screws **B8**.




Figure 6: Attaching the Back plane

6. **Attach the PVC pipe:** Slide the length of PVC pipe you want for the neck into the PVC clamping hub and tighten the screws the secure it.




Figure 7: Attaching the PVC pipe