

Arrays

'primitive' arrays v. vectors (1)

allocate new, 10 elements

```
int a[10];  
  
vector<int> v(10);  
// or:  
vector<int> v;  
v.resize(10);
```

'primitive' arrays v. vectors (1)

allocate new, 10 elements

```
int a[10];  
  
vector<int> v(10);  
// or:  
vector<int> v;  
v.resize(10);
```

access (no bounds checking)

```
int foo = a[3];  
a[4] = 17;  
  
int foo = v[3];  
v[4] = 17;
```

'primitive' arrays v. vectors (1)

allocate new, 10 elements

```
int a[10];  
  
vector<int> v(10);  
// or:  
vector<int> v;  
v.resize(10);
```

access (no bounds checking)

```
int foo = a[3];  
a[4] = 17;  
  
int foo = v[3];  
v[4] = 17;
```

access (with bounds checking)

```
/* no equivalent */  
  
int foo = v.at(3);  
v.at(4) = 17;
```

'primitive' arrays v. vectors (2)

copy

```
int a[10]; int b[10];    vector<int> a;  
...                    vector<int> b;  
// a = b does NOT work ...  
for (int i = 0;         a = b;  
     i < 10; ++i)  
    a[i] = b[i];
```

'primitive' arrays v. vectors (3)

equality

```
int a[10]; int b[10];      vector<int> a;
...                       vector<int> b;
...                       ...

// a == b does NOT work
// instead: checks if    bool isEqual = (a == b);
// a, b are same array
// (not same values)
```

```
bool isEqual = true;
for (int i = 0; i < 10; ++i)
    isEqual = (isEqual &&
               a[i] == b[j]);
```

arrays, pointers, and memory (1)

```
int someInts[3] = {2, 4, 6};  
int *pointer = someInts;
```

memory

address	value
...	...
0x10000	2
0x10004	4
0x10008	6
...	...
???	0x10000
...	...

arrays, pointers, and memory (1)

```
int someInts[3] = {2, 4, 6};  
int *pointer = someInts;
```

memory

address	value	
...	...	
0x10000	2	someInts[0]
0x10004	4	someInts[1]
0x10008	6	someInts[2]
...	...	
???	0x10000	pointer
...	...	

arrays, pointers, and memory (2)

```
int someInts[3] = {2, 4, 6};

cout << "someInts is:_" << someInts << endl;
cout << "&someInts[0] is:_" << &someInts[0] << endl;
cout << "&someInts[1] is:_" << &someInts[1] << endl;
cout << "someInts[1] is:_" << someInts[1] << endl;
```

example output:

```
someInts is: 0x7ffda5455b44
&someInts[0] is: 0x7ffda5455b44
&someInts[1] is: 0x7ffda5455b48
someInts[1] is: 4
```

arrays, pointers, and memory (2)

```
int someInts[3] = {2, 4, 6};
```

```
cout << "someInts is:_" << someInts << endl;  
cout << "&someInts[0] is:_" << &someInts[0] << endl;  
cout << "&someInts[1] is:_" << &someInts[1] << endl;  
cout << "someInts[1] is:_" << someInts[1] << endl;
```

example output: array implicitly converted to pointer to first element

```
someInts is: 0x7ffda5455b44  
&someInts[0] is: 0x7ffda5455b44  
&someInts[1] is: 0x7ffda5455b48  
someInts[1] is: 4
```

arrays, pointers, and memory (2)

```
int someInts[3] = {2, 4, 6};
```

```
cout << "someInts is:_" << someInts << endl;  
cout << "&someInts[0] is:_" << &someInts[0] << endl;  
cout << "&someInts[1] is:_" << &someInts[1] << endl;  
cout << "someInts[1] is:_" << someInts[1] << endl;
```

example output:

arrays elements always at adjacent addresses
(4 bytes apart = ints are 4 bytes)

```
someInts is: 0x7ffda5455b44  
&someInts[0] is: 0x7ffda5455b44  
&someInts[1] is: 0x7ffda5455b48  
someInts[1] is: 4
```

arrays, pointers, and memory (2)

```
int someInts[3] = {2, 4, 6};
```

```
cout << "someInts is:_" << someInts << endl;  
cout << "&someInts[0] is:_" << &someInts[0] << endl;  
cout << "&someInts[1] is:_" << &someInts[1] << endl;  
cout << "someInts[1] is:_" << someInts[1] << endl;
```

exam general rule: $\&\text{array}[i] = \text{array-addr} + \text{sizeof}(\text{array-elem}) * i$

```
someInts is: 0x7ffda5455b44  
&someInts[0] is: 0x7ffda5455b44  
&someInts[1] is: 0x7ffda5455b48  
someInts[1] is: 4
```

arrays as function parameters

```
void someFunc(int ptrToArray[], int size) { /* code */ }  
int main() {  
    int someInts[3];  
    someFunc(someInts, 3);  
    return 0;  
}
```

is **exactly** equivalent to:

```
void someFunc(int *ptrToArray, int size) { /* code */ }  
int main() {  
    int someInts[3];  
    someFunc(someInts, 3);  
    return 0;  
}
```

arrays as function parameters

```
void someFunc(int ptrToArray[], int size) { /* code */ }
```

```
int main() {
```

```
    int someInts[3];
```

so ptrToArray is always an array

re

example: `sizeof(ptrToArray) == sizeof(int*)`

(even though `sizeof(someInts) == 3 * sizeof(int)`)

is exactly equivalent to:

```
void someFunc(int *ptrToArray, int size) { /* code */ }
```

```
int main() {
```

```
    int someInts[3];
```

```
    someFunc(someInts, 3);
```

```
    return 0;
```

```
}
```

arrays of arrays

AKA multidimensional arrays

```
int m[2][3];  
int n[2][3] = { {1,2,3}, {4,5,6} };
```

arrays of arrays

AKA multidimensional arrays

```
int m[2][3];  
int n[2][3] = { {1,2,3}, {4,5,6} };
```

```
// "row" 1  
n[0][0] == 1  
n[0][1] == 2  
n[0][2] == 3
```

```
// "row" 2  
n[1][0] == 4  
n[1][1] == 5  
n[1][2] == 6
```


array of array storage

“row-major” order

address	value
...	...
0x1000	1
0x1004	2
0x1008	3
0x100C	4
0x1010	5
0x1014	6
...	...


array of array storage

“row-major” order

address	value	
...	...	
0x1000	1	$n[0][0]$
0x1004	2	$n[0][1]$
0x1008	3	$n[0][2]$
0x100C	4	$n[1][0]$
0x1010	5	$n[1][1]$
0x1014	6	$n[1][2]$
...	...	


array of array storage

“row-major” order



array of array storage

“row-major” order



pointers to array

(we will not test you on this)

```
int m[3][2] = { {1,2,3}, {4,5,6} }
```

```
// p1 is a "pointer to array of 3 ints"  
// yes, this syntax is really confusing  
// and generally not worth using
```

```
int (*p1)[3];
```

```
p1 = m; // p1 contains address of m[0]
```

```
cout << p1 << endl;
```

```
// OUTPUT: 0x... --- address of m[0][0]
```

```
cout << p1[1] << endl;
```

```
// OUTPUT: 0x... --- address of m[1][0]
```

```
cout << p1[1][1] << endl;
```

```
// OUTPUT: 5
```

command line parameters

```
int main (int argc, char* argv[]) { ... }
```

// same as:

```
int main (int argc, char **argv) { ... }
```

argc — number of arguments + 1

argv — array of C-style strings

argv[0] — program name

argv[1], argv[2], ... — arguments

what about `int main() { ... }`?

okay, but can't get arguments

C strings to strings

given a `char *c_style_string` (like `argv[i]`)

output:

```
cout << c_style_string
```

convert to C++-style string called `s`:

```
string s(c_style_string)
```

```
string s; s = c_style_string;
```

command line parameters

```
int main (int argc, char* argv[]) {  
    // The 0th command line parameter is the program name.  
    cout << "This program is called '" << argv[0]  
        << "'" << endl;  
    cout << "The following are the command "  
        << "line parameters you specified:" << endl;  
    // for loop starts at 1 to avoid printing  
    // name of program (again)  
    for ( int i = 1; i < argc; i++ ) {  
        // we can convert the C-style strings into  
        // C++-style strings, and then print them:  
        string s(argv[i]);  
        cout << "\t" << s << endl;  
    }  
    return 0;  
}
```


command line parameters

```
int main (int argc, char* argv[]) {  
    // The 0th command line parameter is the program name.  
    cout << "This program is called '" << argv[0]  
        << "'" << endl;  
    cout << "The following are the command "  
        << "line parameters you specified:" << endl;  
    // for loop starts at 1 to avoid printing  
    // name of program (again)  
    for ( int i = 1; i < argc; i++ ) {  
        // we can convert the C-style strings into  
        // C++-style strings, and then print them:  
        string s(argv[i]);  
        cout << "\t" << s << endl;  
    }  
    return 0;  
}
```

command line parameters

```
int main (int argc, char* argv[]) {  
    // The 0th command line parameter is the program name.  
    cout << "This program is called '" << argv[0]  
        << "'" << endl;  
    cout << "The following are the command "  
        << "line parameters you specified:" << endl;  
    // for loop starts at 1 to avoid printing  
    // name of program (again)  
    for ( int i = 1; i < argc; i++ ) {  
        // we can convert the C-style strings into  
        // C++-style strings, and then print them:  
        string s(argv[i]);  
        cout << "\t" << s << endl;  
    }  
    return 0;  
}
```