

Documentation of quantumarticle.cls

Contents

1	Introduction	2
2	Important quirks	2
2.1	pdfoutput	2
3	Typesetting documents	2
3.1	Recommended structure	2
3.2	Sectioning	2
3.3	Equations	2
3.4	Floats	2
3.4.1	Figures	2
3.4.2	Tables	3
3.5	Plots	3
3.6	Footnotes	3
3.7	References	3
3.7.1	Manual bibliography	3
3.7.2	BibTeX bibliography	3
3.8	Appendix	4
3.9	Recommended packages	4
4	Package options	4
4.1	Document setup	4
4.1.1	Document format	4
4.1.2	Orientation	5
4.1.3	Fontsize	5
4.1.4	Sides	5
4.1.5	Titlepage	5
4.1.6	Draft	5
4.2	Style options	5
4.2.1	Equations	5
4.2.2	Bibliography	6
4.3	Pre-loaded packages	6
4.4	Publication	6
4.5	Compatibility	6
5	Contributing	8
6	Copyright	8

1 Introduction

The quantumarticle document class is suggested for papers that will be submitted to Quantum – the open journal of quantum science. It is based on the widely used article document class and designed to allow a seamless transition from documents typeset with article, revtex and elsarticle document classes.

As Quantum is an arXiv overlay journal, all papers have to be submitted to the arXiv. To make this submission process as user-friendly as possible, the quantumarticle document class contains some arXiv-specific checks that can be deactivated via the option `noarxiv`.

2 Important quirks

2.1 pdfoutput

In order to get correct line breaks within hyperlinks and to make sure the arXiv produces a PDF as output, please add the line

```
\pdfoutput=1
```

within the first 5 lines of your main LaTeX file, [as suggested by the arXiv](#). By default, the quantumarticle document class will enforce that `pdfoutput` is set to 1. This can be deactivated via the option `nopdfoutputerror`.

3 Typesetting documents

3.1 Recommended structure

Summary section Longer articles should include a section that, early on, explains the main results, their limitations, and assumptions. This section can be used to, for example, present the main theorem, or provide a summary of the results for a wider audience.

4 Title information

You can provide information on authors and affiliations in the common format also used by `revtex`:

```
\title{Title}
\author{Author 1}
\author{Author 2}
\affiliation{Affiliation 1}
\author{Author 3}
\affiliation{Affiliation 2}
\author{Author 4}
\affiliation{Affiliation 1}
\affiliation{Affiliation 3}
```

In this example affiliation 1 will be associated with authors 1, 2, and 4, affiliation 2 with author 3 and affiliation 3 with author 4. Repeated affiliations are automatically recognized and typeset in `superscriptaddress` style. Alternatively you can use a format similar to that of the `authblk` package and the `elsarticle` document class to specify the same affiliation relations as follows:

```
\title{Title}
\author[1]{Author 1}
\author[1]{Author 2}
\author[2]{Author 3}
\author[1,3]{Author 4}
\affil[1]{Affiliation 1}
\affil[2]{Affiliation 1}
\affil[3]{Affiliation 1}
```

4.1 Sectioning

Sections, subsections, subsubsections, and paragraphs should be typeset with the standard LaTeX commands. The paragraph is the smallest unit of sectioning. Feel free to end the paragraph title with a full stop if you find this appropriate.

4.2 Equations

You can use the standard commands for equations. For multi-line equations `align` is preferable over `eqnarray`, please refrain from using the latter. For complex equations you may want to consider using the `IEEEeqnarray` environment from the `IEEEtrantools` package.

How you refer to equations is up to you, but please be consistent and use the `\eqref{...}` command instead of writing `(\ref{...})`.

As a courtesy for your readers and referees, please suppress equation numbers only if there is a specific reason to do so, to not make it unnecessarily difficult to refer to individual results and steps in derivations.

Very wide equations can be shown expanding over both columns using the `widetext` environment. In `onecolumn` mode, the `widetext` environment has no effect. To enable this feature in `twocolumn` mode, `quantumarticle` relies on the package `ltxgrid`. Unfortunately this package has a bug that leads to a sub-optimal placement of extremely long footnotes.

4.3 Floats

Every floating element must have an informative caption and a number. The caption can be placed above, below, or to the side of the figure, as you see fit.

Feel free to place them at the top or bottom of the page, or in the middle of a paragraph as you see fit. Try to place them on the same page as the text referring to them. A figure on the first page can help readers remember and recognize your work more easily.

4.3.1 Figures

Figures are typeset using the standard `figure` environment for single-column figures and `figure*` for multi-column figures.

4.3.2 Tables

TODO: Do we support `table` / `table*`?

4.4 Plots

Quantum provides a Jupyter notebook to create plots that integrate seamlessly with `quantumarticle`.

4.5 Footnotes

Footnotes are typeset using the `footnote` command. They will appear in the bottom of the page. Please do only use footnotes when appropriate and do not mix footnotes with references.

4.6 References

Citations to other works should appear in the References section at the end of the work.

Important: As Quantum is a member of Crossref, all references to works that have a DOI *must* be hyperlinked according to the DOI. Those links must start with `https://doi.org/` (preferred), or `http://dx.doi.org/`. Direct links to the website of the publisher are not sufficient. This can be achieved in several ways, depending on how you are formatting your bibliography.

4.6.1 Manual bibliography

Suppose the DOI of an article that you want to cite is 10.22331/idonotexist. If you are formatting your bibliography manually, you can cite this work using the following in your `thebibliography` environment:

```
\bibitem{examplecitation}
Name Surname,
\href{https://doi.org/10.22331/
idonotexist}{Quantum
\textbf{123}}, 123456 (1916).}
```

Important: If you are formatting your bibliography manually, please do not group multiple citations into one `\bibitem`. Having to search through multiple references to find the cited result makes your work less accessible for authors and grouping references can screw up our automatic extraction of citations.

4.6.2 BibTeX bibliography

We encourage the use of BibTeX to generate your bibliography from the BibTeX meta-data provided by publishers. For DOI linking to work, the BibTeX file must contain the `doi` field as for example in:

```
@article{examplecitation,
author = {Surname, Name},
title = {Title},
journal = {Quantum},
volume = {123},
page = {123456},
year = {1916},
doi = {10.22331/idonotexist},
}
```

Several authors had problems because of Unicode characters in their BibTeX files. Be advised that **BibTeX does not support Unicode characters**. All special characters must be input via their respective LaTeX commands.

natbib If you are using BibTeX, you can load the `natbib` package by putting

```
\usepackage[numbers,sort&compress]{natbib}
```

in the preamble of your document and then use the `plainnat` citation style by including your BibTeX bibliography `mybibliography.bib` where you want the bibliography to appear as follows:

```
\bibliographystyle{plainnat}
\bibliography{mybibliography}
```

The `quantumarticle` class automatically detects that the `natbib` package was loaded and redefines the `\doi` command to create hyperlinks. This is likely the easiest option if you are converting from another document class.

BibLaTeX If you want to use BibLaTeX, you can instead add

```
\usepackage[backend=bibtex]{biblatex}
\addbibresource{mybibliography.bib}
```

to the preamble of your document and then output the bibliography with

```
\printbibliography
```

where appropriate. You then have to upload the .bbl file along with the other source files when submitting to the arXiv. Due to incompatibilities between different LaTeX version we unfortunately cannot recommend this option [?].

The quantumarticle class automatically detects that the `biblatex` package was loaded, sets the default option `doi=true` to include the DOI in the bibliography, and declares a suitable field format to make it a hyperlink. Due to issues with `biber` we recommend to use the `bibtex` backend of `biblatex`.

Feel free to change the appearance of citations in any way you like by using a different `bibliographystyle` or via the advanced mechanisms provided by BibLaTeX. The only two requirements are that citations must uniquely identify the cited work and that they must contain a DOI hyperlink whenever possible.

4.7 Appendix

Quantum allows the usage of appendices. Ideally, the command `\appendix` should be put before the appendices to get appropriate section numbering. The appendices are then numbered alphabetically, with numeric (sub)section numbering. Equations continue to be numbered sequentially. You are free to change this in case it is more appropriate for your article, but a consistent and unambiguous numbering of sections and equations must be ensured.

If you want your appendices to appear in `onecolumn` mode but the rest of the document in `twocolumn` mode, you can insert the command `\onecolumn\newpage` before `\appendix`.

4.8 Recommended packages

Quantum encourages you to load the following extra packages:

```
\usepackage[utf8]{inputenc}
\usepackage[english]{babel}
\usepackage[T1]{fontenc}
\usepackage{amsmath}
\usepackage{hyperref}
```

If you do not load the `hyperref` package, quantumarticle automatically loads it for you. Packages that change font settings, such as `times` or `helvet` should be avoided.

5 Package options

The quantumarticle document class provides a multitude of package options that change the appearance of the final document to the liking of the user.

Default options that need not be given are marked with (*). Options that are only provided for compatibility reasons and that will not alter the typesetting of the document are written in gray font.

5.1 Document setup

5.1.1 Document format

The document class does not specify a default document format, an error is raised if none is specified.

Option	Description
<code>a4paper</code>	Sets the paper size to ISO A4.
<code>a5paper</code>	Sets the paper size to ISO A5.
<code>b5paper</code>	Sets the paper size to ISO B5.
<code>letterpaper</code>	Sets the paper size to ANSI Letter.
<code>legalpaper</code>	Sets the paper size to ANSI Legal.
<code>executivepaper</code>	Sets the paper size to ANSI Executive.

5.1.2 Orientation

By default, the orientation is portrait.

Option	Description
<code>landscape</code>	Sets the orientation of the document to landscape.

5.1.3 Fontsize

By default, the fontsize is 10pt.

Option	Description
<code>10pt (*)</code>	Sets the normal fontsize to 10pt.
<code>11pt</code>	Sets the normal fontsize to 11pt.
<code>12pt</code>	Sets the normal fontsize to 12pt.

5.1.4 Sides

By default, the setting is oneside.

Option	Description
<code>oneside (*)</code>	Prepares the document as onesided.
<code>twoside</code>	Prepares the document as twosided.

5.1.5 Titlepage

By default, the document class is typset with no extra titlepage.

Option	Description
<code>titlepage</code>	Displays the title on a separate titlepage.
<code>notitlepage</code>	Displays the title on the same page as the text.

5.1.6 Draft

By default, the document class is typset as final.

Option	Description
<code>draft</code>	Marks the document as a draft.
<code>final (*)</code>	Does not mark the document as a draft.

5.2 Style options

5.2.1 Equations

By default, equations are typset centered, with equation numbers on the right. **TODO: Clear `fleqn` behaviour**

Option	Description
<code>fleqn</code>	Display equations left aligned.
<code>leqno</code>	Display equation numbers to the left of the equation.

5.2.2 Bibliography

Option	Description
<code>openbib</code>	TODO: Find out what openbib does.

5.3 Pre-loaded packages

The document class only loads packages necessary for its operation, such as `geometry` or `hyperref`. For compatibility reasons, there are commands that load certain widely used classes for the user.

Option	Description
<code>amsmaths</code>	Load the package <code>amsmaths</code> .
<code>noamsmaths</code>	Don't load the package <code>amsmaths</code> .
<code>amssymb</code>	Load the package <code>amssymb</code> .
<code>noamssymb</code>	Don't load the package <code>amssymb</code> .
<code>amsmath</code>	Load the package <code>amsmath</code> .
<code>noamsmath</code>	Don't load the package <code>amsmath</code> .

5.4 Publication

By default, all documents that are created with the `quantumarticle` documentclass are treated as possible submissions to Quantum.

Option	Description
<code>accepted=YYYY-MM-DD</code>	Adds the note 'Accepted in Quantum YYYY-MM-DD' to the document.
<code>unpublished</code>	Intended for works that are not published in Quantum. Disables all Quantum-related branding.
<code>noarxiv</code>	Intended for works that are not meant to be uploaded to the arXiv. Disables all arXiv-related sanity checks in the document. This option also sets <code>unpublished</code> .

5.5 Compatibility

The `quantumarticle` class aims to be maximally compatible with documents that were previously typeset with other document classes. For this reason, a lot of options are present for the sole purpose of compatibility but don't have an effect on how your document will be typeset. These include:

Option	Description
<code>checkin</code>	No effect.
<code>preprint</code>	— " —
<code>reprint</code>	— " —
<code>manuscript</code>	— " —
<code>noshowpacs</code>	— " —
<code>showpacs</code>	— " —
<code>showkeys</code>	— " —
<code>noshowkeys</code>	— " —
<code>balancelastpage</code>	— " —
<code>nobalancelastpage</code>	— " —
<code>nopreprintnumbers</code>	— " —
<code>preprintnumbers</code>	— " —
<code>hyperref</code>	— " —

bibnotes	— " —
nobibnotes	— " —
footinbib	— " —
nofootinbib	— " —
altaffilletter	— " —
altaffilsymbol	— " —
superbib	— " —
citeautoscript	— " —
longbibliography	— " —
nolongbibliography	— " —
eprint	— " —
noeprint	— " —
author-year	— " —
numerical	— " —
galley	— " —
raggedbottom	— " —
tightenlines	— " —
lengthcheck	— " —
reprint	— " —
eqsecnum	— " —
secnumarabic	— " —
floats	— " —
stfloats	— " —
endfloats	— " —
endfloats*	— " —
osa	— " —
osameet	— " —
opex	— " —
tops	— " —
josa	— " —
byrevtex	— " —
floatfix	— " —
nofloatfix	— " —
ltxgridinfo	— " —
outputdebug	— " —
raggedfooter	— " —
noraggedfooter	— " —
frontmatterverbose	— " —
linenumbers	— " —
nomerge	— " —
hypertext	— " —
frontmatterverbose	— " —
inactive	— " —
groupedaddress	— " —
unsortedaddress	— " —
runinaddress	— " —
superscriptaddress	— " —
aps	Triggers revtex compatibility mode
pra	— " —
prb	— " —
pre	— " —
prl	— " —
prx	— " —
aip	— " —

6 Contributing

In case you encounter problems using the article class please consider opening a bug report in our bug-tracker on GitHub. You can also contact us via email under `latex@quantum-journal.org`, but it may take significantly longer to get a response. In any case we need the full source of a document that produces the problem and the log file showing the error to help you.

Improvements submitted as pull requests against the development branch are very much appreciated!

7 Copyright

Copyright 2019 Verein zur Förderung des Open Access Publizierens in den Quantenwissenschaften (<http://quantum-journal.org/about/>).

The document class `quantumarticle` is derived from `article` available from <https://www.ctan.org/pkg/article>.

It may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3c of this license or (at your option) any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3c or later is part of all distributions of L^AT_EX version 2005/12/01 or later.