

# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

not applicable

SPECspeed®2017\_int\_base = 0.2614

SPECspeed®2017\_int\_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: not applicable

Tested by: not applicable

Test Date: Oct-2020

Hardware Availability:

Software Availability:

Threads	0	0.0150	0.0350	0.0550	0.0750	0.0950	0.110	0.125	0.140	0.155	0.170	0.185	0.200	0.215	0.230	0.245	0.265
600.perlbench_s																	
602.gcc_s																	
605.mcf_s																	
620.omnetpp_s																	
623.xalancbmk_s																	
625.x264_s	1																0.261
631.deepsjeng_s																	
641.leela_s																	
648.exchange2_s																	
657.xz_s																	
— SPECspeed®2017_int_base (0.2614)																	

## Hardware

CPU Name: Intel Xeon Bronze 3106  
Max MHz:  
Nominal:  
Enabled: cores, 1 chip, threads/core  
Orderable:  
Cache L1:  
L2:  
L3:  
Other:  
Memory: 78.334 GB fixme: If using DDR4, the format is:  
'N GB (N x N GB nRxn PC4-nnnnX-X)'  
Storage: 6.9 TB add more disk info here  
Other:

## Software

OS: Ubuntu 18.04.3 LTS  
4.15.0-70-generic  
Compiler: C/C++/Fortran: Version 10.1.0 of GCC, the  
GNU Compiler Collection  
Parallel: Yes  
Firmware:  
File System: nfs  
System State: Run level 5 (add definition here)  
Base Pointers: 64-bit  
Peak Pointers: Not Applicable  
Other:  
Power Management: --

## Errors

'reportable' flag not set during run  
605.mcf\_s (base) did not have enough runs!  
600.perlbench\_s (base) did not have enough runs!  
657.xz\_s (base) did not have enough runs!  
620.omnetpp\_s (base) did not have enough runs!  
631.deepsjeng\_s (base) did not have enough runs!  
648.exchange2\_s (base) did not have enough runs!  
641.leela\_s (base) did not have enough runs!  
602.gcc\_s (base) did not have enough runs!  
625.x264\_s (base) did not have enough runs!  
623.xalancbmk\_s (base) did not have enough runs!

(Continued on next page)

# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

not applicable

SPECspeed®2017\_int\_base = 0.2614

SPECspeed®2017\_int\_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: not applicable

Tested by: not applicable

Test Date: Oct-2020

Hardware Availability:

Software Availability:

## Errors (Continued)

Unknown flags were used! See

<https://www.spec.org/cpu2017/Docs/runcpu.html#flagsurl>

for information about how to get rid of this error.

## Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
600.perlbench_s														
602.gcc_s														
605.mcf_s														
620.omnetpp_s														
623.xalancbmk_s														
625.x264_s	1	6750	0.261											
631.deepsjeng_s														
641.leela_s														
648.exchange2_s														
657.xz_s														

SPECspeed®2017\_int\_base = 0.2614

SPECspeed®2017\_int\_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Environment Variables Notes

Environment variables set by runcpu before the start of the run:

LD\_LIBRARY\_PATH =  
"/u/home/schmidt/riscv-gnu-toolchain/build/lib64:/u/home/schmidt/riscv-gnu-toolchain/build/lib:/lib64"

## Platform Notes

Sysinfo program /u/home/schmidt/spec/bin/sysinfo  
Rev: r6365 of 2019-08-21 295195f888a3d7edble6e46a485a0011  
running on sksmall Sun Oct 25 00:24:47 2020

SUT (System Under Test) info as seen by some common utilities.  
For more information on this section, see

(Continued on next page)

# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

not applicable

SPECspeed®2017\_int\_base = 0.2614

SPECspeed®2017\_int\_peak = Not Run

**CPU2017 License:** nnn (Your SPEC license number)

**Test Sponsor:** not applicable

**Tested by:** not applicable

**Test Date:** Oct-2020

**Hardware Availability:**

**Software Availability:**

## Platform Notes (Continued)

<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) Bronze 3106 CPU @ 1.70GHz

1 "physical id"s (chips)

8 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

cpu cores : 8

siblings : 8

physical 0: cores 0 1 2 3 4 5 6 7

From lscpu:

Architecture: x86\_64

CPU op-mode(s): 32-bit, 64-bit

Byte Order: Little Endian

CPU(s): 8

On-line CPU(s) list: 0-7

Thread(s) per core: 1

Core(s) per socket: 8

Socket(s): 1

NUMA node(s): 1

Vendor ID: GenuineIntel

CPU family: 6

Model: 85

Model name: Intel(R) Xeon(R) Bronze 3106 CPU @ 1.70GHz

Stepping: 4

CPU MHz: 1688.902

CPU max MHz: 1700.0000

CPU min MHz: 800.0000

BogoMIPS: 3400.00

Virtualization: VT-x

L1d cache: 32K

L1i cache: 32K

L2 cache: 1024K

L3 cache: 11264K

NUMA node0 CPU(s): 0-7

Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov

pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp

lm constant\_tsc art arch\_perfmon pebs bts rep\_good nopl xtopology nonstop\_tsc cpuid

aperfmpperf pni pclmulqdq dtes64 monitor ds\_cpl vmx smx est tm2 ssse3 sdbg fma cx16

xtpr pdcm pcid dca sse4\_1 sse4\_2 x2apic movbe popcnt tsc\_deadline\_timer aes xsave

avx fl6c rdrand lahf\_lm abm 3dnowprefetch cpuid\_fault epb cat\_l3 cdp\_l3

invpcid\_single pti intel\_ppin ssbd mba ibrs ibpb stibp tpr\_shadow vnmi flexpriority

ept vpid fsgsbase tsc\_adjust bml hle avx2 smep bmi2 erms invpcid rtm cqm mpx rdt\_a

avx512f avx512dq rdseed adx smap clflushopt clwb intel\_pt avx512cd avx512bw avx512vl

xsavesopt xsavec xgetbv1 xsaves cqm\_llc cqm\_occup\_llc cqm\_mbm\_total cqm\_mbm\_local

(Continued on next page)

# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

not applicable

SPECSpeed®2017\_int\_base = 0.2614

SPECSpeed®2017\_int\_peak = Not Run

**CPU2017 License:** nnn (Your SPEC license number)

**Test Sponsor:** not applicable

**Tested by:** not applicable

**Test Date:** Oct-2020

**Hardware Availability:**

**Software Availability:**

## Platform Notes (Continued)

dtherm arat pln pts hwp hwp\_act\_window hwp\_pkg\_req pku ospke md\_clear flush\_llc

/proc/cpuinfo cache data  
cache size : 11264 KB

From numactl --hardware WARNING: a numactl 'node' might or might not correspond to a physical chip.

From /proc/meminfo

MemTotal: 82139464 kB

HugePages\_Total: 0

Hugepagesize: 2048 kB

/usr/bin/lsb\_release -d

Ubuntu 18.04.3 LTS

From /etc/\*release\* /etc/\*version\*

debian\_version: buster/sid

os-release:

NAME="Ubuntu"

VERSION="18.04.3 LTS (Bionic Beaver)"

ID=ubuntu

ID\_LIKE=debian

PRETTY\_NAME="Ubuntu 18.04.3 LTS"

VERSION\_ID="18.04"

HOME\_URL="https://www.ubuntu.com/"

SUPPORT\_URL="https://help.ubuntu.com/"

uname -a:

Linux sksmall 4.15.0-70-generic #79-Ubuntu SMP Tue Nov 12 10:36:11 UTC 2019 x86\_64

x86\_64 x86\_64 GNU/Linux

Kernel self-reported vulnerability status:

itlb\_multihit:

CVE-2018-3620 (L1 Terminal Fault):

Microarchitectural Data Sampling:

CVE-2017-5754 (Meltdown):

CVE-2018-3639 (Speculative Store Bypass): Mitigation: Speculative Store Bypass disabled via prctl and seccomp

CVE-2017-5753 (Spectre variant 1):

Mitigation: usercopy/swapgs barriers and \_\_user pointer sanitization

CVE-2017-5715 (Spectre variant 2):

Mitigation: Full generic retpoline, IBPB: conditional, IBRS\_FW, STIBP: disabled, RSB filling

tsx\_async\_abort:

Mitigation: Clear CPU buffers; SMT disabled

(Continued on next page)

# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

not applicable

SPECspeed®2017\_int\_base = 0.2614

SPECspeed®2017\_int\_peak = Not Run

**CPU2017 License:** nnn (Your SPEC license number)

**Test Sponsor:** not applicable

**Tested by:** not applicable

**Test Date:** Oct-2020

**Hardware Availability:**

**Software Availability:**

## Platform Notes (Continued)

run-level 5 Nov 28 09:46

SPEC is set to: /u/home/schmidt/spec

Filesystem

on

	Type	Size	Used	Avail	Use%	Mounted
nasill0.informatik.tu-muenchen.de:/srv/ill10/home	nfs	6.9T	4.4T	2.3T	66%	/u/home

From /sys/devices/virtual/dmi/id

BIOS: HPE U32 11/13/2019

Vendor: HPE

Product: ProLiant DL360 Gen10

Product Family: ProLiant

Cannot run dmidecode; consider saying (as root)

chmod +s /usr/sbin/dmidecode

(End of data from sysinfo program)

## Compiler Version Notes

=====  
C | 625.x264\_s(base)  
=====

Using built-in specs.

COLLECT\_GCC=/u/home/schmidt/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-gcc

COLLECT\_LTO\_WRAPPER=/u/home/schmidt/riscv-gnu-toolchain/build/libexec/gcc/riscv64-unknown-linux-gnu/10.1.0/lto-wrapper

Target: riscv64-unknown-linux-gnu

Configured with: /u/home/schmidt/riscv-gnu-toolchain/riscv-gcc/configure

--target=riscv64-unknown-linux-gnu

--prefix=/u/home/schmidt/riscv-gnu-toolchain/build

--with-sysroot=/u/home/schmidt/riscv-gnu-toolchain/build/sysroot

--with-system-zlib --enable-shared --enable-tls

--enable-languages=c,c++,fortran --disable-libmudflap --disable-libssp

--disable-libquadmath --disable-lsanitizer --disable-nls

--disable-bootstrap --src=../riscv-gcc --disable-multilib --with-abi=lp64

--with-arch=rv64ima --with-tune=rocket 'CFLAGS\_FOR\_TARGET=-O2

-mmodel=medlow' 'CXXFLAGS\_FOR\_TARGET=-O2 -mmodel=medlow'

Thread model: posix

Supported LTO compression algorithms: zlib

gcc version 10.1.0 (GCC)  
=====

# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

not applicable

SPECspeed®2017\_int\_base = 0.2614

SPECspeed®2017\_int\_peak = Not Run

**CPU2017 License:** nnn (Your SPEC license number)

**Test Sponsor:** not applicable

**Tested by:** not applicable

**Test Date:** Oct-2020

**Hardware Availability:**

**Software Availability:**

## Base Unknown Flags

625.x264\_s: "/u/home/schmidt/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in CC)  
"/u/home/schmidt/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in LD)

## Base Runtime Environment

C benchmarks:

625.x264\_s: No flags used

## Base Compiler Invocation

C benchmarks:

625.x264\_s: gcc

## Base Portability Flags

625.x264\_s: -static(\*) -DSPEC\_LP64

(\*) Indicates a portability flag that was found in a non-portability variable.

## Base Optimization Flags

C benchmarks:

625.x264\_s: -std=c99 -O3 -DSPEC\_SUPPRESS\_OPENMP  
-fno-unsafe-math-optimizations -fno-openmp -fno-strict-aliasing  
-fgnu89-inline

## Base Other Flags

C benchmarks:

625.x264\_s: -fcommon -fallow-argument-mismatch

# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

not applicable

SPECspeed®2017\_int\_base = 0.2614

SPECspeed®2017\_int\_peak = Not Run

**CPU2017 License:** nnn (Your SPEC license number)

**Test Sponsor:** not applicable

**Tested by:** not applicable

**Test Date:** Oct-2020

**Hardware Availability:**

**Software Availability:**

Invalid Result

SPEC CPU and SPECspeed are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU®2017 v1.1.0 on 2020-10-25 00:24:46+0000.

Report generated on 2020-10-25 02:28:36 by CPU2017 PDF formatter v6255.