SPEC CPU®2017 Integer Speed Result

not applicable

SPECspeed®2017_int_base = 0.00

SPECspeed®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)
Test Sponsor: not applicable
Tested by: not applicable

Test Date: Sep-2020
Hardware Availability:
Software Availability:

Threads
600.perlbench_s
602.gcc_s
605.mcf_s
620.omnetpp_s
623.xalancbmk_s
625.x264_s
631.deepsjeng_s
641.leela_s
648.exchange2_s
657.xz_s

Hardware

CPU Name: Intel Xeon Bronze 3106
Max MHz:
Nominal:
Enabled: cores, 1 chip, threads/core
Orderable:
Cache L1:
L2:
L3:
Other:
Memory: 78.334 GB fixme: If using DDR4, the format is: 'N GB (N x N GB nRxn PC4-nnnnX-X)'
Storage: 6.9 TB add more disk info here
Other:

Software

OS: Ubuntu 18.04.3 LTS 4.15.0-70-generic
Compiler: C/C++/Fortran: Version 10.1.0 of GCC, the GNU Compiler Collection
Parallel: Yes
Firmware:
File System: nfs
System State: Run level 5 (add definition here)
Base Pointers: 64-bit
Peak Pointers: Not Applicable
Other:
Power Management: --

Errors

'reportable' flag not set during run
600.perlbench_s (base) did not have enough runs!
602.gcc_s (base) did not have enough runs!
620.omnetpp_s (base) did not have enough runs!
648.exchange2_s (base) did not have enough runs!
605.mcf_s (base) did not have enough runs!
657.xz_s (base) did not have enough runs!
641.leela_s (base) did not have enough runs!
625.x264_s (base) did not have enough runs!
631.deepsjeng_s (base) did not have enough runs!
623.xalancbmk_s (base) did not have enough runs!

(Continued on next page)

SPEC CPU®2017 Integer Speed Result

not applicable

SPECspeed®2017_int_base = 0.00

SPECspeed®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)
Test Sponsor: not applicable
Tested by: not applicable

Test Date: Sep-2020
Hardware Availability:
Software Availability:

Errors (Continued)

600.perlbench_s (base) had invalid runs!
Input set must be 'refspeed' for a valid run (set to 'test' for this run)
Run of 600.perlbench_s (base) was not valid; status is VE
Unknown flags were used! See
https://www.spec.org/cpu2017/Docs/runcpu.html#flagsurl
for information about how to get rid of this error.

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
600.perlbench_s	1	7.92	0.00											
602.gcc_s	1	0.501	0.00											
605.mcf_s	1	46.2	0.00											
620.omnetpp_s	1	23.7	0.00											
623.xalancbmk_s	1	0.982	0.00											
625.x264_s	1	301	0.00											
631.deepsjeng_s	1	48.9	0.00											
641.leela_s	1	32.2	0.00											
648.exchange2_s	1	59.9	0.00											
657.xz_s	1	43.3	0.00											

SPECspeed®2017_int_base = 0.00

SPECspeed®2017_int_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
```

Environment Variables Notes

```
Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH =
      "/u/home/schmidtf/riscv-gnu-toolchain/build/lib64/:/u/home/schmidtf/risc
      v-gnu-toolchain/build/lib/:/lib64"
```

Platform Notes

```
 Sysinfo program /u/home/schmidtf/spec/bin/sysinfo
 Rev: r6365 of 2019-08-21 295195f888a3d7edb1e6e46a485a0011
```

(Continued on next page)

Platform Notes (Continued)

```
running on sksmall Thu Sep 17 12:03:36 2020

SUT (System Under Test) info as seen by some common utilities.
For more information on this section, see
   https://www.spec.org/cpu2017/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) Bronze 3106 CPU @ 1.70GHz
      1  "physical id"s (chips)
      8 "processors"
   cores, siblings (Caution: counting these is hw and system dependent. The following
   excerpts from /proc/cpuinfo might not be reliable.  Use with caution.)
      cpu cores : 8
      siblings  : 8
      physical 0: cores 0 1 2 3 4 5 6 7

From lscpu:
     Architecture:          x86_64
     CPU op-mode(s):        32-bit, 64-bit
     Byte Order:            Little Endian
     CPU(s):                8
     On-line CPU(s) list:   0-7
     Thread(s) per core:    1
     Core(s) per socket:    8
     Socket(s):             1
     NUMA node(s):          1
     Vendor ID:             GenuineIntel
     CPU family:            6
     Model:                 85
     Model name:            Intel(R) Xeon(R) Bronze 3106 CPU @ 1.70GHz
     Stepping:              4
     CPU MHz:               1318.858
     CPU max MHz:           1700.0000
     CPU min MHz:           800.0000
     BogoMIPS:              3400.00
     Virtualization:        VT-x
     L1d cache:             32K
     L1i cache:             32K
     L2 cache:              1024K
     L3 cache:              11264K
     NUMA node0 CPU(s):     0-7
     Flags:                 fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov
     pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp
     lm constant_tsc art arch_perfmon pebs bts rep_good nopl xtopology nonstop_tsc cpuid
     aperfmperf pni pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg fma cx16
     xtpr pdcm pcid dca sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave
     avx f16c rdrand lahf_lm abm 3dnowprefetch cpuid_fault epb cat_l3 cdp_l3
```


(Continued on next page)

Platform Notes (Continued)

```
      invpcid_single pti intel_ppin ssbd mba ibrs ibpb stibp tpr_shadow vnmi flexpriority
      ept vpid fsgsbase tsc_adjust bmi1 hle avx2 smep bmi2 erms invpcid rtm cqm mpx rdt_a
      avx512f avx512dq rdseed adx smap clflushopt clwb intel_pt avx512cd avx512bw avx512vl
      xsaveopt xsavec xgetbv1 xsaves cqm_llc cqm_occup_llc cqm_mbm_total cqm_mbm_local
      dtherm arat pln pts hwp hwp_act_window hwp_pkg_req pku ospke md_clear flush_l1d

  /proc/cpuinfo cache data
     cache size : 11264 KB

  From numactl --hardware  WARNING: a numactl 'node' might or might not correspond to a
  physical chip.

  From /proc/meminfo
     MemTotal:       82139464 kB
     HugePages_Total:       0
     Hugepagesize:       2048 kB

  /usr/bin/lsb_release -d
     Ubuntu 18.04.3 LTS

  From /etc/*release* /etc/*version*
     debian_version: buster/sid
     os-release:
        NAME="Ubuntu"
        VERSION="18.04.3 LTS (Bionic Beaver)"
        ID=ubuntu
        ID_LIKE=debian
        PRETTY_NAME="Ubuntu 18.04.3 LTS"
        VERSION_ID="18.04"
        HOME_URL="https://www.ubuntu.com/"
        SUPPORT_URL="https://help.ubuntu.com/"

  uname -a:
     Linux sksmall 4.15.0-70-generic #79-Ubuntu SMP Tue Nov 12 10:36:11 UTC 2019 x86_64
     x86_64 x86_64 GNU/Linux

  Kernel self-reported vulnerability status:

  itlb_multihit:                          KVM: Mitigation: Split huge pages
  CVE-2018-3620 (L1 Terminal Fault):      Mitigation: PTE Inversion; VMX: conditional
                                          cache flushes, SMT disabled
  Microarchitectural Data Sampling:       Mitigation: Clear CPU buffers; SMT disabled
  CVE-2017-5754 (Meltdown):               Mitigation: PTI
  CVE-2018-3639 (Speculative Store Bypass): Mitigation: Speculative Store Bypass disabled
                                           via prctl and seccomp
  CVE-2017-5753 (Spectre variant 1):      Mitigation: usercopy/swapgs barriers and __user
                                           pointer sanitization
```

(Continued on next page)

Platform Notes (Continued)

```
 CVE-2017-5715 (Spectre variant 2):        Mitigation: Full generic retpoline, IBPB:
                                           conditional, IBRS_FW, STIBP: disabled, RSB
                                           filling
 tsx_async_abort:                          Mitigation: Clear CPU buffers; SMT disabled

 run-level 5 Nov 28 09:46

 SPEC is set to: /u/home/schmidtf/spec
    Filesystem                                     Type  Size  Used Avail Use% Mounted
    on
    nasil10.informatik.tu-muenchen.de:/srv/il10/home nfs   6.9T  4.1T  2.6T  62% /u/home

 From /sys/devices/virtual/dmi/id
     BIOS:    HPE U32 11/13/2019
     Vendor:  HPE
     Product: ProLiant DL360 Gen10
     Product Family: ProLiant

 Cannot run dmidecode; consider saying (as root)
    chmod +s /usr/sbin/dmidecode

 (End of data from sysinfo program)
```

Compiler Version Notes

```
==============================================================================
C       | 600.perlbench_s(base) 602.gcc_s(base) 605.mcf_s(base)
        | 625.x264_s(base) 657.xz_s(base)
------------------------------------------------------------------------------
Using built-in specs.
COLLECT_GCC=/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-gcc
COLLECT_LTO_WRAPPER=/u/home/schmidtf/riscv-gnu-toolchain/build/libexec/gcc/riscv64-unknown-linux-gnu/10.1.0/lto-wrapper
Target: riscv64-unknown-linux-gnu
Configured with: /u/home/schmidtf/riscv-gnu-toolchain/riscv-gcc/configure
  --target=riscv64-unknown-linux-gnu
  --prefix=/u/home/schmidtf/riscv-gnu-toolchain/build
  --with-sysroot=/u/home/schmidtf/riscv-gnu-toolchain/build/sysroot
  --with-system-zlib --enable-shared --enable-tls
  --enable-languages=c,c++,fortran --disable-libmudflap --disable-libssp
  --disable-libquadmath --disable-libsanitizer --disable-nls
  --disable-bootstrap --src=.././riscv-gcc --disable-multilib --with-abi=lp64
  --with-arch=rv64ima --with-tune=rocket 'CFLAGS_FOR_TARGET=-O2
  -mcmodel=medlow' 'CXXFLAGS_FOR_TARGET=-O2   -mcmodel=medlow'
Thread model: posix
Supported LTO compression algorithms: zlib
gcc version 10.1.0 (GCC)
```


(Continued on next page)

Compiler Version Notes (Continued)

```
------------------------------------------------------------------------------

==============================================================================
C++      | 620.omnetpp_s(base) 623.xalancbmk_s(base) 631.deepsjeng_s(base)
         | 641.leela_s(base)
------------------------------------------------------------------------------
Using built-in specs.
COLLECT_GCC=/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-g++
COLLECT_LTO_WRAPPER=/u/home/schmidtf/riscv-gnu-toolchain/build/libexec/gcc/riscv64-unknown-linux-gnu/10.1.0/lto-wrapper
Target: riscv64-unknown-linux-gnu
Configured with: /u/home/schmidtf/riscv-gnu-toolchain/riscv-gcc/configure
  --target=riscv64-unknown-linux-gnu
  --prefix=/u/home/schmidtf/riscv-gnu-toolchain/build
  --with-sysroot=/u/home/schmidtf/riscv-gnu-toolchain/build/sysroot
  --with-system-zlib --enable-shared --enable-tls
  --enable-languages=c,c++,fortran --disable-libmudflap --disable-libssp
  --disable-libquadmath --disable-libsanitizer --disable-nls
  --disable-bootstrap --src=.././riscv-gcc --disable-multilib --with-abi=lp64
  --with-arch=rv64ima --with-tune=rocket 'CFLAGS_FOR_TARGET=-O2
  -mcmodel=medlow' 'CXXFLAGS_FOR_TARGET=-O2   -mcmodel=medlow'
Thread model: posix
Supported LTO compression algorithms: zlib
gcc version 10.1.0 (GCC)
------------------------------------------------------------------------------

==============================================================================
Fortran | 648.exchange2_s(base)
------------------------------------------------------------------------------
Using built-in specs.
COLLECT_GCC=/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-gfortran
COLLECT_LTO_WRAPPER=/u/home/schmidtf/riscv-gnu-toolchain/build/libexec/gcc/riscv64-unknown-linux-gnu/10.1.0/lto-wrapper
Target: riscv64-unknown-linux-gnu
Configured with: /u/home/schmidtf/riscv-gnu-toolchain/riscv-gcc/configure
  --target=riscv64-unknown-linux-gnu
  --prefix=/u/home/schmidtf/riscv-gnu-toolchain/build
  --with-sysroot=/u/home/schmidtf/riscv-gnu-toolchain/build/sysroot
  --with-system-zlib --enable-shared --enable-tls
  --enable-languages=c,c++,fortran --disable-libmudflap --disable-libssp
  --disable-libquadmath --disable-libsanitizer --disable-nls
  --disable-bootstrap --src=.././riscv-gcc --disable-multilib --with-abi=lp64
  --with-arch=rv64ima --with-tune=rocket 'CFLAGS_FOR_TARGET=-O2
  -mcmodel=medlow' 'CXXFLAGS_FOR_TARGET=-O2   -mcmodel=medlow'
Thread model: posix
Supported LTO compression algorithms: zlib
gcc version 10.1.0 (GCC)
------------------------------------------------------------------------------
```

Base Unknown Flags

600.perlbench_s: "/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in CC)
"/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in LD)

602.gcc_s: "/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in CC)
"/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in LD)

605.mcf_s: "/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in CC)
"/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in LD)

620.omnetpp_s: "/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in CXX)
"/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in LD)

623.xalancbmk_s: "/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in CXX)
"/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in LD)

625.x264_s: "/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in CC)
"/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in LD)

631.deepsjeng_s: "/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in CXX)
"/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in LD)

641.leela_s: "/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in CXX)
"/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in LD)

648.exchange2_s: "/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in FC)
"/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in LD)

657.xz_s: "/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in CC)
"/u/home/schmidtf/riscv-gnu-toolchain/build/bin/riscv64-unknown-linux-gnu-" (in LD)

Base Compiler Invocation

C benchmarks:
gcc

C++ benchmarks:
g++

Fortran benchmarks:
gfortran

Base Portability Flags

600.perlbench_s: `-static(*) -DSPEC_LINUX_X64 -DSPEC_LP64`
602.gcc_s: `-static(*) -DSPEC_LP64`
605.mcf_s: `-static(*) -DSPEC_LP64`
620.omnetpp_s: `-static(*) -DSPEC_LP64`
623.xalancbmk_s: `-static(*) -DSPEC_LINUX -DSPEC_LP64`
625.x264_s: `-static(*) -DSPEC_LP64`
631.deepsjeng_s: `-static(*) -DSPEC_LP64`
641.leela_s: `-static(*) -DSPEC_LP64`
648.exchange2_s: `-static(*) -DSPEC_LP64`
657.xz_s: `-static(*) -DSPEC_LP64`

(*) Indicates a portability flag that was found in a non-portability variable.

Base Optimization Flags

C benchmarks:
`-std=c99 -g -O3 -DSPEC_SUPPRESS_OPENMP -fno-unsafe-math-optimizations -fno-tree-loop-vectorize -fno-openmp -fno-strict-aliasing -fgnu89-inline`

C++ benchmarks:
`-std=c++03 -g -O3 -DSPEC_SUPPRESS_OPENMP -fno-unsafe-math-optimizations -fno-tree-loop-vectorize -fno-openmp`

Fortran benchmarks:
`-DSPEC_SUPPRESS_OPENMP -g -O3 -fno-unsafe-math-optimizations -fno-tree-loop-vectorize -fno-openmp`

Base Other Flags

C benchmarks:
`-fcommon`

C++ benchmarks:
`-fcommon`

Fortran benchmarks:
`-fcommon`

not applicable

SPECspeed®2017_int_base = 0.00

SPECspeed®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)
Test Sponsor: not applicable
Tested by: not applicable

Test Date: Sep-2020
Hardware Availability:
Software Availability:

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2017 v1.1.0 on 2020-09-17 12:03:35+0000.
Report generated on 2020-09-17 12:14:44 by CPU2017 PDF formatter v6255.