Matlab Programming Guidelines

Joan Solà LAAS-CNRS

March 31, 2009

Contents

Matlab Help	1
2.2 Line grouping and commenting	
Names of variables and Jacobians.	4
Vectorizing structure arrays.	5
Error messages.	6
	Code readability 2.1 Aligned code reads well!

1 Matlab Help

Prepare your help headers to look really Matlab-like!

```
% FUN One line description with one space between % and FUN.
% FUN(X,Y) Longer description, with explanation of function
% inputs X and Y and the output. There are 4 spaces between
% and FUN(). The function name is in CAPITAL LETTERS.
% Preferably, the input variables X and Y are also in
capital letters.
%
If the paragraph above is too complex, break it into
% different paragraphs.
%
If the list of input arguments is too complex, make a
```

```
list here. Explain ALL input arguments. The list is
    indented another 4 spaces:
응
        X:
            one Bourbon
응
        Y:
             one Scotch
응
    FUN(X,Y,Z) explain extra inputs Z here and what they do.
응
    Explain if they have a default value. If you need to
응
    make a new list, remember the 4 spaces!
응
        Z:
             one beer.
읒
    [out, OUT_x, OUT_y] = FUN(...) returns the Jacobians
    wrt X and Y. Maybe you have to explain something else.
    You do not need to repeat the input parameters so you
    can use the form [out, OUT_x] = FUN(...), with the (...).
응
    Before saving, select entire paragraphs and do RIGHT
용
    CLICK, "Wrap selected comments". This equals all line
응
    lengths to approximately the page width.
    See also FUN2, FUN3. Use it exactly like this, "See also "
    + function names in CAPITAL LETTERS. Matlab parses this line
    and will create links to the functions' helps ONLY IF YOU
    FOLLOW THESE GUIDELINE STRICTLY.
     (c) 2009 You @ LAAS-CNRS. Make yourself famous. See that
    this comment line is disconnected from the Help body (the
    previous line has no % sign).
```

2 Code readability

2.1 Aligned code reads well!

1. When using consecutive lines of code, try to vertically align all EQUAL signs. Examples:

2. Similarly, when commenting multiple lines on the right margin, align comments. Examples:

3. Exceptions are accepted, but use common sense. Examples

```
% GOOD: all possible alignments coincide
                   % these comments are aligned
        = f(y);
х
                            % with the fourth line.
variable = g(z);
        = JAC_y*Y_x + Z_a*A_variable*VARIABLE_x; % Oops!
output
        = JAC_x*P*JAC_x'; % this defines the alignment above.
        = I*dont*know;
                            % over all it is easy to read.
% NOT SO GOOD, BUT OK: alignments come in groups
        = f(y); % these comments are NOT aligned
variable = g(z);
                    % with the fourth and fifth lines.
JAC_x = JAC_y*Y_x + Z_a*A_variable*VARIABLE_x; % Oops!
output
        = JAC_x*P*JAC_x'; % this margin is new
extra
        = I*dont*know;
                            % over all it is easy to read.
```

4. Still, you can try to align consecutive groups of lines. Example

```
x = f(y); % these comments aligned,
variable = g(z); % and the alignment
output = JAC_x*P*JAC_x'; % continues in next group

y = 4; % this follows the same alignment
extra = 5*eye(3); % over all it is easy to read.
```

2.2 Line grouping and commenting.

1. Comment every group of lines performing a coherent action before the group. Example:

```
% get idps to delete
used = [Lmk.used];
idps = strcmp({Lmk.type}, 'idpPnt');
drawn = (strcmp((get([MapFig.estLmk.ellipse], 'visible')), 'on'))';
delIdps = drawn & idps & ¬used;
```

2. Comment individual lines on the right if more info is needed. Example:

```
% get idps to delete
used = [Lmk.used]; % used lmks
idps = strcmp({Lmk.type},'idpPnt'); % lmks that are inverse—depth
delIdps = drawn & idps & ¬used; % these need to be deleted
```

- 3. Separate all groups of lines with an empty line so that the code does not look packed. As a rule, no more than 4 lines should go together.
- 4. Before saving the function, do CNTRL+A, CNTRL+I to make all the indents look nice.

2.3 Line breaking "..."

Make exceptional use of line breaking "...", particularly when functions have long names or many long parameters:

```
[out, OUT_x, OUT_y, OUT_z, OUT_par, OUT_calibration] = ...
functionNameThatMightBeVeryLong(...
Lmk.state.x,... % you can put
Sen(4).par.y,... % comments here
Obs(sen,lmk).nom.N,... % if necessary
Sen(4).par.k,... % to explain the
Sen(4).par.cal); % input data
```

See **USERDATA.M**, **CREATEMAPFIG.M** to see examples of this.

3 Names of variables and Jacobians.

For convention, we are going to do the following:

- 1. Variables inside functions have short names in small letters normally.
- 2. Jacobians are BIG_small, where $Y_x = dy/dx$.

- 3. Jacobians are not Yx, better Y_x.
- 4. Robot, sensor, landmark etc INDICES are always rob, sen, 1mk: For example,

```
Rob(rob).rob = rob;
Obs(sen,lmk).sen = sen;
```

5. Robot, sensor, landmark etc IDENTIFIERS are rid, sid, lid. For example,

```
Rob(rob).id = rid;
Obs(sen,lmk).sid = Sen(sen).id;
```

4 Vectorizing structure arrays.

1. Use vectorization to obtain arrays. Examples:

```
% 3 logical vectors
used = [Lmk.used];
vis = [Obs.vis];
drawn = (strcmp((get([MapFig.estLmk.ellipse],'visible')),'on'))';
% a numeric vector of IDs
lmkIds = [Lmk.id];
```

2. If the field you want to access is a string, try this

```
idps = strcmp({Lmk.type}, 'idpPnt') % a logical vector
```

3. Operate with the logicals to get new logicals. Example:

```
erase = ¬vis & drawn;
usedIdps = used & idps;
```

4. When setting logicals individually, always use true/false, not 1/0:

```
Obs(1).vis = true; % Do not use 1 instead of true, otherwise Obs(2).vis = false; % you turn the whole vector to numeric.
```

5. You can access an array directly with the logical vector

```
Lmk(used) % all the Lmk's that are used
```

6. You can get the indices with **FIND**

```
usedIdx = find(used);
```

7. You can also access an array with indices, of course:

```
Lmk(usedIdx) % this is equivalent to Lmk(used)
```

8. If you want the first N unused Lmk's, do for example

```
Lmk(find(¬used,N,'first'))
```

or, easier to read:

```
notUsed = find(¬[Lmk.used]);
Lmk(notUsed(1:N));
```

5 Error messages.

Be kind to your fellows and stick to Matlab standards:

```
error('??? Unknown sensor type ''%s''.', Sen(sen).type)
```

gives a 'nice' Matlab error message (the second line is ours!):

```
??? Error using ==> createSensors at 46
??? Unknown sensor type 'pinPole'.
```

```
Error in ==> createSLAMstructures at 10
Sen = createSensors(Sensor);

Error in ==> universalSlam at 36
[Rob,Sen,Lmk,Obs,Tim] = createSLAMstructures(...
```

This error information is enough. Matlab has debugging mechanisms to go find further info for the error.