## Demo document with computer code

HPL

Apr 8, 2015

## 1 Data file

Suppose we have some data in a file typeset with !bc dat:

```
# A B C D E
-0.5253 -0.9315 -0.3427 -0.1613 -0.8472
-0.9740 -0.2558 -0.5622 -0.7635 -0.0914
0.9216 0.7702 -0.4818 0.2155 0.2967
```

## 2 Complete program and terminal output

The following program (which breaks a page) reads the data in the file and performs analysis (typeset with !bc pypro):

```
#!/usr/bin/env python
import numpy as np

def readfile(filename):
    """Read tabular data from file and return as numpy array."""
    f = open(filename, 'r')
    data = [] # list of rows in table
    for line in f:
        if line.startswith('#'):
            continue # drop comment lines
        numbers = [float(w) for w in line.split()]
        data.append(numbers)
    return np.array(data)

def analyze(data):
```

The output becomes (typeset with !bc sys):

```
Terminal> python fileread.py
mean = -0.006005
st.dev=0.583542
correlation matrix:
              0.0509676
                           0.52406366 0.20964645 0.1574504 ]
[[ 1.
 [ 0.0509676
                          -0.30920845 -0.12129049 0.7611538 ]
             1.
 [ 0.52406366 -0.30920845 1.
                                       0.49355806 -0.42263817]
 [ 0.20964645 -0.12129049  0.49355806  1.
                                                  -0.38286589]
 [ 0.1574504
               0.7611538 -0.42263817 -0.38286589 1.
                                                             ]]
```

## 3 Code snippet

Fortran 77 is also sometimes handy (typeset with !bc fcod):

```
subroutine process(a, n, c, r)

2  C  Return array r = c*a
    integer n
    real*8 a(n), c, r(n)

5   integer i
    do i = 1,n
        r(i) = c*a(i)

8   end do
   return
   end
```