Demo document with computer code

HPL

Feb 26, 2016

1 Data file

Suppose we have some data in a file. The final result of including this file with @@@CODE mydat.txt (which implies a code environment starting with !bc dat) looks like this:

```
С
                                                Е
  Α
              В
                                     D
-0.5253
           -0.9315
                      -0.3427
                                  -0.1613
                                             -0.8472
-0.9740
           -0.2558
                      -0.5622
                                  -0.7635
                                             -0.0914
0.9216
            0.7702
                      -0.4818
                                  0.2155
                                              0.2967
```

2 Complete program and terminal output

The following program (which breaks a page) reads the data in the file and performs analysis (typeset with !bc pypro):

```
#!/usr/bin/env python

import numpy as np

def readfile(filename):
    """Read tabular data from file and return as numpy array."""
    f = open(filename, 'r')
    data = [] # list of rows in table
    for line in f:
        if line.startswith('#'):
            continue # drop comment lines
        numbers = [float(w) for w in line.split()]
        data.append(numbers)
```

```
return np.array(data)
def analyze(data):
    """Return statistical measures of an array data."""
    return np.mean(data), \
           np.std(data), \
           np.corrcoef(data)
if __name__ == '__main__':
   data = readfile('mydat.txt')
    # Treat each column as a variable
   m, s, c = analyze(data.transpose())
   print """
mean=\%f
st.dev=%f
correlation matrix:
%s
""" % (m, s, c)
```

The output becomes (typeset with !bc sys):

3 Code snippet

Fortran 77 is also sometimes handy (typeset with !bc fcod):

```
subroutine process(a, n, c, r)
C Return array r = c*a
integer n
real*8 a(n), c, r(n)
integer i
do i = 1,n
    r(i) = c*a(i)
end do
return
end
```