Demo document with computer code

HPL

Feb 26, 2016

1 Data file

Suppose we have some data in a file. The final result of including this file with <code>@@@CODE</code> mydat.txt (which implies a code environment starting with !bc dat) looks like this:

```
# A B C D E
-0.5253 -0.9315 -0.3427 -0.1613 -0.8472
-0.9740 -0.2558 -0.5622 -0.7635 -0.0914
0.9216 0.7702 -0.4818 0.2155 0.2967
```

2 Complete program and terminal output

The following program (which breaks a page) reads the data in the file and performs analysis (typeset with !bc pypro):

```
#!/usr/bin/env python
import numpy as np
def readfile(filename):
    """Read tabular data from file and return as numpy array."""
    f = open(filename, 'r')
    data = [] # list of rows in table
    for line in f:
        if line.startswith('#'):
            continue # drop comment lines
        numbers = [float(w) for w in line.split()]
        data.append(numbers)
    return np.array(data)
def analyze(data):
    """Return statistical measures of an array data."""
    np.corrcoef(data)
if __name__ == '__main__':
    data = readfile('mydat.txt')
    # Treat each column as a variable
```

3 Code snippet

Fortran 77 is also sometimes handy (typeset with !bc fcod):

```
subroutine process(a, n, c, r)
Return array r = c*a
integer n
real*8 a(n), c, r(n)
integer i
do i = 1,n
    r(i) = c*a(i)
end do
return
end
```