

Demo document with computer code

HPL

Feb 28, 2016

1 Data file

Suppose we have some data in a file. The final result of including this file with `@@@CODE mydat.txt` (which implies a code environment starting with `!bc dat`) looks like this:

| # | A | B | C | D | E |
|---|---------|---------|---------|---------|---------|
| | -0.5253 | -0.9315 | -0.3427 | -0.1613 | -0.8472 |
| | -0.9740 | -0.2558 | -0.5622 | -0.7635 | -0.0914 |
| | 0.9216 | 0.7702 | -0.4818 | 0.2155 | 0.2967 |

2 Complete program and terminal output

The following program (which breaks a page) reads the data in the file and performs analysis (typeset with `!bc pypro`):

```
#!/usr/bin/env python

import numpy as np

def readfile(filename):
    """Read tabular data from file and return as numpy array."""
    f = open(filename, 'r')
    data = [] # list of rows in table
    for line in f:
        if line.startswith('#'):
            continue # drop comment lines
        numbers = [float(w) for w in line.split()]
        data.append(numbers)
```

```

        return np.array(data)

def analyze(data):
    """Return statistical measures of an array data."""
    return np.mean(data), \
           np.std(data), \
           np.corrcoef(data)

if __name__ == '__main__':
    data = readfile('mydat.txt')
    # Treat each column as a variable
    m, s, c = analyze(data.transpose())
    print ""
    mean=%f
    st.dev=%f
    correlation matrix:
    %s
    """ % (m, s, c)

```

The output becomes (typeset with !bc sys):

Terminal

```

Terminal> python fileread.py

mean=-0.006005
st.dev=0.583542
correlation matrix:
[[ 1.          0.0509676  0.52406366  0.20964645  0.1574504 ]
 [ 0.0509676   1.         -0.30920845 -0.12129049  0.7611538 ]
 [ 0.52406366 -0.30920845  1.          0.49355806 -0.42263817]
 [ 0.20964645 -0.12129049  0.49355806  1.         -0.38286589]
 [ 0.1574504   0.7611538  -0.42263817 -0.38286589  1.          ]]

```

3 Code snippet

Fortran 77 is also sometimes handy. Snippets in that language are typeset inside !bc fcod environments.

Fortran code box.

$$r_i = ca_i, \quad i = 1, \dots, n$$

```
subroutine process(a, n, c, r)
C   This subroutine returns array r = c*a
integer n
real*8 a(n), c, r(n)
integer i
do i = 1,n
    r(i) = c*a(i)
end do
return
end
```