Demo document with computer code

HPL

Feb 26, 2016

1 Data file

Suppose we have some data in a file. The final result of including this file with <code>@@@CODE</code> mydat.txt (which implies a code environment starting with !bc dat) looks like this:

```
# A B C D E
-0.5253 -0.9315 -0.3427 -0.1613 -0.847:
-0.9740 -0.2558 -0.5622 -0.7635 -0.091:
0.9216 0.7702 -0.4818 0.2155 0.296
```

2 Complete program and terminal output

The following program (which breaks a page) reads the data in the file and performs analysis (typeset with !bc pypro):

```
#!/usr/bin/env python
import numpy as np
def readfile(filename):
    """Read tabular data from file and return as numpy array."""
   f = open(filename, 'r')
   data = [] # list of rows in table
   for line in f:
       if line.startswith('#'):
           continue # drop comment lines
       numbers = [float(w) for w in line.split()]
       data.append(numbers)
   return np.array(data)
def analyze(data):
    """Return statistical measures of an array data."""
   np.corrcoef(data)
if __name__ == '__main__':
```

```
data = readfile('mydat.txt')
    # Treat each column as a variable
    m, s, c = analyze(data.transpose())
    print """
mean=%f
st.dev=%f
correlation matrix:
%s
""" % (m, s, c)
```

The output becomes (typeset with !bc sys):

3 Code snippet

Fortran 77 is also sometimes handy (typeset with !bc fcod):

```
subroutine process(a, n, c, r)

C Return array r = c*a
   integer n
   real*8 a(n), c, r(n)
   integer i
   do i = 1,n
       r(i) = c*a(i)
   end do
   return
   end
```