

## **Embree**High Performance Ray Tracing Kernels

Version 2.5.0 (devel) January 30, 2015

## **Contents**

1	Emb	ree Overview 3
	1.1	Version History
	1.2	Supported Platforms
	1.3	Embree Support and Contact
2	Com	piling Embree 7
	2.1	Linux and Mac OS X
	2.2	Intel® Xeon Phi <sup>TM</sup> coprocessor
	2.3	Windows
3	Emb	ree API
	3.1	Scene
	3.2	Geometries
	3.3	Ray Queries
	3.4	Buffer Sharing
	3.5	Linear Motion Blur
	3.6	User Data Pointer
	3.7	Geometry Mask
	3.8	Filter Functions
	3.9	Displacement Mapping Functions
	3.10	Sharing Threads with Embree
4	Emb	ree Tutorials 25
	4.1	Tutorial00
	4.2	Tutorial01
	4.3	Tutorial02
	4.4	Tutorial03
	4.5	Tutorial04
	4.6	Tutorial05
	4.7	Tutorial06
	4.8	Tutorial07
	4.9	Tutorial08
	4.10	Tutorial09
	4.11	Tutorial10

## **Chapter 1 Embree Overview**

Embree is a collection of high-performance ray tracing kernels, developed at Intel. The target user of Embree are graphics application engineers that want to improve the performance of their application by leveraging the optimized ray tracing kernels of Embree. The kernels are optimized for photo-realistic rendering on the latest Intel® processors with support for SSE, AVX, AVX2, and the 16-wide Intel® Xeon Phi<sup>TM</sup> coprocessor vector instructions. Embree supports runtime code selection to choose the traversal and build algorithms that best matches the instruction set of your CPU. We recommend using Embree through its API to get the highest benefit from future improvements. Embree is released as Open Source under the Apache 2.0 license.

Embree supports applications written with the Intel SPMD Programm Compiler (ISPC, https://ispc.github.io/) by also providing an ISPC interface to the core ray tracing algorithms. This makes it possible to write a renderer in ISPC that leverages SSE, AVX, AVX2, and Xeon Phi instructions without any code change. ISPC also supports runtime code selection, thus ISPC will select the best code path for your application, while Embree selects the optimal code path for the ray tracing algorithms.

Embree contains algorithms optimized for incoherent workloads (e.g. Monte Carlo ray tracing algorithms) and coherent workloads (e.g. primary visibility and hard shadow rays). For standard CPUs, the single-ray traversal kernels in Embree provide the best performance for incoherent workloads and are very easy to integrate into existing rendering applications. For Xeon Phi, a renderer written in ISPC using the default hybrid ray/packet traversal algorithms have shown to perform best, but requires writing the renderer in ISPC. In general for coherent workloads, ISPC outperforms the single ray mode on each platform. Embree also supports dynamic scenes by implementing high performance two-level spatial index structure construction algorithms.

In addition to the ray tracing kernels, Embree provides some tutorials to demonstrate how to use the Embree API. The example photorealistic renderer that was originally included in the Embree kernel package is now available in a separate GIT repository (see Embree Example Renderer). Please also check out the OSPRay Ray Tracing based Rendering Engine for High-Fidelity Visualization (https://ospray.github.io/) which builds on Embree.

## 1.1 Version History

#### 1.1.1 New Features in Embree 2.4

- Support for Catmull Clark subdivision surfaces (triangle/quad base primitives)
- Support for vector displacements on Catmull Clark subdivision surfaces

Embree Overview 4

Various bugfixes (e.g. 4-byte alignment of vertex buffers works)

#### 1.1.2 New Features in Embree 2.3.3

- BVH builders more robustly handle invalid input data (Intel® Xeon® processor family)
- Motion blur support for hair geometry (Xeon)
- Improved motion blur performance for triangle geometry (Xeon)
- Improved robust ray tracing mode (Xeon)
- Added rtcCommitThread API call for easier integration into existing tasking systems (Xeon and Intel<sup>®</sup> Xeon Phi<sup>™</sup> coprocessor)
- Added support for recording and replaying all rtcIntersect/rtcOccluded calls (Xeon and Xeon Phi)

#### 1.1.3 New Features in Embree 2.3.2

- Improved mixed AABB/OBB-BVH for hair geometry (Xeon Phi)
- Reduced amount of pre-allocated memory for BVH builders (Xeon Phi)
- New 64 bit Morton code-based BVH builder (Xeon Phi)
- (Enhanced) Morton code-based BVH builders use now tree rotations to improve BVH quality (Xeon Phi)
- Bug fixes (Xeon and Xeon Phi)

#### 1.1.4 New Features in Embree 2.3.1

- High quality BVH mode improves spatial splits which result in up to 30% performance improvement for some scenes (Xeon).
- Compile time enabled intersection filter functions do not reduce performance if no intersection filter is used in the scene (Xeon and Xeon Phi)
- Improved ray tracing performance for hair geometry by >20% on Xeon Phi. BVH for hair geometry requires 20% less memory
- BVH8 for AVX/AVX2 targets improves performance for single ray tracing on Haswell by up to 12% and by up to 5% for hybrid (Xeon)
- Memory conservative BVH for Xeon Phi now uses BVH node quantization to lower memory footprint (requires half the memory footprint of the default BVH)

#### 1.1.5 New Features in Embree 2.3

- Support for ray tracing hair geometry (Xeon and Xeon Phi)
- · Catching errors through error callback function
- Faster hybrid traversal (Xeon and Xeon Phi)
- New memory conservative BVH for Xeon Phi
- Faster Morton code-based builder on Xeon
- Faster binned-SAH builder on Xeon Phi
- Lots of code cleanups/simplifications/improvements (Xeon and Xeon Phi)

#### 1.1.6 New Features in Embree 2.2

- Support for motion blur on Xeon Phi
- Support for intersection filter callback functions
- Support for buffer sharing with the application
- Lots of AVX2 optimizations, e.g. ~20% faster 8-wide hybrid traversal
- Experimental support for 8-wide (AVX/AVX2) and 16-wide BVHs (Xeon Phi)

Embree Overview 5

#### 1.1.7 New Features in Embree 2.1

- New future proof API with a strong focus on supporting dynamic scenes
- Lots of optimizations for 8-wide AVX2 (Haswell architecture)
- Automatic runtime code selection for SSE, AVX, and AVX2
- Support for user-defined geometry
- New and improved BVH builders:
  - Fast adaptive Morton code-based builder (without SAH-based toplevel rebuild)
  - Both the SAH and Morton code-based builders got faster (Xeon Phi)
  - New variant of the SAH-based builder using triangle pre-splits (Xeon Phi)

#### 1.1.8 Example Performance Numbers for Embree 2.1

BVH rebuild performance (including triangle accel generation, excluding memory allocation) for scenes with 2-12 million triangles:

- Intel<sup>®</sup> Core<sup>™</sup> i7 (Haswell-based CPU, 4 cores @ 3.0 GHz)
  - 7-8 million triangles/s for the SAH-based BVH builder
  - 30-36 million triangles/s for the Morton code-based BVH builder
- Intel<sup>®</sup> Xeon Phi<sup>™</sup> 7120
  - 37-40 million triangles/s for the SAH-based BVH builder
  - 140-160 million triangles/s for the Morton code-based BVH builder

Rendering of the Crown model (crown.ecs) with 4 samples per pixel (-spp 4):

- Intel<sup>®</sup> Core<sup>™</sup> i7 (Haswell-based CPU, 4 cores CPU @ 3.0 GHz)
  - 1024×1024 resolution: 7.8 million rays per sec
  - 1920×1080 resolution: 9.9 million rays per sec
- Intel® Xeon Phi<sup>TM</sup> 7120
  - 1024×1024 resolution: 47.1 million rays per sec
  - 1920×1080 resolution: 61.1 million rays per sec

#### 1.1.9 New Features in Embree 2.0

- Support for the Intel<sup>®</sup> Xeon Phi<sup>™</sup> coprocessor platform
- Support for high-performance "packet" kernels on SSE, AVX, and Xeon Phi
- Integration with the Intel® SPMD Program Compiler (ISPC)
- Instantiation and fast BVH reconstruction
- Example photo-realistic rendering engine for both C++ and ISPC

Embree Overview 6

### 1.2 Supported Platforms

Embree supports Windows (32 bit and 64 bit), Linux (64 bit) and Mac OS X (64 bit). The code compiles with the Intel Compiler, GCC, CLANG and the Microsoft Compiler. Embree is tested with Intel Compiler 15.0.0, CLANG 3.4.2, GCC 4.8.2, and Visual Studio 12 2013. Using the Intel Compiler improves performance by approximately 10%.

Performance also varies across different operating systems. Embree is optimized for Intel CPUs supporting SSE, AVX, and AVX2 instructions, and requires at least a CPU with support for SSE2.

The Xeon Phi version of Embree only works under Linux in 64 bit mode. For compilation of the Xeon Phi code the Intel Compiler is required. The host side code compiles with GCC, CLANG, and the Intel Compiler.

## 1.3 Embree Support and Contact

If you encounter bugs please report them via Embree's GitHub Issue Tracker.

For questions please write us at embree\_support@intel.com.

To receive notifications of updates and new features of Embree please subscribe to the Embree mailing list.

For information about compiler optimizations, see our Optimization Notice.

# Chapter 2 Compiling Embree

#### 2.1 Linux and Mac OS X

Embree is tested with Intel<sup>®</sup> Compiler 15.0.0, CLANG 3.4.2, and GCC 4.8.2. If the GCC that comes with your Fedora/Redhat/CentOS distribution is too old then you can run the provided script scripts/install\_linux\_gcc.sh to locally install a recent GCC into \$HOME/devtools-2. We recommend to install the Intel<sup>®</sup> SPMD Program Compiler (ISPC). If you do not want to use ISPC, simply disable ENABLE\_ISPC\_SUPPORT in cmake. Otherwise, download and install the ISPC binaries (we have tested ISPC version 1.8.0) from ispc.github.io. After installation, either put the path to the ispc executable permanently into your PATH:

```
export PATH=path-to-ispc:$PATH
```

Or provide the path to the ispc executable to CMake via the  $\ensuremath{\mathsf{ISPC\_EXE-CUTABLE}}$  variable.

You additionally have to install CMake 2.8.12 or higher and the developer version of GLUT. Under Mac OS X, these dependencies can be installed using MacPorts:

```
sudo port install cmake freeglut
```

Under Linux you can install these dependencies using yum or apt-get. Depending on your Linux distribution, some of these packages might already be installed or might have slightly different names.

Type the following to install the dependencies using yum:

```
sudo yum install cmake.x86_64
sudo yum install freeglut.x86_64 freeglut-devel.x86_64
sudo yum install libXmu.x86_64 libXi.x86_64
sudo yum install libXmu-devel.x86_64 libXi-devel.x86_64
```

Type the following to install the dependencies using apt-get:

```
sudo apt-get install cmake-curses-gui
sudo apt-get install freeglut3-dev
sudo apt-get install libxmu-dev libxi-dev
```

Finally you can compile Embree using CMake. Create a build directory and execute "ccmake .." inside this directory.

```
mkdir build cd build ccmake ..
```

Compiling Embree 8

This will open a configuration dialog where you can perform various configurations as described below. After having configured Embree, press c (for configure) and g (for generate) to generate a Makefile and leave the configuration. The code can be compiled by executing make.

#### make

The executables will be generated inside the build folder. We recommend to finally install the Embree library and header files on your system:

#### sudo make install

If you cannot install Embree on your system (e.g. when you don't have administrator rights) you need to add embree\_root\_directory/build to your LD\_LIBRARY\_PATH (and SINK\_LD\_LIBRARY\_PATH in case you want to use Embree on Intel® Xeon  $Phi^{TM}$  coprocessors).

The default configuration in the configuration dialog should be appropriate for most usages. The following table described all parameters that can be configured:

Option	Description	Default
CMAKE_BUILD_TYPE	Can be used to switch between Debug mode (Debug) and Release mode (Release).	Release
COMPILER	Select either GCC, ICC, or CLANG as compiler.	GCC
ENABLE_ISPC_SUPPORT	Enables ISPC support of Embree.	ON
ENABLE_STATIC_LIB	Builds Embree as a static library.	OFF
ENABLE_TUTORIALS	Enables build of Embree tutorials.	ON
ENABLE_XEON_PHI_SUPPORT	Enables generation of the Xeon Phi version of Embree.	OFF
RTCORE_BACKFACE_CULLING	Enables backface culling, i.e. only surfaces facing a ray can be hit.	OFF
RTCORE_BUFFER_STRIDE	Enables the buffer stride feature.	ON
RTCORE_INTERSECTION_FILTER	Enables the intersection filter feature.	ON
RTCORE_RAY_MASK	Enables the ray masking feature.	OFF
RTCORE_RETURN_SUBDIV_NORMAL	Instead of the triangle normal the ray returns a smooth normal based on evaluating the subdivision surface patch.	OFF
RTCORE_SPINLOCKS	Enables faster spinlocks for some builders.	OFF
RTCORE_TASKING_SYSTEM	Selects the used tasking system. Choose between an internal implementation (LOCKSTEP) or Intel® Threading Building Blocks (TBB).	LOCKSTEP
XEON_ISA	Select highest supported ISA on Intel® Xeon® CPUs (SSE2, SSE3, SSSE3, SSE4.1, SSE4.2, AVX, AVX-I, or AVX2).	AVX2

## 2.2 Intel® Xeon Phi™ coprocessor

Embree supports the Intel® Xeon Phi™ coprocessor under Linux. To compile Embree for Xeon Phi you need to enable the XEON\_PHI\_ISA option in CMake and have the Intel Compiler and the Intel® Manycore Platform Software Stack (Intel® MPSS) installed.

Enabling the buffer stride feature reduces performance for building spatial hierarchies on Xeon Phi.

Compiling Embree 9

#### 2.3 Windows

Embree requires Visual Studio 12 2013 and the Intel SPMD Program Compiler (ISPC) to compile. We have tested ISPC version 1.8.0, but more recent versions of ISPC should also work. You can download and install the ISPC binaries from ispc.github.io. After installation, put the path to ispc.exe permanently into your PATH environment variable or you need to correctly set the ISPC\_EXECUTABLE variable during CMake configuration.

You additionally have to install CMake (version 2.8.12 or higher). Note that you need a native Windows CMake installation, because CMake under Cygwin cannot generate solution files for Visual Studio.

#### 2.3.1 Using the IDE

Run cmake-gui, browse to the Embree sources, set the build directory and click Configure. Now you can select the Generator, e.g. "Visual Studio 12 2013" for a 32 bit build or "Visual Studio 12 2013 Win64" for a 64 bit build. Most configuration parameters described for the Linux build can be set under Windows as well. Finally, click "Generate" to create the Visual Studio solution files.

Table 2.2 -	- windows-specif	ic Civiake build	options for	Embree.

Option	Description	Default
CMAKE_CONFIGURATION_TYPE USE_STATIC_RUNTIME	List of generated configurations.  Use the static version of the C/C++ runtime library.	Debug;Release;RelWithDebInfo OFF

For compilation of Embree under Windows use the generated Visual Studio solution file embree.sln. The solution is by default setup to use the Microsoft Compiler. You can switch to the Intel Compiler by right clicking onto the solution in the Solution Explorer and then selecting the Intel Compiler. We recommend using 64 bit mode and the Intel Compiler for best performance.

To build Embree with support for the AVX2 instruction set you need at least Visual Studio 2013 Update 4. When switching to the Intel Compiler to build with AVX2 you currently need to manually *remove* the switch /arch:AVX2 from the embree\_avx2 project, which can be found under Properties  $\Rightarrow$  C/C++  $\Rightarrow$  All Options  $\Rightarrow$  Additional Options.

To build all projects of the solution it is recommend to build the CMake utility project ALL\_BUILD, which depends on all projects. Using "Build Solution" would also build all other CMake utility projects (such as INSTALL), which is usually not wanted.

We recommend enabling syntax highlighting for the .ispc source and .isph header files. To do so open Visual Studio 2008, go to Tools  $\Rightarrow$  Options  $\Rightarrow$  Text Editor  $\Rightarrow$  File Extension and add the isph and ispc extension for the "Microsoft Visual C++" editor.

#### 2.3.2 Using the Command Line

Embree can also be configured and built without the IDE using the Visual Studio command prompt:

```
cd path\to\embree
mkdir build
cd build
cmake -G "Visual Studio 12 2013 Win64" ...
```

Compiling Embree 10

```
{\sf cmake} \ {\it --build} \ . \ {\it --config} \ {\sf Release}
```

You can also build only some projects with the --target switch. Additional parameters after "--" will be passed to msbuild. For example, to build the Embree library in parallel use

```
cmake --build . --config Release --target embree -- \mbox{/m}
```

## Chapter 3 Embree API

The Embree API is a low level ray tracing API that supports defining and committing of geometry and performing ray queries of different types. Static and dynamic scenes are supported, that may contain triangular geometry (including linear motions for motion blur), instanced geometry, and user defined geometry. Supported ray queries are, finding the closest scene intersection along a ray, and testing a ray segment for any intersection with the scene. Single rays, as well as packets of rays in a struct of array layout can be used for packet sizes of 1, 4, 8, and 16 rays. Filter callback functions are supported, that get invoked for every intersection encountered during traversal.

The Embree API exists in a C++ and ISPC version. This document describes the C++ version of the API, the ISPC version is almost identical. The only differences are that the ISPC version needs some ISPC specific uniform type modifiers, and limits the ray packets to the native SIMD size the ISPC code is compiled for.

The user is supposed to include the embree2/rtcore.h, and the embree2/rtcore\_ray.h file, but none of the other header files. If using the ISPC version of the API, the user should include embree2/rtcore.isph and embree2/rtcore\_ray.isph.

```
#include <embree2/rtcore.h>
#include <embree2/rtcore_ray.h>
```

All API calls carry the prefix rtc which stands for ray tracing core. Before invoking any API call, the Embree ray tracing core has to get initialized through the rtcInit call. Before the application exits it should call rtcExit. Initializing Embree again after an rtcExit is allowed.

```
rtcInit(NULL);
...
rtcExit();
```

The rtcInit call initializes the ray tracing core. An optional configuration string can be passed through this function to configure implementation specific parameters. If this string is NULL, a default configuration is used, that is optimal for most usages.

API calls that access geometries are only thread safe as long as different geometries are accessed. Accesses to one geometry have to get sequenced by the application. All other API calls are thread safe. The rtcIntersect and rtcOccluded calls are re-entrant, but only for other rtcIntersect and rtcOccluded calls. It is thus safe to trace new rays when intersecting a user defined object, but not supported to create new geometry inside the intersect callback function of a user defined geometry.

Each user thread has its own error flag in the API. If an error occurs when invoking some API function, this flag is set to an error code if it stores no previous

error. The rtcGetError function reads and returns the currently stored error and clears the error flag again. For performance reasons the ray query functions do not set an error flag in release mode, but do so if Embree is compiled in debug mode.

Possible error codes returned by rtcGetError are:

Table 3.1 - Return values of rtcGetError.

Error Code	Description
RTC_NO_ERROR	No error occurred.
RTC_UNKNOWN_ERROR	An unknown error has occurred.
RTC_INVALID_ARGUMENT	An invalid argument was specified.
RTC_INVALID_OPERATION	The operation is not allowed for the specified object.
RTC_OUT_OF_MEMORY	There is not enough memory left to complete the operation.
RTC_UNSUPPORTED_CPU	The CPU is not supported as it does not support SSE2.

Using the rtcSetErrorFunction call, it is also possible to set a callback function that is called whenever an error occurs. The callback function gets passed the error code, as well as some string that describes the error further. Passing NULL to rtcSetErrorFunction disables the set callback function again. The previously described error flags are also set if an error callback function is present.

#### 3.1 Scene

A scene is a container for a set of geometries of potentially different types. A scene is created using the rtcNewScene function call, and destroyed using the rtcDeleteScene function call. Two types of scenes are supported, dynamic and static scenes. Different flags specify the type of scene to create and the type of ray query operations that can later be performed on the scene. The following example creates a scene that supports dynamic updates and the single ray rtcIntersect and rtcOccluded calls.

```
RTCScene scene = rtcNewScene(RTC_SCENE_DYNAMIC, RTC_INTERSECT1);
...
rtcDeleteScene(scene);
```

Using the following scene flags the user can select between creating a static and dynamic scene.

Scene Flag	Description
RTC_SCENE_STATIC	Scene is optimized for static geometry.
RTC_SCENE_DYNAMIC	Scene is optimized for dynamic geometry.

A dynamic scene is created by invoking rtcNewScene with the RTC\_SCENE\_DYNAMIC flag. Different geometries can now be created inside that scene. Geometries are enabled by default. Once the scene geometry is specified, an rtc-Commit call will finish the scene description and trigger building of internal data structures. After the rtcCommit call it is safe to perform ray queries of the type specified at scene construction time. Geometries can get disabled (rtcDisable call), enabled again (rtcEnable call), and deleted (rtcDeleteGeometry call). Geometries can also get modified, including their vertex and index arrays. After the modification of some geometry, rtcUpdate or rtcUpdateBuffer has to get

Table 3.2 – Dynamic type flags for rtc-NewScene.

called for that geometry to specify which buffers got modified. Each modified buffer can specified separately using the rtcUpdateBuffer function. In contrast the rtcUpdate function simply tags each buffer of some geometry as modified. If geometries got enabled, disabled, deleted, or modified an rtcCommit call has to get invoked before performing any ray queries for the scene, otherwise the effect of the ray query is undefined.

A static scene is created by the rtcNewScene call with the RTC\_SCENE\_STATIC flag. Geometries can only be created and modified until the first rtc-Commit call. After the rtcCommit call, each access to any geometry of that static scene is invalid, including enabling, disabling, modifying, and deletion of geometries. Consequently, geometries that got created inside a static scene can only get deleted by deleting the entire scene.

The following flags can be used to tune the used acceleration structure. These flags are only hints and may be ignored by the implementation.

Scene Flag	Description
RTC_SCENE_COMPACT	Creates a compact data structure and avoids algorithms that consume much memory.
RTC_SCENE_COHERENT	Optimize for coherent rays (e.g. primary rays).
RTC_SCENE_INCOHERENT	Optimize for in-coherent rays (e.g. diffuse reflection rays).
RTC SCENE HIGH QUALITY	Build higher quality spatial data structures.

Table 3.3 – Acceleration structure flags for rtcNewScene.

The following flags can be used to tune the traversal algorithm that is used by Embree. These flags are only hints and may be ignored by the implementation.

Scene Flag	Description
RTC_SCENE_ROBUST	Avoid optimizations that reduce arithmetic accuracy.

Table 3.4 – Traversal algorithm flags for rtcNewScene.

The second argument of the rtcNewScene function are algorithm flags, that allow to specify which ray queries are required by the application. Calling for a scene a ray query API function that is different to the ones specified at scene creation time is not allowed. Further, the application should only pass ray query requirements that are really needed, to give Embree most freedom in choosing the best algorithm. E.g. in case Embree implements no packet traversers for some highly optimized data structure for single rays, then this data structure cannot be used if the user enables any ray packet query.

Table 3.5 - Enabled algorithm flags for rtcNewScene.

Algorithm Flag	Description
RTC_INTERSECT1	Enables the rtcIntersect and rtcOccluded functions (single ray interface) for this scene.
RTC_INTERSECT4	Enables the rtcIntersect4 and rtcOccluded4 functions (4-wide packet interface) for this scene.
RTC_INTERSECT8	Enables the rtcIntersect8 and rtcOccluded8 functions (8-wide packet interface) for this scene.
RTC_INTERSECT16	Enables the rtcIntersect16 and rtcOccluded16 functions (16-wide packet interface) for this scene.

#### 3.2 Geometries

Geometries are always contained in the scene they are created in. Each geometry is assigned an integer ID at creation time, which is unique for that scene. The current version of the API supports triangle meshes (rtcNewTriangleMesh), Catmull-Clark subdivision surfaces (rtcNewSubdivisionMesh), hair geometries (rtcNewHairGeometry), single level instances of other scenes (rtcNewInstance), and user defined geometries (rtcNewUserGeometry). The API is designed in a way that easily allows adding new geometry types in later releases.

For dynamic scenes, the assigned geometry IDs fulfill the following properties. As long as no geometry got deleted, all IDs are assigned sequentially, starting from 0. If geometries got deleted, the implementation will reuse IDs later on in an implementation dependent way. Consequently sequential assignment is no longer guaranteed, but a compact range of IDs. These rules allow the application to manage a dynamic array to efficiently map from geometry IDs to its own geometry representation.

For static scenes, geometry IDs are assigned sequentially starting at 0. This allows the application to use a fixed size array to map from geometry IDs to its own geometry representation.

#### 3.2.1 Triangle Meshes

Triangle meshes are created using the rtcNewTriangleMesh function call, and potentially deleted using the rtcDeleteGeometry function call.

The number of triangles, the number of vertices, and optionally the number of time steps (1 for normal meshes, and 2 for linear motion blur) have to get specified at construction time of the mesh. The user can also specify additional flags that choose the strategy to handle that mesh in dynamic scenes. The following example demonstrates how to create a triangle mesh without motion blur:

unsigned geomID = rtcNewTriangleMesh(scene, geomFlags, numTriangles, numVertices);

The following geometry flags can be specified at construction time of the triangle mesh:

Table 3.6 - Flags for the creation of new geometries.

Geometry Flag	Description
RTC_GEOMETRY_STATIC	The mesh is considered static and should get modified rarely by the application. This flag has to get used in static scenes.
RTC_GEOMETRY_DEFORMABLE	The mesh is considered to deform in a coherent way, e.g. a skinned character. The connectivity of the mesh has to stay constant, thus modifying the index array is not allowed. The implementation is free to choose a BVH refitting approach for handling meshes tagged with that flag.
RTC_GEOMETRY_DYNAMIC	The mesh is considered highly dynamic and changes frequently, possibly in an unstructured way. Embree will rebuild data structures from scratch for this type of mesh.

The triangle indices can be set by mapping and writing to the index buffer (RTC\_INDEX\_BUFFER) and the triangle vertices can be set by mapping and writing into the vertex buffer (RTC\_VERTEX\_BUFFER). The index buffer contains an array of three 32 bit indices, while the vertex buffer contains an array of three float values aligned to 16 bytes. The 4th component of the aligned vertices can be arbitrary. All buffers have to get unmapped before an rtcCommit call to the scene.

```
struct Vertex { float x, y, z, a; };
struct Triangle { int v0, v1, v2; };

Vertex* vertices = (Vertex*) rtcMapBuffer(scene, geomID, RTC_VERTEX_BUFFER);

// fill vertices here
rtcUnmapBuffer(scene, geomID, RTC_VERTEX_BUFFER);

Triangle* triangles = (Triangle*) rtcMapBuffer(scene, geomID, RTC_INDEX_BUFFER);

// fill triangle indices here
rtcUnmapBuffer(scene, geomID, RTC_INDEX_BUFFER);
```

Also see tutorial00 for an example of how to create triangle meshes.

#### 3.2.2 Subdivision Surfaces

Catmull-Clark subdivision surfaces for meshes consisting of triangle and quad primitives (even mixed inside one mesh) are supported, including support for edge creases, vertex creases, holes, and non-manifold geometry.

A subdivision surface is created using the rtcNewSubdivisionMesh function call, and deleted again using the rtcDeleteGeometry function call.

The number of faces (numFaces), edges/indices (numEdges), vertices (numVertices), edge creases (numEdgeCreases), vertex creases (numVertexCreases), holes (numHoles), and time steps (numTimeSteps) have to get specified at construction time.

The following buffers have to get setup by the application: the face buffer (RTC\_FACE\_BUFFER) contains the number edges/indices (3 or 4) of each of the numFaces faces, the index buffer (RTC\_INDEX\_BUFFER) contains multiple (3 or 4) 32 bit vertex indices for each face and numEdges indices in total, the vertex buffer (RTC\_VERTEX\_BUFFER) stores numVertices vertices as single precision x, y, z floating point coordinates aligned to 16 bytes. The value of the 4th float used for alignment can be arbitrary.

Optionally, the application can setup the hole buffer (RTC\_HOLE\_BUFFER) with numHoles many 32 bit indices of faces that should be considered non-existing.

Optionally, the application can fill the level buffer (RTC\_LEVEL\_BUFFER) with a tessellation level for each or the edges of each face, making a total of numEdges values. The tessellation level is a positive floating point value, that specifies how many quads along the edge should get generated during tessellation. The tessellation level is a lower bound, thus the implementation is free to choose a larger level. If no level buffer is specified a level of 1 is used. Note that some edge may be shared between (typically 2) faces. To guarantee a watertight tessellation, the level of these shared edges has to be exactly identical.

Optionally, the application can fill the sparse edge crease buffers to make some edges appear sharper. The edge crease index buffer (RTC\_EDGE\_CREASE\_INDEX\_BUFFER) contains numEdgeCreases many pairs of 32 bit vertex indices

that specify unoriented edges. The edge crease weight buffer (RTC\_EDGE\_CREASE\_WEIGHT\_BUFFER) stores for each of theses crease edges a positive floating point weight. The larger this weight, the sharper the edge. Specifying a weight of infinity is supported and marks an edge as infinitely sharp. Storing an edge multiple times with the same crease weight is allowed, but has lower performance. Storing an edge multiple times with different crease weights results in undefined behavior. For a stored edge (i,j), the reverse direction edges (j,i) does not have to get stored, as both are considered the same edge.

Optionally, the application can fill the sparse vertex crease buffers to make some vertices appear sharper. The vertex crease index buffer (RTC\_VERTEX\_CREASE\_INDEX\_BUFFER), contains numVertexCreases many 32 bit vertex indices to specify a set of vertices. The vertex crease weight buffer (RTC\_VERTEX\_CREASE\_WEIGHT\_BUFFER) specifies for each of these vertices a positive floating point weight. The larger this weight, the sharper the vertex. Specifying a weight of infinity is supported and makes the vertex infinitely sharp. Storing a vertex multiple times with the same crease weight is allowed, but has lower performance. Storing a vertex multiple times with different crease weights results in undefined behavior.

Like for triangle meshes, the user can also specify a geometry mask and additional flags that choose the strategy to handle that subdivision mesh in dynamic scenes.

Also see tutorial08 for an example of how to create subdivision surfaces.

#### 3.2.3 Hair Geometry

Hair geometries are supported, which consist of multiple hairs represented as cubic Bézier curves with varying radius per control point. Individual hairs are considered to be subpixel sized which allows the implementation to approximate the intersection calculation. This in particular means that zooming onto one hair might show geometric artifacts.

Hair geometries are created using the rtcNewHairGeometry function call, and potentially deleted using the rtcDeleteGeometry function call.

The number of hair curves, the number of vertices, and optionally the number of time steps (1 for normal curves, and 2 for linear motion blur) have to get specified at construction time of the hair geometry.

The curve indices can be set by mapping and writing to the index buffer (RTC\_INDEX\_BUFFER) and the control vertices can be set by mapping and writing into the vertex buffer (RTC\_VERTEX\_BUFFER). In case of linear motion blur, two vertex buffers (RTC\_VERTEX\_BUFFER0 and RTC\_VERTEX\_BUFFER1) have to get filled, one for each time step.

The index buffer contains an array of 32 bit indices pointing to the ID of the first of four control vertices, while the vertex buffer stores all control points in the form of a single precision position and radius stored in x, y, z, r order in memory. All buffers have to get unmapped before an rtcCommit call to the scene.

Like for triangle meshes, the user can also specify a geometry mask and additional flags that choose the strategy to handle that mesh in dynamic scenes.

The following example demonstrates how to create some hair geometry:

```
unsigned geomID = rtcNewHairGeometry(scene, geomFlags, numCurves, numVertices);
struct Vertex { float x, y, z, r; };

Vertex* vertices = (Vertex*) rtcMapBuffer(scene, geomID, RTC_VERTEX_BUFFER);

// fill vertices here
rtcUnmapBuffer(scene, geomID, RTC_VERTEX_BUFFER);
```

```
int* triangles = (int*) rtcMapBuffer(scene, geomID, RTC_INDEX_BUFFER);
// fill indices here
rtcUnmapBuffer(scene, geomID, RTC_INDEX_BUFFER);
```

Also see tutorial07 for an example of how to create and use hair geometry.

#### 3.2.4 User Defined Geometry

User defined geometries make it possible to extend Embree with arbitrary types of geometry. This is achieved by introducing arrays of user geometries as a special geometry type. These objects do not contain a single user geometry, but a set of such geometries, each specified by an index. The user has to provide a user data pointer, bounding function as well as user defined intersect and occluded functions to create a set of user geometries. The user geometry to process is specified by passing its user data pointer and index to each invocation of the bounding, intersect, and occluded function. The bounding function is used to query the bounds of each user geometry. When performing ray queries, Embree will invoke the user intersect (and occluded) functions to test rays for intersection (and occlusion) with the specified user defined geometry.

As Embree supports different ray packet sizes, one potentially has to provide different versions of user intersect and occluded function pointers for these packet sizes. However, the ray packet size of the called user function always matches the packet size of the originally invoked ray query function. Consequently, an application only operating on single rays only has to provide single ray intersect and occluded function pointers.

User geometries are created using the rtcNewUserGeometry function call, and potentially deleted using the rtcDeleteGeometry function call. The following example illustrates creating an array with two user geometries:

```
struct UserObject { ... };
void userBoundsFunction(UserObject* userGeom, size_t i, RTCBounds& bounds) {
 bounds = <bounds of userGeom[i]>;
void userIntersectFunction(UserObject* userGeom, RTCRay& ray, size_t i) {
 if (<ray misses userGeom[i]>)
    return;
  <update ray hit information>;
}
void userOccludedFunction(UserObject* userGeom, RTCRay& ray, size_t i) {
  if (<ray misses userGeom[i]>)
    return;
 geomID = 0;
}
UserObject* userGeom = new UserObject[2];
userGeom[0] = ...
userGeom[1] = ...
unsigned geomID = rtcNewUserGeometry(scene, 2);
rtcSetUserData(scene, geomID, userGeom);
rtcSetBounds(scene, geomID, userBoundsFunction);
rtcSetIntersectFunction(scene, geomID, userIntersectFunction);
rtcSetOccludedFunction(scene, geomID, userOccludedFunction);
```

The user intersect function (userIntersectFunction) and user occluded function (userOccludedFunction) get as input the pointer provided through the rtcSetUserData function call, a ray, and the index of the geometry to process. For ray packets, the user intersect and occluded functions also get a pointer to a valid mask as input. The user provided functions should not modify any ray that is disabled by that valid mask.

The user intersect function should return without modifying the ray structure if the user geometry is missed. If the geometry is hit, it has to update the hit information of the ray (tfar, u, v, Ng, geomID, primID).

Also the user occluded function should return without modifying the ray structure if the user geometry is missed. If the geometry is hit, it should set the geomID member of the ray to 0.

Is is supported to invoke the rtcIntersect and rtcOccluded function calls inside such user functions. It is not supported to invoke any other API call inside these user functions.

See tutorial02 for an example of how to use the user defined geometries.

#### 3.2.5 Instances

Embree supports instancing of scenes inside another scene by some transformation. As the instanced scene is stored only a single time, even if instanced to multiple locations, this feature can be used to create extremely large scenes. Only single level instancing is supported by Embree natively, however, multi-level instancing can principally be implemented through user geometries.

Instances are created using the rtcNewInstance function call, and potentially deleted using the rtcDeleteGeometry function call. To instantiate a scene, one first has to generate the scene B to instantiate. Now one can add an instance of this scene inside a scene A the following way:

```
unsigned instID = rtcNewInstance(sceneA, sceneB);
rtcSetTransform(sceneA, instID, RTC_MATRIX_COLUMN_MAJOR, &column_matrix_3x4);
```

One has to call rtcCommit on scene B before one calls rtcCommit on scene A. When modifying scene B one has to call rtcModified for all instances of that scene. If a ray hits the instance, then the geomID and primID members of the ray are set to the geometry ID and primitive ID of the primitive hit in scene B, and the instID member of the ray is set to the instance ID returned from the rtcNewInstance function.

The rtcSetTransform call can be passed an affine transformation matrix with different data layouts:

Layout	Description
RTC_MATRIX_ROW_MAJOR	The 3×4 float matrix is laid out in row major form.
RTC_MATRIX_COLUMN_MAJOR	The 3×4 float matrix is laid out in column major form.
RTC_MATRIX_COLUMN_MAJOR_ALIGNED16	The $3\times4$ float matrix is laid out in column major form, with each column padded by an additional 4th component.

Table 3.7 - Matrix layouts for rtcSetTransform.

Passing homogeneous 4×4 matrices is possible as long as the last row is (0, 0, 0, 1). If this homogeneous matrix is laid out in row major form, use the RTC\_MATRIX\_ROW\_MAJOR layout. If this homogeneous matrix is laid out in column major form, use the RTC\_MATRIX\_COLUMN\_MAJOR\_ALIGNED16 mode. In both cases, Embree will ignore the last row of the matrix.

The transformation passed to rtcSetTransform transforms from the local space of the instantiated scene to world space.

See tutorial04 for an example of how to use instances.

### 3.3 Ray Queries

The API supports finding the closest hit of a ray segment with the scene (rtcIntersect functions), and determining if any hit between a ray segment and the scene exists (rtcOccluded functions).

The ray layout to be passed to the ray tracing core is defined in the embree2/rtcore\_ray.h header file. It is up to the user if he wants to use the ray structures defined in that file, or resemble the exact same binary data layout with their own vector classes. The ray layout might change with new Embree releases as new features get added, however, will stay constant as long as the major Embree release number does not change. The ray contains the following data members:

Member	In/Out	Description
org	in	ray origin
dir	in	ray direction (can be unnormalized)
tnear	in	start of ray segment
tfar	in/out	end of ray segment, set to hit distance after intersection
time	in	time used for motion blur
mask	in	ray mask to mask out geometries
Ng	out	unnormalized geometry normal
u	out	barycentric u-coordinate of hit
v	out	barycentric v-coordinate of hit
geomID	out	geometry ID of hit geometry
primID	out	primitive ID of hit primitive
instID	out	instance ID of hit instance

Table 3.8 - Data fields of a ray.

This structure is in struct of array layout (SOA) for ray packets. Note that the tfar member functions as an input and output.

In the ray packet mode (with packet size of N), the user has to provide a pointer to N 32 bit integers that act as a ray activity mask. If one of these integers is set to 0x00000000 the corresponding ray is considered inactive and if the integer is set to 0xFFFFFFFF, the ray is considered active. Rays that are inactive will not update any hit information. Data alignment requirements for ray query functions operating on single rays is 16 bytes for the ray.

Data alignment requirements for query functions operating on AOS packets of 4, 8, or 16 rays, is 16, 32, and 64 bytes respectively, for the valid mask and the ray. To operate on packets of 4 rays, the CPU has to support SSE, to operate on packets of 8 rays, the CPU has to support AVX-256, and to operate on packets of

16 rays, the CPU has to support the Intel<sup>®</sup> Xeon Phi<sup>™</sup> coprocessor instructions. Additionally, the required ISA has to be enabled in Embree at compile time to use the desired packet size.

Finding the closest hit distance is done through the rtcIntersect functions. These get the activity mask, the scene, and a ray as input. The user has to initialize the ray origin (org), ray direction (dir), and ray segment (tnear, tfar). The ray segment has to be in the range  $[0, \infty)$ , thus ranges that start behind the ray origin are not valid, but ranges can reach to infinity. The geometry ID (geomID member) has to get initialized to RTC\_INVALID\_GEOMETRY\_ID (-1). If the scene contains instances, also the instance ID (instID) has to get initialized to RTC\_ INVALID\_GEOMETRY\_ID (-1). If the scene contains linear motion blur, also the ray time (time) has to get initialized to a value in the range [0, 1]. If ray masks are enabled at compile time, also the ray mask (mask) has to get initialized. After tracing the ray, the hit distance (tfar), geometry normal (Ng), local hit coordinates (u, v), geometry ID (geomID), and primitive ID (primID) are set. If the scene contains instances, also the instance ID (instID) is set, if an instance is hit. The geometry ID corresponds to the ID returned at creation time of the hit geometry, and the primitive ID corresponds to the nth primitive of that geometry, e.g. nth triangle. The instance ID corresponds to the ID returned at creation time of the

The following code properly sets up a ray and traces it through the scene:

```
RTCRay ray;
ray.org = ray_origin;
ray.dir = ray_direction;
ray.tnear = 0.f;
ray.tfar = inf;
ray.geomID = RTC_INVALID_GEOMETRY_ID;
ray.primID = RTC_INVALID_GEOMETRY_ID;
ray.instID = RTC_INVALID_GEOMETRY_ID;
ray.mask = 0xFFFFFFFF;
ray.time = 0.f;
rtcIntersect(scene, ray);
```

Testing if any geometry intersects with the ray segment is done through the rtcOccluded functions. Initialization has to be done as for rtcIntersect. If some geometry got found along the ray segment, the geometry ID (geomID) will get set to 0. Other hit information of the ray is undefined after calling rtcOccluded.

See tutorial00 for an example of how to trace rays.

## 3.4 Buffer Sharing

Embree supports sharing of buffers with the application. Each buffer that can be mapped for a specific geometry can also be shared with the application, by pass a pointer, offset, and stride of the application side buffer using the rtcSetBuffer API function.

The rtcSetBuffer function has to get called before any call to rtcMap-Buffer for that buffer, otherwise the buffer will get allocated internally and the call to rtcSetBuffer will fail. The buffer has to remain valid as long as the geometry exists, and the user is responsible to free the buffer when the geometry gets deleted. When a buffer is shared, it is safe to modify that buffer without

mapping and unmapping it. However, for dynamic scenes one still has to call rtcModified for modified geometries and the buffer data has to stay constant from the rtcCommit call to after the last ray query invocation.

The offset parameter specifies a byte offset to the start of the first element and the stride parameter specifies a byte stride between the different elements of the shared buffer. This support for offset and stride allows the application quite some freedom in the data layout of these buffers, however, some restrictions apply. Index buffers always store 32 bit indices and vertex buffers always store single precision floating point data. The start address ptr+offset and stride always have to be aligned to 4 bytes on Intel® Xeon® CPUs and 16 bytes on Xeon Phi accelerators, otherwise the rtcSetBuffer function will fail. For vertex buffers, the 4 bytes after the z-coordinate of the last vertex have to be readable memory, thus padding is required for some layouts.

The following is an example of how to create a mesh with shared index and vertex buffers:

```
unsigned geomID = rtcNewTriangleMesh(scene, geomFlags, numTriangles, numVertices);
rtcSetBuffer(scene, geomID, RTC_VERTEX_BUFFER, vertexPtr, 0, 3*sizeof(float));
rtcSetBuffer(scene, geomID, RTC_INDEX_BUFFER, indexPtr, 0, 3*sizeof(int));
```

Sharing buffers can significantly reduce the memory required by the application, thus we recommend using this feature. When enabling the RTC\_COMPACT scene flag, the spatial index structures of Embree might also share the vertex buffer, resulting in even higher memory savings.

The support for offset and stride is enabled by default, but can get disabled at compile time using the RTCORE\_BUFFER\_STRIDE parameter in CMake. Disabling this feature enables the default offset and stride which increases performance of spatial index structure build, thus can be useful for dynamic content.

#### 3.5 Linear Motion Blur

Triangle meshes and hair geometries with linear motion blur support are created by setting the number of time steps to 2 at geometry construction time. Specifying a number of time steps of 0 or larger than 2 is invalid. For a triangle mesh or hair geometry with linear motion blur, the user has to set the RTC\_VERTEX\_BUFFER1 vertex arrays, one for each time step.

```
unsigned geomID = rtcNewTriangleMesh(scene, geomFlags, numTris, numVertices, 2);
rtcSetBuffer(scene, geomID, RTC_VERTEX_BUFFER0, vertex0Ptr, 0, sizeof(Vertex));
rtcSetBuffer(scene, geomID, RTC_VERTEX_BUFFER1, vertex1Ptr, 0, sizeof(Vertex));
rtcSetBuffer(scene, geomID, RTC_INDEX_BUFFER, indexPtr, 0, sizeof(Triangle));
```

If a scene contains geometries with linear motion blur, the user has to set the time member of the ray to a value in the range [0,1]. The ray will intersect the scene with the vertices of the two time steps linearly interpolated to this specified time. Each ray can specify a different time, even inside a ray packet.

#### 3.6 User Data Pointer

A user data pointer can be specified and queried per geometry, to efficiently map from the geometry ID returned by ray queries to the application representation for that geometry.

```
void rtcSetUserData (RTCScene scene, unsigned geomID, void* ptr);
void* rtcGetUserData (RTCScene scene, unsigned geomID);
```

The user data pointer of some user defined geometry get additionally passed to the intersect and occluded callback functions of that user geometry. Further, the user data pointer is also passed to intersection filter callback functions attached to some geometry.

## 3.7 Geometry Mask

A 32 bit geometry mask can be assigned to triangle meshes and hair geometries using the rtcSetMask call.

```
rtcSetMask(scene, geomID, mask);
```

Only if the bitwise and operation of this mask with the mask stored inside the ray is not 0, primitives of this geometry are hit by a ray. This feature can be used to disable selected triangle mesh or hair geometries for specifically tagged rays, e.g. to disable shadow casting for some geometry. This API feature is disabled in Embree by default at compile time, and can be enabled in CMake through the RTCORE\_ENABLE\_RAY\_MASK parameter.

#### 3.8 Filter Functions

The API supports per geometry filter callback functions that are invoked for each intersection found during the rtcIntersect or rtcOccluded calls. The former ones are called intersection filter functions, the latter ones occlusion filter functions. The filter functions can be used to implement various useful features, such as accumulating opacity for transparent shadows, counting the number of surfaces along a ray, collecting all hits along a ray, etc. Filter functions can also be used to selectively reject hits to enable backface culling for some geometries. If the backfaces should be culled in general for all geometries then it is faster to enable RTCORE\_BACKFACE\_CULLING during compilation of Embree instead of using filter functions.

The filter functions provided by the user have to have the following signature:

The valid pointer points to a valid mask of the same format as expected as input by the ray query functions. The userPtr is a user pointer optionally set per geometry through the rtcSetUserData function. The ray passed to the filter function is the ray structure initially provided to the ray query function by the user. For that reason, it is safe to extend the ray by additional data and access this data inside the filter function (e.g. to accumulate opacity). All hit information inside the ray is valid. If the hit geometry is instanced, the instID member of the ray is valid and the ray origin, direction, and geometry normal visible through the ray are in object space. The filter function can reject a hit by setting the geomID member of the ray to RTC\_INVALID\_GEOMETRY\_ID, otherwise the hit is accepted. The filter function is not allowed to modify the ray input data (org, dir, tnear, tfar), but can modify the hit data of the ray (u, v, Ng, geomID, primID).

The intersection filter functions for different ray types are set for some geometry of a scene using the following API functions:

```
void rtcSetIntersectionFilterFunction (RTCScene, unsigned geomID, RTCFilterFunc );
void rtcSetIntersectionFilterFunction4 (RTCScene, unsigned geomID, RTCFilterFunc4 );
```

```
void rtcSetIntersectionFilterFunction8 (RTCScene, unsigned geomID, RTCFilterFunc8 );
void rtcSetIntersectionFilterFunction16(RTCScene, unsigned geomID, RTCFilterFunc16);
```

These functions are invoked during execution of the rtcIntersect type queries of the matching ray type. The occlusion filter functions are set using the following API functions:

```
void rtcSetOcclusionFilterFunction (RTCScene, unsigned geomID, RTCFilterFunc );
void rtcSetOcclusionFilterFunction4 (RTCScene, unsigned geomID, RTCFilterFunc4 );
void rtcSetOcclusionFilterFunction8 (RTCScene, unsigned geomID, RTCFilterFunc8 );
void rtcSetOcclusionFilterFunction16(RTCScene, unsigned geomID, RTCFilterFunc16);
```

See tutorial05 for an example of how to use the filter functions.

## 3.9 Displacement Mapping Functions

The API supports displacement mapping for subdivision meshes. A displacement function can be set for some subdivision mesh using the rtcSetDisplacement-Function API call.

```
void rtcSetDisplacementFunction(RTCScene, unsigned geomID, RTCDisplacementFunc, RTCBounds*);
```

A displacement function of NULL will delete an already set displacement function. The bounds parameter is optional. If NULL is passed as bounds, then the displacement shader will get evaluated during the build process to properly bound displaced geometry. If a pointer to some bounds of the displacement are passed, then the implementation can choose to use these bounds to bound displaced geometry. When bounds are specified, then these bounds have to be conservative and should be tight for best performance.

The displacement function has to have the following type:

The displacement function is called with the user data pointer of the geometry (ptr), the geometry ID (geomID) and primitive ID (primID) of a patch to displace. For this patch, a number N of points to displace are specified in a struct of array layout. For each point to displace the local patch UV coordinates (u and v arrays), the normalized geometry normal (nx, ny, and nz arrays), as well as world space position (px, py, and pz arrays) are provided. The task of the displacement function is to use this information and move the world space position inside the allowed specified bounds around the point.

All passed arrays are guaranteed to be 64 bytes aligned, and properly padded to make wide vector processing inside the displacement function possible.

The displacement mapping functions might get called during the rtcCommit call, or lazily during the rtcIntersect or rtcOccluded calls.

Also see tutorial09 for an example of how to use the displacement mapping functions.

## 3.10 Sharing Threads with Embree

Embree supports using the application threads when building internal data structures, by using the

void rtcCommitThread(RTCScene, unsigned threadIndex, unsigned threadCount);

API call to commit the scene. This function has to get called by all threads that want to cooperate in the scene commit. Each call is provided the scene to commit, the index of the calling thread in the range [0, threadCount-1], and the number of threads that will call into this commit operation for the scene. Multiple such scene commit operations can also be running at the same time, e.g. it is possible to commit many small scenes in parallel using one thread per commit operation. Subsequent commit operations for the same scene can use different number of threads or the Embree internal threads using the

void rtcCommitThread()

call.

## Chapter 4 Embree Tutorials

Embree comes with a set of tutorials aimed at helping users understand how Embree can be used and extended. All tutorials exist in an ISPC and C version to demonstrate the two versions of the API. Look for files named tutorialXX\_device.ispc for the ISPC implementation of the tutorial, and files named tutorialXX\_device.cpp for the single ray C++ version of the tutorial. To start the C++ version use the tutorialXX executables, to start the ISPC version use the tutorialXX\_ispc executables.

Under Linux Embree also comes with an ISPC version of all tutorials for the  $Intel^{\circledast}$  Xeon  $Phi^{\intercal M}$  coprocessor. The executables of this version of the tutorials are named tutorialXX\_xeonphi and only work if a Xeon Phi coprocessor is present in the system. The Xeon Phi version of the tutorials get started on the host CPU, just like all other tutorials, and will connect automatically to one installed Xeon Phi coprocessor in the system.

For all tutorials, you can select an initial camera using the -vp (camera position), -vi (camera look-at point), -vu (camera up vector), and -fov (vertical field of view) command line parameters:

```
./tutorial00 -vp 10 10 10 -vi 0 0 0
```

You can select the initial windows size using the -size command line parameter, or start the tutorials in fullscreen using the -fullscreen parameter:

```
./tutorial00 -size 1024 1024
./tutorial00 -fullscreen
```

Implementation specific parameters can be passed to the ray tracing core through the -rtcore command line parameter, e.g.:

```
./tutorial00 -rtcore verbose=2,threads=1,accel=bvh4.triangle1
```

The navigation in the interactive display mode follows the camera orbit model, where the camera revolves around the current center of interest. With the left mouse button you can rotate around the center of interest (the point initially set with -vi). Holding Control pressed while clicking the left mouse button rotates the camera around its location. You can also use the arrow keys for navigation.

You can use the following keys:

- F1 Default shading
- F2 Gray EyeLight shading
- F3 Wireframe shading
- F4 UV Coordinate visualization
- F5 Geometry normal visualization

- F6 Geometry ID visualization
- F7 Geometry ID and Primitive ID visualization
- F8 Simple shading with 16 rays per pixel for benchmarking.
- F9 Switches to render cost visualization. Pressing again reduces brightness.
- F10 Switches to render cost visualization. Pressing again increases brightness.
- f Enters or leaves full screen mode.
- c Prints camera parameters.
- ESC Exists the tutorial.
- q Exists the tutorial.

#### 4.1 Tutorial00




Figure 4.1

This tutorial demonstrates the creation of a static cube and ground plane using triangle meshes. It also demonstrates the use of the rtcIntersect and rtcOccluded functions to render primary visibility and hard shadows. The cube sides are colored based on the ID of the hit primitive.

#### 4.2 Tutorial01




Figure 4.2

This tutorial demonstrates the creation of a dynamic scene, consisting of several deformed spheres. Half of the spheres use the RTC\_GEOMETRY\_DEFORMABLE flag, which allows Embree to use a refitting strategy for these spheres, the other half uses the RTC\_GEOMETRY\_DYNAMIC flag, causing a rebuild of their spatial data structure each frame. The spheres are colored based on the ID of the hit sphere geometry.

#### 4.3 Tutorial02




Figure 4.3

This tutorial shows the use of user defined geometry, to re-implement instancing and to add analytic spheres. A two level scene is created, with a triangle mesh as ground plane, and several user geometries, that instance other scenes with a small number of spheres of different kind. The spheres are colored using the instance ID and geometry ID of the hit sphere, to demonstrate how the same geometry, instanced in different ways can be distinguished.

#### 4.4 Tutorial03



Figure 4.4

This tutorial demonstrates a simple OBJ viewer that traces primary visibility rays only. A scene consisting of multiple meshes is created, each mesh sharing the index and vertex buffer with the application. Demonstrated is also how to support additional per vertex data, such as shading normals.

You need to specify an OBJ file at the command line for this tutorial to work:

./tutorial03 -i model.obj

#### 4.5 Tutorial04

This tutorial demonstrates the in-build instancing feature of Embree, by instancing a number of other scenes build from triangulated spheres. The spheres are again colored using the instance ID and geometry ID of the hit sphere, to demonstrate how the same geometry, instanced in different ways can be distinguished.




Figure 4.5

#### 4.6 Tutorial05




Figure 4.6

This tutorial demonstrates the use of filter callback functions to efficiently implement transparent objects. The filter function used for primary rays, lets the ray pass through the geometry if it is entirely transparent. Otherwise the shading loop handles the transparency properly, by potentially shooting secondary rays. The filter function used for shadow rays accumulates the transparency of all surfaces along the ray, and terminates traversal if an opaque occluder is hit.

#### 4.7 Tutorial06



Figure 4.7

This tutorial is a simple path tracer, building on tutorial03.

You need to specify an OBJ file and light source at the command line for this tutorial to work:

./tutorial06 -i model.obj -ambientlight 1 1 1

#### 4.8 Tutorial07



Figure 4.8

This tutorial demonstrates the use of the hair geometry to render a hairball.

#### 4.9 Tutorial08




Figure 4.9

This tutorial demonstrates the use of Catmull Clark subdivision surfaces. Per default the edge tessellation level is set adaptively based on the distance to the camera origin. Embree currently supports three different modes for efficiently handling subdivision surfaces in various rendering scenarios. These three modes can be selected at the command line, e.g. -lazy builds internal per subdivision patch data structures on demand, -cache uses a small (per thread) tessellation cache for caching per patch data, and -pregenerate to generate and store most per patch data during the initial build process. The cache mode is most effective for coherent rays while providing a fixed memory footprint. The pregenerate modes is most effective for incoherent ray distributions while requiring more memory. The lazy mode works similar to the pregenerate mode but provides a middle ground in terms of memory consumption as it only builds and stores data only when the corresponding patch is accessed during the ray traversal. The cache mode is currently a bit more efficient at handling dynamic scenes where only the edge tessellation levels are changing per frame.

## **4.10 Tutorial09**



Figure 4.10

This tutorial demonstrates the use of Catmull Clark subdivision surfaces with procedural displacement mapping using a constant edge tessellation level.

### **4.11 Tutorial10**




Figure 4.11

This tutorial loads an .obj file and renders the mesh as a Catmull Clark subdivision surface object. The edge tessellation level is chosen adaptively based on the distance to the camera.