LattePanda 3 Delta Specification

Content	Specs.
Processor	Intel® Celeron® Processor N5105 (Frequency: 2.00GHz ~ 2.90GHz)
Graphics	Intel® UHD Graphics (Frequency: 450MHz ~ 800MHz)
Memory	Samsung 8GB LPDDR4 2933MHz
Storage	SanDisk 64GB eMMC V5.1
Wireless	Intel® AX201 WiFi 6 (802.11ax), 2.4GHz and 5GHz (160MHz) Supported; Bluetooth® 5.2
Ethernet	Intel® I211-AT / I225-V PCIe Gigabit LAN, Wake-On-LAN Supported
Video	HDMI 2.0b; DP 1.4 via USB Type-C; eDP 30Pin (two lanes)
Audio	Microphone + Headphone Combo Connector
USB	1x USB 3.2 gen 2 Type-A; 2x USB 3.2 gen1 Type-A; 1x USB 2.0 Type-C

Content	Specs.
Expansion Slots	M.2 Key B(2242/2252/2280): SATA III, USB2.0, USB3.0, SIM; M.2 Key M(2280): PCIe 3.0 x2; Micro-SD + Micro-SIM Combo Card Connector
Coprocessor	Microchip® ATmega32U4-MU
GPIO Female Headers	Atmega32U4 Pinout; BIOS Flash Pinout; 5V & 3.3V Output; 12V DC Input; USB 2.0; RS232; Audio; Status Control & Indication
TPM	Built-in TPM (2.0)
BIOS Function	Auto Power On, Watchdog Timer, Serial Port Redirection, etc.
Power	PH2.0-4Pin DC Input: 12V; USB Type-C PD Input: 15V DC
RTC	CR927 3V
Dimension	125mm x 78mm x16mm
Default Built-in OS	Windows 10 Pro 21H2; Windows 10 IoT Enterprise 2021 LTSC
Compatible OS	Windows 10, Windows 11, Ubuntu
Environment	Operating Temperature: 0~60°C; Relative Humidity:

Content	**Specs.**
	0%~80%
Certification	CE, FCC, KC, RoHS