RK3308 Key Interface Introduction

Document ID: RK-KF-YF-318

Release Version: V1.0.1

Date: 2020-03-02

Security Level: □Top-Secret □Secret □Internal ■Public

DISCLAIMER

THIS DOCUMENT IS PROVIDED "AS IS". FUZHOU ROCKCHIP ELECTRONICS CO., LTD. ("ROCKCHIP")DOES NOT PROVIDE ANY WARRANTY OF ANY KIND, EXPRESSED, IMPLIED OR OTHERWISE, WITH RESPECT TO THE ACCURACY, RELIABILITY, COMPLETENESS, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR NON-INFRINGEMENT OF ANY REPRESENTATION, INFORMATION AND CONTENT IN THIS DOCUMENT. THIS DOCUMENT IS FOR REFERENCE ONLY. THIS DOCUMENT MAY BE UPDATED OR CHANGED WITHOUT ANY NOTICE AT ANY TIME DUE TO THE UPGRADES OF THE PRODUCT OR ANY OTHER REASONS.

Trademark Statement

"Rockchip", "瑞芯微", "瑞芯" shall be Rockchip's registered trademarks and owned by Rockchip. All the other trademarks or registered trademarks mentioned in this document shall be owned by their respective owners.

All rights reserved. ©2019. Fuzhou Rockchip Electronics Co., Ltd.

Beyond the scope of fair use, neither any entity nor individual shall extract, copy, or distribute this document in any form in whole or in part without the written approval of Rockchip.

Fuzhou Rockchip Electronics Co., Ltd.

No.18 Building, A District, No.89, software Boulevard Fuzhou, Fujian, PRC

Website: www.rock-chips.com

Customer service Tel: +86-4007-700-590

Customer service Fax: +86-591-83951833

Customer service e-Mail: fae@rock-chips.com

Preface

Overview

This document describes the interfaces in RK3308 DeviceIo library.

Chipset

RK3308

Intended Audience

This document (this guide) is intended primarily for the following engineers:

Field Application Engineer

Software Development Engineer

Revision History

Date	Revision No.	Author	Revision History
2019-3-29	V1.0.0	Jacky Ge	Initial version
2020-03-02	V1.0.1	Ruby Zhang	Update the format and the name of the document

Contents

RK3308 Key Interface Introduction

Preface

Contents

- 1. Overview
- 2. Interface Introduction
- 3. Application Example

1. Overview

This code module is integrated in the libDeviceIo.so dynamic library, based on the input_event input subsystem, including short press, long press, and combination key common requirements which are packaged to facilitate development.

2. Interface Introduction

• Callback function definition

It is the most basic callback, which will callback up and down events for each key press:

```
1 | typedef int (*RK_input_callback)(const int key_code, const int key_value);
```

It is a processed callback, and only be called back once by a short press event:

```
1 | typedef int (*RK_input_press_callback)(const int key_code);
```

Long press event callback interface:

```
typedef int (*RK_input_long_press_callback) (const int key_code, const
uint32_t time);
```

Heartbeat long press event callback interface(That is, if the button is kept pressed, the callback interface will be callback regularly after meeting the long-press condition.)

```
1 typedef int (*RK_input_long_press_hb_callback)(const int key_code, const int
times);
```

Combination key callback interface:

```
typedef int (*RK_input_compose_press_callback) (const char* compose, const
uint32_t time);
```

Transaction key callback interface:

```
typedef int (*RK_input_transaction_press_callback) (const char* trans, const
uint32_t time);
```

Multiple press callback interface:

```
1 typedef int (*RK_input_multiple_press_callback)(const int key_code, const int times);
```

Key module initialization interface, which need to be assigned a basic RK_input_callback function:

```
1 | int RK_input_init(RK_input_callback input_callback_cb)
```

Register a key press event callback and triggered by single click:

```
1 | int RK_input_register_press_callback(RK_input_press_callback cb)
```

Register a long press event with the time of "time ms" for key_code:

```
int RK_input_register_long_press_callback(RK_input_long_press_callback cb,
const uint32_t time, const int key_code)
```

Register a "hb" long press event for key_code key, triggered every "time ms":

```
int RK_input_register_long_press_hb_callback(RK_input_long_press_hb_callback
cb, const uint32_t time, const int key_code)
```

Register times multi-press events for key_code key (that is, times of pressing key_code, the time difference between each two press should not exceed 500ms):

```
1 int
    RK_input_register_multiple_press_callback(RK_input_multiple_press_callback
    cb, const int key_code, const int times)`
```

Register combination events for key_code key set, triggered when key_code key set is pressed at the same time for time ms:

```
int RK_input_register_compose_press_callback(RK_input_compose_press_callback
cb, const uint32_t time, const int key_code, ...)
```

Register transaction events for the collection of key_code, which is triggered when the collection of key_code pressed in order:

```
int
    RK_input_register_transaction_press_callback(RK_input_transaction_press_callb
    ack cb, const uint32_t time, int key_code, ...)
```

Key module exits and releases related resources:

```
1 | int RK_input_exit(void)`
```

3. Application Example

```
#include <stdio.h>
   #include <string.h>
   #include <unistd.h>
   #include <linux/input.h>
   #include <DeviceIo/Rk key.h>
7
   static int RK input callback(const int key code, const int key value)
8
       printf("_RK_input_callback key_code:%d; key_value:%d\n", key_code,
    key_value);
       return 0;
11
12
    static int _RK_input_press_callback(const int key_code)
13
14
      printf(" RK input press callback key code:%d;\n", key code);
16
      return 0;
17
18
19
   static int RK input long press callback(const int key code, const uint32 t
    time)
20
    printf("_RK_input_long_press_callback key_code:%d; time:%lu\n",
    key code, time);
22
      return 0;
24
25 static int _RK_input_long_press_hb_callback(const int key_code, const int
    times)
26
      printf("_RK_input_long_press_hb_callback key_code:%d; times:%d\n",
    key code, times);
     return 0;
28
29
   static int _RK_input_multiple_press_callback(const int key_code, const int
    times)
      printf(" RK input multiple press callback key code:%d; times:%d\n",
    key code, times);
      return 0;
34
    static int RK input transaction press callback(const char* trans, const
    uint32 t time)
38
    printf(" RK input transaction press callback trans:%s; time:%lu\n",
39
    trans, time);
40
     return 0;
41
42
43 static int _RK_input_compose_press_callback(const char* compose, const
    uint32 t time)
```

```
printf(" RK input compose press callback compose:%s; time:%lu\n",
    compose, time);
       return 0;
46
47
   int main(int argc, char **argv)
49
51
       // Initialize the input module
52
      RK input init( RK input callback);
       // Register single press callback
54
      RK input register press callback( RK input press callback);
55
       // Register 5000ms long press event of KEY VOLUMEUP key
56
       RK_input_register_long_press_callback(_RK_input_long_press_callback,
    5000, KEY VOLUMEUP);
       // Register a hb long-press event of the KEY VOLUMEDOWN button,
    triggering hb every 500ms
58
    RK_input_register_long_press_hb_callback(_RK_input_long_press_hb_callback,
    500, KEY VOLUMEDOWN);
        // Register KEY POWER double-press event
59
    RK_input_register_multiple_press_callback(_RK_input_multiple_press_callback,
    KEY POWER, 2);
      // Register KEY VOLUMEUP->KEY VOLUMEUP->KEY VOLUMEDOWN->KEY VOLUMEDOWN
61
    transaction event
62
    RK_input_register_transaction_press_callback(_RK_input_transaction_press_cal
    lback, 2000, 4, KEY VOLUMEUP, KEY VOLUMEUP, KEY VOLUMEDOWN, KEY VOLUMEDOWN);
        // Register KEY VOLUMEUP + KEY VOLUMEDOWN 5000ms key combination
63
    RK_input_register_compose_press_callback(_RK_input_compose_press_callback,
    5000, 2, KEY_VOLUMEUP, KEY_VOLUMEDOWN);
65
66
67
       for (;;);
        RK input exit();
69
        return 0;
71
```