

Y.A.S.K. Yet Another Stencil Kernel

Chuck Yount, Principal Engineer Intel Corporation

June 23, 2016

chuck.yount@intel.com

Legal Disclaimer & Optimization Notice

INFORMATION IN THIS DOCUMENT IS PROVIDED "AS IS". NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. INTEL ASSUMES NO LIABILITY WHATSOEVER AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO THIS INFORMATION INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products.

Optimization Notice

Intel's compilers may or may not optimize to the same degree for non-Intel microprocessors for optimizations that are not unique to Intel microprocessors. These optimizations include SSE2, SSE3, and SSSE3 instruction sets and other optimizations. Intel does not guarantee the availability, functionality, or effectiveness of any optimization on microprocessors not manufactured by Intel. Microprocessor-dependent optimizations in this product are intended for use with Intel microprocessors. Certain optimizations not specific to Intel microarchitecture are reserved for Intel microprocessors. Please refer to the applicable product User and Reference Guides for more information regarding the specific instruction sets covered by this notice.

Notice revision #20110804

Outline

Overview

YASK Features

- Vector folding and the fold builder
- Loop-code generator
- Memory accessor
- Debug output

Using YASK

- Build and test
- Output
- Use model
- Run-time options: hierarchy sizes, wave-front blocking, MPI
- Stencil, vectorization, loop, and advanced customization
- Collaboration



Overview

YASK: Yet Another Stencil Kernel

 Goal: facilitate exploration of the stencil-performance design space for Intel® Xeon Phi[™] coprocessor or any Intel® Xeon[™] processor supporting the AVX, AVX2, or AVX-512 instruction sets


Features

- Supports trade-off studies for coding options for
 - Vector-folding
 - Cache blocking
 - Memory layout
 - Loop construction
 - Temporal wave-front blocking
 - And more
- Is a collection of C++ code, code-generators and other scripts
- Focused on single-node OpenMP optimizations
 - Minimal MPI enabled at this time



YASK Features

High-level components



Vector-folding introduction

Concept

- Store small 2D or 3D block of data into each vector
- Pros: reduces memory BW requirements compared to traditional 1D in-line vectors
- Cons: requires data pre-conditioning (element rearranging) and additional shift and blend operations preceding SIMD arithmetic operations

Results


- Significant speedup shown on Intel® Xeon Phi[™] Coprocessor
- Combining with loop tiling enables even more speedup

For more information

Refer to paper on <u>Vector Folding from HPCC 2015</u>



Traditional in-line 1D vectorization




*Assuming cache line size = vector size.




Reduce BW via vector folding

25-point 3D stencil input vectorized using 8-element vectors, each containing a 4x2 grid in the x-y plane









One 8-element (4x2) vector output per iteration

 Need to read only 7 new cache lines for each iteration (vectors overlap in x-y dimensions within an iteration and in z dimension between iterations)

Steady-state memory BW = 7
new cache lines input to
calculate each vector of output:
2.4x lower than in-line

Fold-builder code generator

Goal: automate the tedious and error-prone process of creating high-performance stencil code

Input

- Inherit from a C++ abstract 'StencilBase' class to create a new stencil type
- Define the grid(s) to be used and the names of their dimensions, e.g., "t", "x", "y", "z"
- · Implement the 'define' method to define how one point in each grid is calculated from others
- Use loops, functions for coefficients, recursion, etc.

Process

- Compile code into fold-builder executable
- Run executable, specifying any stencil parameters (e.g., order), target architecture, etc.
- Code generator evaluates the 'define' method to create an abstract syntax tree (AST)
- AST is traversed, and optimized code is output

Output

- Efficient function to calculate stencil
 - Unrolled loops, intrinsics to construct unaligned vectors of points, etc.
 - Calls to memory accessor object
- Functions for prefetching to L1 and L2



Example input stencil code

```
class Iso3dfdStencil : public StencilOrderBase {
INIT GRID 4D (pressure, t, x, y, z), \leftarrow
 INIT GRID 3D(vel, x, y, z)
virtual void define(const IntTuple& offsets) {
        // start with center value multiplied by coeff T
        GridValue v = pressure(t, x, y, z) * coeff(0);
        // add values from x, y, and z axes multiplied by the
        // coeff for the given radius.
        for (int r = 1; r' <= order/2; r++) {
            // Add values from axes at radius r.
            \forall += (
                  // x-axis.
                  pressure(t, x-r, y, z) +
                  pressure(t, x+r, y, z) +
                  // y-axis.
                  pressure(t, x, y-r, z) +
                  pressure(t, x, y+r, z) +
                  // z-axis.
                  pressure(t, x, y, z-r) +
                  pressure(t, x, y, z+r)
                  ) * coeff(r);
        // finish equation, including t-1 and velocity components.
        v = (2.0 * pressure(t, x, y, z))
            - pressure (t-1, x, y, \bar{z}) // subtract pressure from t-1.
            + (v * vel(x, y, z));
                                        // add y velocity.
        // define the value at t+1 to be equivalent to v.
        pressure(t+1, x, y, z) == v;
```

Declare 2 grids: 4D "pressure" and 3D "vel"

Write function to define equation for "pressure" update

The final equation uses "==" in a declarative (not imperative) style

Example output stencil code


- The above class was generated from the code on the previous slide using this command: ./foldBuilder -st iso3dfd -or 16 -fold x=4,y=4,z=1 -p512
 - See the foldBuilder help message for information on the options
- The above code is a small sample from over 2500 lines of generated code
 - The 'calc_vector' method, when inlined into an inner loop, compiles to ~110 instrs, including 5 SIMD FMAs, 47 SIMD add/sub/muls, 12 VALIGND, and 12 VPERMI2D instrs
 - It also contains methods for scalar reference and prefetch

Loop-code generator

Script that generates code for nested loops

- Input: Very simple DSL (domain-specific language)
 - omp loop(y) { loop(x, z) { calc(stencil); } }
 - Can easily change loop types, index ordering
- Output: C++ code to be included in function bodies
 - Loops annotated with OMP as requested
 - Inner loop might generate several loops, e.g.,
 - Prefetch L2
 - Prefetch L1
 - Calculate stencil and prefetch L2 and L1
 - Calculate and prefetch L1 only to avoid over-prefetching L2

Loops applied at multiple block levels



Memory accessor

- C++ classes to allocate and access 3D & 4D matrices of vectors of floats or doubles
 - Construction specifies 'n, x, y, z' dimensions and padding sizes;
 padding includes halos (add 'n' for 4D)
 - Read and write access via methods: per vector for highest speed; per element for scalar code.
- Actual memory layout is encapsulated and defined via inheritance
 - Map 3D or 4D indices to 1-D mem address
 - 24 simple permutations of minor-to-major ordering
 - More complex mappings possible, e.g., tiling, space-filling curves
 - 'n' dimension is used for time and/or grid indices
- Uses concrete inheritance to allow inlining
 - Gives compiler full access to memory-layout formula
 - Allows common sub-expression elimination and other optimizations



Debug features

Can enable or disable various output by setting macros and rebuilding, e.g.,

- TRACE: print each stencil calculation
- TRACE_MEM: print each matrix read, write, prefetch, eviction
- TRACE_INTRINSICS: print before-and-after each permutation

Built-in memory-access tracker

- Models an infinite L1 or L2 cache
- Tracks reads, writes, prefetches, evictions
- Reports any un-prefetched read or un-read prefetch
- Reports summary stats
- Very useful for debugging prefetch code



Example cache-model output

```
modeling cache...
cache L2: redundant prefetch of 0x2aaabfa45a40 at line 193 after a read at line 85.
cache L2: redundant prefetch of 0x2aaabfa45a80 at line 193 after a read at line 85.
cache L2: redundant prefetch of 0x2aaabfa45a40 at line 195 after a prefetch at line 193.
cache L2: redundant prefetch of 0x2aaabfa45a40 at line 196 after a prefetch at line 195.
done modeling cache...
cache L2: read of 0x2aaabf9c3240 from line 85 without any eviction.
cache L2: read of 0x2aaabf9c3280 from line 85 without any eviction.
cache L2: prefetch of 0x2aaabfa53b00 from line 318 without any read.
cache L2: prefetch of 0x2aaabfa53b40 from line 318 without any read.
cache L2 stats:
 cur size = 324714 lines (19.8190 MB).
max size = 324714 lines (19.8190 MB).
 ave size = 185126 lines (11.2992 \text{ MB}).
 num reads = 722400.
  num reads of missing lines = 0.
  num lines read but never evicted = 321700.
 num prefetches = 1458800.
  num prefetches of lines never subsequently read = 3014.
  num prefetches of lines already in cache = 404686.
 num evictitions = 0.
  num evictions to non-existant lines = 0.
 num prefetches into L1 = 729400.
  num prefetches into L1 of missing lines = 0.
```

Using YASK

Initial build and test

Install

- Download the code from the 'GIT REPO' link at https://01.org/yask
- Install all the prerequisites from the README file

Build and run the default test program

- Type 'make –arch name –stencil name' per the README file
- Run the program using the stencil-run.sh script
 - Run natively on Xeon™ or Xeon Phi™ processors
 - Use the -mic option to run on a Xeon Phi[™] coprocessor
 - Run under SDE to emulate hardware you don't have
- If it doesn't build and/or run, check the prerequisites

Typical run and output

Settings are printed

- Sizes (spatial and temporal): problem, region, block, cluster, and vector
- Stencil shape and order
- Other miscellaneous compile-time and run-time settings

A number of trials (default=3) is run

- Time and throughput (points per sec) are printed
- FP-rate is estimated based on number of FP ops in original scalar spec
- Best result across the trials is re-printed

Validation

- If the '-v' option was used, a non-vectorized, non-tiled version of the code is run, the results are compared, and 'PASSED' or 'FAILED' is printed
- Validation is slow; run with a small problem size!



Use model

Review

- YASK is a tool for exploring the stencil design space
- It is not a library

Typical usage model

- Identify stencil(s) used in your application
- Use existing stencil(s) in YASK or write your own
- Use YASK to find well-performing parameters
- Integrate the stencil code back into your application

Common run-time options

Settings controlled from the 'stencil-run.sh' script

- Binary selection via 'arch' option
- OpenMP affinity
- Which Xeon Phi coprocessor or other host to use
- Run with '-h' option to get help

Settings controlled from the 'stencil.arch.exe' binary (passed through from the stencil-run.sh script)

- Spatial/temporal rank-domain size (overall problem if not using MPI): -d*/-dt
- Spatial/temporal region size (used for temporal wave-front blocking): -r*/-rt
- Cache-block size: -b*
- Padding: -p*
 - Used to fine-tune data alignment across rows and columns
 - The specified value is added to the halo size
- Number of trials: -t
- Validation: -v
- Run with '-h' option to get help



Enabling temporal wave-front blocking

Purpose

 The temporal blocking in YASK is designed to exploit large shared caches, e.g., when using the Intel® Xeon Phi[™] processor in MCDRAM cache mode

Usage

- Temporal wave-front blocking is done using the "regions" level of the hierarchy shown earlier
 - Spatial blocks within each region are evaluated in parallel using OpenMP
 - The time slices within each region are evaluated sequentially to reuse memory
 - Regions are evaluated sequentially to increase shared-cache locality
- Executable run-time options
 - rt <n> sets the number of time slices in each region
 - r* <n> sets the spatial size of each region
 - Example: stencil-run.sh -d 1920 -dt 50 -r 768 -rt 25
 - Note: the default setting of -rt is one (1), and the default setting of -r is zero (0), which means the region size is the same as the rank size.



Enabling MPI

Purpose

- The current MPI implementation in YASK is minimal: it is only applied in the x-dimension
- It was targeted for one multi-socket node or a very small number of nodes, not large clusters

Usage

- Compile with MPI enabled using "make mpi=1 ..."
- Run "stencil-run.sh -ranks <n>" to control the number of ranks used
- Note: the -d* options control the rank size (weak scaling), so divide the x-size by the number of ranks to keep the problem size constant (strong scaling)

Stencil customization

Stencil Type

- Use the 'stencil=stencil-name' argument to the make command to select a stencil
 - The stencil-name string is passed to the foldBuilder tool
- Current provided stencils
 - 'iso3dfd': an isotropic acoustic wave equation
 - '3axis', '9axis', '3plane', and 'cube': common 3D symmetric shapes (defined in the <u>vector-folding paper</u>)
 - 'ave': the simple 27-pt stencil from the miniGhost benchmark
 - 'awp': a simplified version of <u>AWP-ODC</u> earthquake simulation stencils
- Write your own by modifying code in src/foldBuilder
 - Implement the StencilBase interface using the stencils/*Stencil.hpp files as examples
 - Modify main.cpp to include your new .hpp file

Stencil customization (cont.)

Stencil size

- Use the 'order=n' argument to the make command
 - The n value is passed to the 'foldBuilder' tool
 - Default=16; 2 for 'ave' stencil; ignored for 'awp'
 - For the current example stencils, any even value of n is allowed
 - Also controls size of halos automatically allocated by kernel
- Write your own by modifying code in src/foldBuilder
 - Follow the existing examples to pass the 'order' parameter to your stencil code if applicable

Other parameters

 If you're developing your own stencil, you can add more parameters similar to the 'order' one

Stencil customization (cont.)

Advanced

- The provided stencils assume uniformity across the entire 3D grid
 - The 'foldBuilder' tool evaluates the stencil code only from the origin to the extent of a vector
- Some stencil applications require special code at boundaries or other conditions
 - To achieve this using the 'foldBuilder' tool, you can provide a parameter to distinguish each condition, e.g., top boundary, bottom boundary, etc.
 - Then, you would need to generate separate code for each condition
 - For even more complex stencils, you may need to study and modify the 'foldBuilder' code beyond adding new stencils and command-line parameters
 - Another (often simpler) way to handle boundary code is to write it in scalar code that is run after the generated vector code; this would be added to your final application, but not necessarily in the YASK kernel

Vector-folding customization

Vector fold

- Use the fold='x=n,y=n,z=n' argument to the make command to control how much vectorization is done in each dimension
 - The values are passed to the 'foldBuilder' tool
 - Example: make fold='x=1,y=2,z=8' generates code using a 1x2x8 fold
 - Make sure the product of the fold lengths equals the vector size of the target architecture and FP precision (single or double)
- See the <u>vector-folding paper</u> for a detailed discussion

Vector cluster

- Use the cluster='x=n,y=n,z=n' argument to the make command to control how many vectors are calculated and output in each 'calc' method
 - The values are passed to the 'foldBuilder' tool
 - The default is 1x1x1, or one HW vector
 - This essentially implements loop unrolling in multiple dimensions



Loop-structure customization

The 'gen-loops.pl' script creates the loop-control code

- There are 3 loop-control codes
 - Outer' loops break the whole problem into OpenMP regions (typically, only one OpenMP region is used)
 - 'Region' loops break each OpenMP region into cache blocks
 - Block' loops iterate over each vector cluster in a cache block

Usage

- See the Makefile for default invocations or run 'make -n'
- Run './gen-loops.pl' without any parameters to get help on more options: index ordering, OpenMP scheduling, etc.
- Run the script before the make command or specify the *LOOP_ARGS variables in the make command to override



Misc. advanced customization

More compile-time options to the make command

- Use 'crew=n' to enable (n=1) or disable (n=0) Intel Crew threading
 - If you get a link-time error that 'kmp*' symbols cannot be found, your compiler does not support crew; use 'crew=0'
- Use 'real_bytes=n' to set the size of a float: n=4 for single-precision or n=8 for double-precision (default=4; 8 for 'ave' stencil)
- Use `EXTRA_MACROS='macro-settings'' set other CPP macros
 - 'PFDL1=n1 PFDL2=n2' to change the prefetch distances; only used in the prefetch code generated from 'gen-loops.pl', not in compiler-generated prefetch code
 - Example: 'make MACROS='PFDL2=15"
 - See *.hpp for macro definitions
- Run 'make settings' to see other make variables

Collaboration

Use the blog at https://01.org/yask to ask and/or answer questions

Submit useful changes for review via github

Contact the author of this presentation for further collaboration opportunities

