FilterPro Design Report
Schematic

Design Name: Lowpass, Multiple Feedback, Butterworth **Part:** Ideal Opamp **Order:** 4 **Stages:** 2
Gain: 4.5 V/V (13.0616267406625 dB) **Allowable PassBand Ripple:** 1 dB **Passband Frequency:** 500 Hz
Corner Frequency Attenuation: 10.062 dB



Filter Stage:	1
Passband Gain(Ao) :	2.121
Cutoff Frequency(fn):	500 Hz
QualityFactor (Q):	0.54
Filter Response:	Butterworth
Circuit Topology:	MultipleFeedback
Min GBW reqd.:	57.267 kHz

Filter Stage:	2
Passband Gain(Ao) :	2.121
Cutoff Frequency(fn):	500 Hz
QualityFactor (Q):	1.31
Filter Response:	Butterworth
Circuit Topology:	MultipleFeedback
Min GBW reqd.:	138.9255 kHz

FilterPro Design Report
Frequency and Phase Responses

Design Name: Lowpass, Multiple Feedback, Butterworth **Part:** Ideal Opamp **Order:** 4 **Stages:** 2
Gain: 4.5 V/V (13.0616267406625 dB) **Allowable PassBand Ripple:** 1 dB **Passband Frequency:** 500 Hz
Corner Frequency Attenuation: 10.062 dB





FilterPro Design Report
Bill of Materials

Design Name: Lowpass, Multiple Feedback, Butterworth **Part:** Ideal Opamp **Order:** 4 **Stages:** 2
Gain: 4.5 V/V (13.0616267406625 dB) **Allowable PassBand Ripple:** 1 dB **Passband Frequency:** 500 Hz
Corner Frequency Attenuation: 10.062 dB

Element ID	Quantity	Part Number	Value	Tolerance	Description	Manufacturer
R1 (Stage 1)	1	Standard	1.39KΩ	Exact: 0%	Resistor	
R2 (Stage 1)	1	Standard	2.94KΩ	Exact: 0%	Resistor	
R3 (Stage 1)	1	Standard	942.3Ω	Exact: 0%	Resistor	
C1 (Stage 1)	1	Standard	100nF	Exact: 0%	Capacitor	
C2 (Stage 1)	1	Standard	365.63nF	Exact: 0%	Capacitor	
OpAmp (Stage 1)	1	Standard			Ideal OpAmp	
R1 (Stage 2)	1	Standard	574.3Ω	Exact: 0%	Resistor	
R2 (Stage 2)	1	Standard	1.22KΩ	Exact: 0%	Resistor	
R3 (Stage 2)	1	Standard	390.3Ω	Exact: 0%	Resistor	
C1 (Stage 2)	1	Standard	100nF	Exact: 0%	Capacitor	
C2 (Stage 2)	1	Standard	2.13uF	Exact: 0%	Capacitor	
OpAmp (Stage 2)	1	Standard			Ideal OpAmp	

FilterPro Design Report
Design Notes

Design Name: Lowpass, Multiple Feedback, Butterworth **Part:** Ideal Opamp **Order:** 4 **Stages:** 2
Gain: 4.5 V/V (13.0616267406625 dB) **Allowable PassBand Ripple:** 1 dB **Passband Frequency:** 500 Hz
Corner Frequency Attenuation: 10.062 dB