

Lab 1

Data Structures C++ for C Coders

한동대학교 김영섭교수
idebtor@gmail.com

C vs C++
const
cout
new & delete
reference

Lab 1: Convert a C program to C++

```
#include <stdio.h>
#define N 40
void sum(int d[], int n, int* p) {
    *p = 0;
    for(int i = 0; i < n; ++i)
        *p = *p + d[i];
}

int main() {
    int total = 0;
    int data[N];
    for(int i = 0; i < N; ++i) data[i] = i;
    sum(data, N, &total);
    printf("total is %d\n", total);
    return 0;
}
```

Use a reference operator, but not a pointer.
Use const, not but #define.
Use new and delete operators.
Use cout instead of printf().
Use namespace std.

Lab 1: Convert a C program to C++

```
#include <stdio.h>
#define N 40
void sum(int d[], int n, int* p) {
    *p = 0;
    for(int i = 0; i < n; ++i)
        *p = *p + d[i];
}

int main() {
    int total = 0;
    int data[N];
    for(int i = 0; i < N; ++i) data[i] = i;
    sum(data, N, &total);
    printf("total is %d\n", total);
    return 0;
}
```

Lab 1

Data Structures C++ for C Coders

한동대학교 김영섭교수
idebtor@gmail.com

C vs C++
const
cout
new & delete
reference