

ASSIGNMENT-5

DBMS LAB

Subhajit Samanta

2020CSB046

- CREATION OF TABLES:

Creation of Customer Table:

```
CREATE TABLE Customer
(cust_id int(10) PRIMARY KEY CHECK(cust_id BETWEEN 100 AND 10000),
annual_revenue int(10),
cust_type varchar(30) CHECK(cust_type IN
('MANUFACTURER','WHOLESALER','RETAILER')));
```

Inserting Values in Customer Table:

```
INSERT into Customer
values
(103,150000,'RETAILER','Akash'),
(104,200000,'RETAILER','Sai'),
(105,400000,'RETAILER','Prasad'),
(107,275000,'WHOLESALER','Subhajit'),
(108,800000,'MANUFACTURER','Anubhav'),
(109,250000,'RETAILER','Tahha'),
(112,1000000,'MANUFACTURER','Vijay'),
(116,650000,'WHOLESALER','Vicky'),
(118,600000,'WHOLESALER','Pradip'),
(120,400000,'WHOLESALER','Ram');
```

Customer table after insertion of values:

```
mysql> select *
-> from Customer;
```

cust_id	annual_revenue	cust_type	cust_name
103	150000	RETAILER	Akash
104	200000	RETAILER	Sai
105	400000	RETAILER	Prasad
107	275000	WHOLESALER	Subhajit
108	800000	MANUFACTURER	Anubhav
109	250000	RETAILER	Tahha
112	1000000	MANUFACTURER	Vijay
116	650000	WHOLESALER	Vicky
118	600000	WHOLESALER	Pradip
120	400000	WHOLESALER	Ram

Creation of Truck table:

```
CREATE TABLE Truck  
(truck_no int(10) PRIMARY KEY,  
driver_name varchar(30));
```

Inserting values in Truck table:

```
INSERT into Truck  
values  
(1, 'IQBAL'),  
(2, 'RAHIM'),  
(3, 'RAM'),  
(4, 'MADAN'),  
(5, 'SURYA'),  
(6, 'MOHAN'),  
(7, 'MITHUN');
```

Truck table after insertion of values:

```
mysql> select *  
-> from Truck;
```

truck_no	driver_name
1	IQBAL
2	RAHIM
3	RAM
4	MADAN
5	SURYA
6	MOHAN
7	MITHUN

Creation of table City:

```
CREATE TABLE City
(city_name varchar(30) PRIMARY KEY,
population int(20));
```

Inserting values in table City:

```
INSERT into City
values
('Kolkata',55000000),
('Chennai',60000000),
('Mumbai',80000000),
('Delhi',70000000),
('Pune',10000000),
('Medinipur',600000);
```

City table after insertion of values:

```
mysql> select *
-> from City;
```

city_name	population
Chennai	60000000
Delhi	70000000
Kolkata	55000000
Medinipur	600000
Mumbai	80000000
Pune	10000000

Creation of table Shipment:

```
CREATE TABLE Shipment
(shipment_no int(10),
cust_id int(10),
weight int(10) CHECK(weight<1000),
truck_no int(10),
destination varchar(30),
ship_date date,
PRIMARY KEY(shipment_no,cust_id),
constraint cust_id foreign key(cust_id) references Customer(cust_id) on delete
cascade,
constraint truck_no foreign key(truck_no) references Truck(truck_no) on delete
set null,
constraint destination foreign key(destination) references City(city_name) on
delete cascade);
```

Inserting values in Shipment:

```
INSERT into Shipment
values
(100,103,220,2,'Kolkata','2021-12-31'),
(100,104,210,4,'Chennai','2021-12-30'),
(100,105,200,5,'Kolkata','2021-12-29'),
(101,105,400,5,'Chennai','2021-12-28'),
(101,107,50,7,'Mumbai','2021-12-27'),
(102,105,101,5,'Mumbai','2021-12-26'),
(102,108,66,6,'Kolkata','2022-12-25'),
(102,109,202,7,'Chennai','2022-12-24'),
(102,112,350,1,'Delhi','2022-12-23'),
(103,116,320,1,'Medinipur','2022-12-22'),
(105,118,460,2,'Pune','2022-12-21'),
(105,120,60,6,'Chennai','2022-12-20'),
(106,105,70,5,'Delhi','2022-12-19'),
(107,105,100,5,'Medinipur','2022-12-18'),
(109,105,70,5,'Pune','2022-12-17'),
(109,103,120,4,'Kolkata','2022-12-16');
```

Shipment table after insertion of values:

```
mysql> select *  
-> from Shipment;
```

shipment_no	cust_id	weight	truck_no	destination	ship_date
100	103	220	2	Kolkata	2021-12-31
100	104	210	4	Chennai	2021-12-30
100	105	200	5	Kolkata	2021-12-29
101	105	400	5	Chennai	2021-12-28
101	107	50	7	Mumbai	2021-12-27
102	105	101	5	Mumbai	2021-12-26
102	108	66	6	Kolkata	2022-12-25
102	109	202	7	Chennai	2022-12-24
102	112	350	1	Delhi	2022-12-23
103	116	320	1	Medinipur	2022-12-22
105	118	460	2	Pune	2022-12-21
105	120	60	6	Chennai	2022-12-20
106	105	70	5	Delhi	2022-12-19
107	105	100	5	Medinipur	2022-12-18
109	103	120	4	Kolkata	2022-12-16
109	105	70	5	Pune	2022-12-17

- QUERIES:

1. Give names of customer who have sent packages (shipments) to Kolkata, Chennai and Mumbai. (You have to solve this problem using set theoretic operation)

```
select cust_name from Customer
where cust_id in (select cust_id
from Shipment
where destination='Kolkata')
AND
cust_id in (select cust_id
from Shipment
where destination='Mumbai')
AND
cust_id in (select cust_id
from Shipment
where destination='Chennai');
```

```
mysql> select cust_name from Customer
-> where cust_id in (select cust_id
-> from Shipment
-> where destination='Kolkata')
-> AND
-> cust_id in (select cust_id
-> from Shipment
-> where destination='Mumbai')
-> AND
-> cust_id in (select cust_id
-> from Shipment
-> where destination='Chennai');
+-----+
| cust_name |
+-----+
| Prasad    |
+-----+
```

2. List the names of the driver who have delivered shipments weighing over 200 pounds.

```
select driver_name
from Truck
where truck_no in (select truck_no
from Shipment
where weight>200);
```

```
mysql> select driver_name
-> from Truck
-> where truck_no in (select truck_no
-> from Shipment
-> where weight>200);
```

driver_name
IQBAL
RAHIM
MADAN
SURYA
MITHUN

3. Retrieve the maximum and minimum weights of the shipments. Rename the output as Max_Weight and Min_Weight respectively.

```
select max(weight) MAX_WEIGHT,min(weight) MIN_WEIGHT
from Shipment;
```

```
mysql> select max(weight) MAX_WEIGHT,min(weight) MIN_WEIGHT
-> from Shipment;
+-----+-----+
| MAX_WEIGHT | MIN_WEIGHT |
+-----+-----+
|          460 |          50 |
+-----+-----+
```

4. For each customer, what is the average weight of package sent by the customer?

```
select cust_id,avg(weight)
from Shipment
group by cust_id;
```

```
mysql> select cust_id,avg(weight)
-> from Shipment
-> group by cust_id;
+-----+-----+
| cust_id | avg(weight) |
+-----+-----+
|      103 |      170.0000 |
|      104 |      210.0000 |
|      105 |      156.8333 |
|      107 |       50.0000 |
|      108 |       66.0000 |
|      109 |      202.0000 |
|      112 |      350.0000 |
|      116 |      320.0000 |
|      118 |      460.0000 |
|      120 |       60.0000 |
+-----+-----+
```

5. List the names and populations of cities that have received shipments weighing over 100 pounds.

```
select city_name,population
from City
where city_name in (select destination
from Shipment
where weight>100);
```

```
mysql> select city_name,population
-> from City
-> where city_name in (select destination
-> from Shipment
-> where weight>100);
```

city_name	population
Chennai	60000000
Delhi	70000000
Kolkata	55000000
Medinipur	600000
Mumbai	80000000
Pune	10000000

6. List cities that have received shipments from every customer.

```
select destination
from Shipment
group by cust_id
having count(distinct destination)=(select count(*)
from City);
```

```
mysql> select destination
-> from Shipment
-> group by cust_id
-> having count(distinct destination)=(select count(*)
-> from City);
```

destination
Kolkata

7. For each city, what is the maximum weight of a package sent to that city?

```
select destination,max(weight)
from Shipment
group by destination;
```

```
mysql> select destination,max(weight)
-> from Shipment
-> group by destination;
```

destination	max(weight)
Chennai	400
Delhi	350
Kolkata	220
Medinipur	320
Mumbai	101
Pune	460

8. List the name and annual revenue of customers whose shipments have been delivered by truck driver 'IQBAL'.

```
select cust_name,annual_revenue
from Customer
where cust_id in (select cust_id
from Shipment
where truck_no in (select truck_no
from Truck
where driver_name='IQBAL'));
```

```
mysql> select cust_name,annual_revenue
-> from Customer
-> where cust_id in (select cust_id
-> from Shipment
-> where truck_no in (select truck_no
-> from Truck
-> where driver_name='IQBAL'));
```

cust_name	annual_revenue
Vijay	1000000
Vicky	650000

9. List drivers who have delivered shipments to every city.

```
select driver_name
from Truck
where truck_no in (select truck_no
from Shipment
group by truck_no
having count(distinct destination)=(select count(*) from City));
```

```
mysql> select driver_name
-> from Truck
-> where truck_no in (select truck_no
-> from Shipment
-> group by truck_no
-> having count(distinct destination)=(select count(*) from City));
+-----+
| driver_name |
+-----+
| SURYA      |
+-----+
```

10. For each city, with population over 1 million, what is the minimum weight of a package sent to that city.

```
select destination,min(weight)
from Shipment
where destination in (select city_name
from City
where population>1000000)
group by destination;
```

```
mysql> select destination,min(weight)
-> from Shipment
-> where destination in (select city_name
-> from City
-> where population>1000000)
-> group by destination;
```

destination	min(weight)
Chennai	60
Delhi	70
Kolkata	66
Mumbai	50
Pune	70