

# Python Basics for Web App Pentesters Part 2

Justin Searle  
Managing Partner - UtiliSec  
[justin@utilisec.com](mailto:justin@utilisec.com)

# Why Python

---

- Pre-installed on Mac and Linux
- Easy to install on Windows
- Easy to write scripts that run on all OSes
- Easy to read and collaborate
- Very complete set of standard libraries
- Many stable and powerful 3<sup>rd</sup> party libraries

# Python Shell

---

- Using an interactive python shell
  - type “python” on your command line
  - type python commands
  - they execute when you hit enter
- Why use the shell?
  - Easy way to learn the language
  - Great way to debug portions of code
  - Nice for PoC functions and loops
- Beyond the basic shell
  - Consider ipython or IDLE after you get your feet wet
  - Provide richer functionality and productivity

# Input and Output

```
print('This site is protected by SSL.')
```

Basic output

```
answer = raw_input('Do you wish to continue? ')
```

Basic input

object oriented bliss

```
if answer.lower() == 'no':  
    print('Exiting the program.')  
else:  
    print('Continuing Program.')
```

if / then / else  
conditional  
statements. Notice  
the colons followed  
by mandatory line  
indentations

# A Tale of Two Libraries

---

## urllib2

HTTP, HTTPS, & FTP

Auto Parses URI

Follows Redirections

Uses a Cookie Jar

Auth: Basic & Digest

Methods: GET & POST

Supports Proxy Servers

Auto Closes Connections

## httplib

HTTP & HTTPS

No URI Parsing

Doesn't Follow Redirects

Doesn't Store Cookies

Authentication: None

Method: Any

No Proxy Support

Manually Close Connection

# Using httplib

Create a “connection” object

```
import httplib
```

Domain only

```
connection = httplib.HTTPConnection("secureideas.net")  
connection.request("TRACE", "/index.html")
```

Network request  
made here

```
response = connection.getresponse()  
payload = response.read()
```

Extract response

```
print(payload)
```

Extract payload

# Using urllib2

The library that does the magic

```
import urllib2
```

This doesn't make the request, it simply packages the request

```
request = urllib2.Request('http://www.utilisec.com')
```

Don't forget the "http://"

```
response = urllib2.urlopen(request)  
payload = response.read()
```

```
print(payload)
```

This sends the request, catches the response, and extracts out the response payload

# POST Requests

---

```
import urllib2, urllib
```

```
url = 'http://whois.arin.net/ui/query.do'
```

```
data = { 'flushCache' : 'false',  
        'queryinput' : '198.60.22.2' }
```

```
data = urllib.urlencode(data)
```

```
request = urllib2.Request(url, data)
```

```
response = urllib2.urlopen(request)
```

```
payload = response.read()
```

```
print(payload)
```

Add your POST data to a dictionary

Then urlencode your data  
(don't forget to import urllib)

If you provide urllib2 with request data, it will assume a POST



# Working with Headers

---

```
import urllib2
```

```
url = 'http://google.com/#q=samurai-wtf'
```

```
headers = { 'User-Agent' : 'Mozilla/5.0 (iPhone)' }
```

```
request = urllib2.Request(url, None, headers)
```

```
response = urllib2.urlopen(request)
```

```
headers = response.headers
```

```
print(headers)
```

Add your headers to a dictionary

If you are doing a GET, use None for data

# Writing to a File

---

```
import urllib2
```

```
request = urllib2.Request('http://www.utilisec.com')
```

```
response = urllib2.urlopen(request)  
payload = response.read()
```

Try opening a file, in  
write and binary  
modes

```
with open('index.html', 'wb') as file:  
    file.write(payload)
```

Write the payload to the file

# Filtering Responses

---

```
import urllib2, re
request = urllib2.Request('http://inguardians.com/info')
response = urllib2.urlopen(request)
payload = response.read()
```

Build your regex  
using a raw string,  
grouping desired text

```
regex = r'<dt class="title">(.*?)</dt>'
results = re.findall( regex , payload )
```

Search payload  
for all instances  
of your regex

```
for result in results:
    print(result)
```

Loop through your results printing them

# Basic Authentication

```
import urllib2
```

Setup needed variables

```
url = 'http://browserspy.dk/password-ok.php'
```

```
username = 'test'
```

```
password = 'test'
```

Setup password manager

```
password_mgr = urllib2.HTTPPasswordMgrWithDefaultRealm()
```

```
password_mgr.add_password(None, url, username, password)
```

```
authhandler = urllib2.HTTPBasicAuthHandler(password_mgr)
```

```
opener = urllib2.build_opener(authhandler)
```

```
urllib2.install_opener(opener)
```

Add passwords

Connect handler

```
response = urllib2.urlopen(url)
```

```
payload = response.read()
```

```
print( payload )
```

Build and install so all requests automatically use the password manager

# Fuzzing and Brute Force

```
import urllib2, re
```

```
list = (1533095958 + i for i in range(0, 20) )
```

Create list of 20 Facebook IDs

```
for item in list:
```

```
    url = 'http://m.facebook.com/people/a/' + str(item)
```

```
    try:
```

```
        response = urllib2.urlopen(url)
```

```
    except IOError:
```

```
        pass
```

```
    else:
```

```
        payload = response.read()
```

```
        regex = r'<strong>([^\<]*)'
```

```
        match = re.search(regex, payload)
```

```
        if match:
```

```
            name = match.groups()
```

```
            site = response.geturl().split("?")[0]
```

```
            print("{0} = {1} {2}".format(item, name[0], site) )
```

Prevent missing pages from throwing an error and stopping the script

Extract name from page

Grab url and remove redirect reference

Format output

# Cookie Jars

---

```
import urllib2, cookielib

headers = { 'User-Agent' : 'Mozilla/5.0 (iPhone)' }

cookiejar = cookielib.CookieJar()
opener = urllib2.build_opener(urllib2.HTTPCookieProcessor(cookiejar))
urllib2.install_opener(opener)

request1 = urllib2.Request('http://www.google.com', None, headers)
response1 = urllib2.urlopen(request1)

request2 = urllib2.Request('http://www.google.com', None, headers)
response2 = urllib2.urlopen(request2)
payload2 = response2.read()

print(payload2)
```

# Custom HTTP Methods in urllib2

---

```
import urllib2

method = 'TRACE'
request = urllib2.Request('http://www.secureideas.net')
request.get_method = lambda: method.upper()

response = urllib2.urlopen(request)
payload = response.read()

print(payload)
```

# Multi-Threading

---

```
import urllib2
from Queue import *
from threading import *
num_worker_threads = 10
url = 'http://www.google.com'
def grab():
    while True:
        q.get(True,None)
        req = urllib2.Request(url)
        response = urllib2.urlopen(req)
        payload = response.read()
        print(payload)
        q.task_done()
q = Queue(10)
for i in range(num_worker_threads):
    t = Thread(target=grab)
    t.setDaemon(True)
    t.start()

q.join()
```



# pyCIT

---

- Python Commandline Interface Templates
  - <http://code.google.com/p/pycit>
  - a collection of python templates for creating command line tools
  - great tool for beginners to show how to do the basics
  - saves advanced users time by providing the basic and much more
- Each templates will give you:
  - Built in command line arguments, easily modifiable
  - Provides a help page if no arguments are given
  - Tracks and displays your script version
  - Verbosity and debug functions with command line flags
  - Command line options and functions for reading and writing to files

# pyCIT Templates

---

- Completed Templates
  - Basic file read/write access
  - Single-threaded http requests (basic wget/curl functions)
- Templates in Progress
  - Multi-threaded http requests (basic wget/curl functions)
- Planned Templates
  - Binary file read/write access with hex decode (basic xxd/hexdump functions)
  - Raw socket client and service (basic netcat functions)
  - Raw usb device access
  - Interactive CLI interface

# Contact Information

---

Justin Searle  
Managing Partner - UtiliSec

work: [justin@utilisec.com](mailto:justin@utilisec.com)

personal: [justin@meeas.com](mailto:justin@meeas.com)

twitter: @meeas

<http://code.google.com/p/pycit>

<http://samurai-wtf.org>