

















	Quantit		Precisi			
Designator C1, C2, C4, C5, C6, C7, C8, C11, C12, C14, C15, C16,	у	Value	on	Comment	Footprint	Description
C17, C19, C22, C25, C27, C29, C33, C38, C48.A, C48.B, C48.C, C49.A, C49.B, C49.C, C50.A, C50.B, C50.C, C51.A, C51.B, C51.C, C54.A, C54.B, C54.C,						
C56.A, C56.B, C57.A, C57.B, C58.A, C58.B, C59.A, C59.B, C62.A, C62.B	45	1uF		Capacitor	C0805	ceramic chip capacitor
C3, C36, C46	3	10uF		Capacitor	C1206	ceramic chip capacitor
C9, C10, C13, C35, C39, C40, C41, C42, C43, C44, C45, C52.A, C52.B, C52.C, C53.A, C53.B, C53.C, C55.A,						
C55.B, C55.C, C60.A, C60.B, C61.A, C61.B, C63.A, C63.B	26	100nF		Capacitor	C0805	ceramic chip capacitor
C18, C20, C23, C26, C28, C30, C34	7	10nF		Capacitor	C0805	ceramic chip capacitor
C21, C24	2	18pF		Capacitor	C0805	ceramic chip capacitor
C31, C32	2	2.2uF		Capacitor	C0805	ceramic chip capacitor
C37		470pF		Capacitor	C0805	ceramic chip capacitor
C47 F1, F2, F3.A, F3.B, F3.C, F4.A, F4.B, F4.C, F5.A, F5.B,	1	1nF		Capacitor	C1206	ceramic chip capacitor
F6.A, F6.B	12			MF-USMF005	F1210	PTC Resettable Fuse 0.05A
HL1	1			FYLS-0603UWC	FYLS-0603UWC	SMD LED
L1	1	1uH		LQM21FN1R0N00D (MUR)	R0805	Inductor
Q1	1	25MHz		ABM8G	3.2x2.5 SMD CRYSTAL	Quarz in SMD package
R1, R3	2	4.7k	1%	Resistor	R0805	Chip resistor
R2	1	39k	1%	Resistor	R0805	Chip resistor
R4, R5, R22.A, R22.B, R22.C, R25.A, R25.B, R25.C, R32.A, R32.B, R35.A, R35.B	12	10	1%	Resistor	R1206	Chip resistor
R6, R9, R10, R16, R19.A, R19.B, R19.C, R20.A, R20.B, R20.C, R23.A, R23.B, R23.C, R26.A, R26.B, R26.C,			170	NCSISCO!	N1233	onp resistor
R29.A, R29.B, R30.A, R30.B, R33.A, R33.B, R36.A, R36.B	24	10k	1%	Resistor	R0603	Chip resistor
R7	1	1k	1%	Resistor	R0603	Chip resistor
R8	1	510	1%	Resistor	R0603	Chip resistor
R11, R12, R13, R14	4	49.9	1%	Resistor	R0805	Chip resistor
R15	1	12.1k	1%	Resistor	R0603	Chip resistor
R17, R18	2	680	1%	Resistor	R0603	Chip resistor
R21.A, R21.B, R21.C, R24.A, R24.B, R24.C, R27.A, R27.B, R27.C, R28.A, R28.B, R28.C, R31.A, R31.B, R34.A, R34.B, R37.A, R37.B, R38.A, R38.B	20	10	1%	Resistor	R0603	Chip resistor
SA1	1			кнопка тактовая	B3U-3000P(M)-B	
U1	1			LD1117S33CTR	SOT-223	Линейный регулятор - [SOT- 223]; Тип: LDO; Uвх: 4.7515 В; Uвых: 3.2353.365 В; Регул.: FIX; Івых: 800 мА; Іпотр: 5 мА
U2, U8.A, U8.B, U8.C, U11.A, U11.B	6			ADum1401BRW	RW-16	3I/10 Data Digital Isolator
U3, U9.A, U9.B, U9.C, U12.A, U12.B	6			SN65HVD1785Dx	SOIC127P600X175- 8N	x Fault-Protected RS-485 Transceivers With Extended Common-Mode Range
						ARM Cortex-M4 32-bit MCU+FPU, 512 KB Flash, 192 KB Internal RAM, 82 I/Os, 100- Pin LQFP, -40 to 85 degC,
U4	1			STM32F407VET6TR	STM-LQFP100_N	Tape and Reel
U5	1			LAN8720AI	QFN-24 4x4mm	Ethernet PYH controller (-40°C to 85°C)
U6	1			HR911105A	HR911105A	HR911105A Ethernet connector
U7.A, U7.B, U7.C, U10.A, U10.B	5			MAX232IDR	SOIC127P780X200- 16M	Dual EIA-232 Drivers/Receivers
UV1	1			F2405S-1WR2 (mornsun)	SIP-7_AM2D- XXXXSH30/40Z	1W isolated DC-DC
						1W 1kV isolated dual
UV2, UV3, UV4 VD1	1			P6CUI-050505ZLF BAV70	SIP-7 DualPeak SOT-23	separate output DC-DC High-speed double diode
	<u> </u>					Low-Voltage Adjustable
VD2 VD3, VD4, VD5.A, VD5.B, VD5.C, VD6.A, VD6.B,	1			TLV431x	SOT-23	Precision Shunt Regulator
VD6.C, VD7.A, VD7.B, VD8.A, VD8.B	12			SM6T15CA	SMB (DO-214AA) DPAK228P972X240-	Supressor NPN SILICON POWER
VT1	1			MJD340	DPAK228P972X240- 3N	TRANSISTOR
VT2.A, VT2.B, VT2.C, VT3.A, VT3.B, VT3.C, VT4.A, VT4.B, VT5.A, VT5.B	10			NTR4101P	SOT-23	Trench Power MOSFET -20 V, Single P-Channel, SOT-23
X1, X4.A, X4.B	3			Weidmuller_ 1069710000		PCB plug-in connector, right, male header
İ	1	1			PINHEAD 6x1	
X2	1			PLS-6x1	2.54_H SHL-	PLS PINHEAD 6x1, 2.54 PCB plug-in connector, left,