

Control Systems

G V V Sharma*

CONTENTS		
1	Signal Flow Graph	1
1.1	Mason's Gain Formula	1
1.2	Matrix Formula	1
1.3	Example	1
2	Bode Plot	1
2.1	Introduction	1
2.2	Example	1
2.3	Phase	3
3	Second order System	3
3.1	Damping	3
3.2	Example	3
3.3	Settling Time	3
4	Routh Hurwitz Criterion	3
4.1	Routh Array	3
4.2	Marginal Stability	3
4.3	Stability	3
4.4	Example	3
4.5	Example	3
5	State-Space Model	3
5.1	Controllability and Observability	3
5.2	Second Order System	3
5.3	Example	3
5.4	Example	3
5.5	Example	3
5.6	Example	3
5.7	Example	3
6	Nyquist Plot	3
6.1	Introduction	3
6.2	Example	3
7	Compensators	3
7.1	Phase Lead	3
7.2	Lag Lead	3
7.3	Example	3
8	Gain Margin	3
8.1	Introduction	3
8.2	Example	3
8.3	Example	3
9	Phase Margin	3
9.1	Intoduction	3
9.2	Example	3
10	Oscillator	3
10.1	Introduction	3
10.2	Example	3
11	Root Locus	3
11.1	Introduction	3

Abstract—This manual is an introduction to control systems based on GATE problems. Links to sample Python codes are available in the text.

Download python codes using

```
svn co https://github.com/gadepall/school/trunk/control/codes
```

1 SIGNAL FLOW GRAPH

1.1 Mason's Gain Formula

1.2 Matrix Formula

1.3 Example

2 BODE PLOT

2.1 Introduction

2.2 Example

2.1. For an LTI system, the Bode plot for its gain defined as

$$G(s) = 20 \log |H(s)| \quad (2.1.1)$$

is as illustrated in the Fig. 2.1. Find the corner frequencies ω_{01} and ω_{02} from the plot.

*The author is with the Department of Electrical Engineering, Indian Institute of Technology, Hyderabad 502285 India e-mail: gadepall@iith.ac.in. All content in this manual is released under GNU GPL. Free and open source.




Fig. 2.1

Solution: The corner frequencies can be calculated as follows:

$$\text{slope} = \frac{M_2 - M_1}{\log \omega_2 - \log \omega_1}$$

Therefore for ω_{02} ,

$$-40 = \frac{0 - 12}{\log 8 - \log \omega_{02}}$$

$$\log 8 - \log \omega_{02} = \frac{12}{40}$$

$$\log \omega_{02} = \log 8 - \frac{12}{40}$$

$$\omega_{02} = 4$$

And for ω_{01} ,

$$20 = \frac{0 - 12}{\log 0.5 - \log \omega_{01}}$$

$$\log 0.5 - \log \omega_{01} = \frac{-12}{20}$$

$$\log \omega_{01} = \log 0.5 + \frac{12}{20}$$

$$\omega_{01} = 2$$

So, the corner frequencies are $\omega_{01}=2$ and $\omega_{02} = 4$.

2.2. Find the transfer function from the calculated frequencies.

Solution: By looking to the plot, we can say that since the initial slope is +20, there must

be a zero at the origin. At ω_{01} , the change in slope is -20dB, so there exists one pole at this frequency.

At ω_{02} , the change in slope is -40dB, so there exists two poles at this frequency.

The denominators have the form,

$$\left(1 + \frac{s}{\omega}\right)$$

So, the denominator of the transfer function is

$$\left(1 + \frac{s}{2}\right)\left(1 + \frac{s}{4}\right)^2$$

Therefore, the transfer function is,

$$\frac{cs}{\left(1 + \frac{s}{2}\right)\left(1 + \frac{s}{4}\right)^2}$$

here c is some constant

2.3. Compare the above calculated transfer function with one of the options that best represents it.

$$(A) \frac{2s}{(1 + 0.5s)(1 + 0.25s)^2} \quad (B) \frac{4(1 + 0.5s)}{s(1 + 0.25s)}$$

$$(C) \frac{2s}{(1 + 2s)(1 + 4s)} \quad (D) \frac{4s}{(1 + 2s)(1 + 4s)^2}$$

Solution: From the above given options, we can see that option (A) best represents our transfer function.

$$\frac{2s}{(1 + 0.5s)(1 + 0.25s)^2}$$

2.4. Verify the above transfer function by plotting the bode plot.

Solution: Refer Fig. 2.4 for the bode plot:

The plot was plotted using the following code:

```
import numpy as np
import control.matlab as ml
import matplotlib.pyplot as plt

# If using termux
import subprocess
import shlex
#end if
```




Fig. 2.4: Plot of $G(s)$

```
# num is the numerator of the transfer function which is (2s)
# den is the denominator of the transfer function which is (0.25s + 1)(0.25s + 1)
# (0.5s + 1)
num = np.array([2, 0])
den = np.polymul(np.array([0.5, 1]), np.array([0.25, 1]))
den = np.polymul(den, np.array([0.25, 1]))

# Generating the transfer function
g = ml.tf(num, den)
print("The transfer function is: ", g)
print("The poles of the above function are ", ml.pole(g))
print("The zeros of the above function are ", ml.zero(g))

# Generating the bode plot as well as plotting it
mag, phase, w = ml.bode(g)

# If using termux
plt.savefig("../figs/ep18btech11016_plot.pdf")
plt.savefig("../figs/ep18btech11016_plot.eps")
subprocess.run(shlex.split("termux-open ../figs/ep18btech11016_plot.pdf"))
# else
plt.show()
```

2.3 Phase

3 SECOND ORDER SYSTEM

3.1 Damping

3.2 Example

3.3 Settling Time

4 ROUTH HURWITZ CRITERION

4.1 Routh Array

4.2 Marginal Stability

4.3 Stability

4.4 Example

4.5 Example

5 STATE-SPACE MODEL

5.1 Controllability and Observability

5.2 Second Order System

5.3 Example

5.4 Example

5.5 Example

5.6 Example

5.7 Example

6 NYQUIST PLOT

6.1 Introduction

6.2 Example

7 COMPENSATORS

7.1 Phase Lead

7.2 Lag Lead

7.3 Example

8 GAIN MARGIN

8.1 Introduction

8.2 Example

8.3 Example

9 PHASE MARGIN

9.1 Introduction

9.2 Example

10 OSCILLATOR

10.1 Introduction

10.2 Example

11 ROOT LOCUS

11.1 Introduction