


EN1060 Signals and Systems: Discrete-Time Fourier Series

Ranga Rodrigo
ranga@uom.lk

The University of Moratuwa, Sri Lanka

November 28, 2016

- Now, we have studied Fourier series and Fourier transform for CT signals.
- In this lesson we will develop similar tool for discrete time.
- Specifically, we consider the representation of discrete-time signals through a decomposition as a linear combination of complex exponentials.
 - DT periodic signals \rightarrow DT Fourier series
 - DT aperiodic signals \rightarrow DT Fourier transform



Decompose the input as

$$x = a_1\phi_1 + a_2\phi_2 + \cdots \quad \text{linear combination of basic inputs}$$

Then

$$y = a_1\psi_1 + a_2\psi_2 + \cdots \quad \text{linear combination of corresponding outputs}$$

Choose $\phi_k(t)$ or $\phi_k[n]$ such that

- Broad class of signals can be constructed, and
- Response to ϕ_k s easy to compute.

Continuous-Time:

$$\phi_k(t) = e^{j\omega_k t}:$$

$$e^{j\omega_k t} \longrightarrow H(\omega_k) e^{j\omega_k t} \quad (\text{a scaled-version of the input})$$

“Discrete-Time”:

Determine and sketch the DTFT of

$$x[n] = 1 + \sin \omega_0 n + 3 \cos \omega_0 n + \cos \left(2\omega_0 n + \frac{\pi}{2} \right).$$

Determine and sketch the DTFT of $x[n]$ of which is shown in the figure.

