

Package ‘radiant.model’

April 18, 2017

Type Package

Title Model Menu for Radiant: Business Analytics using R and Shiny

Version 0.7.17

Date 2017-4-17

Description The Radiant Model menu includes interfaces for linear and logistic regression, Neural Networks, model evaluation, decision analysis, and simulation. The application extends the functionality in radiant.data.

Depends R (>= 3.3.0),
radiant.data (>= 0.7.10)

Imports radiant.basics (>= 0.7.1),
shiny (>= 0.14),
nnet (>= 7.3.12),
NeuralNetTools (>= 1.4.0),
sandwich (>= 2.3.4),
car (>= 2.1.3),
ggplot2 (>= 2.1.0),
gridExtra (>= 2.0.0),
data.tree (>= 0.7.0),
yaml (>= 2.1.13),
stringr (>= 1.1.0),
pryr (>= 0.1.2),
lubridate (>= 1.6.0),
tidyr (>= 0.6.0),
dplyr (>= 0.5),
magrittr (>= 1.5),
DiagrammeR (>= 0.9.0),
import (>= 1.1.0),
psych (>= 1.6.6),
e1071 (>= 1.6.8),
rpart (>= 4.1.10),
methods

Suggests testthat (>= 1.0.0),
covr (>= 1.2.0)

URL <https://github.com/radiant-rstats/radiant.model>

BugReports <https://github.com/radiant-rstats/radiant.model/issues>

License AGPL-3 | file LICENSE

LazyData true

RoxygenNote 5.0.1

R topics documented:

ann	3
auc	4
catalog	5
cf	6
confint_robust	6
confusion	7
crs	8
crtree	8
direct_marketing	10
dtree	10
dtree_parser	11
dvd	11
evalbin	12
evalreg	13
find_max	13
find_min	14
houseprices	14
ideal	15
logistic	15
minmax	16
nb	17
plot.ann	18
plot.confusion	19
plot.crs	19
plot.crtree	20
plot.dtree	21
plot.evalbin	22
plot.evalreg	23
plot.logistic	23
plot.model.predict	24
plot.nb	25
plot.nb.predict	26
plot.regress	27
plot.repeater	28
plot.simulator	28
predict.ann	29
predict.crtree	30
predict.logistic	31
predict.nb	32
predict.regress	33
predict_model	34
print.ann.predict	35
print.crtree.predict	35
print.logistic.predict	36
print.nb.predict	36
print.regress.predict	37

print_predict_model	37
radiant.model	38
radiant.model-deprecated	38
regress	38
render.DiagrammeR	39
repeater	40
scaledf	41
sdw	41
sensitivity	42
sensitivity.dtree	42
simulator	43
sim_cleaner	44
sim_splitter	45
sim_summary	45
store.crs	46
store.model	46
store.model.predict	47
store.nb.predict	47
store_ann	48
store_glm	49
store_reg	49
summary.ann	50
summary.confusion	50
summary.crs	51
summary.crtree	51
summary.dtree	52
summary.evalbin	53
summary.evalreg	53
summary.logistic	54
summary.nb	55
summary.regress	56
summary.repeater	57
summary.simulator	57
test_specs	58
var_check	58
write.coeff	59
Index	60

ann

*Artificial Neural Networks***Description**

Artificial Neural Networks

Usage

```
ann(dataset, rvar, evar, type = "classification", lev = "", size = 1,
     decay = 0.5, wts = "None", seed = NA, check = "standardize",
     data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
rvar	The response variable in the model
evvar	Explanatory variables in the model
type	Model type (i.e., "classification" or "regression")
lev	The level in the response variable defined as <code>_success_</code>
size	Number of units (nodes) in the hidden layer
decay	Parameter decay
weights	Weights to use in estimation
seed	Random seed to use as the starting point
check	Optional estimation parameters ("standardize" is the default)
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://radiant-rstats.github.io/docs/model/ann.html> for an example in Radiant

Value

A list with all variables defined in `ann` as an object of class `ann`

See Also

`summary.ann` to summarize results

`plot.ann` to plot results

`predict.ann` for prediction

Examples

```
result <- ann("titanic", "survived", c("pclass","sex"), lev = "Yes")
result <- ann("titanic", "survived", c("pclass","sex"))
result <- ann("diamonds", "price", c("carat","clarity"), type = "regression")
```

auc

Area Under the Curve (AUC)

Description

Area Under the Curve (AUC)

Usage

```
auc(pred, rvar, lev)
```

Arguments

pred	Prediction or predictor
rvar	Response variable
lev	The level in the response variable defined as <code>_success_</code>

Details

See <http://radiant-rstats.github.io/docs/model/evalbin.html> for an example in Radiant

Value

AUC statistic

See Also

[evalbin](#) to calculate results
[summary.evalbin](#) to summarize results
[plot.evalbin](#) to plot results

Examples

```
auc(runif(nrow(mtcars)), mtcars$vs, 1)
```

catalog

Catalog sales for men's and women's apparel

Description

Catalog sales for men's and women's apparel

Usage

```
data(catalog)
```

Format

A data frame with 200 rows and 5 variables

Details

Description provided in `attr(catalog,"description")`

cf	<i>Movie ratings</i>
----	----------------------

Description

Movie ratings

Usage

```
data(cf)
```

Format

A data frame with 110 rows and 4 variables

Details

Use collaborative filtering to create recommendations based on ratings from existing users. Description provided in attr(df,"description")

confint_robust	<i>Confidence interval for robust estimators</i>
----------------	--

Description

Confidence interval for robust estimators

Usage

```
confint_robust(object, parm, level = 0.95, vcov = NULL, ...)
```

Arguments

object	A fitted model object
parm	A specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered
level	The confidence level required
vcov	Covariance matrix generated by, e.g., sandwich::vcovHC
...	Additional argument(s) for methods

Details

Wrapper for confint.default with robust standard errors. See <http://stackoverflow.com/a/3820125/1974918>

confusion*Confusion matrix*

Description

Confusion matrix

Usage

```
confusion(dataset, pred, rvar, lev = "", cost = 1, margin = 2,  
  train = "", data_filter = "", ...)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
pred	Predictions or predictors
rvar	Response variable
lev	The level in the response variable defined as <code>_success_</code>
cost	Cost for each connection (e.g., email or mailing)
margin	Margin on each customer purchase
train	Use data from training ("Training"), validation ("Validation"), both ("Both"), or all data ("All") to evaluate model evalbin
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/evalbin.html> for an example in Radiant

Value

A list of results

See Also

[summary.confusion](#) to summarize results

[plot.confusion](#) to plot results

crs	<i>Collaborative Filtering</i>
-----	--------------------------------

Description

Collaborative Filtering

Usage

```
crs(dataset, id, prod, pred, rate, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
id	String with name of the variable containing user ids
prod	String with name of the variable with product ids
pred	Products to predict for
rate	String with name of the variable with product ratings
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "training == 1")

Details

See <http://radiant-rstats.github.io/docs/model/crs.html> for an example in Radiant

Value

A data.frame with the original data and a new column with predicted ratings

crtree	<i>Classification and regression trees</i>
--------	--

Description

Classification and regression trees

Usage

```
crtree(dataset, rvar, evar, type = "", lev = "", wts = "None",
        cp = 0.001, nodes = NA, K = 10, seed = 1234, split = "gini",
        prior = NA, cost = NA, margin = NA, check = "", data_filter = "")
```


Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
rvar	The response variable in the model
evvar	Explanatory variables in the model
type	Model type (i.e., "classification" or "regression")
lev	The level in the response variable defined as <code>_success_</code>
weights	Weights to use in estimation
cp	Minimum proportion of root node deviance required for split (default = 0.00001)
nodes	Maximum size of tree in number of nodes to return. If equal to NA no pruning is done
K	Number of folds use in cross-validation
seed	Random seed used for cross-validation
split	Splitting criterium to use (i.e., "gini" or "information")
prior	Adjust the initial probability for the selected level (e.g., set to .5 in unbalanced samples)
cost	Cost for each connection (e.g., email or mailing)
margin	Margin on each customer purchase
check	Optional estimation parameters ("standardize" is the default)
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://radiant-rstats.github.io/docs/model/crtree.html> for an example in Radiant

Value

A list with all variables defined in `crtree` as an object of class `tree`

See Also

`summary.crtree` to summarize results

`plot.crtree` to plot results

`predict.crtree` for prediction

Examples

```
result <- crtree("titanic", "survived", c("pclass","sex"), lev = "Yes")
result <- crtree("titanic", "survived", c("pclass","sex"))
result <- crtree("diamonds", "price", c("carat","clarity"), type = "regression")
```

direct_marketing	<i>Direct marketing data</i>
------------------	------------------------------

Description

Direct marketing data

Usage

```
data(direct_marketing)
```

Format

A data frame with 1,000 rows and 12 variables

Details

Description provided in `attr(direct_marketing,"description")`

dtree	<i>Create a decision tree</i>
-------	-------------------------------

Description

Create a decision tree

Usage

```
dtree(y1, opt = "max", base = character(0))
```

Arguments

y1	A yaml string or a list (e.g., from <code>yaml::yaml.load_file()</code>)
opt	Find the maximum ("max") or minimum ("min") value for each decision node
base	List of variable definitions from a base tree used when calling a sub-tree

Details

See <http://radiant-rstats.github.io/docs/model/dtree.html> for an example in Radiant

Value

A list with the initial tree and the calculated tree

See Also

[summary.dtree](#) to summarize results

[plot.dtree](#) to plot results

[sensitivity.dtree](#) to plot results

dtree_parser	<i>Parse yaml input for dtree to provide (more) useful error messages</i>
--------------	---

Description

Parse yaml input for dtree to provide (more) useful error messages

Usage

```
dtree_parser(y1)
```

Arguments

y1	A yaml string
----	---------------

Details

See <http://radiant-rstats.github.io/docs/model/dtree.html> for an example in Radiant

Value

An updated yaml string or a vector messages to return to the users

See Also

[dtree](#) to calculate tree
[summary.dtree](#) to summarize results
[plot.dtree](#) to plot results

dvd	<i>Data on DVD sales</i>
-----	--------------------------

Description

Data on DVD sales

Usage

```
data(dvd)
```

Format

A data frame with 20,000 rows and 4 variables

Details

Binary purchase response to coupon value. Description provided in attr(dvd,"description")

`evalbin`*Model evalbin*

Description

Model evalbin

Usage

```
evalbin(dataset, pred, rvar, lev = "", qnt = 10, cost = 1, margin = 2,  
        train = "", method = "xtile", data_filter = "")
```

Arguments

<code>dataset</code>	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
<code>pred</code>	Predictions or predictors
<code>rvar</code>	Response variable
<code>lev</code>	The level in the response variable defined as <code>_success_</code>
<code>qnt</code>	Number of bins to create
<code>cost</code>	Cost for each connection (e.g., email or mailing)
<code>margin</code>	Margin on each customer purchase
<code>train</code>	Use data from training ("Training"), validation ("Validation"), both ("Both"), or all data ("All") to evaluate model evalbin
<code>method</code>	Use either <code>ntile</code> or <code>xtile</code> to split the data (default is <code>xtile</code>)
<code>data_filter</code>	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://radiant-rstats.github.io/docs/model/evalbin.html> for an example in Radiant

Value

A list of results

See Also

`summary.evalbin` to summarize results

`plot.evalbin` to plot results

Examples

```
result <- evalbin("titanic", c("age", "fare"), "survived")
```

`evalreg`*Model evalreg*

Description

Model evalreg

Usage

```
evalreg(dataset, pred, rvar, train = "", data_filter = "")
```

Arguments

<code>dataset</code>	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
<code>pred</code>	Predictions or predictors
<code>rvar</code>	Response variable
<code>train</code>	Use data from training ("Training"), validation ("Validation"), both ("Both"), or all data ("All") to evaluate model evalreg
<code>data_filter</code>	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://radiant-rstats.github.io/docs/model/evalreg.html> for an example in Radiant

Value

A list of results

See Also[summary.evalreg](#) to summarize results[plot.evalreg](#) to plot results

`find_max`*Find maxium value of a vector*

Description

Find maxium value of a vector

Usage

```
find_max(var, val = "")
```

Arguments

<code>var</code>	Variable to find the maximum for
<code>val</code>	Variable to find the value for at the maximum of <code>var</code>

Value

Value of `val` at the maximum of `var`

<code>find_min</code>	<i>Find minimum value of a vector</i>
-----------------------	---------------------------------------

Description

Find minimum value of a vector

Usage

```
find_min(var, val = "")
```

Arguments

<code>var</code>	Variable to find the minimum for
<code>val</code>	Variable to find the value for at the maximum of <code>var</code>

Value

Value of `val` at the minimum of `var`

<code>houseprices</code>	<i>Houseprices</i>
--------------------------	--------------------

Description

Houseprices

Usage

```
data(houseprices)
```

Format

A data frame with 128 home sales and 6 variables

Details

Description provided in `attr(houseprices,"description")`

ideal	<i>Ideal data for linear regression</i>
-------	---

Description

Ideal data for linear regression

Usage

```
data(ideal)
```

Format

A data frame with 1,000 rows and 4 variables

Details

Description provided in `attr(ideal,"description")`

logistic	<i>Logistic regression</i>
----------	----------------------------

Description

Logistic regression

Usage

```
logistic(dataset, rvar, evar, lev = "", int = "", wts = "None",
  check = "", data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
rvar	The response variable in the model
evar	Explanatory variables in the model
lev	The level in the response variable defined as <code>_success_</code>
int	Interaction term to include in the model
wts	Weights to use in estimation
check	Use "standardize" to see standardized coefficient estimates. Use "stepwise-backward" (or "stepwise-forward", or "stepwise-both") to apply step-wise selection of variables in estimation
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://radiant-rstats.github.io/docs/model/logistic.html> for an example in Radiant

Value

A list with all variables defined in `logistic` as an object of class `logistic`

See Also

`summary.logistic` to summarize the results

`plot.logistic` to plot the results

`predict.logistic` to generate predictions

`plot.model.predict` to plot prediction output

Examples

```
result <- logistic("titanic", "survived", c("pclass","sex"), lev = "Yes")
result <- logistic("titanic", "survived", c("pclass","sex"))
```

minmax

Calculate min and max before standardization

Description

Calculate min and max before standardization

Usage

```
minmax(dat)
```

Arguments

`dat` Data frame

Value

Data frame min and max attributes

nb	<i>Naive Bayes using e1071::naiveBayes</i>
----	--

Description

Naive Bayes using e1071::naiveBayes

Usage

```
nb(dataset, rvar, evar, laplace = 0, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
rvar	The response variable in the logit (probit) model
evar	Explanatory variables in the model
laplace	Positive double controlling Laplace smoothing. The default (0) disables Laplace smoothing.
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://radiant-rstats.github.io/docs/model/naivebayes.html> for an example in Radiant

Value

A list with all variables defined in nb as an object of class nb

See Also

`summary.nb` to summarize results

`plot.nb` to plot results

`predict.nb` for prediction

Examples

```
result <- nb("titanic", "survived", c("pclass", "sex", "age"))
```

plot.ann	<i>Plot method for the ann function</i>
----------	---

Description

Plot method for the ann function

Usage

```
## S3 method for class 'ann'
plot(x, plots = "garson", shiny = FALSE, custom = FALSE,
     ...)
```

Arguments

x	Return value from ann
plots	Plots to produce for the specified ANN model. Use "" to avoid showing any plots (default). Options are "olden" or "garson" for importance plots, or "net" to depict the network structure
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/ann.html> for an example in Radiant

See Also

[ann](#) to generate results
[summary.ann](#) to summarize results
[predict.ann](#) for prediction

Examples

```
result <- ann("titanic", "survived", c("pclass","sex"), lev = "Yes")
plot(result, plots = c("olden","net"))
```

plot.confusion	<i>Plot method for the confusion matrix</i>
----------------	---

Description

Plot method for the confusion matrix

Usage

```
## S3 method for class 'confusion'
plot(x, vars = c("kappa", "index", "ROME", "AUC"),
     scale_y = TRUE, ...)
```

Arguments

x	Return value from confusion
vars	Measures to plot, i.e., one or more of "TP", "FP", "TN", "FN", "total", "TPR", "TNR", "precision", "accuracy", "kappa", "profit", "index", "ROME", "contact", "AUC"
scale_y	Free scale in faceted plot of the confusion matrix (TRUE or FALSE)
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/evalbin.html> for an example in Radiant

See Also

[confusion](#) to generate results
[summary.confusion](#) to summarize results

plot.crs	<i>Plot method for the crs function</i>
----------	---

Description

Plot method for the crs function

Usage

```
## S3 method for class 'crs'
plot(x, ...)
```

Arguments

x	Return value from crs
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/crs.html> for an example in Radiant

See Also

[crs](#) to generate results

[summary.crs](#) to summarize results

plot.crtree	<i>Plot method for the crtree function</i>
-------------	--

Description

Plot method for the crtree function

Usage

```
## S3 method for class 'crtree'
plot(x, plots = "tree", orient = "LR", labs = TRUE,
     dec = 2, shiny = FALSE, custom = FALSE, ...)
```

Arguments

x	Return value from crtree
plots	Plots to produce for the specified rpart tree. "tree" shows a tree diagram. "prune" shows a line graph to evaluate appropriate tree pruning. "imp" shows a variable importance plot
orient	Plot orientation: LR for vertical and TD for horizontal
labs	Use factor labels in plot (TRUE) or revert to default letters used by tree (FALSE)
dec	Decimal places to round results to
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/crtree.html> for an example in Radiant. The standard tree plot used by the rpart package can be generated by `plot.rpart(result$model)`. See [plot.rpart](#) for additional details.

See Also

[crtree](#) to generate results

[summary.crtree](#) to summarize results

[predict.crtree](#) for prediction

Examples

```

result <- ctree("titanic", "survived", c("pclass","sex"), lev = "Yes")
plot(result)
result <- ctree("diamonds", "price", c("carat","clarity", "cut"))
plot(result, plots = "prune")
result <- ctree("dvd", "buy", c("coupon","purch", "last"), cp = .01)
plot(result, plots = "imp")

```

plot.dtree

*Plot method for the dtree function***Description**

Plot method for the dtree function

Usage

```

## S3 method for class 'dtree'
plot(x, symbol = "$", dec = 2, final = FALSE,
     orient = "LR", ...)

```

Arguments

x	Return value from dtree
symbol	Monetary symbol to use (\$ is the default)
dec	Decimal places to round results to
final	If TRUE plot the decision tree solution, else the initial decision tree
orient	Plot orientation: LR for vertical and TD for horizontal
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/dtree.html> for an example in Radiant

See Also

[dtree](#) to generate the result
[summary.dtree](#) to summarize results
[sensitivity.dtree](#) to plot results

plot.evalbin	<i>Plot method for the evalbin function</i>
--------------	---

Description

Plot method for the evalbin function

Usage

```
## S3 method for class 'evalbin'
plot(x, plots = c("lift", "gains"), shiny = FALSE,
      custom = FALSE, ...)
```

Arguments

x	Return value from evalbin
plots	Plots to return
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/evalbin.html> for an example in Radiant

See Also

[evalbin](#) to generate results

[summary.evalbin](#) to summarize results

Examples

```
evalbin("titanic", "age", "survived") %>% plot
evalbin("titanic", c("age", "fare"), "survived") %>% plot
evalbin("titanic", c("age", "fare"), "survived", method = "xtile") %>% plot
evalbin("titanic", c("age", "fare"), "survived") %>% summary
```

plot.evalreg	<i>Plot method for the evalreg function</i>
--------------	---

Description

Plot method for the evalreg function

Usage

```
## S3 method for class 'evalreg'
plot(x, vars = c("Rsq", "RSME", "MAE"), ...)
```

Arguments

x	Return value from evalreg
vars	Measures to plot, i.e., one or more of "Rsq", "RSME", "MAE"
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/evalreg.html> for an example in Radiant

See Also

[evalreg](#) to generate results
[summary.evalreg](#) to summarize results

plot.logistic	<i>Plot method for the logistic function</i>
---------------	--

Description

Plot method for the logistic function

Usage

```
## S3 method for class 'logistic'
plot(x, plots = "", conf_lev = 0.95, intercept = FALSE,
     shiny = FALSE, custom = FALSE, ...)
```

Arguments

x	Return value from logistic
plots	Plots to produce for the specified GLM model. Use "" to avoid showing any plots (default). "dist" shows histograms (or frequency bar plots) of all variables in the model. "scatter" shows scatter plots (or box plots for factors) for the response variable with each explanatory variable. "dashboard" is a series of four plots used to visually evaluate model. "coef" provides a coefficient plot

conf_lev	Confidence level to use for coefficient and odds confidence intervals (.95 is the default)
intercept	Include the intercept in the coefficient plot (TRUE or FALSE). FALSE is the default
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/logistic.html> for an example in Radiant

See Also

[logistic](#) to generate results
[plot.logistic](#) to plot results
[predict.logistic](#) to generate predictions
[plot.model.predict](#) to plot prediction output

Examples

```
result <- logistic("titanic", "survived", c("pclass","sex"), lev = "Yes")
plot(result, plots = "coef")
```

plot.model.predict	<i>Plot method for model.predict functions</i>
--------------------	--

Description

Plot method for model.predict functions

Usage

```
## S3 method for class 'model.predict'
plot(x, xvar = "", facet_row = ".",
     facet_col = ".", color = "none", conf_lev = 0.95, ...)
```

Arguments

x	Return value from predict functions (e.g., predict.regress)
xvar	Variable to display along the X-axis of the plot
facet_row	Create vertically arranged subplots for each level of the selected factor variable
facet_col	Create horizontally arranged subplots for each level of the selected factor variable

color	Adds color to a scatter plot to generate a heat map. For a line plot one line is created for each group and each is assigned a different colour
conf_lev	Confidence level to use for prediction intervals (.95 is the default)
...	further arguments passed to or from other methods

See Also

[predict.regress](#) to generate predictions

[predict.logistic](#) to generate predictions

Examples

```
regress("diamonds", "price", c("carat","clarity")) %>%
  predict(pred_cmd = "carat = 1:10") %>%
  plot(xvar = "carat")
logistic("titanic", "survived", c("pclass","sex","age"), lev = "Yes") %>%
  predict(pred_cmd="pclass=levels(pclass), sex=levels(sex), age=seq(0,100,20)") %>%
  plot(xvar = "age", color = "sex", facet_col = "pclass")
```

plot.nb

Plot method for the nb function

Description

Plot method for the nb function

Usage

```
## S3 method for class 'nb'
plot(x, ...)
```

Arguments

x	Return value from nb
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/nb.html> for an example in Radiant

See Also

[nb](#) to generate results

[summary.nb](#) to summarize results

[predict.nb](#) for prediction

Examples

```
result <- nb("titanic", "survived", c("pclass","sex"))
plot(result)
result <- nb("titanic", "pclass", c("sex","age"))
plot(result)
```

plot.nb.predict

*Plot method for nb.predict function***Description**

Plot method for nb.predict function

Usage

```
## S3 method for class 'nb.predict'
plot(x, xvar = "", facet_row = ".", facet_col = ".",
     color = ".class", ...)
```

Arguments

x	Return value from predict function predict.nb
xvar	Variable to display along the X-axis of the plot
facet_row	Create vertically arranged subplots for each level of the selected factor variable
facet_col	Create horizontally arranged subplots for each level of the selected factor variable
color	Adds color to a scatter plot to generate a heat map. For a line plot one line is created for each group and each is assigned a different colour
...	further arguments passed to or from other methods

See Also

[predict.nb](#) to generate predictions

Examples

```
result <- nb("titanic", "survived", c("pclass","sex","age"))
pred <- predict(result, pred_cmd="pclass=levels(pclass), sex=levels(sex), age=seq(0,100,20)")
plot(pred, xvar = "age", facet_col = "sex", facet_row = "pclass")
pred <- predict(result, pred_data="titanic")
plot(pred, xvar = "age", facet_col = "sex")
```

plot.regress

*Plot method for the regress function***Description**

Plot method for the regress function

Usage

```
## S3 method for class 'regress'
plot(x, plots = "", lines = "", conf_lev = 0.95,
      intercept = FALSE, shiny = FALSE, custom = FALSE, ...)
```

Arguments

x	Return value from regress
plots	Regression plots to produce for the specified regression model. Enter "" to avoid showing any plots (default). "dist" to shows histograms (or frequency bar plots) of all variables in the model. "correlations" for a visual representation of the correlation matrix selected variables. "scatter" to show scatter plots (or box plots for factors) for the response variable with each explanatory variable. "dashboard" for a series of six plots that can be used to evaluate model fit visually. "resid_pred" to plot the explanatory variables against the model residuals. "coef" for a coefficient plot with adjustable confidence intervals. "leverage" to show leverage plots for each explanatory variable
lines	Optional lines to include in the select plot. "line" to include a line through a scatter plot. "loess" to include a polynomial regression fit line. To include both use c("line","loess")
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)
intercept	Include the intercept in the coefficient plot (TRUE, FALSE). FALSE is the default
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/regress.html> for an example in Radiant

See Also

[regress](#) to generate the results
[summary.regress](#) to summarize results
[predict.regress](#) to generate predictions

Examples

```
result <- regress("diamonds", "price", c("carat","clarity"))
plot(result, plots = "dashboard", lines = c("line","loess"))
plot(result, plots = "coef", conf_lev = .99, intercept = TRUE)
plot(result, plots = "dist")
plot(result, plots = "scatter", lines = c("line","loess"))
plot(result, plots = "correlations")
plot(result, plots = "resid_pred", lines = "line")
```

plot.repeater	<i>Plot repeated simulation</i>
---------------	---------------------------------

Description

Plot repeated simulation

Usage

```
## S3 method for class 'repeater'
plot(x, shiny = FALSE, custom = FALSE, ...)
```

Arguments

x	Return value from repeater
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

plot.simulater	<i>Plot method for the simulater function</i>
----------------	---

Description

Plot method for the simulater function

Usage

```
## S3 method for class 'simulater'
plot(x, shiny = FALSE, custom = FALSE, ...)
```

Arguments

x	Return value from simulator
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/simulator> for an example in Radiant

See Also

[simulator](#) to generate the result
[summary.simulator](#) to summarize results

Examples

```
result <- simulator(const = "cost 3", norm = "demand 2000 1000",
                    discrete = "price 5 8 .3 .7",
                    form = "profit = demand * (price - cost)")
plot(result)
```

predict.ann	<i>Predict method for the ann function</i>
-------------	--

Description

Predict method for the ann function

Usage

```
## S3 method for class 'ann'
predict(object, pred_data = "", pred_cmd = "",
        conf_lev = 0.95, se = FALSE, dec = 3, ...)
```

Arguments

object	Return value from ann
pred_data	Provide the name of a dataframe to generate predictions (e.g., "titanic"). The dataset must contain all columns used in the estimation
pred_cmd	Generate predictions using a command. For example, 'pclass = levels(pclass)' would produce predictions for the different levels of factor 'pclass'. To add another variable use a ',' (e.g., 'pclass = levels(pclass), age = seq(0,100,20)')
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)

se	Logical that indicates if prediction standard errors should be calculated (default = FALSE)
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/ann.html> for an example in Radiant

See Also

[ann](#) to generate the result

[summary.ann](#) to summarize results

Examples

```
result <- ann("titanic", "survived", c("pclass","sex"), lev = "Yes")
predict(result, pred_cmd = "pclass = levels(pclass)")
result <- ann("diamonds", "price", "carat:color", type = "regression")
predict(result, pred_cmd = "carat = 1:3")
predict(result, pred_data = "diamonds") %>% head
```

predict.crtree	<i>Predict method for the crtree function</i>
----------------	---

Description

Predict method for the crtree function

Usage

```
## S3 method for class 'crtree'
predict(object, pred_data = "", pred_cmd = "",
        conf_lev = 0.95, se = FALSE, dec = 3, ...)
```

Arguments

object	Return value from crtree
pred_data	Provide the name of a dataframe to generate predictions (e.g., "titanic"). The dataset must contain all columns used in the estimation
pred_cmd	Generate predictions using a command. For example, 'pclass = levels(pclass)' would produce predictions for the different levels of factor 'pclass'. To add another variable use a ',' (e.g., 'pclass = levels(pclass), age = seq(0,100,20)')
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)
se	Logical that indicates if prediction standard errors should be calculated (default = FALSE)
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/crtree.html> for an example in Radiant

See Also

`crtree` to generate the result

`summary.crtree` to summarize results

Examples

```
result <- crtree("titanic", "survived", c("pclass","sex"), lev = "Yes")
predict(result, pred_cmd = "pclass = levels(pclass)")
result <- crtree("titanic", "survived", "pclass", lev = "Yes")
predict(result, pred_data = "titanic") %>% head
```

predict.logistic	<i>Predict method for the logistic function</i>
------------------	---

Description

Predict method for the logistic function

Usage

```
## S3 method for class 'logistic'
predict(object, pred_data = "", pred_cmd = "",
  conf_lev = 0.95, se = FALSE, dec = 3, ...)
```

Arguments

object	Return value from <code>logistic</code>
pred_data	Provide the name of a dataframe to generate predictions (e.g., "titanic"). The dataset must contain all columns used in the estimation
pred_cmd	Generate predictions using a command. For example, 'pclass = levels(pclass)' would produce predictions for the different levels of factor 'pclass'. To add another variable use a ',' (e.g., 'pclass = levels(pclass), age = seq(0,100,20)')
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)
se	Logical that indicates if prediction standard errors should be calculated (default = FALSE)
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/logistic.html> for an example in Radiant

See Also

`logistic` to generate the result
`summary.logistic` to summarize results
`plot.logistic` to plot results
`plot.model.predict` to plot prediction output

Examples

```
result <- logistic("titanic", "survived", c("pclass","sex"), lev = "Yes")
predict(result, pred_cmd = "pclass = levels(pclass)")
logistic("titanic", "survived", c("pclass","sex"), lev = "Yes") %>%
  predict(pred_cmd = "sex = c('male','female')")
logistic("titanic", "survived", c("pclass","sex"), lev = "Yes") %>%
  predict(pred_data = "titanic")
```

predict.nb	<i>Predict method for the nb function</i>
------------	---

Description

Predict method for the nb function

Usage

```
## S3 method for class 'nb'
predict(object, pred_data = "", pred_cmd = "",
  pred_names = "", dec = 3, ...)
```

Arguments

object	Return value from <code>nb</code>
pred_data	Provide the name of a dataframe to generate predictions (e.g., "titanic"). The dataset must contain all columns used in the estimation
pred_cmd	Generate predictions using a command. For example, 'pclass = levels(pclass)' would produce predictions for the different levels of factor 'pclass'. To add another variable use a ',' (e.g., 'pclass = levels(pclass), age = seq(0,100,20)')
pred_names	Names for the predictions to be stored. If one name is provided, only the first column of predictions is stored. If empty, the level in the response variable of the nb model will be used
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/nb.html> for an example in Radiant

See Also

[nb](#) to generate the result

[summary.nb](#) to summarize results

Examples

```
result <- nb("titanic", "survived", c("pclass", "sex", "age"))
predict(result, pred_data = "titanic")
predict(result, pred_data = "titanic", pred_names = c("Yes", "No"))
predict(result, pred_cmd = "pclass = levels(pclass)")
result <- nb("titanic", "pclass", c("survived", "sex", "age"))
predict(result, pred_data = "titanic")
predict(result, pred_data = "titanic", pred_names = c("1st", "2nd", "3rd"))
predict(result, pred_data = "titanic", pred_names = "")
predict(result, pred_data = "titanic", pred_names = NA)
```

predict.regress

Predict method for the regress function

Description

Predict method for the regress function

Usage

```
## S3 method for class 'regress'
predict(object, pred_data = "", pred_cmd = "",
        conf_lev = 0.95, se = TRUE, dec = 3, ...)
```

Arguments

object	Return value from regress
pred_data	Name of the dataset to use for prediction
pred_cmd	Command used to generate data for prediction
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)
se	Logical that indicates if prediction standard errors should be calculated (default = FALSE)
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/regress.html> for an example in Radiant

See Also

[regress](#) to generate the result

[summary.regress](#) to summarize results

[plot.regress](#) to plot results

Examples

```
result <- regress("diamonds", "price", c("carat","clarity"))
predict(result, pred_cmd = "carat = 1:10")
predict(result, pred_cmd = "clarity = levels(clarity)")
result <- regress("diamonds", "price", c("carat","clarity"), int = c("carat:clarity"))
dpred <- getdata("diamonds") %>% slice(1:10)
predict(result, pred_data = "dpred")
rm(dpred, envir = .GlobalEnv)
```

predict_model	<i>Predict method for model functions</i>
---------------	---

Description

Predict method for model functions

Usage

```
predict_model(object, pfun, mclass, pred_data = "", pred_cmd = "",
  conf_lev = 0.95, se = FALSE, dec = 3, ...)
```

Arguments

object	Return value from regress
pfun	Function to use for prediction
mclass	Model class to attach
pred_data	Name of the dataset to use for prediction
pred_cmd	Command used to generate data for prediction
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)
se	Logical that indicates if prediction standard errors should be calculated (default = FALSE)
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/regress.html> for an example in Radiant

print.ann.predict	<i>Print method for predict.ann</i>
-------------------	-------------------------------------

Description

Print method for predict.ann

Usage

```
## S3 method for class 'ann.predict'  
print(x, ..., n = 10)
```

Arguments

x	Return value from prediction method
...	further arguments passed to or from other methods
n	Number of lines of prediction results to print. Use -1 to print all lines

print.crtree.predict	<i>Print method for predict.crtree</i>
----------------------	--

Description

Print method for predict.crtree

Usage

```
## S3 method for class 'crtree.predict'  
print(x, ..., n = 10)
```

Arguments

x	Return value from prediction method
...	further arguments passed to or from other methods
n	Number of lines of prediction results to print. Use -1 to print all lines

```
print.logistic.predict
```

Print method for logistic.predict

Description

Print method for logistic.predict

Usage

```
## S3 method for class 'logistic.predict'  
print(x, ..., n = 10)
```

Arguments

x	Return value from prediction method
...	further arguments passed to or from other methods
n	Number of lines of prediction results to print. Use -1 to print all lines

```
print.nb.predict
```

Print method for predict.nb

Description

Print method for predict.nb

Usage

```
## S3 method for class 'nb.predict'  
print(x, ..., n = 10)
```

Arguments

x	Return value from prediction method
...	further arguments passed to or from other methods
n	Number of lines of prediction results to print. Use -1 to print all lines

print.regress.predict *Print method for predict.regress*

Description

Print method for predict.regress

Usage

```
## S3 method for class 'regress.predict'  
print(x, ..., n = 10)
```

Arguments

x	Return value from prediction method
...	further arguments passed to or from other methods
n	Number of lines of prediction results to print. Use -1 to print all lines

print_predict_model *Print method for the model prediction*

Description

Print method for the model prediction

Usage

```
print_predict_model(x, ..., n = 10, header = "")
```

Arguments

x	Return value from prediction method
...	further arguments passed to or from other methods
n	Number of lines of prediction results to print. Use -1 to print all lines
header	Header line

radiant.model	<i>radiant.model</i>
---------------	----------------------

Description

radiant.model
Launch Radiant in the default browser

Usage

radiant.model()

Details

See <http://radiant-rstats.github.io/docs> for documentation and tutorials

radiant.model-deprecated	<i>Deprecated function(s) in the radiant.model package</i>
--------------------------	--

Description

These functions are provided for compatibility with previous versions of radiant. They will eventually be removed.

Usage

regression(...)

Arguments

... Parameters to be passed to the updated functions

Details

regression is now a synonym for [regress](#)
 glm_reg is now a synonym for [logistic](#)
 performance is now a synonym for [evalbin](#)

regress	<i>Linear regression using OLS</i>
---------	------------------------------------

Description

Linear regression using OLS

Usage

```
regress(dataset, rvar, evar, int = "", check = "", data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
rvar	The response variable in the regression
evar	Explanatory variables in the regression
int	Interaction terms to include in the model
check	Use "standardize" to see standardized coefficient estimates. Use "stepwise-backward" (or "stepwise-forward", or "stepwise-both") to apply step-wise selection of variables in estimation
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://radiant-rstats.github.io/docs/model/regress.html> for an example in Radiant

Value

A list of all variables used in the regress function as an object of class `regress`

See Also

`summary.regress` to summarize results
`plot.regress` to plot results
`predict.regress` to generate predictions

Examples

```
result <- regress("diamonds", "price", c("carat","clarity"))
result <- regress("diamonds", "price", c("carat","clarity"), check = "standardize")
```

render.DiagrammeR	<i>Method to render DiagrammeR plots</i>
-------------------	--

Description

Method to render DiagrammeR plots

Usage

```
## S3 method for class 'DiagrammeR'
render(object, ...)
```

Arguments

object	DiagrammeR plot
...	Additional arguments

repeater	<i>Repeat simulation</i>
----------	--------------------------

Description

Repeat simulation

Usage

```
repeater(nr = 12, vars = "", grid = "", sum_vars = "", byvar = "sim",
  fun = "sum_rm", form = "", seed = "", name = "", sim = "")
```

Arguments

nr	Number times to repeat the simulation
vars	Variables to use in repeated simulation
grid	Expression to use in grid search for constants
sum_vars	(Numeric) variables to summaries
byvar	Variable(s) to group data by before summarizing
fun	Functions to use for summarizing
form	A string with the formula to apply to the summarized data
seed	To repeat a simulation with the same randomly generated values enter a number into Random seed input box.
name	To save the simulated data for further analysis specify a name in the Sim name input box. You can then investigate the simulated data by choosing the specified name from the Datasets dropdown in any of the other Data tabs.
sim	Return value from the simulator function

Examples

```
result <- simulator(const = "var_cost 5;fixed_cost 1000;", norm = "E 0 100;",
  discrete = "price 6 8 .3 .7;",
  form = "demand = 1000 - 50*price + E;
  profit = demand*(price-var_cost) - fixed_cost;
  profit_small = profit < 100",
  seed = "1234")
repeater(nr = 12, vars = c("E","price"), sum_vars = "profit",
  byvar = "sim", form = "profit_365 = profit < 36500",
  seed = "1234", sim = result) %>% head
```

scaledf	<i>Center or standardize variables in a data frame</i>
---------	--

Description

Center or standardize variables in a data frame

Usage

```
scaledf(dat, center = TRUE, scale = TRUE, sf = 2, wts = NULL,  
        calc = TRUE)
```

Arguments

dat	Data frame
center	Center data (TRUE or FALSE)
scale	Scale data (TRUE or FALSE)
sf	Scaling factor (default is 2)
wts	Weights to use (default is NULL for no weights)
calc	Calculate mean and sd or use attributes attached to dat

Value

Scaled data frame

See Also

[copy_attr](#) to copy attributes from a training to a validation dataset

sdw	<i>Standard deviation of weighted sum of variables</i>
-----	--

Description

Standard deviation of weighted sum of variables

Usage

```
sdw(...)
```

Arguments

...	A matched number of weights and stocks
-----	--

Value

A vector of standard deviation estimates

sensitivity	<i>Method to evaluate sensitivity of an analysis</i>
-------------	--

Description

Method to evaluate sensitivity of an analysis

Usage

```
sensitivity(object, ...)
```

Arguments

object	Object of relevant class for which to evaluate sensitivity
...	Additional arguments

sensitivity.dtree	<i>Evaluate sensitivity of the decision tree</i>
-------------------	--

Description

Evaluate sensitivity of the decision tree

Usage

```
## S3 method for class 'dtree'
sensitivity(object, vars = NULL, decs = NULL,
  shiny = FALSE, custom = FALSE, ...)
```

Arguments

object	Return value from dtree
vars	Variables to include in the sensitivity analysis
decs	Decisions to include in the sensitivity analysis
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	Additional arguments

Details

See <http://radiant-rstats.github.io/docs/model/dtree.html> for an example in Radiant

See Also

[dtree](#) to generate the result
[plot.dtree](#) to summarize results
[summary.dtree](#) to summarize results

simulater

*Simulate data for decision analysis***Description**

Simulate data for decision analysis

Usage

```
simulater(const = "", lnorm = "", norm = "", unif = "", discrete = "",
  binom = "", sequ = "", grid = "", data = "", form = "", seed = "",
  name = "", nr = 1000, dat = NULL)
```

Arguments

const	A string listing the constants to include in the analysis (e.g., "cost = 3; size = 4")
lnorm	A string listing the log-normally distributed random variables to include in the analysis (e.g., "demand 2000 1000" where the first number is the log-mean and the second is the log-standard deviation)
norm	A string listing the normally distributed random variables to include in the analysis (e.g., "demand 2000 1000" where the first number is the mean and the second is the standard deviation)
unif	A string listing the uniformly distributed random variables to include in the analysis (e.g., "demand 0 1" where the first number is the minimum value and the second is the maximum value)
discrete	A string listing the random variables with a discrete distribution to include in the analysis (e.g., "price 5 8 .3 .7" where the first set of numbers are the values and the second set the probabilities)
binom	A string listing the random variables with a binomial distribution to include in the analysis (e.g., "crash 100 .01") where the first number is the number of trials and the second is the probability of success)
sequ	A string listing the start and end for a sequence to include in the analysis (e.g., "trend 1 100 1"). The number of 'steps' is determined by the number of simulations.
grid	A string listing the start, end, and step for a set of sequences to include in the analysis (e.g., "trend 1 100 1"). The number of rows in the expanded will override the number of simulations
data	Name of a dataset to be used in the calculations
form	A string with the formula to evaluate (e.g., "profit = demand * (price - cost)")
seed	To repeat a simulation with the same randomly generated values enter a number into Random seed input box.
name	To save the simulated data for further analysis specify a name in the Sim name input box. You can then investigate the simulated data by choosing the specified name from the Datasets dropdown in any of the other Data tabs.
nr	Number of simulations
dat	Data list from previous simulation. Used by repeater function

Details

See <http://radiant-rstats.github.io/docs/model/simulator.html> for an example in Radiant

Value

A data.frame with the created variables

See Also

`summary.simulater` to summarize results

`plot.simulater` to plot results

Examples

```
result <- simulator(const = "cost 3", norm = "demand 2000 1000",
  discrete = "price 5 8 .3 .7",
  form = "profit = demand * (price - cost)")
```

sim_cleaner

Clean input command string

Description

Clean input command string

Usage

```
sim_cleaner(x)
```

Arguments

x Input string

Value

Cleaned string

sim_splitter	<i>Split input command string</i>
--------------	-----------------------------------

Description

Split input command string

Usage

```
sim_splitter(x, symbol = " ")
```

Arguments

x	Input string
symbol	Symbol used to split the command string

Value

Split input command string

sim_summary	<i>Print simulation summary</i>
-------------	---------------------------------

Description

Print simulation summary

Usage

```
sim_summary(dat, dc = getclass(dat), fun = "", dec = 4)
```

Arguments

dat	Simulated data
dc	Variable classes
fun	Summary function to apply
dec	Number of decimals to show

store.crs	<i>Store predicted values generated in the crs function</i>
-----------	---

Description

Store predicted values generated in the crs function

Usage

```
## S3 method for class 'crs'
store(object, name = "predict_cf", envir = parent.frame(),
      ...)
```

Arguments

object	Return value from crs
name	Name of the dataset to store
envir	Environment to assign 'new' dataset (optional). Used when an r_data list is not available
...	further arguments passed to or from other methods

Details

Store data frame with predictions in Radiant r_data list if available. See <http://radiant-rstats.github.io/docs/model/crs.html> for an example in Radiant

store.model	<i>Store residuals from a model</i>
-------------	-------------------------------------

Description

Store residuals from a model

Usage

```
## S3 method for class 'model'
store(object, ..., name = "residuals")
```

Arguments

object	Return value from a model function
...	Additional arguments
name	Variable name(s) assigned to predicted values

Details

See <http://radiant-rstats.github.io/docs/model/regress.html> for an example in Radiant

Examples

```
regress(diamonds, rvar = "price", evar = c("carat","cut")) %>%
  store %>% head
```

store.model.predict	<i>Store predicted values generated in model functions</i>
---------------------	--

Description

Store predicted values generated in model functions

Usage

```
## S3 method for class 'model.predict'
store(object, ..., data = attr(object, "pred_data"),
      name = "prediction")
```

Arguments

object	Return value from model function
...	Additional arguments
data	Data or dataset name (e.g., data = mtcars or data = "mtcars")
name	Variable name(s) assigned to predicted values

Details

See <http://radiant-rstats.github.io/docs/model/regress.html> for an example in Radiant

Examples

```
regress(diamonds, rvar = "price", evar = c("carat","cut")) %>%
  predict(diamonds) %>%
  store(name = "pred, pred_low, pred_high") %>% head
```

store.nb.predict	<i>Store predicted values generated in the nb function</i>
------------------	--

Description

Store predicted values generated in the nb function

Usage

```
## S3 method for class 'nb.predict'
store(object, ..., data = attr(object, "pred_data"),
      name = "")
```

Arguments

object	Return value from model function
...	Additional arguments
data	Data or dataset name (e.g., data = mtcars or data = "mtcars")
name	Variable name(s) assigned to predicted values. If empty, the levels of the response variable will be used

Details

See <http://radiant-rstats.github.io/docs/model/nb.html> for an example in Radiant

Examples

```
result <- nb("titanic", "survived", c("pclass", "sex", "age"))
pred <- predict(result, pred_data = "titanic")
store(pred, data = titanic, name = "pred") %>% head
store(pred, data = titanic) %>% head
```

store_ann	<i>Deprecated function to store predictions from an ANN</i>
-----------	---

Description

Deprecated function to store predictions from an ANN

Usage

```
store_ann(object, data = object$dataset, name = paste0("predict_ann"))
```

Arguments

object	Return value from predict.ann
data	Dataset name
name	Variable name assigned to the residuals or predicted values

Details

Use [store.model.predict](#) or [store.model](#) instead

store_glm	<i>Deprecated function to store logistic regression residuals and predictions</i>
-----------	---

Description

Deprecated function to store logistic regression residuals and predictions

Usage

```
store_glm(object, data = object$dataset, type = "residuals",  
          name = paste0(type, "_logit"))
```

Arguments

object	Return value from logistic or predict.logistic
data	Dataset name
type	Residuals ("residuals") or predictions ("predictions"). For predictions the dataset name must be provided
name	Variable name assigned to the residuals or predicted values

Details

Use [store.model.predict](#) or [store.model](#) instead

store_reg	<i>Deprecated function to store regression residuals and predictions</i>
-----------	--

Description

Deprecated function to store regression residuals and predictions

Usage

```
store_reg(object, data = object$dataset, type = "residuals",  
          name = paste0(type, "_reg"))
```

Arguments

object	Return value from regress or predict.regress
data	Dataset name
type	Residuals ("residuals") or predictions ("predictions"). For predictions the dataset name must be provided
name	Variable name assigned to the residuals or predicted values

Details

Use [store.model.predict](#) or [store.model](#) instead

summary.ann	<i>Summary method for the ann function</i>
-------------	--

Description

Summary method for the ann function

Usage

```
## S3 method for class 'ann'  
summary(object, prn = TRUE, ...)
```

Arguments

object	Return value from ann
prn	Print list of weights
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/ann.html> for an example in Radiant

See Also

[ann](#) to generate results
[plot.ann](#) to plot results
[predict.ann](#) for prediction

Examples

```
result <- ann("titanic", "survived", "pclass", lev = "Yes")  
summary(result)
```

summary.confusion	<i>Summary method for the confusion matrix</i>
-------------------	--

Description

Summary method for the confusion matrix

Usage

```
## S3 method for class 'confusion'  
summary(object, ...)
```

Arguments

object	Return value from confusion
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/evalbin.html> for an example in Radiant

See Also

[confusion](#) to generate results

[plot.confusion](#) to visualize result

summary.crs

Summary method for Collaborative Filter

Description

Summary method for Collaborative Filter

Usage

```
## S3 method for class 'crs'
summary(object, n = 36, ...)
```

Arguments

object	Return value from crs
n	Number of lines of recommendations to print. Use -1 to print all lines
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/crs.html> for an example in Radiant

See Also

[crs](#) to generate the results

[plot.crs](#) to plot results

summary.crtree

Summary method for the crtree function

Description

Summary method for the crtree function

Usage

```
## S3 method for class 'crtree'
summary(object, prn = TRUE, ...)
```

Arguments

object	Return value from crtree
prn	Print tree in text form
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/crtree.html> for an example in Radiant

See Also

[crtree](#) to generate results
[plot.crtree](#) to plot results
[predict.crtree](#) for prediction

Examples

```
result <- crtree("titanic", "survived", c("pclass","sex"), lev = "Yes")
summary(result)
result <- crtree("diamonds", "price", c("carat","color"), type = "regression")
summary(result)
```

summary.dtree	<i>Summary method for the dtree function</i>
---------------	--

Description

Summary method for the dtree function

Usage

```
## S3 method for class 'dtree'
summary(object, ...)
```

Arguments

object	Return value from simulator
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/dtree.html> for an example in Radiant

See Also

[dtree](#) to generate the results
[plot.dtree](#) to plot results
[sensitivity.dtree](#) to plot results

summary.evalbin	<i>Summary method for the evalbin function</i>
-----------------	--

Description

Summary method for the evalbin function

Usage

```
## S3 method for class 'evalbin'  
summary(object, prn = TRUE, ...)
```

Arguments

object	Return value from evalbin
prn	Print full table of measures per model and bin
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/evalbin.html> for an example in Radiant

See Also

[evalbin](#) to summarize results
[plot.evalbin](#) to plot results

Examples

```
evalbin("titanic", "age", "survived") %>% summary  
evalbin("titanic", c("age", "fare"), "survived") %>% summary
```

summary.evalreg	<i>Summary method for the evalreg function</i>
-----------------	--

Description

Summary method for the evalreg function

Usage

```
## S3 method for class 'evalreg'  
summary(object, ...)
```

Arguments

object	Return value from evalreg
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/evalreg.html> for an example in Radiant

See Also

[evalreg](#) to summarize results

[plot.evalreg](#) to plot results

summary.logistic	<i>Summary method for the logistic function</i>
------------------	---

Description

Summary method for the logistic function

Usage

```
## S3 method for class 'logistic'
summary(object, sum_check = "", conf_lev = 0.95,
        test_var = "", dec = 3, ...)
```

Arguments

object	Return value from logistic
sum_check	Optional output. "vif" to show multicollinearity diagnostics. "confint" to show coefficient confidence interval estimates. "odds" to show odds ratios and confidence interval estimates.
conf_lev	Confidence level to use for coefficient and odds confidence intervals (.95 is the default)
test_var	Variables to evaluate in model comparison (i.e., a competing models Chi-squared test)
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/logistic.html> for an example in Radiant

See Also

[logistic](#) to generate the results

[plot.logistic](#) to plot the results

[predict.logistic](#) to generate predictions

[plot.model.predict](#) to plot prediction output

Examples

```
result <- logistic("titanic", "survived", "pclass", lev = "Yes")
summary(result, test_var = "pclass")
res <- logistic("titanic", "survived", c("pclass","sex"), int="pclass:sex", lev="Yes")
summary(res, sum_check = c("vif","confint","odds"))
titanic %>% logistic("survived", c("pclass","sex","age"), lev = "Yes") %>% summary("vif")
```

summary.nb

*Summary method for the nb function***Description**

Summary method for the nb function

Usage

```
## S3 method for class 'nb'
summary(object, dec = 3, ...)
```

Arguments

object	Return value from nb
dec	Decimals
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/nb.html> for an example in Radiant

See Also

[nb](#) to generate results
[plot.nb](#) to plot results
[predict.nb](#) for prediction

Examples

```
result <- nb("titanic", "survived", c("pclass","sex","age"))
summary(result)
```

summary.regress

*Summary method for the regress function***Description**

Summary method for the regress function

Usage

```
## S3 method for class 'regress'
summary(object, sum_check = "", conf_lev = 0.95,
        test_var = "", dec = 3, ...)
```

Arguments

object	Return value from regress
sum_check	Optional output. "rsme" to show the root mean squared error and the standard deviation of the residuals. "sumsquares" to show the sum of squares table. "vif" to show multicollinearity diagnostics. "confint" to show coefficient confidence interval estimates.
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)
test_var	Variables to evaluate in model comparison (i.e., a competing models F-test)
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/regress.html> for an example in Radiant

See Also

[regress](#) to generate the results
[plot.regress](#) to plot results
[predict.regress](#) to generate predictions

Examples

```
result <- regress("diamonds", "price", c("carat","clarity"))
summary(result, sum_check = c("rmse","sumsquares","vif","confint"), test_var = "clarity")
result <- regress("ideal", "y", c("x1","x2"))
summary(result, test_var = "x2")
ideal %>% regress("y", "x1:x3") %>% summary
```

summary.repeater	<i>Summarize repeated simulation</i>
------------------	--------------------------------------

Description

Summarize repeated simulation

Usage

```
## S3 method for class 'repeater'  
summary(object, dec = 4, ...)
```

Arguments

object	Return value from repeater
dec	Number of decimals to show
...	further arguments passed to or from other methods

summary.simulater	<i>Summary method for the simulater function</i>
-------------------	--

Description

Summary method for the simulater function

Usage

```
## S3 method for class 'simulater'  
summary(object, dec = 4, ...)
```

Arguments

object	Return value from simulater
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <http://radiant-rstats.github.io/docs/model/simulater.html> for an example in Radiant

See Also

[simulater](#) to generate the results
[plot.simulater](#) to plot results

Examples

```
result <- simulater(norm = "demand 2000 1000")  
summary(result)
```

test_specs	<i>Add interaction terms to list of test variables if needed</i>
------------	--

Description

Add interaction terms to list of test variables if needed

Usage

```
test_specs(test_var, int)
```

Arguments

test_var	List of variables to use for testing for regress or logistic
int	Interaction terms specified

Details

See <http://radiant-rstats.github.io/docs/model/regress.html> for an example in Radiant

Value

A vector of variables names to test

Examples

```
test_specs("a", c("a:b", "b:c"))
```

var_check	<i>Check if main effects for all interaction effects are included in the model If ':' is used to select a range _evar_ is updated</i>
-----------	---

Description

Check if main effects for all interaction effects are included in the model If ':' is used to select a range _evar_ is updated

Usage

```
var_check(ev, cn, intv = "")
```

Arguments

ev	List of explanatory variables provided to _regress_ or _logistic_
cn	Column names for all explanatory variables in _dat_
intv	Interaction terms specified

Details

See <http://radiant-rstats.github.io/docs/model/regress.html> for an example in Radiant

Value

'vars' is a vector of right-hand side variables, possibly with interactions, 'iv' is the list of explanatory variables, and intv are interaction terms

Examples

```
var_check("a:d", c("a", "b", "c", "d"))
var_check(c("a", "b"), c("a", "b"), "a:c")
```

write.coeff	<i>Write coefficient table for linear and logistic regression</i>
-------------	---

Description

Write coefficient table for linear and logistic regression

Usage

```
write.coeff(object, file = "", sort = FALSE)
```

Arguments

object	A fitted model object of class regress or logistic
file	A character string naming a file. "" indicates output to the console
sort	Sort table by variable importance

Details

Write coefficients and importance scores to csv

Examples

```
regress(diamonds, rvar = "price", evar = "carat:x", check = "standardize") %>%
  write.coeff(sort = TRUE) %>%
  formatdf(dec = 3)
```

Index

*Topic **datasets**

- catalog, [5](#)
- cf, [6](#)
- direct_marketing, [10](#)
- dvd, [11](#)
- houseprices, [14](#)
- ideal, [15](#)

ann, [3](#), [18](#), [29](#), [30](#), [50](#)

auc, [4](#)

catalog, [5](#)

cf, [6](#)

confint_robust, [6](#)

confusion, [7](#), [19](#), [50](#), [51](#)

copy_attr, [41](#)

crs, [8](#), [19](#), [20](#), [51](#)

crtree, [8](#), [20](#), [30](#), [31](#), [52](#)

direct_marketing, [10](#)

dtree, [10](#), [11](#), [21](#), [42](#), [52](#)

dtree_parser, [11](#)

dvd, [11](#)

evalbin, [5](#), [12](#), [22](#), [38](#), [53](#)

evalreg, [13](#), [23](#), [53](#), [54](#)

find_max, [13](#)

find_min, [14](#)

glm_reg (radiant.model-deprecated), [38](#)

houseprices, [14](#)

ideal, [15](#)

logistic, [15](#), [23](#), [24](#), [31](#), [32](#), [38](#), [49](#), [54](#)

minmax, [16](#)

nb, [17](#), [25](#), [32](#), [33](#), [55](#)

performance (radiant.model-deprecated), [38](#)

plot.ann, [4](#), [18](#), [50](#)

plot.confusion, [7](#), [19](#), [51](#)

plot.crs, [19](#), [51](#)

plot.crtree, [9](#), [20](#), [52](#)

plot.dtree, [10](#), [11](#), [21](#), [42](#), [52](#)

plot.evalbin, [5](#), [12](#), [22](#), [53](#)

plot.evalreg, [13](#), [23](#), [54](#)

plot.logistic, [16](#), [23](#), [24](#), [32](#), [54](#)

plot.model.predict, [16](#), [24](#), [24](#), [32](#), [54](#)

plot.nb, [17](#), [25](#), [55](#)

plot.nb.predict, [26](#)

plot.regress, [27](#), [33](#), [39](#), [56](#)

plot.repeater, [28](#)

plot.rpart, [20](#)

plot.simulator, [28](#), [44](#), [57](#)

predict.ann, [4](#), [18](#), [29](#), [48](#), [50](#)

predict.crtree, [9](#), [20](#), [30](#), [52](#)

predict.logistic, [16](#), [24](#), [25](#), [31](#), [49](#), [54](#)

predict.nb, [17](#), [25](#), [26](#), [32](#), [55](#)

predict.regress, [25](#), [27](#), [33](#), [39](#), [49](#), [56](#)

predict_model, [34](#)

print.ann.predict, [35](#)

print.crtree.predict, [35](#)

print.logistic.predict, [36](#)

print.nb.predict, [36](#)

print.regress.predict, [37](#)

print_predict_model, [37](#)

radiant.model, [38](#)

radiant.model-deprecated, [38](#)

radiant.model-deprecated-package (radiant.model-deprecated), [38](#)

radiant.model-package (radiant.model), [38](#)

regress, [27](#), [33](#), [34](#), [38](#), [38](#), [49](#), [56](#)

regression (radiant.model-deprecated), [38](#)

render.DiagrammeR, [39](#)

repeater, [28](#), [40](#), [57](#)

scaledf, [41](#)

sdw, [41](#)

sensitivity, [42](#)

sensitivity.dtree, [10](#), [21](#), [42](#), [52](#)

sim_cleaner, [44](#)

sim_splitter, [45](#)

`sim_summary`, 45
`simulator`, 29, 43, 52, 57
`store.crs`, 46
`store.model`, 46, 48, 49
`store.model.predict`, 47, 48, 49
`store.nb.predict`, 47
`store_ann`, 48
`store_glm`, 49
`store_reg`, 49
`summary.ann`, 4, 18, 30, 50
`summary.confusion`, 7, 19, 50
`summary.crs`, 20, 51
`summary.crtree`, 9, 20, 31, 51
`summary.dtree`, 10, 11, 21, 42, 52
`summary.evalbin`, 5, 12, 22, 53
`summary.evalreg`, 13, 23, 53
`summary.logistic`, 16, 32, 54
`summary.nb`, 17, 25, 33, 55
`summary.regress`, 27, 33, 39, 56
`summary.repeater`, 57
`summary.simulator`, 29, 44, 57

`test_specs`, 58

`var_check`, 58

`write.coeff`, 59