

Package ‘radiant.design’

June 24, 2016

Type Package

Title Design menu for Radiant. Builds on the radiant.data package

Version 0.5.0

Date 2016-6-24

Description Design menu for Radiant.

Depends R (>= 3.2.0),
radiant.data (>= 0.5)

Imports dplyr (>= 0.4.3),
broom (>= 0.4.0),
shiny (>= 0.13.2.9003),
AlgDesign (>= 1.1.7.3),
import (>= 1.1.0),
methods

URL <https://github.com/radiant-rstats/radiant.design>, <http://vnijs.github.io/radiant/>

BugReports <https://github.com/radiant-rstats/radiant.design/issues>

License AGPL-3 | file LICENSE

LazyData true

RoxygenNote 5.0.1

R topics documented:

doe	2
radiant.design	2
rndnames	3
sample_size	3
sample_size_comp	4
sampling	5
summary.doe	6
summary.sample_size	6
summary.sample_size_comp	7
summary.sampling	8

Index	9
--------------	----------

doe	<i>Create (partial) factorial design</i>
-----	--

Description

Create (partial) factorial design

Usage

```
doe(factors, int = "", trials = NA, seed = NA)
```

Arguments

factors	Categorical variables used as input for design
int	Vector of interaction terms to consider when generating design
trials	Number of trial to create. If NA then all feasible designs will be considered until a design with perfect D-efficiency is found
seed	Random seed to use as the starting point

Details

See <http://vnijs.github.io/radiant/analytics/doe.html> for an example in Radiant

Value

A list with all variables defined in the function as an object of class doe

See Also

[summary.doe](#) to summarize results

Examples

```
"price; $10; $13; $16\nfood; popcorn; gourmet; no food" %>% doe
```

radiant.design	<i>radiant.design</i>
----------------	-----------------------

Description

radiant.design
Launch Radiant in the default browser

Usage

```
radiant.design()
```

Details

See <http://vnijs.github.io/radiant> for documentation and tutorials

<code>rndnames</code>	<i>100 random names</i>
-----------------------	-------------------------

Description

100 random names

Usage

```
data(rndnames)
```

Format

A data frame with 100 rows and 2 variables

Details

A list of 100 random names generated by listofrandomnames.com. Description provided in `attr(rndnames,"description")`

<code>sample_size</code>	<i>Sample size calculation</i>
--------------------------	--------------------------------

Description

Sample size calculation

Usage

```
sample_size(type = "mean", err_mean = 2, sd_mean = 10, err_prop = 0.1,  
            p_prop = 0.5, conf_lev = 1.96, incidence = 1, response = 1,  
            pop_correction = "no", pop_size = 1000000)
```

Arguments

<code>type</code>	Choose "mean" or "proportion"
<code>err_mean</code>	Acceptable Error for Mean
<code>sd_mean</code>	Standard deviation for Mean
<code>err_prop</code>	Acceptable Error for Proportion
<code>p_prop</code>	Initial proportion estimate for Proportion
<code>conf_lev</code>	Confidence level
<code>incidence</code>	Incidence rate (i.e., fraction of valid respondents)
<code>response</code>	Response rate
<code>pop_correction</code>	Apply correction for population size ("yes","no")
<code>pop_size</code>	Population size

Details

See http://vnijs.github.io/radiant/quant/sample_size.html for an example in Radiant

Value

A list of variables defined in sample_size as an object of class sample_size

See Also

`summary.sample_size` to summarize results

Examples

```
result <- sample_size(type = "mean", err_mean = 2, sd_mean = 10)
```

sample_size_comp

Sample size calculation for comparisons

Description

Sample size calculation for comparisons

Usage

```
sample_size_comp(type, n = NULL, p1 = NULL, p2 = NULL, delta = NULL,
  sd = NULL, conf_lev = NULL, power = NULL, ratio = 1,
  alternative = "two.sided")
```

Arguments

type	Choose "mean" or "proportion"
n	Sample size
p1	Proportion 1 (only used when "proportion" is selected)
p2	Proportion 2 (only used when "proportion" is selected)
delta	Difference in means between two groups (only used when "mean" is selected)
sd	Standard deviation (only used when "mean" is selected)
conf_lev	Confidence level
power	Power
ratio	Sampling ratio (n1 / n2)
alternative	Two or one sided test

Details

See http://vnijs.github.io/radiant/quant/sample_size_comp.html for an example in Radiant

Value

A list of variables defined in sample_size_comp as an object of class sample_size_comp

See Also

[summary.sample_size_comp](#) to summarize results

sampling	<i>Simple random sampling</i>
----------	-------------------------------

Description

Simple random sampling

Usage

```
sampling(dataset, var, sample_size, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
var	The variable to sample from
sample_size	Number of units to select
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://vnijs.github.io/radiant/quant/sampling.html> for an example in Radiant

Value

A list of variables defined in sampling as an object of class `sampling`

See Also

[summary.sampling](#) to summarize results

Examples

```
result <- sampling("rndnames", "Names", 10)
```

summary.doe	<i>Summary method for doe function</i>
-------------	--

Description

Summary method for doe function

Usage

```
## S3 method for class 'doe'  
summary(object, eff = TRUE, part = TRUE, full = TRUE, ...)
```

Arguments

object	Return value from doe
eff	If TRUE print efficiency output
part	If TRUE print partial factorial
full	If TRUE print full factorial
...	further arguments passed to or from other methods.

Details

See <http://vnijs.github.io/radiant/analytics/doe.html> for an example in Radiant

See Also

[doe](#) to calculate results

Examples

```
"price; $10; $13; $16\nfood; popcorn; gourmet; no food" %>% doe %>% summary
```

summary.sample_size	<i>Summary method for the sample_size function</i>
---------------------	--

Description

Summary method for the sample_size function

Usage

```
## S3 method for class 'sample_size'  
summary(object, ...)
```

Arguments

object	Return value from sample_size
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/sample_size for an example in Radiant

See Also

[sample_size](#) to generate the results

Examples

```
result <- sample_size(type = "mean", err_mean = 2, sd_mean = 10)
summary(result)
```

```
summary.sample_size_comp
```

Summary method for the sample_size_comp function

Description

Summary method for the sample_size_comp function

Usage

```
## S3 method for class 'sample_size_comp'
summary(object, ...)
```

Arguments

object	Return value from sample_size_comp
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/sample_size_comp for an example in Radiant

See Also

[sample_size_comp](#) to generate the results

summary.sampling	<i>Summary method for the sampling function</i>
------------------	---

Description

Summary method for the sampling function

Usage

```
## S3 method for class 'sampling'  
summary(object, print_sf = TRUE, ...)
```

Arguments

object	Return value from sampling
print_sf	Print full sampling frame. Default is TRUE
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/sampling> for an example in Radiant

See Also

[sampling](#) to generate the results

Examples

```
set.seed(1234)  
result <- sampling("rndnames", "Names", 10)  
summary(result)
```


Index

*Topic **datasets**

 rndnames, [3](#)

doe, [2](#), [6](#)

radiant.design, [2](#)

radiant.design-package
 (radiant.design), [2](#)

rndnames, [3](#)

sample_size, [3](#), [6](#), [7](#)

sample_size_comp, [4](#), [7](#)

sampling, [5](#), [8](#)

summary.doe, [2](#), [6](#)

summary.sample_size, [4](#), [6](#)

summary.sample_size_comp, [5](#), [7](#)

summary.sampling, [5](#), [8](#)