

Package ‘radiant.multivariate’

May 1, 2018

Type Package

Title Multivariate Menu for Radiant: Business Analytics using R and Shiny

Version 0.9.3.1

Date 2018-4-27

Description The Radiant Multivariate menu includes interfaces for perceptual mapping, factor analysis, cluster analysis, and conjoint analysis. The application extends the functionality in radiant.data.

Depends R (>= 3.3.0),
radiant.data (>= 0.9.3.1)

Imports radiant.model (>= 0.9.3.1),
shiny (>= 1.0.5),
dplyr (>= 0.7.4),
rlang (>= 0.2.0),
ggplot2 (>= 2.2.1),
gridExtra (>= 2.0.0),
scales (>= 0.4.0),
magrittr (>= 1.5),
psych (>= 1.8.3.3),
GPArotation (>= 2014.11-1),
car (>= 2.1.1),
MASS (>= 7.3),
import (>= 1.1.0),
Gmedian (>= 1.2.3),
rstudioapi (>= 0.7),
ggrepel (>= 0.7),
methods

Suggests testthat (>= 2.0.0)

URL <https://github.com/radiant-rstats/radiant.multivariate>, <https://radiant-rstats.github.io/docs>

BugReports <https://github.com/radiant-rstats/radiant.multivariate/issues>

License AGPL-3 | file LICENSE

LazyData true

Encoding UTF-8

RoxygenNote 6.0.1

R topics documented:

carpet	3
city	3
city2	4
clean_loadings	4
computer	5
conjoint	5
full_factor	6
hclus	7
kclus	8
mds	9
movie	10
mp3	10
plot.conjoint	11
plot.full_factor	12
plot.hclus	13
plot.kclus	14
plot.mds	15
plot.pre_factor	16
plot.prmap	17
predict.conjoint	18
predict_conjoint_by	19
pre_factor	19
print.conjoint.predict	20
prmap	21
radiant.multivariate	22
radiant.multivariate-deprecated	22
radiant.multivariate_viewer	23
radiant.multivariate_window	23
retailers	24
shopping	24
store.conjoint	25
store.conjoint.predict	25
store.full_factor	26
store.kclus	26
summary.conjoint	27
summary.full_factor	28
summary.hclus	29
summary.kclus	29
summary.mds	30
summary.pre_factor	31
summary.prmap	31
the_table	32
toothpaste	33
tpbrands	33

carpet

Carpet cleaners

Description

Carpet cleaners

Usage

```
data(carpet)
```

Format

A data frame with 18 rows and 5 variables

Details

Rankings reflect the evaluation of 18 alternative carpet cleaners by one respondent. Description provided in `attr(carpet, "description")`

city

City distances

Description

City distances

Usage

```
data(city)
```

Format

A data frame with 45 rows and 3 variables

Details

Distance in miles between nine cities in the USA. The dataset is used to illustrate multi-dimensional scaling (MDS). Description provided in `attr(city, "description")`

city2

*City distances 2***Description**

City distances 2

Usage

data(city2)

Format

A data frame with 78 rows and 3 variables

Details

Distance in miles between 12 cities in the USA. The dataset is used to illustrate multi-dimensional scaling (MDS). Description provided in attr(city2, "description")

clean_loadings

*Sort and clean loadings***Description**

Sort and clean loadings

Usage

clean_loadings(floadings, cutoff = 0, fsort = FALSE, dec = 8, repl = NA)

Arguments

floadings	Data frame with loadings
cutoff	Show only loadings with (absolute) values above cutoff (default = 0)
fsort	Sort factor loadings
dec	Number of decimals to show
repl	Replace loadings below the cutoff by NA (or "")

Details

See https://radiant-rstats.github.io/docs/multivariate/full_factor.html for an example in Radiant

Examples

```
result <- full_factor(diamonds, c("price", "carat", "table", "x", "y"))
clean_loadings(result$floadings, TRUE, .5, 2)
```

computer	<i>Perceptions of computer (re)sellers</i>
----------	--

Description

Perceptions of computer (re)sellers

Usage

```
data(computer)
```

Format

A data frame with 5 rows and 8 variables

Details

Perceptions of computer (re)sellers. The dataset is used to illustrate perceptual maps. Description provided in `attr(computer, "description")`

conjoint	<i>Conjoint analysis</i>
----------	--------------------------

Description

Conjoint analysis

Usage

```
conjoint(dataset, rvar, evar, int = "", by = "none", reverse = FALSE,
  data_filter = "")
```

Arguments

dataset	Dataset
rvar	The response variable (e.g., profile ratings)
evar	Explanatory variables in the regression
int	Interaction terms to include in the model
by	Variable to group data by before analysis (e.g., a respondent id)
reverse	Reverse the values of the response variable ('rvar')
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <https://radiant-rstats.github.io/docs/multivariate/conjoint.html> for an example in Radiant

Value

A list with all variables defined in the function as an object of class `conjoint`

See Also

[summary.conjoint](#) to summarize results

[plot.conjoint](#) to plot results

Examples

```
result <- conjoint(mp3, rvar = "Rating", evar = "Memory:Shape")
result <- mp3 %>% conjoint(rvar = "Rating", evar = "Memory:Shape")
```

full_factor

Factor analysis (PCA)

Description

Factor analysis (PCA)

Usage

```
full_factor(dataset, vars, method = "PCA", nr_fact = 1,
  rotation = "varimax", data_filter = "")
```

Arguments

dataset	Dataset
vars	Variables to include in the analysis
method	Factor extraction method to use
nr_fact	Number of factors to extract
rotation	Apply varimax rotation or no rotation ("varimax" or "none")
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See https://radiant-rstats.github.io/docs/multivariate/full_factor.html for an example in Radiant

Value

A list with all variables defined in the function as an object of class `full_factor`

See Also

[summary.full_factor](#) to summarize results

[plot.full_factor](#) to plot results

Examples

```
result <- full_factor(diamonds, c("price", "carat", "table", "x", "y"))
result <- full_factor(diamonds, c("price", "carat", "table", "x", "y"), method = "maxlik")
result <- diamonds %>% full_factor(c("price", "carat", "table", "x", "y"), method = "maxlik")
```

hclus

Hierarchical cluster analysis

Description

Hierarchical cluster analysis

Usage

```
hclus(dataset, vars, distance = "sq.euclidian", method = "ward.D",
       max_cases = 5000, data_filter = "")
```

Arguments

dataset	Dataset
vars	Vector of variables to include in the analysis
distance	Distance
method	Method
max_cases	Maximum number of cases allowed (default is 1000)
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <https://radiant-rstats.github.io/docs/multivariate/hclus.html> for an example in Radiant

Value

A list of all variables used in hclus as an object of class hclus

See Also

[summary.hclus](#) to summarize results

[plot.hclus](#) to plot results

Examples

```
result <- hclus(shopping, vars = "v1:v6")
```

kclus*K-clustering*

Description

K-clustering

Usage

```
kclus(dataset, vars, fun = "mean", hc_init = TRUE,  
       distance = "sq.euclidian", method = "ward.D", seed = 1234,  
       nr_clus = 2, data_filter = "")
```

Arguments

dataset	Dataset
vars	Vector of variables to include in the analysis
fun	Function to use: "mean" or "median"
hc_init	Use centers from hclus as the starting point
distance	Distance for hclus
method	Method for hclus
seed	Random see to use for k-clustering if hc_init is FALSE
nr_clus	Number of clusters to extract
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <https://radiant-rstats.github.io/docs/multivariate/kclus.html> for an example in Radiant

Value

A list of all variables used in kclus as an object of class kclus

See Also

[summary.kclus](#) to summarize results

[plot.kclus](#) to plot results

[store.kclus](#) to add cluster membership to the selected dataset

Examples

```
result <- kclus(shopping, c("v1:v6"))
```

mds	(Dis)similarity based brand maps (MDS)
-----	--

Description

(Dis)similarity based brand maps (MDS)

Usage

```
mds(dataset, id1, id2, dis, method = "metric", nr_dim = 2, seed = 1234,  
      data_filter = "")
```

Arguments

dataset	Dataset
id1	A character variable or factor with unique entries
id2	A character variable or factor with unique entries
dis	A numeric measure of brand dissimilarity
method	Apply metric or non-metric MDS
nr_dim	Number of dimensions
seed	Random seed
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <https://radiant-rstats.github.io/docs/multivariate/mds.html> for an example in Radiant

Value

A list of all variables defined in the function as an object of class mds

See Also

[summary.mds](#) to summarize results

[plot.mds](#) to plot results

Examples

```
result <- mds(city, "from", "to", "distance")  
summary(result)  
result <- mds(diamonds, "clarity", "cut", "price")  
summary(result)
```

movie	<i>Conjoint data for Movie theaters</i>
-------	---

Description

Conjoint data for Movie theaters

Usage

```
data(movie)
```

Format

A data frame with 18 rows and 6 variables

Details

Rankings reflect the evaluation of 18 alternative movie theaters by one respondent. Description provided in `attr(movie, "description")`

mp3	<i>Conjoint data for MP3 players</i>
-----	--------------------------------------

Description

Conjoint data for MP3 players

Usage

```
data(mp3)
```

Format

A data frame with 18 rows and 6 variables

Details

Ratings reflect the evaluation of 18 alternative MP3 players by one respondent. Description provided in `attr(mp3, "description")`

plot.conjoint	<i>Plot method for the conjoint function</i>
---------------	--

Description

Plot method for the conjoint function

Usage

```
## S3 method for class 'conjoint'
plot(x, plots = "pw", show = "", scale_plot = FALSE,
     shiny = FALSE, custom = FALSE, ...)
```

Arguments

x	Return value from conjoint
plots	Show either the part-worth ("pw") or importance-weights ("iw") plot
show	Level in by variable to analyse (e.g., a specific respondent)
scale_plot	Scale the axes of the part-worth plots to the same range
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/conjoint.html> for an example in Radiant

See Also

[conjoint](#) to generate results
[summary.conjoint](#) to summarize results

Examples

```
result <- conjoint(mp3, rvar = "Rating", evar = "Memory:Shape")
plot(result, scale_plot = TRUE)
plot(result, plots = "iw")
```

plot.full_factor	<i>Plot method for the full_factor function</i>
------------------	---

Description

Plot method for the full_factor function

Usage

```
## S3 method for class 'full_factor'  
plot(x, shiny = FALSE, custom = FALSE, ...)
```

Arguments

x	Return value from full_factor
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See https://radiant-rstats.github.io/docs/multivariate/full_factor.html for an example in Radiant

See Also

[full_factor](#) to calculate results

[plot.full_factor](#) to plot results

Examples

```
result <- full_factor(diamonds, c("price", "carat", "table"))  
plot(result)  
result <- full_factor(computer, "high_end:business")  
summary(result)
```

plot.hclus

*Plot method for the hclus function***Description**

Plot method for the hclus function

Usage

```
## S3 method for class 'hclus'
plot(x, plots = c("scree", "change"), cutoff = 0.05,
     shiny = FALSE, custom = FALSE, ...)
```

Arguments

x	Return value from hclus
plots	Plots to return. "change" shows the percentage change in within-cluster heterogeneity as respondents are grouped into different number of clusters, "dendro" shows the dendrogram, "scree" shows a scree plot of within-cluster heterogeneity
cutoff	For large datasets plots can take time to render and become hard to interpret. By selection a cutoff point (e.g., 0.05 percent) the initial steps in hierarchical cluster analysis are removed from the plot
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/hclus.html> for an example in Radiant

See Also

[hclus](#) to generate results
[summary.hclus](#) to summarize results

Examples

```
result <- hclus(shopping, vars = c("v1:v6"))
plot(result, plots = c("change", "scree"), cutoff = .05)
plot(result, plots = "dendro", cutoff = 0)
shopping %>% hclus(vars = c("v1:v6")) %>% plot
```

plot.kclus

*Plot method for kclus***Description**

Plot method for kclus

Usage

```
## S3 method for class 'kclus'
plot(x, plots = "density", shiny = FALSE, custom = FALSE,
     ...)
```

Arguments

x	Return value from kclus
plots	One of "density", "bar", or "scatter")
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/kclus.html> for an example in Radiant

See Also

[kclus](#) to generate results

[summary.kclus](#) to summarize results

[store.kclus](#) to add cluster membership to the selected dataset

Examples

```
result <- kclus(shopping, vars = "v1:v6")
plot(result)
shopping %>% kclus(vars = c("v1:v6")) %>% plot()
```

plot.mds	<i>Plot method for the mds function</i>
----------	---

Description

Plot method for the mds function

Usage

```
## S3 method for class 'mds'
plot(x, rev_dim = NULL, fontsz = 5, shiny = FALSE,
      custom = FALSE, ...)
```

Arguments

x	Return value from mds
rev_dim	Flip the axes in plots
fontsz	Font size to use in plots
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/mds.html> for an example in Radiant

See Also

[mds](#) to calculate results
[summary.mds](#) to plot results

Examples

```
result <- mds(city, "from", "to", "distance")
plot(result)
plot(result, rev_dim = 1:2)
plot(result, rev_dim = 1:2, fontsz = 8)
```

plot.pre_factor	<i>Plot method for the pre_factor function</i>
-----------------	--

Description

Plot method for the pre_factor function

Usage

```
## S3 method for class 'pre_factor'
plot(x, plots = c("scree", "change"), cutoff = 0.2,
     shiny = FALSE, custom = FALSE, ...)
```

Arguments

x	Return value from pre_factor
plots	Plots to return. "change" shows the change in eigenvalues as variables are grouped into different number of factors, "scree" shows a scree plot of eigenvalues
cutoff	For large datasets plots can take time to render and become hard to interpret. By selection a cutoff point (e.g., eigenvalues of .8 or higher) factors with the least explanatory power are removed from the plot
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See https://radiant-rstats.github.io/docs/multivariate/pre_factor.html for an example in Radiant

See Also

[pre_factor](#) to calculate results
[summary.pre_factor](#) to summarize results

Examples

```
result <- pre_factor(diamonds, c("price", "carat", "table"))
plot(result)
plot(result, plots = c("change", "scree"), cutoff = .05)
```

plot.prmmap	<i>Plot method for the prmap function</i>
-------------	---

Description

Plot method for the prmap function

Usage

```
## S3 method for class 'prmap'
plot(x, plots = "", scaling = 2, fontsz = 5,
     seed = 1234, shiny = FALSE, custom = FALSE, ...)
```

Arguments

x	Return value from prmap
plots	Components to include in the plot ("brand", "attr"). If data on preferences is available use "pref" to add preference arrows to the plot
scaling	Arrow scaling in the brand map
fontsz	Font size to use in plots
seed	Random seed
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/prmap.html> for an example in Radiant

See Also

[prmap](#) to calculate results
[summary.prmmap](#) to plot results

Examples

```
result <- prmap(computer, brand = "brand", attr = "high_end:business")
plot(result, plots = "brand")
plot(result, plots = c("brand", "attr"))
plot(result, scaling = 1, plots = c("brand", "attr"))
result <- prmap(
  retailers, brand = "retailer",
  attr = "good_value:cluttered",
  pref = c("segment1", "segment2")
)
plot(result, plots = c("brand", "attr", "pref"))
```

predict.conjoint	<i>Predict method for the conjoint function</i>
------------------	---

Description

Predict method for the conjoint function

Usage

```
## S3 method for class 'conjoint'
predict(object, pred_data = NULL, pred_cmd = "",
        conf_lev = 0.95, se = FALSE, interval = "confidence", dec = 3, ...)
```

Arguments

object	Return value from conjoint
pred_data	Provide the dataframe to generate predictions. The dataset must contain all columns used in the estimation
pred_cmd	Command used to generate data for prediction
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)
se	Logical that indicates if prediction standard errors should be calculated (default = FALSE)
interval	Type of interval calculation ("confidence" or "prediction"). Set to "none" if se is FALSE
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/conjoint.html> for an example in Radiant

See Also

[conjoint](#) to generate the result
[summary.conjoint](#) to summarize results
[plot.conjoint](#) to plot results

Examples

```
result <- conjoint(mp3, rvar = "Rating", evar = "Memory:Shape")
predict(result, pred_data = mp3)
```

predict_conjoint_by	<i>Predict method for the conjoint function when a by variables is used</i>
---------------------	---

Description

Predict method for the conjoint function when a by variables is used

Usage

```
predict_conjoint_by(object, pfun, pred_data = NULL, pred_cmd = "",
  conf_lev = 0.95, se = FALSE, dec = 3, ...)
```

Arguments

object	Return value from conjoint
pfun	Function to use for prediction
pred_data	Name of the dataset to use for prediction
pred_cmd	Command used to generate data for prediction
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)
se	Logical that indicates if prediction standard errors should be calculated (default = FALSE)
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/conjoint.html> for an example in Radiant

See Also

[conjoint](#) to generate the result
[summary.conjoint](#) to summarize results
[plot.conjoint](#) to plot results

pre_factor	<i>Evaluate if data are appropriate for PCA / Factor analysis</i>
------------	---

Description

Evaluate if data are appropriate for PCA / Factor analysis

Usage

```
pre_factor(dataset, vars, data_filter = "")
```

Arguments

dataset	Dataset
vars	Variables to include in the analysis
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See https://radiant-rstats.github.io/docs/multivariate/pre_factor.html for an example in Radiant

Value

A list with all variables defined in the function as an object of class pre_factor

See Also

[summary.pre_factor](#) to summarize results

[plot.pre_factor](#) to plot results

Examples

```
result <- pre_factor(diamonds, c("price", "carat", "table"))
```

```
print.conjoint.predict
```

Print method for predict.conjoint

Description

Print method for predict.conjoint

Usage

```
## S3 method for class 'conjoint.predict'
print(x, ..., n = 20)
```

Arguments

x	Return value from prediction method
...	further arguments passed to or from other methods
n	Number of lines of prediction results to print. Use -1 to print all lines

prmap	<i>Attribute based brand maps</i>
-------	-----------------------------------

Description

Attribute based brand maps

Usage

```
prmap(dataset, brand, attr, pref = "", nr_dim = 2, data_filter = "")
```

Arguments

dataset	Dataset
brand	A character variable with brand names
attr	Names of numeric variables
pref	Names of numeric brand preference measures
nr_dim	Number of dimensions
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <https://radiant-rstats.github.io/docs/multivariate/prmap.html> for an example in Radiant

Value

A list of all variables defined in the function as an object of class prmap

See Also

[summary.prmap](#) to summarize results

[plot.prmap](#) to plot results

Examples

```
result <- prmap(computer, brand = "brand", attr = "high_end:business")
```

`radiant.multivariate` *`radiant.multivariate`*

Description

`radiant.multivariate`

Launch `radiant.multivariate` in the default browser

Usage

`radiant.multivariate()`

Details

See <https://radiant-rstats.github.io/docs> for documentation and tutorials

Examples

```
## Not run:
radiant.multivariate()

## End(Not run)
```

`radiant.multivariate-deprecated`

Deprecated function(s) in the `radiant.multivariate` package

Description

These functions are provided for compatibility with previous versions of `radiant`. They will eventually be removed.

Usage

`kmeans_clus(...)`

Arguments

`...` Parameters to be passed to the updated functions

Details

`kmeans_clus` is now a synonym for `kclus`
`hier_clus` is now a synonym for `hclus`
`pmap` is now a synonym for `prmap`

`radiant.multivariate_viewer`*Launch radiant.multivariate in the Rstudio viewer*

Description

Launch radiant.multivariate in the Rstudio viewer

Usage

```
radiant.multivariate_viewer()
```

Details

See <https://radiant-rstats.github.io/docs> for documentation and tutorials

Examples

```
## Not run:  
radiant.multivariate_viewer()  
  
## End(Not run)
```

`radiant.multivariate_window`*Launch radiant.multivariate in an Rstudio window*

Description

Launch radiant.multivariate in an Rstudio window

Usage

```
radiant.multivariate_window()
```

Details

See <https://radiant-rstats.github.io/docs> for documentation and tutorials

Examples

```
## Not run:  
radiant.multivariate_window()  
  
## End(Not run)
```

retailers	<i>Perceptions of retailers</i>
-----------	---------------------------------

Description

Perceptions of retailers

Usage

```
data(retailers)
```

Format

A data frame with 6 rows and 10 variables

Details

Consumer evaluations for a set of retailers in the Chicago area on 7 attributes. The dataset is used to illustrate perceptual maps. Description provided in `attr(retailers, "description")`

shopping	<i>Shopping attitudes</i>
----------	---------------------------

Description

Shopping attitudes

Usage

```
data(shopping)
```

Format

A data frame with 20 rows and 7 variables

Details

Attitudinal data on shopping for 20 consumers. Description provided in `attr(shopping, "description")`

store.conjoint	<i>Store method for the Multivariate > Conjoint tab</i>
----------------	--

Description

Store method for the Multivariate > Conjoint tab

Usage

```
## S3 method for class 'conjoint'
store(dataset, object, name, ...)
```

Arguments

dataset	Dataset
object	Return value from conjoint
name	Variable name(s) assigned to predicted values
...	further arguments passed to or from other methods

Details

Store data frame with PWs or IWs in Radiant r_data list if available

store.conjoint.predict	<i>Store predicted values generated in predict.conjoint</i>
------------------------	---

Description

Store predicted values generated in predict.conjoint

Usage

```
## S3 method for class 'conjoint.predict'
store(dataset, object, name = "prediction", ...)
```

Arguments

dataset	Dataset to add predictions to
object	Return value from model predict function
name	Variable name(s) assigned to predicted values
...	Additional arguments

Details

See <https://radiant-rstats.github.io/docs/multivariate/conjoint.html> for an example in Radiant

store.full_factor	<i>Store factor scores to active dataset</i>
-------------------	--

Description

Store factor scores to active dataset

Usage

```
## S3 method for class 'full_factor'
store(dataset, object, name = "", ...)
```

Arguments

dataset	Dataset to append to factor scores to
object	Return value from <code>full_factor</code>
name	Name of factor score variables
...	Additional arguments

Details

See https://radiant-rstats.github.io/docs/multivariate/full_factor.html for an example in Radiant

See Also

`full_factor` to generate results
`summary.full_factor` to summarize results
`plot.full_factor` to plot results

Examples

```
full_factor(shopping, "v1:v6", nr_fact = 3) %>%
  store(shopping, .) %>%
  head()
```

store.kclus	<i>Add a cluster membership variable to the active dataset</i>
-------------	--

Description

Add a cluster membership variable to the active dataset

Usage

```
## S3 method for class 'kclus'
store(dataset, object, name = "", ...)
```

Arguments

dataset	Dataset to append to cluster membership variable to
object	Return value from kclus
name	Name of cluster membership variable
...	Additional arguments

Details

See <https://radiant-rstats.github.io/docs/multivariate/kclus.html> for an example in Radiant

See Also

[kclus](#) to generate results
[summary.kclus](#) to summarize results
[plot.kclus](#) to plot results

Examples

```
kclus(shopping, vars = "v1:v6") %>%
  store(shopping, .) %>%
  head()
```

summary.conjoint

*Summary method for the conjoint function***Description**

Summary method for the conjoint function

Usage

```
## S3 method for class 'conjoint'
summary(object, show = "", mc_diag = FALSE,
  additional = FALSE, dec = 3, ...)
```

Arguments

object	Return value from conjoint
show	Level in by variable to analyse (e.g., a specific respondent)
mc_diag	Shows multicollinearity diagnostics.
additional	Show additional regression results
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/conjoint.html> for an example in Radiant

See Also

[conjoint](#) to generate results
[plot.conjoint](#) to plot results

Examples

```
result <- conjoint(mp3, rvar = "Rating", evar = "Memory:Shape")
summary(result, mc_diag = TRUE)
mp3 %>% conjoint(rvar = "Rating", evar = "Memory:Shape") %>% summary(mc_diag = TRUE)
```

summary.full_factor	<i>Summary method for the full_factor function</i>
---------------------	--

Description

Summary method for the full_factor function

Usage

```
## S3 method for class 'full_factor'
summary(object, cutoff = 0, fsort = FALSE, dec = 2,
  ...)
```

Arguments

object	Return value from full_factor
cutoff	Show only loadings with (absolute) values above cutoff (default = 0)
fsort	Sort factor loadings
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See https://radiant-rstats.github.io/docs/multivariate/full_factor.html for an example in Radiant

See Also

[full_factor](#) to calculate results
[plot.full_factor](#) to plot results

Examples

```
result <- full_factor(diamonds , c("price", "carat", "depth", "table", "x"))
summary(result)
summary(result, cutoff = 0, fsort = FALSE)
summary(result, cutoff = 0, fsort = TRUE)
summary(result, cutoff = .5, fsort = TRUE)
diamonds %>% full_factor(c("price", "carat", "depth", "table", "x")) %>% summary()
diamonds %>% full_factor(c("price", "carat", "depth", "table", "x")) %>% summary(cutoff = .5)
```

summary.hclus	<i>Summary method for the hclus function</i>
---------------	--

Description

Summary method for the hclus function

Usage

```
## S3 method for class 'hclus'  
summary(object, ...)
```

Arguments

object	Return value from hclus
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/hclus.html> for an example in Radiant

See Also

[hclus](#) to generate results
[plot.hclus](#) to plot results

Examples

```
result <- hclus(shopping, vars = c("v1:v6"))  
summary(result)
```

summary.kclus	<i>Summary method for kclus</i>
---------------	---------------------------------

Description

Summary method for kclus

Usage

```
## S3 method for class 'kclus'  
summary(object, dec = 2, ...)
```

Arguments

object	Return value from kclus
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/kclus.html> for an example in Radiant

See Also

[kclus](#) to generate results

[plot.kclus](#) to plot results

[store.kclus](#) to add cluster membership to the selected dataset

Examples

```
result <- kclus(shopping, vars = c("v1:v6"))
summary(result)
shopping %>% kclus(vars = c("v1:v6"), nr_clus = 3) %>% summary()
```

summary.mds	<i>Summary method for the mds function</i>
-------------	--

Description

Summary method for the mds function

Usage

```
## S3 method for class 'mds'
summary(object, dec = 2, ...)
```

Arguments

object	Return value from mds
dec	Rounding to use for output (default = 2). +1 used for stress measure
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/mds.html> for an example in Radiant

See Also

[mds](#) to calculate results

[plot.mds](#) to plot results

Examples

```
result <- mds(city, "from", "to", "distance")
summary(result)
summary(result, dec = 2)
city %>% mds("from", "to", "distance") %>% summary()
```

summary.pre_factor	Summary method for the pre_factor function
--------------------	--

Description

Summary method for the pre_factor function

Usage

```
## S3 method for class 'pre_factor'  
summary(object, dec = 2, ...)
```

Arguments

object	Return value from pre_factor
dec	Rounding to use for output
...	further arguments passed to or from other methods

Details

See https://radiant-rstats.github.io/docs/multivariate/pre_factor.html for an example in Radiant

See Also

[pre_factor](#) to calculate results
[plot.pre_factor](#) to plot results

Examples

```
result <- pre_factor(diamonds, c("price", "carat", "table"))  
summary(result)  
diamonds %>% pre_factor(c("price", "carat", "table")) %>% summary()  
result <- pre_factor(computer, "high_end:business")  
summary(result)
```

summary.prmmap	Summary method for the prmap function
----------------	---------------------------------------

Description

Summary method for the prmap function

Usage

```
## S3 method for class 'prmap'  
summary(object, cutoff = 0, dec = 2, ...)
```

Arguments

object	Return value from prmap
cutoff	Show only loadings with (absolute) values above cutoff (default = 0)
dec	Rounding to use for output
...	further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/multivariate/prmap.html> for an example in Radiant

See Also

[prmap](#) to calculate results
[plot.prmap](#) to plot results

Examples

```
result <- prmap(computer, brand = "brand", attr = "high_end:business")
summary(result)
summary(result, cutoff = .3)
result <- prmap(
  computer, brand = "brand", attr = "high_end:dated",
  pref = c("innovative", "business")
)
summary(result)
computer %>%
  prmap(
    brand = "brand", attr = "high_end:dated",
    pref = c("innovative", "business")
  ) %>%
  summary()
```

the_table

Function to calculate the PW and IW table for conjoint

Description

Function to calculate the PW and IW table for conjoint

Usage

```
the_table(model, dataset, evar)
```

Arguments

model	Tidied model results (broom) output from conjoint passed on by summary.conjoint
dataset	Conjoint data
evar	Explanatory variables used in the conjoint regression

Details

See <https://radiant-rstats.github.io/docs/multivariate/conjoint.html> for an example in Radiant

See Also

`conjoint` to generate results
`summary.conjoint` to summarize results
`plot.conjoint` to plot results

Examples

```
result <- conjoint(mp3, rvar = "Rating", evar = "Memory:Shape")
the_table(tidy(result$model_list[[1]][["model"]]), result$dataset, result$evar)
```

toothpaste	<i>Toothpaste attitudes</i>
------------	-----------------------------

Description

Toothpaste attitudes

Usage

```
data(toothpaste)
```

Format

A data frame with 60 rows and 10 variables

Details

Attitudinal data on toothpaste for 60 consumers. Description provided in `attr(toothpaste, "description")`

tpbrands	<i>Toothpaste brands</i>
----------	--------------------------

Description

Toothpaste brands

Usage

```
data(tpbrands)
```

Format

A data frame with 45 rows and 4 variables

Details

Perceived (dis)similarity of a set of toothpaste brands. The dataset is used to illustrate multi-dimensional scaling (MDS). Description provided in `attr(tpbrands, "description")`

Index

*Topic **datasets**

- carpet, [3](#)
- city, [3](#)
- city2, [4](#)
- computer, [5](#)
- movie, [10](#)
- mp3, [10](#)
- retailers, [24](#)
- shopping, [24](#)
- toothpaste, [33](#)
- tpbrands, [33](#)

carpet, [3](#)

city, [3](#)

city2, [4](#)

clean_loadings, [4](#)

computer, [5](#)

conjoint, [5](#), [11](#), [18](#), [19](#), [27](#), [28](#), [32](#), [33](#)

full_factor, [6](#), [12](#), [26](#), [28](#)

hclus, [7](#), [13](#), [22](#), [29](#)

hier_clus
(radiant.multivariate-deprecated), [22](#)

kclus, [8](#), [14](#), [22](#), [27](#), [29](#), [30](#)

kmeans_clus
(radiant.multivariate-deprecated), [22](#)

mds, [9](#), [15](#), [30](#)

movie, [10](#)

mp3, [10](#)

plot.conjoint, [6](#), [11](#), [18](#), [19](#), [28](#), [33](#)

plot.full_factor, [6](#), [12](#), [12](#), [26](#), [28](#)

plot.hclus, [7](#), [13](#), [29](#)

plot.kclus, [8](#), [14](#), [27](#), [30](#)

plot.mds, [9](#), [15](#), [30](#)

plot.pre_factor, [16](#), [20](#), [31](#)

plot.prmap, [17](#), [21](#), [32](#)

pmap (radiant.multivariate-deprecated), [22](#)

pre_factor, [16](#), [19](#), [31](#)

predict.conjoint, [18](#)

predict_conjoint_by, [19](#)

print.conjoint.predict, [20](#)

prmap, [17](#), [21](#), [22](#), [32](#)

radiant.multivariate, [22](#)

radiant.multivariate-deprecated, [22](#)

radiant.multivariate-deprecated-package
(radiant.multivariate-deprecated), [22](#)

radiant.multivariate-package
(radiant.multivariate), [22](#)

radiant.multivariate_viewer, [23](#)

radiant.multivariate_window, [23](#)

retailers, [24](#)

shopping, [24](#)

store.conjoint, [25](#)

store.conjoint.predict, [25](#)

store.full_factor, [26](#)

store.kclus, [8](#), [14](#), [26](#), [30](#)

summary.conjoint, [6](#), [11](#), [18](#), [19](#), [27](#), [33](#)

summary.full_factor, [6](#), [26](#), [28](#)

summary.hclus, [7](#), [13](#), [29](#)

summary.kclus, [8](#), [14](#), [27](#), [29](#)

summary.mds, [9](#), [15](#), [30](#)

summary.pre_factor, [16](#), [20](#), [31](#)

summary.prmap, [17](#), [21](#), [31](#)

the_table, [32](#)

toothpaste, [33](#)

tpbrands, [33](#)