

# Package ‘radiant.data’

May 1, 2018

**Title** Data Menu for Radiant: Business Analytics using R and Shiny

**Version** 0.9.3.1

**Date** 2018-4-30

**Description** The Radiant Data menu includes interfaces for loading, saving, viewing, visualizing, summarizing, transforming, and combining data. It also contains functionality to generate reproducible reports of the analyses conducted in the application.

**Depends** R (>= 3.4.0),  
magrittr (>= 1.5),  
ggplot2 (>= 2.2.1),  
lubridate (>= 1.7.4),  
tidyr (>= 0.8.0),  
dplyr (>= 0.7.4)

**Imports** tibble (>= 1.4.2),  
rlang (>= 0.2.0),  
broom (>= 0.4.3),  
car (>= 3.0-0),  
grid (>= 3.3.1),  
gridExtra (>= 2.0.0),  
knitr (>= 1.20),  
markdown (>= 0.8),  
rmarkdown (>= 1.9),  
pryr (>= 0.1.2),  
shiny (>= 1.0.5),  
jsonlite (>= 1.0),  
shinyAce (>= 0.3.0.1),  
psych (>= 1.8.3.3),  
DT (>= 0.4),  
readr (>= 1.1.1),  
readxl (>= 1.0.0),  
writexl (>= 0.2),  
scales (>= 0.4.0),  
curl (>= 2.5),  
rstudioapi (>= 0.7),  
import (>= 1.1.0),  
plotly (>= 4.7.1),  
feather (>= 0.3.1),  
glue,  
base64enc,

methods

**Suggests** DBI (>= 0.7),  
 RSQLite (>= 2.0),  
 odbc (>= 1.1.4),  
 webshot (>= 0.5.0),  
 testthat (>= 2.0.0)

**URL** <https://github.com/radiant-rstats/radiant.data>,  
<https://radiant-rstats.github.io/docs>

**BugReports** <https://github.com/radiant-rstats/radiant.data/issues>

**License** AGPL-3 | file LICENSE

**LazyData** true

**Encoding** UTF-8

**RoxygenNote** 6.0.1

## R topics documented:

add_class . . . . .	5
as_character . . . . .	5
as_distance . . . . .	6
as_dmy . . . . .	6
as_dmy_hm . . . . .	7
as_dmy_hms . . . . .	7
as_duration . . . . .	8
as_factor . . . . .	8
as_hm . . . . .	9
as_hms . . . . .	9
as_integer . . . . .	10
as_mdy . . . . .	10
as_mdy_hm . . . . .	11
as_mdy_hms . . . . .	12
as_numeric . . . . .	12
as_tibble . . . . .	13
as_ymd . . . . .	13
as_ymd_hm . . . . .	13
as_ymd_hms . . . . .	14
avengers . . . . .	14
center . . . . .	15
choose_dir . . . . .	15
choose_files . . . . .	16
ci_label . . . . .	16
ci_perc . . . . .	17
combinedata . . . . .	17
copy_all . . . . .	18
copy_attr . . . . .	19
copy_from . . . . .	19
cv . . . . .	20
describe . . . . .	20
diamonds . . . . .	21

does_vary . . . . .	21
dtab . . . . .	22
dtab.character . . . . .	22
dtab.data.frame . . . . .	23
dtab.explore . . . . .	24
dtab.pivotr . . . . .	25
empty_level . . . . .	26
explore . . . . .	26
filterdata . . . . .	27
find_dropbox . . . . .	28
find_gdrive . . . . .	28
find_project . . . . .	29
fixMS . . . . .	29
fix_names . . . . .	30
flip . . . . .	30
formatdf . . . . .	31
formatnr . . . . .	31
getclass . . . . .	32
getdata . . . . .	33
getsummary . . . . .	33
ggplotly . . . . .	34
glance . . . . .	34
glue . . . . .	34
indexr . . . . .	35
install_webshot . . . . .	35
inverse . . . . .	35
is_empty . . . . .	36
is_not . . . . .	36
is_numeric . . . . .	37
is_string . . . . .	37
items . . . . .	38
knit_print . . . . .	38
kurtosi . . . . .	39
launch . . . . .	39
level_list . . . . .	40
ln . . . . .	40
load_clip . . . . .	41
load_csv . . . . .	41
make_train . . . . .	42
month . . . . .	42
mutate_ext . . . . .	43
normalize . . . . .	43
n_missing . . . . .	44
n_obs . . . . .	44
p025 . . . . .	45
p05 . . . . .	45
p10 . . . . .	46
p25 . . . . .	46
p75 . . . . .	47
p90 . . . . .	47
p95 . . . . .	48
p975 . . . . .	48

parse_path . . . . .	49
pivotr . . . . .	49
plot.character . . . . .	50
plot.pivotr . . . . .	50
print.gtable . . . . .	51
prop . . . . .	52
publishers . . . . .	52
radiant.data . . . . .	53
radiant.data-deprecated . . . . .	53
radiant.data_viewer . . . . .	54
radiant.data_window . . . . .	54
read_files . . . . .	55
refactor . . . . .	55
register . . . . .	56
render . . . . .	56
render.character . . . . .	56
render.datatables . . . . .	57
render.plotly . . . . .	57
render.shiny.render.function . . . . .	57
rounddf . . . . .	58
rownames_to_column . . . . .	58
save_clip . . . . .	59
sdpop . . . . .	59
sdprop . . . . .	60
se . . . . .	60
Search . . . . .	61
seprop . . . . .	61
set_attr . . . . .	62
show_duplicated . . . . .	62
sig_stars . . . . .	63
skew . . . . .	63
square . . . . .	64
sshh . . . . .	64
sshhr . . . . .	65
standardize . . . . .	65
store . . . . .	66
store.character . . . . .	66
store.explore . . . . .	67
store.pivotr . . . . .	67
subplot . . . . .	68
summary.explore . . . . .	68
summary.pivotr . . . . .	69
superheroes . . . . .	70
table2data . . . . .	70
tibble . . . . .	70
tidy . . . . .	71
titanic . . . . .	71
toFct . . . . .	71
varpop . . . . .	72
varprop . . . . .	72
viewdata . . . . .	73
visualize . . . . .	73

<code>add_class</code>	5
<code>wday</code>	75
<code>weighted.sd</code>	76
<code>which.pmax</code>	76
<code>which.pmin</code>	77
<code>write_feather</code>	77
<code>xtile</code>	78
<b>Index</b>	<b>79</b>

---

<code>add_class</code>	<i>Convenience function to add a class</i>
------------------------	--

---

## Description

Convenience function to add a class

## Usage

```
add_class(x, cl)
```

## Arguments

<code>x</code>	Object
<code>cl</code>	Vector of class labels to add

## Examples

```
foo <- "some text" %>% add_class("text")
foo <- "some text" %>% add_class(c("text", "another class"))
```

---

<code>as_character</code>	<i>Wrapper for <code>as.character</code></i>
---------------------------	--

---

## Description

Wrapper for `as.character`

## Usage

```
as_character(x)
```

## Arguments

<code>x</code>	Input vector
----------------	--------------

---

as_distance	<i>Distance in kilometers or miles between two locations based on lat-long Function based on <a href="http://www.movable-type.co.uk/scripts/latlong.html">http://www.movable-type.co.uk/scripts/latlong.html</a>. Uses the haversine formula</i>
-------------	--

---

### Description

Distance in kilometers or miles between two locations based on lat-long Function based on <http://www.movable-type.co.uk/scripts/latlong.html>. Uses the haversine formula

### Usage

```
as_distance(lat1, long1, lat2, long2, unit = "km", R = c(km = 6371, miles = 3959)[[unit]])
```

### Arguments

lat1	Latitude of location 1
long1	Longitude of location 1
lat2	Latitude of location 2
long2	Longitude of location 2
unit	Measure kilometers ("km", default) or miles ("miles")
R	Radius of the earth

### Value

Distance between two points

### Examples

```
as_distance(32.8245525, -117.0951632, 40.7033127, -73.979681, unit = "km")
as_distance(32.8245525, -117.0951632, 40.7033127, -73.979681, unit = "miles")
```

---

as_dmy	<i>Convert input in day-month-year format to date</i>
--------	---

---

### Description

Convert input in day-month-year format to date

### Usage

```
as_dmy(x)
```

### Arguments

x	Input variable
---	----------------

**Value**

Date variable of class Date

**Examples**

```
as_dmy("1-2-2014")
```

---

as\_dmy\_hm

*Convert input in day-month-year-hour-minute format to date-time*

---

**Description**

Convert input in day-month-year-hour-minute format to date-time

**Usage**

```
as_dmy_hm(x)
```

**Arguments**

x                      Input variable

**Value**

Date-time variable of class Date

**Examples**

```
as_mdym_hm("1-1-2014 12:15")
```

---

as\_dmy\_hms

*Convert input in day-month-year-hour-minute-second format to date-time*

---

**Description**

Convert input in day-month-year-hour-minute-second format to date-time

**Usage**

```
as_dmy_hms(x)
```

**Arguments**

x                      Input variable

**Value**

Date-time variable of class Date

**Examples**

```
as_mdy_hms("1-1-2014 12:15:01")
```

---

as_duration	<i>Wrapper for lubridate's as.duration function. Result converted to numeric</i>
-------------	--

---

**Description**

Wrapper for lubridate's as.duration function. Result converted to numeric

**Usage**

```
as_duration(x)
```

**Arguments**

x	Time difference
---	-----------------

---

as_factor	<i>Wrapper for factor with ordered = FALSE</i>
-----------	--

---

**Description**

Wrapper for factor with ordered = FALSE

**Usage**

```
as_factor(x, ordered = FALSE)
```

**Arguments**

x	Input vector
ordered	Order factor levels (TRUE, FALSE)



---

`as_hm`*Convert input in hour-minute format to time*

---

**Description**

Convert input in hour-minute format to time

**Usage**

```
as_hm(x)
```

**Arguments**

x                      Input variable

**Value**

Time variable of class Period

**Examples**

```
as_hm("12:45")
## Not run:
as_hm("12:45") %>% minute()

## End(Not run)
```

---

`as_hms`*Convert input in hour-minute-second format to time*

---

**Description**

Convert input in hour-minute-second format to time

**Usage**

```
as_hms(x)
```

**Arguments**

x                      Input variable

**Value**

Time variable of class Period

**Examples**

```
as_hms("12:45:00")
## Not run:
as_hms("12:45:00") %>% hour
as_hms("12:45:00") %>% second

## End(Not run)
```

---

as\_integer

---

*Convert variable to integer avoiding potential issues with factors*


---

**Description**

Convert variable to integer avoiding potential issues with factors

**Usage**

```
as_integer(x)
```

**Arguments**

x                      Input variable

**Value**

Integer

**Examples**

```
as_integer(rnorm(10))
as_integer(letters)
as_integer(as.factor(5:10))
as.integer(as.factor(5:10))
as_integer(c("a","b"))
```

---

as\_mdy

---

*Convert input in month-day-year format to date*


---

**Description**

Convert input in month-day-year format to date

**Usage**

```
as_mdy(x)
```

**Arguments**

x                      Input variable

**Details**

Use as.character if x is a factor

**Value**

Date variable of class Date

**Examples**

```
as_mdy("2-1-2014")
## Not run:
as_mdy("2-1-2014") %>% month(label = TRUE)
as_mdy("2-1-2014") %>% week()
as_mdy("2-1-2014") %>% wday(label = TRUE)

## End(Not run)
```

---

as\_mdy\_hm

*Convert input in month-day-year-hour-minute format to date-time*

---

**Description**

Convert input in month-day-year-hour-minute format to date-time

**Usage**

```
as_mdy_hm(x)
```

**Arguments**

x                      Input variable

**Value**

Date-time variable of class Date

**Examples**

```
as_mdy_hm("1-1-2014 12:15")
```

---

as_mdy_hms	<i>Convert input in month-day-year-hour-minute-second format to date-time</i>
------------	---

---

**Description**

Convert input in month-day-year-hour-minute-second format to date-time

**Usage**

```
as_mdy_hms(x)
```

**Arguments**

x	Input variable
---	----------------

**Value**

Date-time variable of class Date

**Examples**

```
as_mdy_hms("1-1-2014 12:15:01")
```

---

as_numeric	<i>Convert variable to numeric avoiding potential issues with factors</i>
------------	---

---

**Description**

Convert variable to numeric avoiding potential issues with factors

**Usage**

```
as_numeric(x)
```

**Arguments**

x	Input variable
---	----------------

**Value**

Numeric

**Examples**

```
as_numeric(rnorm(10))
as_numeric(letters)
as_numeric(as.factor(5:10))
as.numeric(as.factor(5:10))
as_numeric(c("a", "b"))
as_numeric(c("3", "4"))
```

---

as_tibble	<i>Exporting as_tibble from tibble</i>
-----------	--

---

**Description**

Exporting as\_tibble from tibble

**Details**

See [as\\_tibble](#) in the tibble package for more details

---

as_ymd	<i>Convert input in year-month-day format to date</i>
--------	---

---

**Description**

Convert input in year-month-day format to date

**Usage**

```
as_ymd(x)
```

**Arguments**

x	Input variable
---	----------------

**Value**

Date variable of class Date

**Examples**

```
as_ymd("2013-1-1")
```

---

as_ymd_hm	<i>Convert input in year-month-day-hour-minute format to date-time</i>
-----------	--

---

**Description**

Convert input in year-month-day-hour-minute format to date-time

**Usage**

```
as_ymd_hm(x)
```

**Arguments**

x	Input variable
---	----------------

**Value**

Date-time variable of class Date

**Examples**

```
as_ymd_hm("2014-1-1 12:15")
```

---

as\_ymd\_hms

*Convert input in year-month-day-hour-minute-second format to date-time*

---

**Description**

Convert input in year-month-day-hour-minute-second format to date-time

**Usage**

```
as_ymd_hms(x)
```

**Arguments**

x                      Input variable

**Value**

Date-time variable of class Date

**Examples**

```
as_ymd_hms("2014-1-1 12:15:01")
## Not run:
as_ymd_hms("2014-1-1 12:15:01") %>% as.Date
as_ymd_hms("2014-1-1 12:15:01") %>% month
as_ymd_hms("2014-1-1 12:15:01") %>% hour

## End(Not run)
```

---

avengers

*Avengers*

---

**Description**

Avengers

**Usage**

```
data(avengers)
```

**Format**

A data frame with 7 rows and 4 variables

**Details**

List of avengers. The dataset is used to illustrate data merging / joining. Description provided in `attr(avengers,"description")`

---

center	<i>Center</i>
--------	---------------

---

**Description**

Center

**Usage**

```
center(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

If x is a numeric variable return  $x - \text{mean}(x)$

---

choose_dir	<i>Select a directory. Uses JavaScript on Mac, utils::choose.dir on Windows, and dirname(file.choose()) on Linux</i>
------------	--

---

**Description**

Select a directory. Uses JavaScript on Mac, `utils::choose.dir` on Windows, and `dirname(file.choose())` on Linux

**Usage**

```
choose_dir(...)
```

**Arguments**

...	Arguments passed to <code>utils::choose.dir</code> on Windows
-----	---

**Value**

Path to the directory selected by the user

**Examples**

```
if (interactive()) {
  choose_dir()
}
```

---

choose_files	<i>Select files. Uses JavaScript on Mac, utils::choose.files on Windows, and file.choose() on Linux</i>
--------------	---

---

**Description**

Select files. Uses JavaScript on Mac, utils::choose.files on Windows, and file.choose() on Linux

**Usage**

```
choose_files(...)
```

**Arguments**

...	Strings used to determine which file types are available for selection (e.g., "csv" or "pdf")
-----	---

**Value**

Vector of paths to files selected by the user

**Examples**

```
if (interactive()) {
  choose_files("pdf", "csv")
}
```

---

ci_label	<i>Labels for confidence intervals</i>
----------	--

---

**Description**

Labels for confidence intervals

**Usage**

```
ci_label(alt = "two.sided", cl = 0.95, dec = 3)
```

**Arguments**

alt	Type of hypothesis ("two.sided", "less", "greater")
cl	Confidence level
dec	Number of decimals to show

**Value**

A character vector with labels for a confidence interval



**Examples**

```
ci_label("less",.95)
ci_label("two.sided",.95)
ci_label("greater",.9)
```

---

ci_perc	<i>Values at confidence levels</i>
---------	------------------------------------

---

**Description**

Values at confidence levels

**Usage**

```
ci_perc(dat, alt = "two.sided", cl = 0.95)
```

**Arguments**

dat	Data
alt	Type of hypothesis ("two.sided", "less", "greater")
cl	Confidence level

**Value**

A vector with values at a confidence level

**Examples**

```
ci_perc(0:100, "less", .95)
ci_perc(0:100, "greater", .95)
ci_perc(0:100, "two.sided", .80)
```

---

combinedata	<i>Combine datasets using dplyr's bind and join functions</i>
-------------	---

---

**Description**

Combine datasets using dplyr's bind and join functions

**Usage**

```
combinedata(x, y, by = "", add = "", type = "inner_join",
  data_filter = "", ...)
```

**Arguments**

x	Dataset
y	Dataset to combine with x
by	Variables used to combine 'x' and 'y'
add	Variables to add from 'y'
type	The main bind and join types from the dplyr package are provided. <b>inner_join</b> returns all rows from x with matching values in y, and all columns from x and y. If there are multiple matches between x and y, all match combinations are returned. <b>left_join</b> returns all rows from x, and all columns from x and y. If there are multiple matches between x and y, all match combinations are returned. <b>right_join</b> is equivalent to a left join for datasets y and x. <b>full_join</b> combines two datasets, keeping rows and columns that appear in either. <b>semi_join</b> returns all rows from x with matching values in y, keeping just columns from x. A semi join differs from an inner join because an inner join will return one row of x for each matching row of y, whereas a semi join will never duplicate rows of x. <b>anti_join</b> returns all rows from x without matching values in y, keeping only columns from x. <b>bind_rows</b> and <b>bind_cols</b> are also included, as are <b>intersect</b> , <b>union</b> , and <b>setdiff</b> . See <a href="https://radiant-rstats.github.io/docs/data/combine.html">https://radiant-rstats.github.io/docs/data/combine.html</a> for further details
data_filter	Expression used to filter the dataset. This should be a string (e.g., "price > 10000")
...	further arguments passed to or from other methods

**Details**

See <https://radiant-rstats.github.io/docs/data/combine.html> for an example in Radiant

**Value**

If list 'r\_data' exists the combined dataset is added as 'name'. Else the combined dataset will be returned as 'name'

**Examples**

```

avengers %>% combinedata(superheroes, type = "bind_cols")
combinedata(avengers, superheroes, type = "bind_cols")
avengers %>% combinedata(superheroes, type = "bind_rows")
avengers %>% combinedata(superheroes, add = "publisher", type = "bind_rows")

```

---

copy\_all

---

*Source all package functions*


---

**Description**

Source all package functions

**Usage**

```
copy_all(.from)
```

**Arguments**

.from                      The package to pull the function from

**Details**

Equivalent of source with local=TRUE for all package functions. Adapted from functions by smbache, author of the import package. See <https://github.com/smbache/import/issues/4> for a discussion. This function will be deprecated when (if) it is included in <https://github.com/smbache/import>

**Examples**

```
copy_all(radiant.data)
```

---

copy_attr	<i>Copy attributes from on object to another</i>
-----------	--

---

**Description**

Copy attributes from on object to another

**Usage**

```
copy_attr(to, from, attr)
```

**Arguments**

to                      Object to copy attributes to  
 from                    Object to copy attributes from  
 attr                    Vector of attributes. If missing all attributes will be copied

---

copy_from	<i>Source for package functions</i>
-----------	-------------------------------------

---

**Description**

Source for package functions

**Usage**

```
copy_from(.from, ...)
```

**Arguments**

.from                    The package to pull the function from  
 ...                      Functions to pull

**Details**

Equivalent of source with local=TRUE for package functions. Written by smbache, author of the import package. See <https://github.com/smbache/import/issues/4> for a discussion. This function will be deprecated when (if) it is included in <https://github.com/smbache/import>

**Examples**

```
copy_from(radiant.data, getdata)
```

---

cv	<i>Coefficient of variation</i>
----	---------------------------------

---

**Description**

Coefficient of variation

**Usage**

```
cv(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

Coefficient of variation

**Examples**

```
cv(runif (100))
```

---

describe	<i>Show dataset description, if available, in html form in Rstudio viewer or default browser</i>
----------	--

---

**Description**

Show dataset description, if available, in html form in Rstudio viewer or default browser

**Usage**

```
describe(dataset)
```

**Arguments**

dataset	Dataset
---------	---------

---

diamonds*Diamond prices*

---

**Description**

Diamond prices

**Usage**

```
data(diamonds)
```

**Format**

A data frame with 3000 rows and 10 variables

**Details**

A sample of 3,000 from the diamonds dataset bundled with ggplot2. Description provided in `attr(diamonds,"description")`

---

does\_vary*Does a vector have non-zero variability?*

---

**Description**

Does a vector have non-zero variability?

**Usage**

```
does_vary(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

Logical. TRUE if there is variability

**Examples**

```
summarise_all(diamonds, funs(does_vary)) %>% as.logical
```

---

dtab	<i>Method to create datatables</i>
------	------------------------------------

---

**Description**

Method to create datatables

**Usage**

```
dtab(object, ...)
```

**Arguments**

object	Object of relevant class to render
...	Additional arguments

**See Also**

See [dtab.explore](#) to create the an interactivce table from an [explore](#) object  
 See [dtab.pivotr](#) to create the an interactivce table from a [pivotr](#) object  
 See [dtab.data.frame](#) to create an interactive table from a data.frame

---

dtab.character	<i>Create a DT table with bootstrap theme</i>
----------------	---

---

**Description**

Create a DT table with bootstrap theme

**Usage**

```
## S3 method for class 'character'
dtab(...)
```

**Arguments**

...	Arguments to pass on to dtab.data.frame
-----	---

**Details**

View, search, sort, etc. your data. For styling options see <http://rstudio.github.io/DT/functions.html>

**Examples**

```
dtab(mtcars)
```

---

dtab.data.frame	Create a DT table with bootstrap theme
-----------------	--

---

## Description

Create a DT table with bootstrap theme

## Usage

```
## S3 method for class 'data.frame'
dtab(object, vars = "", filt = "", rows = NULL,
      nr = NULL, na.rm = FALSE, dec = 3, filter = "top", pageLength = 10,
      dom = "", style = "bootstrap", rownames = FALSE, ...)
```

## Arguments

object	Data.frame to display
vars	Variables to show (default is all)
filt	Filter to apply to the specified dataset. For example "price > 10000" if dataset is "diamonds" (default is "")
rows	Select rows in the specified dataset. For example "1:10" for the first 10 rows or "n()-10:n()" for the last 10 rows (default is NULL)
nr	Number of rows of data to include in the table
na.rm	Remove rows with missing values (default is FALSE)
dec	Number of decimal places to show. Default is no rounding (NULL)
filter	Show filter in DT table. Options are "none", "top", "bottom"
pageLength	Number of rows to show in table
dom	Table control elements to show on the page. See <a href="https://datatables.net/reference/option/dom">https://datatables.net/reference/option/dom</a>
style	Table formatting style ("bootstrap" or "default")
rownames	Show data.frame rownames. Default is FALSE
...	Additional arguments

## Details

View, search, sort, etc. your data. For styling options see <http://rstudio.github.io/DT/functions.html>

## Examples

```
dtab(mtcars)
```

---

dtab.explore	<i>Make a tabel of summary statistics in DT</i>
--------------	---

---

## Description

Make a tabel of summary statistics in DT

## Usage

```
## S3 method for class 'explore'
dtab(object, dec = 3, searchCols = NULL, order = NULL,
      pageLength = NULL, ...)
```

## Arguments

object	Return value from <a href="#">explore</a>
dec	Number of decimals to show
searchCols	Column search and filter. Used to save and restore state
order	Column sorting. Used to save and restore state
pageLength	Page length. Used to save and restore state
...	further arguments passed to or from other methods

## Details

See <https://radiant-rstats.github.io/docs/data/explore.html> for an example in Radiant

## See Also

[pivotr](#) to create the pivot-table using dplyr  
[summary.pivotr](#) to print a plain text table

## Examples

```
tab <- explore(diamonds, "price:x") %>% dtab()
tab <- explore(diamonds, "price", byvar = "cut", fun = c("n_obs", "skew"), top = "byvar") %>%
  dtab()
```



---

dtab.pivotr	<i>Make a pivot tabel in DT</i>
-------------	---------------------------------

---

## Description

Make a pivot tabel in DT

## Usage

```
## S3 method for class 'pivotr'
dtab(object, format = "none", perc = FALSE, dec = 3,
      searchCols = NULL, order = NULL, pageLength = NULL, ...)
```

## Arguments

object	Return value from <a href="#">pivotr</a>
format	Show Color bar ("color_bar"), Heat map ("heat"), or None ("none")
perc	Display numbers as percentages (TRUE or FALSE)
dec	Number of decimals to show
searchCols	Column search and filter. Used to save and restore state
order	Column sorting. Used to save and restore state
pageLength	Page length. Used to save and restore state
...	further arguments passed to or from other methods

## Details

See <https://radiant-rstats.github.io/docs/data/pivotr.html> for an example in Radiant

## See Also

[pivotr](#) to create the pivot-table using dplyr

[summary.pivotr](#) to print a plain text table

## Examples

```
pivotr(diamonds, cvars = "cut") %>% dtab()
pivotr(diamonds, cvars = c("cut","clarity")) %>% dtab(format = "color_bar")
ret <- pivotr(diamonds, cvars = c("cut","clarity"), normalize = "total") %>%
  dtab(format = "color_bar", perc = TRUE)
```

---

empty_level	<i>Convert categorical variables to factors and deal with empty/missing values (used in pivotr and explore)</i>
-------------	---

---

**Description**

Convert categorical variables to factors and deal with empty/missing values (used in pivotr and explore)

**Usage**

```
empty_level(x)
```

**Arguments**

x                      Categorical variable used in table

**Value**

Variable with updated levels

---

explore	<i>Explore data</i>
---------	---------------------

---

**Description**

Explore data

**Usage**

```
explore(dataset, vars = "", byvar = "", fun = c("mean", "sd"),
  top = "fun", tabfilt = "", tabsort = "", nr = NULL,
  data_filter = "", shiny = FALSE)
```

**Arguments**

dataset	Dataset to explore
vars	(Numerical) variables to summaries
byvar	Variable(s) to group data by before summarizing
fun	Functions to use for summarizing
top	The variable (type) to display at the top of the table
tabfilt	Expression used to filter the table. This should be a string (e.g., "Total > 10000")
tabsort	Expression used to sort the table (e.g., "-Total")
nr	Number of rows to display
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
shiny	Logical (TRUE, FALSE) to indicate if the function call originate inside a shiny app

## Details

See <https://radiant-rstats.github.io/docs/data/explore.html> for an example in Radiant

## Value

A list of all variables defined in the function as an object of class `explore`

## See Also

See `summary.explore` to show summaries

## Examples

```
result <- explore(diamonds, "price:x")
summary(result)
result <- explore(diamonds, c("price", "carat"), byvar = "cut", fun = c("n_missing", "skew"))
summary(result)
diamonds %>% explore("price", byvar = "cut", fun = c("n_obs", "n_distinct"))
```

---

filterdata	<i>Filter data with user-specified expression</i>
------------	---

---

## Description

Filter data with user-specified expression

## Usage

```
filterdata(dataset, filt = "", drop = TRUE)
```

## Arguments

dataset	Data frame to filter
filt	Filter expression to apply to the specified dataset (e.g., "price > 10000" if dataset is "diamonds")
drop	Drop unused factor levels after filtering (default is TRUE)

## Value

Filtered data frame

---

find_dropbox	<i>Find a user's Dropbox folder</i>
--------------	-------------------------------------

---

**Description**

Find a user's Dropbox folder

**Usage**

```
find_dropbox(account = 1)
```

**Arguments**

account	If multiple accounts exist specifies the one to use. By default, the first account listed is used
---------	---

**Value**

Path to Dropbox account

---

find_gdrive	<i>Find a user's Google Drive folder</i>
-------------	--

---

**Description**

Find a user's Google Drive folder

**Usage**

```
find_gdrive()
```

**Value**

Path to Google Drive folder

---

find_project	<i>Find a rstudio project directory</i>
--------------	---

---

**Description**

Find a rstudio project directory

**Usage**

```
find_project(mess = TRUE)
```

**Arguments**

mess	Show or hide messages (default mess = TRUE)
------	---

**Value**

Path to rstudio project directory

---

fixMS	<i>Replace Windows smart quotes etc.</i>
-------	--

---

**Description**

Replace Windows smart quotes etc.

**Usage**

```
fixMS(text, all = FALSE)
```

**Arguments**

text	Text to be parsed
all	Should all non-ascii characters be removed (default = FALSE)

---

fix_names	<i>Make column names that are valid in R</i>
-----------	--

---

**Description**

Make column names that are valid in R

**Usage**

```
fix_names(x)
```

**Arguments**

x	Data.frame or vector of column names
---	--------------------------------------

**Details**

Removes symbols, trailing and leading spaces and converts to valid R column names

---

flip	<i>Flip the DT table to put Function, Variable, or Group by on top</i>
------	--

---

**Description**

Flip the DT table to put Function, Variable, or Group by on top

**Usage**

```
flip(expl, top = "fun")
```

**Arguments**

expl	Return value from <a href="#">explore</a>
top	The variable (type) to display at the top of the table ("fun" for Function, "var" for Variable, and "byvar" for Group by. "fun" is the default)

**Details**

See <https://radiant-rstats.github.io/docs/data/explore.html> for an example in Radiant

**See Also**

[explore](#) to generate summaries

[dtab.explore](#) to create the DT table

**Examples**

```
result <- explore(diamonds, "price:x", top = "var")
result <- explore(diamonds, "price", byvar = "cut", fun = c("n_obs", "skew"), top = "byvar")
```

---

formatdf	<i>Format a data.frame with a specified number of decimal places</i>
----------	--

---

**Description**

Format a data.frame with a specified number of decimal places

**Usage**

```
formatdf(tbl, dec = NULL, perc = FALSE, mark = "", ...)
```

**Arguments**

tbl	Data.frame
dec	Number of decimals to show
perc	Display numbers as percentages (TRUE or FALSE)
mark	Thousand separator
...	Additional arguments for formatnr

**Value**

Data.frame for printing

**Examples**

```
data.frame(x = c("a", "b"), y = c(1L, 2L), z = c(-0.0005, 3)) %>%
  formatdf(dec = 4)
data.frame(x = c(1L, 2L), y = c(0.05, 0.8)) %>%
  formatdf(dec = 2, perc = TRUE)
```

---

formatnr	<i>Format a number with a specified number of decimal places, thousand sep, and a symbol</i>
----------	--

---

**Description**

Format a number with a specified number of decimal places, thousand sep, and a symbol

**Usage**

```
formatnr(x, sym = "", dec = 2, perc = FALSE, mark = ",", ...)
```

**Arguments**

x	Number or vector
sym	Symbol to use
dec	Number of decimals to show
perc	Display number as a percentage
mark	Thousand separator
...	Additional arguments

**Value**

Character (vector) in the desired format

**Examples**

```
formatnr(2000, "$")
formatnr(2000, dec = 4)
formatnr(.05, perc = TRUE)
formatnr(c(.1, .99), perc = TRUE)
formatnr(data.frame(a = c(.1, .99)), perc = TRUE)
formatnr(data.frame(a = 1000), sym = "$", dec = 0)
```

---

getclass	<i>Get variable class</i>
----------	---------------------------

---

**Description**

Get variable class

**Usage**

```
getclass(dat)
```

**Arguments**

dat	Dataset to evaluate
-----	---------------------

**Details**

Get variable class information for each column in a data.frame

**Value**

Vector with class information for each variable

**Examples**

```
getclass(mtcars)
```



---

getdata	<i>Get data for analysis functions</i>
---------	--

---

**Description**

Get data for analysis functions

**Usage**

```
getdata(dataset, vars = "", filt = "", rows = NULL, na.rm = TRUE)
```

**Arguments**

dataset	Dataset or name of the data.frame
vars	Variables to extract from the data.frame
filt	Filter to apply to the specified dataset. For example "price > 10000" if dataset is "diamonds" (default is "")
rows	Select rows in the specified dataset. For example "1:10" for the first 10 rows or "n()-10:n()" for the last 10 rows (default is NULL)
na.rm	Remove rows with missing values (default is TRUE)

**Value**

Data.frame with specified columns and rows

---

getsummary	<i>Create data.frame summary</i>
------------	----------------------------------

---

**Description**

Create data.frame summary

**Usage**

```
getsummary(dataset, dc = getclass(dataset))
```

**Arguments**

dataset	Data.frame
dc	Class for each variable

**Details**

Used in Radiant's Data > Transform tab

---

ggplotly	<i>Workaround to avoid messages from ggplotly</i>
----------	---

---

**Description**

Workaround to avoid messages from ggplotly

**Usage**

```
ggplotly(...)
```

**Arguments**

... Arguments to pass to plotly::ggplotly

**See Also**

See the [ggplotly](#) in the plotly package for details (`?plotly::ggplotly`)

---

glance	<i>Exporting glance from broom</i>
--------	------------------------------------

---

**Description**

Exporting glance from broom

**Details**

See [glance](#) in the broom package for more details

---

glue	<i>Exporting glue from glue</i>
------	---------------------------------

---

**Description**

Exporting glue from glue

**Details**

See [glue](#) in the glue package for more details

---

indexr	<i>Find index corrected for missing values and filters</i>
--------	--

---

**Description**

Find index corrected for missing values and filters

**Usage**

```
indexr(dataset, vars = "", filt = "", cmd = "")
```

**Arguments**

dataset	Dataset
vars	Variables to select
filt	Data filter
cmd	A command used to customize the data

---

install_webshot	<i>Install webshot and phantomjs</i>
-----------------	--------------------------------------

---

**Description**

Install webshot and phantomjs

**Usage**

```
install_webshot()
```

---

inverse	<i>Calculate inverse of a variable</i>
---------	--

---

**Description**

Calculate inverse of a variable

**Usage**

```
inverse(x)
```

**Arguments**

x	Input variable
---	----------------

**Value**

1/x

---

is_empty	<i>Is a character variable defined</i>
----------	--

---

**Description**

Is a character variable defined

**Usage**

```
is_empty(x, empty = "\\s*")
```

**Arguments**

x	Character value to evaluate
empty	Indicate what 'empty' means. Default is empty string (i.e., "")

**Details**

Is a variable NULL or an empty string

**Value**

TRUE if empty, else FALSE

**Examples**

```
is_empty("")
is_empty(NULL)
is_empty(NA)
is_empty(c())
is_empty("none", empty = "none")
is_empty("")
is_empty(" ")
is_empty(" something ")
is_empty(c("", "something"))
is_empty(c(NA, 1:100))
is_empty(mtcars)
```

---

is_not	<i>Convenience function for is.null or is.na</i>
--------	--

---

**Description**

Convenience function for is.null or is.na

**Usage**

```
is_not(x)
```

**Arguments**

x                      Input

**Examples**

```
is_not(NA)
is_not(NULL)
is_not(c())
is_not(list())
is_not(data.frame())
```

---

is_numeric	<i>Is input numeric (and not a date type)?</i>
------------	--

---

**Description**

Is input numeric (and not a date type)?

**Usage**

```
is_numeric(x)
```

**Arguments**

x                      Input

**Value**

TRUE if double and not a type of date, else FALSE

---

is_string	<i>Is input a string?</i>
-----------	---------------------------

---

**Description**

Is input a string?

**Usage**

```
is_string(x)
```

**Arguments**

x                      Input

**Value**

TRUE if string, else FALSE

**Examples**

```
is_string(" ")
is_string("data")
is_string(c("data", ""))
is_string(NULL)
is_string(NA)
```

---

items

---

*Create a vector of interaction terms*


---

**Description**

Create a vector of interaction terms

**Usage**

```
iterms(vars, nway, sep = ":")
```

**Arguments**

vars	Variables lables to use
nway	2-way (2) or 3-way (3) interactions labels to create
sep	Separator between variable names (default is :)

**Value**

Character vector of interaction term labels

**Examples**

```
paste0("var", 1:3) %>% iterms(2)
paste0("var", 1:3) %>% iterms(3)
paste0("var", 1:3) %>% iterms(2, sep = ".")
```

---

knit\_print

---

*Exporting knit\_print from knitr*


---

**Description**

Exporting knit\_print from knitr

**Details**

See [knit\\_print](#) in the knitr package for more details

---

kurtosi	<i>Exporting kurtosi from psych</i>
---------	-------------------------------------

---

**Description**

Exporting kurtosi from psych

**Details**

See [kurtosi](#) in the psych package for more details

---

launch	<i>Launch radiant apps in default browser or Rstudio viewer</i>
--------	---

---

**Description**

Launch radiant apps in default browser or Rstudio viewer

**Usage**

```
launch(package = "radiant.data", run = "viewer")
```

**Arguments**

package	Radiant package to start. One of "radiant.data", "radiant.design", "radiant.basics", "radiant.model", "radiant.multivariate", "radiant"
run	Run radiant app in an external browser ("browser"), an Rstudio window ("window"), or in the Rstudio viewer ("viewer")

**Details**

See <https://radiant-rstats.github.io/docs> for documentation and tutorials

**Examples**

```
## Not run:  
launch()  
launch(run = "viewer")  
launch(run = "window")  
launch(run = "browser")  
  
## End(Not run)
```

---

level_list	<i>Generate list of levels and unique values</i>
------------	--

---

**Description**

Generate list of levels and unique values

**Usage**

```
level_list(dataset, ...)
```

**Arguments**

dataset	A data.frame
...	Unquoted variable names to evaluate

**Examples**

```
data.frame(a = c(rep("a",5),rep("b",5)), b = c(rep(1,5),6:10)) %>% level_list
level_list(mtcars, mpg, cyl)
```

---

ln	<i>Natural log</i>
----	--------------------

---

**Description**

Natural log

**Usage**

```
ln(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	Remove missing values (default is TRUE)

**Value**

Natural log of vector

**Examples**

```
ln(runif(10,1,2))
```



load\_clip

*Load data through clipboard on Windows or macOS***Description**

Load data through clipboard on Windows or macOS

**Usage**

```
load_clip(delim = "\t", text, suppress = TRUE)
```

**Arguments**

delim	Delimiter to use (tab is the default)
text	Text input to convert to table
suppress	Suppress warnings

**Details**

See <https://radiant-rstats.github.io/docs/data/manage.html> for an example in Radiant

load\_csv

*Load a csv file***Description**

Load a csv file

**Usage**

```
load_csv(file, delim = ",", col_names = TRUE, dec = ".", n_max = Inf,
  saf = TRUE, safx = 20)
```

**Arguments**

file	Path or connection
delim	Use , (default) or ; or \t
col_names	Header in file (TRUE, FALSE)
dec	Decimal separator
n_max	Maximum number of rows to read
saf	Convert character variables to factors if (1) there are less than 100 distinct values and (2) there are X (see safx) more values than levels
safx	Values-to-levels ratio to use when converting strings to factors

**Value**

Data frame with (some) variables converted to factors

---

make_train	<i>Generate a variable used to selected a training sample</i>
------------	---

---

**Description**

Generate a variable used to selected a training sample

**Usage**

```
make_train(n = 0.7, nr = 100, seed = 1234)
```

**Arguments**

n	Number (or fraction) of observations to label as training
nr	Number of rows in the dataset
seed	Random seed

**Value**

0/1 variables for filtering

**Examples**

```
make_train(.5, 10)
```

---

month	<i>Add ordered argument to lubridate::month</i>
-------	---

---

**Description**

Add ordered argument to lubridate::month

**Usage**

```
month(x, label = FALSE, abbr = TRUE, ordered = FALSE)
```

**Arguments**

x	Input date vector
label	Month as label (TRUE, FALSE)
abbr	Abbreviate label (TRUE, FALSE)
ordered	Order factor (TRUE, FALSE)

**See Also**

See the [month](#) function in the lubridate package for additional details

---

mutate_ext	<i>Add transformed variables to a data frame (NSE)</i>
------------	--

---

**Description**

Add tranformed variables to a data frame (NSE)

**Usage**

```
mutate_ext(.tbl, .funs, ..., .ext = "", .vars = c())
```

**Arguments**

.tbl	Data frame to add transformed variables to
.funs	Function(s) to apply (e.g., funs(log))
...	Variables to transform
.ext	Extension to add for each variable
.vars	A list of columns generated by dplyr::vars(), or a character vector of column names, or a numeric vector of column positions.

**Details**

Wrapper for dplyr::mutate\_at that allows custom variable name extensions

**Examples**

```
mutate_ext(mtcars, funs(log), mpg, cyl, .ext = "_ln")
mutate_ext(mtcars, funs(log), .ext = "_ln")
mutate_ext(mtcars, funs(log))
mutate_ext(mtcars, funs(log), .ext = "_ln", .vars = vars(mpg, cyl))
```

---

normalize	<i>Normalize a variable x by a variable y</i>
-----------	---

---

**Description**

Normalize a variable x by a variable y

**Usage**

```
normalize(x, y)
```

**Arguments**

x	Input variable
y	Normalizing variable

**Value**

x/y

---

n_missing	<i>Number of missing values</i>
-----------	---------------------------------

---

**Description**

Number of missing values

**Usage**

```
n_missing(x, ...)
```

**Arguments**

x	Input variable
...	Additional arguments

**Value**

number of missing values

**Examples**

```
n_missing(c("a", "b", NA))
```

---

n_obs	<i>Number of observations</i>
-------	-------------------------------

---

**Description**

Number of observations

**Usage**

```
n_obs(x, ...)
```

**Arguments**

x	Input variable
...	Additional arguments

**Value**

number of observations

**Examples**

```
n_obs(c("a", "b", NA))
```

---

p025	<i>2.5th percentile</i>
------	-------------------------

---

**Description**

2.5th percentile

**Usage**

```
p025(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

2.5th percentile

**Examples**

```
p025(rnorm(100))
```

---

p05	<i>5th percentile</i>
-----	-----------------------

---

**Description**

5th percentile

**Usage**

```
p05(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

5th percentile

**Examples**

```
p05(rnorm(100))
```

---

p10	<i>10th percentile</i>
-----	------------------------

---

**Description**

10th percentile

**Usage**

```
p10(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

10th percentile

**Examples**

```
p10(rnorm(100))
```

---

p25	<i>25th percentile</i>
-----	------------------------

---

**Description**

25th percentile

**Usage**

```
p25(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

25th percentile

**Examples**

```
p25(rnorm(100))
```

---

p75	75th percentile
-----	-----------------

---

**Description**

75th percentile

**Usage**

```
p75(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

75th percentile

**Examples**

```
p75(rnorm(100))
```

---

p90	90th percentile
-----	-----------------

---

**Description**

90th percentile

**Usage**

```
p90(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

90th percentile

**Examples**

```
p90(rnorm(100))
```

---

p95	95th percentile
-----	-----------------

---

**Description**

95th percentile

**Usage**

```
p95(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

95th percentile

**Examples**

```
p95(rnorm(100))
```

---

p975	97.5th percentile
------	-------------------

---

**Description**

97.5th percentile

**Usage**

```
p975(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

97.5th percentile

**Examples**

```
p975(rnorm(100))
```



---

parse_path	<i>Parse path into useful components (used by read_files function)</i>
------------	--

---

**Description**

Parse path into useful components (used by read\_files function)

**Usage**

```
parse_path(path, chr = "\"", pdir = getOption("radiant.project_dir", ""))
```

**Arguments**

path	Path to be parsed
chr	Character to wrap around path for display
pdir	Project directory if available

---

pivotr	<i>Create a pivot table using dplyr</i>
--------	---

---

**Description**

Create a pivot table using dplyr

**Usage**

```
pivotr(dataset, cvars = "", nvar = "None", fun = "mean",
        normalize = "None", tabfilt = "", tabsort = "", nr = NULL,
        data_filter = "", shiny = FALSE)
```

**Arguments**

dataset	Dataset to tabulate
cvars	Categorical variables
nvar	Numerical variable
fun	Function to apply to numerical variable
normalize	Normalize the table by "row" total,"column" totals, or overall "total"
tabfilt	Expression used to filter the table. This should be a string (e.g., "Total > 10000")
tabsort	Expression used to sort the table (e.g., "-Total")
nr	Number of rows to display
data_filter	Expression used to filter the dataset. This should be a string (e.g., "price > 10000")
shiny	Logical (TRUE, FALSE) to indicate if the function call originate inside a shiny app

**Details**

Create a pivot-table. See <https://radiant-rstats.github.io/docs/data/pivotr.html> for an example in Radiant

**Examples**

```
pivotr(diamonds, cvars = "cut")$tab
pivotr(diamonds, cvars = c("cut", "clarity", "color"))$tab
pivotr(diamonds, cvars = "cut:clarity", nvar = "price")$tab
pivotr(diamonds, cvars = "cut", nvar = "price")$tab
pivotr(diamonds, cvars = "cut", normalize = "total")$tab
```

---

plot.character	<i>Don't try to plot strings</i>
----------------	----------------------------------

---

**Description**

Don't try to plot strings

**Usage**

```
## S3 method for class 'character'
plot(x, ...)
```

**Arguments**

x	A character returned from a function
...	Any additional arguments

---

plot.pivotr	<i>Plot method for the pivotr function</i>
-------------	--

---

**Description**

Plot method for the pivotr function

**Usage**

```
## S3 method for class 'pivotr'
plot(x, type = "dodge", perc = FALSE, flip = FALSE,
     fillcol = "blue", opacity = 0.5, ...)
```

**Arguments**

x	Return value from <a href="#">pivotr</a>
type	Plot type to use ("fill" or "dodge" (default))
perc	Use percentage on the y-axis
flip	Flip the axes in a plot (FALSE or TRUE)
fillcol	Fill color for bar-plot when only one categorical variable has been selected (default is "blue")
opacity	Opacity for plot elements (0 to 1)
...	further arguments passed to or from other methods

**Details**

See <https://radiant-rstats.github.io/docs/data/pivotr> for an example in Radiant

**See Also**

[pivotr](#) to generate summaries

[summary.pivotr](#) to show summaries

**Examples**

```
pivotr(diamonds, cvars = "cut") %>% plot
pivotr(diamonds, cvars = c("cut", "clarity")) %>% plot
pivotr(diamonds, cvars = c("cut", "clarity", "color")) %>% plot
```

---

print.gtable

---

*Print/draw method for grobs produced by gridExtra*


---

**Description**

Print/draw method for grobs produced by gridExtra

**Usage**

```
## S3 method for class 'gtable'
print(x, ...)
```

**Arguments**

x	a gtable object
...	further arguments passed to or from other methods

**Details**

Print method for ggplot grobs created using grid.arrange. Code is based on <https://github.com/baptiste/gridextra/blob/master/inst/testing/shiny.R>

**Value**

A plot

---

prop	<i>Calculate proportion</i>
------	-----------------------------

---

**Description**

Calculate proportion

**Usage**

```
prop(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

Proportion of first level for a factor and of the maximum value for numeric

**Examples**

```
prop(c(rep(1L, 10), rep(0L, 10)))
prop(c(rep(4, 10), rep(2, 10)))
prop(rep(0, 10))
prop(factor(c(rep("a", 20), rep("b", 10))))
```

---

publishers	<i>Comic publishers</i>
------------	-------------------------

---

**Description**

Comic publishers

**Usage**

```
data(publishers)
```

**Format**

A data frame with 3 rows and 2 variables

**Details**

List of comic publishers from [http://stat545-ubc.github.io/bit001\\_dplyr-cheatsheet.html](http://stat545-ubc.github.io/bit001_dplyr-cheatsheet.html). The dataset is used to illustrate data merging / joining. Description provided in attr(publishers,"description")

---

<code>radiant.data</code>	<i><code>radiant.data</code></i>
---------------------------	----------------------------------

---

**Description**`radiant.data`Launch `radiant.data` in default browser**Usage**`radiant.data()`**Details**See <https://radiant-rstats.github.io/docs> for documentation and tutorials**Examples**

```
## Not run:
radiant.data()
radiant.data("viewer")

## End(Not run)
```

---

`radiant.data-deprecated`
*Deprecated function(s) in the radiant.data package***Description**These functions are provided for compatibility with previous versions of `radiant` but will be removed**Usage**`mean_rm(...)`**Arguments**`...` Parameters to be passed to the updated functions**Details**

Replace `mean_rm` by [mean](#)  
 Replace `median_rm` by [median](#)  
 Replace `min_rm` by [min](#)  
 Replace `max_rm` by [max](#)  
 Replace `sd_rm` by [sd](#)  
 Replace `var_rm` by [var](#)  
 Replace `sum_rm` by [sum](#)

---

<code>radiant.data_viewer</code>	<i>Launch radiant.data in the Rstudio viewer</i>
----------------------------------	--

---

**Description**

Launch radiant.data in the Rstudio viewer

**Usage**

```
radiant.data_viewer()
```

**Details**

See <https://radiant-rstats.github.io/docs> for documentation and tutorials

**Examples**

```
## Not run:  
radiant.data_viewer()  
  
## End(Not run)
```

---

<code>radiant.data_window</code>	<i>Launch radiant.data in the Rstudio window</i>
----------------------------------	--

---

**Description**

Launch radiant.data in the Rstudio window

**Usage**

```
radiant.data_window()
```

**Details**

See <https://radiant-rstats.github.io/docs> for documentation and tutorials

**Examples**

```
## Not run:  
radiant.data_window()  
  
## End(Not run)
```

---

read_files	<i>Return code to read file at specified path. Will open a file browser of no path is provided</i>
------------	--

---

**Description**

Return code to read file at specified path. Will open a file browser of no path is provided

**Usage**

```
read_files(path, type = "rmd", to = "", clipboard = TRUE,
  radiant = FALSE)
```

**Arguments**

path	Path to file. If empty, a file browser will be opened
type	Code for "rmd" or "r"
to	Object name to use for object. If empty, will use file name to derive an appropriate object name
clipboard	Return code to clipboard (not available on Linux)
radiant	Should returned code be formatted for use with other code generated by Radiant

---

refactor	<i>Remove/reorder levels</i>
----------	------------------------------

---

**Description**

Remove/reorder levels

**Usage**

```
refactor(x, levs = levels(x), repl = NA)
```

**Arguments**

x	Character or Factor
levs	Set of levels to use
repl	String (or NA) used to replace missing levels

**Details**

Keep only a specific set of levels in a factor. By removing levels the base for comparison in, e.g., regression analysis, becomes the first level. To relabel the base use, for example, repl = 'other'

**Examples**

```
refactor(diamonds$cut, c("Premium", "Ideal")) %>% head()
refactor(diamonds$cut, c("Premium", "Ideal", "Other")) %>% head()
```

---

register	<i>Register a data.frame or list in Radiant</i>
----------	---

---

**Description**

Register a data.frame or list in Radiant

**Usage**

```
register(new, org = "", descr = "", env)
```

**Arguments**

new	String containing the name of the data.frame to register
org	Name of the original data.frame if a (working) copy is being made
descr	Data description in markdown format
env	Environment to assign data to

---

render	<i>Method to render objects (i.e., htmlwidgets and rmarkdown files)</i>
--------	---

---

**Description**

Method to render objects (i.e., htmlwidgets and rmarkdown files)

**Usage**

```
render(object, ...)
```

**Arguments**

object	Object of relevant class to render
...	Additional arguments

---

render.character	<i>Method to render rmarkdown documents</i>
------------------	---

---

**Description**

Method to render rmarkdown documents

**Usage**

```
## S3 method for class 'character'
render(object, ...)
```

**Arguments**

object	File path to an R-markdown file
...	Additional arguments passed on to rmarkdown::render



---

render.datatables	<i>Method to render DT tabels</i>
-------------------	-----------------------------------

---

**Description**

Method to render DT tabels

**Usage**

```
## S3 method for class 'datatables'  
render(object, ...)
```

**Arguments**

object	DT table
...	Additional arguments

---

---

render.plotly	<i>Method to render plotly plots</i>
---------------	--------------------------------------

---

**Description**

Method to render plotly plots

**Usage**

```
## S3 method for class 'plotly'  
render(object, ...)
```

**Arguments**

object	plotly object
...	Additional arguments

---

---

render.shiny.render.function	<i>Method to avoid re-rendering a shiny.render.function</i>
------------------------------	---

---

**Description**

Method to avoid re-rendering a shiny.render.function

**Usage**

```
## S3 method for class 'shiny.render.function'  
render(object, ...)
```

**Arguments**

object	Shiny render function
...	Additional arguments

---

rounddf	<i>Round double in a data.frame to a specified number of decimal places</i>
---------	---

---

**Description**

Round double in a data.frame to a specified number of decimal places

**Usage**

```
rounddf(tbl, dec = 3)
```

**Arguments**

tbl	Data frame
dec	Number of decimals to show

**Value**

Data frame with rounded doubles

**Examples**

```
data.frame(x = as.factor(c("a", "b")), y = c(1L, 2L), z = c(-0.0005, 3.1)) %>%  
  rounddf(dec = 2)
```

---

rownames_to_column	<i>Exporting rownames_to_column from tibble</i>
--------------------	---

---

**Description**

Exporting rownames\_to\_column from tibble

**Details**

See [rownames](#) in the tibble package for more details

---

`save_clip`*Save data.frame or tibble to clipboard on Windows or macOS*

---

**Description**

Save data.frame or tibble to clipboard on Windows or macOS

**Usage**

```
save_clip(dataset)
```

**Arguments**

dataset            Dataset to push to clipboard

**Details**

See <https://radiant-rstats.github.io/docs/data/manage.html> for an example in Radiant

---

`sdpop`*Standard deviation for the population*

---

**Description**

Standard deviation for the population

**Usage**

```
sdpop(x, na.rm = TRUE)
```

**Arguments**

x                    Input variable  
na.rm                If TRUE missing values are removed before calculation

**Value**

Standard deviation for the population

**Examples**

```
sdpop(rnorm(100))
```

---

sdprop	<i>Standard deviation for proportion</i>
--------	--

---

**Description**

Standard deviation for proportion

**Usage**

```
sdprop(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

Standard deviation for proportion

**Examples**

```
sdprop(c(rep(1L, 10), rep(0L, 10)))
```

---

se	<i>Standard error</i>
----	-----------------------

---

**Description**

Standard error

**Usage**

```
se(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

Standard error

**Examples**

```
se(rnorm(100))
```

---

Search	<i>Search for a string in all columns of a data.frame</i>
--------	---

---

**Description**

Search for a string in all columns of a data.frame

**Usage**

```
Search(pattern, dataset, ignore.case = TRUE, fixed = FALSE)
```

**Arguments**

pattern	String to match
dataset	Data.frame to search
ignore.case	Should search be case sensitive or not (default is FALSE)
fixed	Allow regular expersions or not (default is FALSE)

**Details**

See <https://radiant-rstats.github.io/docs/data/view.html> for an example in Radiant

**See Also**

See [grepl](#) for a more detailed description of the function arguments

---

seprop	<i>Standard error for proportion</i>
--------	--------------------------------------

---

**Description**

Standard error for proportion

**Usage**

```
seprop(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

Standard error for proportion

**Examples**

```
seprop(c(rep(1L, 10), rep(0L, 10)))
```

---

set_attr	<i>Alias used to add an attribute</i>
----------	---------------------------------------

---

**Description**

Alias used to add an attribute

**Usage**

```
set_attr(x, which, value)
```

**Arguments**

x	Object
which	Attribute name
value	Value to set

**Examples**

```
foo <- data.frame(price = 1:5) %>% set_attr("desc", "price set in experiment ...")
```

---

show_duplicated	<i>Show all rows with duplicated values (not just the first or last)</i>
-----------------	--

---

**Description**

Show all rows with duplicated values (not just the first or last)

**Usage**

```
show_duplicated(.tbl, ...)
```

**Arguments**

.tbl	Data frame to add transformed variables to
...	Variables used to evaluate row uniqueness

**Details**

If an entire row is duplicated use "duplicated" to show only one of the duplicated rows. When using a subset of variables to establish uniqueness it may be of interest to show all rows that have (some) duplicate elements

**Examples**

```
bind_rows(mtcars, mtcars[c(1,5,7),]) %>%
  show_duplicated(mpg, cyl)
bind_rows(mtcars, mtcars[c(1,5,7),]) %>%
  show_duplicated
```

---

sig_stars	<i>Add stars '***' to a data.frame (from broom's 'tidy' function) based on p.values</i>
-----------	---

---

### Description

Add stars '\*\*\*' to a data.frame (from broom's 'tidy' function) based on p.values

### Usage

```
sig_stars(pval)
```

### Arguments

pval	Vector of p-values
------	--------------------

### Details

Add stars to output from broom's 'tidy' function

### Value

A vector of stars

### Examples

```
sig_stars(c(.0009, .049, .009, .4, .09))
```

---

skew	<i>Exporting skew from psych</i>
------	----------------------------------

---

### Description

Exporting skew from psych

### Details

See [skew](#) in the psych package for more details

---

square	<i>Calculate square of a variable</i>
--------	---------------------------------------

---

**Description**

Calculate square of a variable

**Usage**

```
square(x)
```

**Arguments**

x	Input variable
---	----------------

**Value**

$x^2$

---

sshh	<i>Hide warnings and messages and return invisible</i>
------	--

---

**Description**

Hide warnings and messages and return invisible

**Usage**

```
sshh(...)
```

**Arguments**

...	Inputs to keep quiete
-----	-----------------------

**Details**

Adapted from <http://www.onthelambda.com/2014/09/17/fun-with-rprofile-and-customizing-r-startup/>

**Examples**

```
sshh(library(dplyr))
```



---

sshhr	<i>Hide warnings and messages and return result</i>
-------	---

---

**Description**

Hide warnings and messages and return result

**Usage**

```
sshhr(...)
```

**Arguments**

...	Inputs to keep quiet
-----	----------------------

**Details**

Adapted from <http://www.onthelambda.com/2014/09/17/fun-with-rprofile-and-customizing-r-startup/>

**Examples**

```
sshhr(library(dplyr))
```

---

standardize	<i>Standardize</i>
-------------	--------------------

---

**Description**

Standardize

**Usage**

```
standardize(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

If x is a numeric variable return  $\text{center}(x) / \text{mean}(x)$

---

store	<i>Method to store variables in a dataset in Radiant</i>
-------	--

---

### Description

Method to store variables in a dataset in Radiant

### Usage

```
store(dataset, object = "deprecated", ...)
```

### Arguments

dataset	Dataset
object	Object of relevant class that has information to be stored
...	Additional arguments

---

store.character	<i>Method for error messages that a user tries to store</i>
-----------------	---

---

### Description

Method for error messages that a user tries to store

### Usage

```
## S3 method for class 'character'
store(dataset = NULL, object, ...)
```

### Arguments

dataset	Dataset
object	Object of type character
...	Additional arguments

---

store.explore	<i>Deprecated: Store method for the explore function</i>
---------------	--

---

### Description

Deprecated: Store method for the explore function

### Usage

```
## S3 method for class 'explore'  
store(dataset, object, name, ...)
```

### Arguments

dataset	Dataset
object	Return value from <a href="#">explore</a>
name	Name to assign to the dataset
...	further arguments passed to or from other methods

### Details

Return the summarized data. See <https://radiant-rstats.github.io/docs/data/explore.html> for an example in Radiant

### See Also

[explore](#) to generate summaries

---

store.pivotr	<i>Deprecated: Store method for the pivotr function</i>
--------------	---

---

### Description

Deprecated: Store method for the pivotr function

### Usage

```
## S3 method for class 'pivotr'  
store(dataset, object, name, ...)
```

### Arguments

dataset	Dataset
object	Return value from <a href="#">pivotr</a>
name	Name to assign to the dataset
...	further arguments passed to or from other methods

**Details**

Return the summarized data. See <https://radiant-rstats.github.io/docs/data/pivotr.html> for an example in Radiant

**See Also**

[pivotr](#) to generate summaries

---

subplot

*Workaround to avoid messages from subplot*


---

**Description**

Workaround to avoid messages from subplot

**Usage**

```
subplot(..., margin = 0.04)
```

**Arguments**

...	Arguments to pass to <code>plotly::subplot</code>
margin	Default margin to use between plots

**See Also**

See the [subplot](#) in the plotly package for details (`?plotly::subplot`)

---

summary.explore

*Summary method for the explore function*


---

**Description**

Summary method for the explore function

**Usage**

```
## S3 method for class 'explore'
summary(object, dec = 3, ...)
```

**Arguments**

object	Return value from <a href="#">explore</a>
dec	Number of decimals to show
...	further arguments passed to or from other methods

**Details**

See <https://radiant-rstats.github.io/docs/data/explore.html> for an example in Radiant

**See Also**

[explore](#) to generate summaries

**Examples**

```
result <- explore(diamonds, "price:x")
summary(result)
result <- explore(diamonds, "price", byvar = "cut", fun = c("n_obs", "skew"))
summary(result)
diamonds %>% explore("price:x") %>% summary()
diamonds %>% explore("price", byvar = "cut", fun = c("n_obs", "skew")) %>% summary()
```

summary.pivotr

*Summary method for pivotr***Description**

Summary method for pivotr

**Usage**

```
## S3 method for class 'pivotr'
summary(object, perc = FALSE, dec = 3, chi2 = FALSE,
        shiny = FALSE, ...)
```

**Arguments**

object	Return value from <a href="#">pivotr</a>
perc	Display numbers as percentages (TRUE or FALSE)
dec	Number of decimals to show
chi2	If TRUE calculate the chi-square statistic for the (pivot) table
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

**Details**

See <https://radiant-rstats.github.io/docs/data/pivotr.html> for an example in Radiant

**See Also**

[pivotr](#) to create the pivot-table using dplyr

**Examples**

```
pivotr(diamonds, cvars = "cut") %>% summary(chi2 = TRUE)
pivotr(diamonds, cvars = "cut", tabsort = "-n_obs") %>% summary()
pivotr(diamonds, cvars = "cut", tabsort = "desc(n_obs)") %>% summary()
pivotr(diamonds, cvars = "cut", tabfilt = "n_obs > 700") %>% summary()
pivotr(diamonds, cvars = "cut:clarity", nvar = "price") %>% summary()
```

---

`superheroes`*Super heroes*

---

**Description**

Super heroes

**Usage**

```
data(superheroes)
```

**Format**

A data frame with 7 rows and 4 variables

**Details**

List of super heroes from [http://stat545-ubc.github.io/bit001\\_dplyr-cheatsheet.html](http://stat545-ubc.github.io/bit001_dplyr-cheatsheet.html).

The dataset is used to illustrate data merging / joining. Description provided in `attr(superheroes,"description")`

---

`table2data`*Create data.frame from a table*

---

**Description**

Create data.frame from a table

**Usage**

```
table2data(dataset, freq = tail(colnames(dataset), 1))
```

**Arguments**

`dataset`            Data.frame

`freq`               Column name with frequency information

**Examples**

```
data.frame(price = c("$200", "$300"), sale = c(10, 2)) %>% table2data()
```

---

`tibble`*Exporting tibble from tibble*

---

**Description**

Exporting tibble from tibble

**Details**

See [tibble](#) in the tibble package for more details

---

tidy	<i>Exporting tidy from broom</i>
------	----------------------------------

---

**Description**

Exporting tidy from broom

**Details**

See [tidy](#) in the broom package for more details

---

titanic	<i>Survival data for the Titanic</i>
---------	--------------------------------------

---

**Description**

Survival data for the Titanic

**Usage**

```
data(titanic)
```

**Format**

A data frame with 1043 rows and 10 variables

**Details**

Survival data for the Titanic. Description provided in attr(titanic,"description")

---

toFct	<i>Convert character to factors as needed</i>
-------	---

---

**Description**

Convert character to factors as needed

**Usage**

```
toFct(dataset, safx = 30)
```

**Arguments**

dataset	Data frame
safx	Values to levels ratio

**Value**

Data frame with factors

---

varpop	<i>Variance for the population</i>
--------	------------------------------------

---

**Description**

Variance for the population

**Usage**

```
varpop(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

Variance for the population

**Examples**

```
varpop(rnorm(100))
```

---

varprop	<i>Variance for proportion</i>
---------	--------------------------------

---

**Description**

Variance for proportion

**Usage**

```
varprop(x, na.rm = TRUE)
```

**Arguments**

x	Input variable
na.rm	If TRUE missing values are removed before calculation

**Value**

Variance for proportion

**Examples**

```
varprop(c(rep(1L, 10), rep(0L, 10)))
```



---

viewdata	<i>View data in a shiny-app</i>
----------	---------------------------------

---

## Description

View data in a shiny-app

## Usage

```
viewdata(dataset, vars = "", filt = "", rows = NULL, na.rm = FALSE,
  dec = 3)
```

## Arguments

dataset	Data.frame or name of the dataframe to view
vars	Variables to show (default is all)
filt	Filter to apply to the specified dataset. For example "price > 10000" if dataset is "diamonds" (default is "")
rows	Select rows in the specified dataset. For example "1:10" for the first 10 rows or "n()-10:n()" for the last 10 rows (default is NULL)
na.rm	Remove rows with missing values (default is FALSE)
dec	Number of decimals to show

## Details

View, search, sort, etc. your data

## Examples

```
if (interactive()) {
  viewdata(mtcars)
  mtcars %>% viewdata()
}
```

---

visualize	<i>Visualize data using ggplot2</i> <a href="http://ggplot2.tidyverse.org">http://ggplot2.tidyverse.org</a>
-----------	---

---

## Description

Visualize data using ggplot2 <http://ggplot2.tidyverse.org>

## Usage

```
visualize(dataset, xvar, yvar = "", comby = FALSE, combx = FALSE,
  type = ifelse(is_empty(yvar), "dist", "scatter"), nrobs = -1,
  facet_row = ".", facet_col = ".", color = "none", fill = "none",
  size = "none", fillcol = "blue", linecol = "black",
  pointcol = "black", bins = 10, smooth = 1, fun = "mean", check = "",
  axes = "", alpha = 0.5, xlim = NULL, ylim = NULL, data_filter = "",
  shiny = FALSE, custom = FALSE)
```

## Arguments

dataset	Data to plot (data.frame or tibble)
xvar	One or more variables to display along the X-axis of the plot
yvar	Variable to display along the Y-axis of the plot (default = "none")
comby	Combine yvars in plot (TRUE or FALSE, FALSE is the default)
combx	Combine xvars in plot (TRUE or FALSE, FALSE is the default)
type	Type of plot to create. One of Distribution ('dist'), Density ('density'), Scatter ('scatter'), Surface ('surface'), Line ('line'), Bar ('bar'), or Box-plot ('box')
nrobs	Number of data points to show in scatter plots (-1 for all)
facet_row	Create vertically arranged subplots for each level of the selected factor variable
facet_col	Create horizontally arranged subplots for each level of the selected factor variable
color	Adds color to a scatter plot to generate a 'heat map'. For a line plot one line is created for each group and each is assigned a different color
fill	Display bar, distribution, and density plots by group, each with a different color. Also applied to surface plots to generate a 'heat map'
size	Numeric variable used to scale the size of scatter-plot points
fillcol	Color used for bars, boxes, etc. when no color or fill variable is specified
linecol	Color for lines when no color variable is specified
pointcol	Color for points when no color variable is specified
bins	Number of bins used for a histogram (1 - 50)
smooth	Adjust the flexibility of the loess line for scatter plots
fun	Set the summary measure for line and bar plots when the X-variable is a factor (default is "mean"). Also used to plot an error bar in a scatter plot when the X-variable is a factor. Options are "mean" and/or "median"
check	Add a regression line ("line"), a loess line ("loess"), or jitter ("jitter") to a scatter plot
axes	Flip the axes in a plot ("flip") or apply a log transformation (base e) to the y-axis ("log_y") or the x-axis ("log_x")
alpha	Opacity for plot elements (0 to 1)
xlim	Set limit for y-axis (e.g., c(0, 1))
ylim	Set limit for y-axis (e.g., c(0, 1))
data_filter	Expression used to filter the dataset. This should be a string (e.g., "price > 10000")
shiny	Logical (TRUE, FALSE) to indicate if the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and <a href="http://docs.ggplot2.org/">http://docs.ggplot2.org/</a> for options.

## Details

See <https://radiant-rstats.github.io/docs/data/visualize.html> for an example in Radiant

**Value**

Generated plots

**Examples**

```
visualize(diamonds, "price:cut", type = "dist", fillcol = "red")
visualize(diamonds, "carat:cut", yvar = "price", type = "scatter",
  pointcol = "blue", fun = c("mean", "median"), linecol = c("red", "green"))
visualize(diamonds, yvar = "price", xvar = c("cut", "clarity"),
  type = "bar", fun = "median")
visualize(diamonds, yvar = "price", xvar = c("cut", "clarity"),
  type = "line", fun = "max")
visualize(diamonds, yvar = "price", xvar = "carat", type = "scatter",
  size = "table", custom = TRUE) + scale_size(range=c(1,10), guide = "none")
visualize(diamonds, yvar = "price", xvar = "carat", type = "scatter", custom = TRUE) +
  labs(title = "A scatterplot", x = "price in $")
visualize(diamonds, xvar = "price:carat", custom = TRUE) %>%
  gridExtra::grid.arrange(grobs = ., top = "Histograms", ncol = 2)
visualize(diamonds, xvar = "cut", yvar = "price", type = "bar",
  facet_row = "cut", fill = "cut")
```

---

wday

---

*Add ordered argument to lubridate::wday*


---

**Description**

Add ordered argument to lubridate::wday

**Usage**

```
wday(x, label = FALSE, abbr = TRUE, ordered = FALSE)
```

**Arguments**

x	Input date vector
label	Weekday as label (TRUE, FALSE)
abbr	Abbreviate label (TRUE, FALSE)
ordered	Order factor (TRUE, FALSE)

**See Also**

See the [lubridate::wday\(\)](#) function in the lubridate package for additional details

---

weighted.sd	<i>Weighted standard deviation</i>
-------------	------------------------------------

---

**Description**

Weighted standard deviation

**Usage**

```
weighted.sd(x, wt, na.rm = TRUE)
```

**Arguments**

x	Numeric vector
wt	Numeric vector of weights
na.rm	Remove missing values (default is TRUE)

**Details**

Calculated a weighted standard deviation

---

which.pmax	<i>Returns the index of the (parallel) maxima of the input values</i>
------------	---

---

**Description**

Returns the index of the (parallel) maxima of the input values

**Usage**

```
which.pmax(...)
```

**Arguments**

...	Numeric or character vectors of the same length
-----	---

**Value**

Vector of rankings

**Examples**

```
which.pmax(1:10, 10:1)
which.pmax(2, 10:1)
which.pmax(mtcars)
```

---

which.pmin

*Returns the index of the (parallel) minima of the input values*


---

**Description**

Returns the index of the (parallel) minima of the input values

**Usage**

```
which.pmin(...)
```

**Arguments**

...                      Numeric or character vectors of the same length

**Value**

Vector of rankings

**Examples**

```
which.pmin(1:10, 10:1)
which.pmin(2, 10:1)
which.pmin(mtcars)
```

---

write\_feather

*Workaround to add description using feather::write\_feather*


---

**Description**

Workaround to add description using feather::write\_feather

**Usage**

```
write_feather(x, path, description = attr(x, "description"))
```

**Arguments**

x                      A data frame to write to disk  
path                    Path to feather file  
description            Data description

---

`xtile`*Create quantiles*

---

**Description**

Create quantiles

**Usage**

```
xtile(x, n = 5, rev = FALSE)
```

**Arguments**

<code>x</code>	Numeric variable
<code>n</code>	number of bins to create
<code>rev</code>	Reverse the order of the xtiles

**Details**

Approach used produces results most similar to Stata

**Examples**

```
xtile(1:10,5)
xtile(1:10,5, rev = TRUE)
```

# Index

## \*Topic **datasets**

- avengers, [14](#)
- diamonds, [21](#)
- publishers, [52](#)
- superheroes, [70](#)
- titanic, [71](#)

- add\_class, [5](#)
- as\_character, [5](#)
- as\_distance, [6](#)
- as\_dmy, [6](#)
- as\_dmy\_hm, [7](#)
- as\_dmy\_hms, [7](#)
- as\_duration, [8](#)
- as\_factor, [8](#)
- as\_hm, [9](#)
- as\_hms, [9](#)
- as\_integer, [10](#)
- as\_mdy, [10](#)
- as\_mdy\_hm, [11](#)
- as\_mdy\_hms, [12](#)
- as\_numeric, [12](#)
- as\_tibble, [13](#), [13](#)
- as\_ymd, [13](#)
- as\_ymd\_hm, [13](#)
- as\_ymd\_hms, [14](#)
- avengers, [14](#)

- center, [15](#)
- choose\_dir, [15](#)
- choose\_files, [16](#)
- ci\_label, [16](#)
- ci\_perc, [17](#)
- combinedata, [17](#)
- copy\_all, [18](#)
- copy\_attr, [19](#)
- copy\_from, [19](#)
- cv, [20](#)

- describe, [20](#)
- diamonds, [21](#)
- does\_vary, [21](#)
- dtab, [22](#)
- dtab.character, [22](#)

- dtab.data.frame, [22](#), [23](#)
- dtab.explore, [22](#), [24](#), [30](#)
- dtab.pivotr, [22](#), [25](#)
- empty\_level, [26](#)
- explore, [22](#), [24](#), [26](#), [30](#), [67–69](#)

- filterdata, [27](#)
- find\_dropbox, [28](#)
- find\_gdrive, [28](#)
- find\_project, [29](#)
- fix\_names, [30](#)
- fixMS, [29](#)
- flip, [30](#)
- formatdf, [31](#)
- formatnr, [31](#)

- getclass, [32](#)
- getdata, [33](#)
- getsummary, [33](#)
- ggplotly, [34](#), [34](#)
- glance, [34](#), [34](#)
- glue, [34](#), [34](#)
- grepl, [61](#)

- indexr, [35](#)
- install\_webshot, [35](#)
- inverse, [35](#)
- is\_empty, [36](#)
- is\_not, [36](#)
- is\_numeric, [37](#)
- is\_string, [37](#)
- iterms, [38](#)

- knit\_print, [38](#), [38](#)
- kurtosi, [39](#), [39](#)

- launch, [39](#)
- level\_list, [40](#)
- ln, [40](#)
- load\_clip, [41](#)
- load\_csv, [41](#)
- lubridate::wday(), [75](#)

- make\_train, [42](#)

- max, [53](#)
- mean, [53](#)
- mean\_rm (radiant.data-deprecated), [53](#)
- mean\_rmn (radiant.data-deprecated), [53](#)
- median, [53](#)
- min, [53](#)
- month, [42](#), [42](#)
- mutate\_ext, [43](#)
  
- n\_missing, [44](#)
- n\_obs, [44](#)
- normalize, [43](#)
  
- p025, [45](#)
- p05, [45](#)
- p10, [46](#)
- p25, [46](#)
- p75, [47](#)
- p90, [47](#)
- p95, [48](#)
- p975, [48](#)
- parse\_path, [49](#)
- pivotr, [22](#), [24](#), [25](#), [49](#), [51](#), [67–69](#)
- plot.character, [50](#)
- plot.pivotr, [50](#)
- print.gtable, [51](#)
- prop, [52](#)
- publishers, [52](#)
  
- radiant.data, [53](#)
- radiant.data-deprecated, [53](#)
- radiant.data-deprecated-package (radiant.data-deprecated), [53](#)
- radiant.data-package (radiant.data), [53](#)
- radiant.data\_viewer, [54](#)
- radiant.data\_window, [54](#)
- read\_files, [55](#)
- refactor, [55](#)
- register, [56](#)
- render, [56](#)
- render.character, [56](#)
- render.datatables, [57](#)
- render.plotly, [57](#)
- render.shiny.render.function, [57](#)
- rounddf, [58](#)
- rownames, [58](#)
- rownames\_to\_column, [58](#)
  
- save\_clip, [59](#)
- sd, [53](#)
- sdpop, [59](#)
- sdprop, [60](#)
- se, [60](#)
  
- Search, [61](#)
- seprop, [61](#)
- set\_attr, [62](#)
- show\_duplicated, [62](#)
- sig\_stars, [63](#)
- skew, [63](#), [63](#)
- square, [64](#)
- sshh, [64](#)
- sshhr, [65](#)
- standardize, [65](#)
- store, [66](#)
- store.character, [66](#)
- store.explore, [67](#)
- store.pivotr, [67](#)
- subplot, [68](#), [68](#)
- sum, [53](#)
- summary.explore, [27](#), [68](#)
- summary.pivotr, [24](#), [25](#), [51](#), [69](#)
- superheroes, [70](#)
  
- table2data, [70](#)
- tibble, [70](#), [70](#)
- tidy, [71](#), [71](#)
- titanic, [71](#)
- toFct, [71](#)
  
- var, [53](#)
- varpop, [72](#)
- varprop, [72](#)
- viewdata, [73](#)
- visualize, [73](#)
  
- wday, [75](#)
- weighted.sd, [76](#)
- which.pmax, [76](#)
- which.pmin, [77](#)
- write\_feather, [77](#)
  
- xtile, [78](#)