Interactive Design Layout Report

LinguaLink – AI Language Translation Application

Course: Human Computer Interaction (CS5015)
Faculty: B Sivaselvan
Student Name: Lohith Pakala
Roll Number: CS23B2030
Date: February 28, 2026

Contents

1 Abstract **3**

2 Introduction to HCI and Application Context **3**

2.1 What is HCI? 3

2.2 Need for HCI in Language Translation Applications 3

3 Problem Definition and Target Users **3**

3.1 User Groups 3

3.2 Context of Use 4

4 Application of 80–20 Rule (Vital Few Focus) **4**

4.1 Identification of Critical 20% Features 4

4.2 Supporting 80% Features 4

5 Overall Design Architecture **5**

5.1 Information Architecture 5

6 Screen-wise Design Analysis **6**

6.1 Home Screen 6

6.2 Language Selection Screen 7

6.3 Translation Result Screen 8

6.4 Voice Translation Screen 9

7 Shneiderman's 8 Golden Rules Application **9**

8 Nielsen's Usability Heuristics **11**

9 Classical Design Laws Applied **11**

9.1 Miller's 7±2 Rule 11

9.2 Primacy and Recency Effect 12

9.3 Fitts' Law 13

9.4 Mental Models 14

9.5 Inverted Pyramid Principle 15

10 Tesler's Law vs Vital Few Balance **16**

11 Usability Evaluation **17**

12 Asimov's Interaction Laws Applied **17**

13 Conclusion **18**

14 Appendix **18**

14.1 Prototype Link 18

1 Abstract

LinguaLink is a mobile-first AI language translation application designed with usability as the primary focus. The system supports real-time translation in cognitively demanding contexts such as travel and cross-cultural communication, where efficiency and clarity are essential. From an HCI perspective, the interface minimizes cognitive load, reduces reliance on short-term memory, and prioritizes recognition over recall. Core translation actions are visually emphasized to support fast task completion.

The design integrates Shneiderman's Golden Rules and Nielsen's Usability Heuristics to ensure consistency, feedback, and error prevention. Classical cognitive laws such as Miller's 7±2 Rule, Fitts' Law, Primacy–Recency Effect, Mental Models, and the Vital Few (80–20 Principle) guide feature organization and interaction design. Tesler's Law is applied to manage complexity internally while preserving interface simplicity.

2 Introduction to HCI and Application Context

2.1 What is HCI?

Human–Computer Interaction (HCI) is the study and design of interactive systems with a focus on usability, cognitive compatibility, and effective task completion. It examines the relationship between the user, the computer system, and the interface, ensuring that functionality can be efficiently utilized without imposing unnecessary cognitive or motor burden.

2.2 Need for HCI in Language Translation Applications

Language translation applications are typically used in real-time and often stressful environments such as travel and business communication. In such contexts, users cannot afford high cognitive load, ambiguous controls, or delayed feedback. Therefore, LinguaLink prioritizes cognitive simplicity, motor efficiency, recognition over recall, and immediate system status visibility.

3 Problem Definition and Target Users

3.1 User Groups

- Travelers
- Students
- Professionals

- Tourists

3.2 Context of Use

LinguaLink is primarily used on mobile devices under cognitively demanding conditions such as noisy environments, time constraints, and one-handed interaction scenarios. Accordingly, the interface emphasizes large touch targets (Fitts' Law), minimal navigation depth, high-contrast hierarchy, and continuous feedback to reduce memory load and improve efficiency.

4 Application of 80–20 Rule (Vital Few Focus)

4.1 Identification of Critical 20% Features

The interface is structured around the Vital Few principle, where a small subset of features delivers the majority of user value:

- Text Translation
- Voice Translation
- Camera Translation
- Language Selection and Swap Control
- Primary Translate Action

These features dominate the visual hierarchy through size, placement, and contrast.

4.2 Supporting 80% Features

Secondary features such as History, Settings, and Help are organized within bottom navigation and secondary menus. This separation reduces cognitive overload while preserving robustness, aligning with Tesler's Law of complexity conservation.

5 Overall Design Architecture

5.1 Information Architecture



Figure 1: Overall Information Architecture and Navigation Structure

The navigation follows a flat hierarchy with five bottom navigation elements, complying with Miller's 7±2 Rule. Primary translation flows require minimal steps, supporting recognition over recall.

6 Screen-wise Design Analysis

6.1 Home Screen



Figure 2: Home Screen – Vital Few Prioritization

The home screen emphasizes the Translate action using size and contrast (Fitts' Law). Primary tasks are positioned above the fold (Primacy Effect), while selected language states remain visible (Visibility of System Status).

6.2 Language Selection Screen



Figure 3: Language Selection Interface

Languages are grouped logically rather than purely alphabetically.

6.3 Translation Result Screen



Figure 4: Translation Output with Feedback and Closure

The Translation Result screen provides immediate and informative feedback through the highlighted output card, confidence indicator ("92% match"), and distinct language labeling. The visual separation between input and translated output establishes clear closure, signaling successful task completion. Action controls such as Copy, Share, and Undo are positioned directly beneath the translated text, reducing cursor or thumb travel distance in accordance with Fitts' Law. Additionally, the proximity of these controls to the output supports recognition over recall by allowing users to act on the result without navigating away or searching for secondary menus.

6.4 Voice Translation Screen



Figure 5: Voice Translation with System Status Visibility

The Voice Translation screen maintains continuous visibility of system status through dynamic indicators such as the "Translating..." progress bar, animated waveform visualization, and real-time speech capture display ("You Said"). These elements reduce user uncertainty during processing delays and align with Nielsen's principle of visibility of system status. The large central microphone control follows Fitts' Law by providing an easily reachable and prominent interaction target for start/stop recording. Additionally, the clear distinction between captured speech and translated output establishes task transparency, while retry and recovery mechanisms support robustness and error tolerance in noisy or unstable environments.

7 Shneiderman's 8 Golden Rules Application

Golden Rule	Application in LinguaLink
Strive for Consistency	Uniform iconography (mic, camera, flags), consistent card-based layout for input/output, and identical bottom navigation across all screens (Home, Voice, Camera, History, Settings) ensure structural and visual consistency.
Enable Frequent Users to Use Shortcuts	Auto-detect language, recent language chips, and quick access bottom navigation reduce repeated configuration effort for returning users.
Offer Informative Feedback	Real-time indicators such as "Translating...", waveform animation, "Scanning for text...", confidence percentage (92%), and "Translation complete" messages provide immediate system status visibility.
Design Dialogues to Yield Closure	Clear completion states are displayed after translation through highlighted output cards and confirmation indicators, signaling successful task completion.
Offer Error Prevention	Input validation, visible character limits (54/5000), and structured action buttons reduce accidental misuse. Settings such as "Clear History – Cannot be undone" explicitly warn users before destructive actions.
Permit Easy Reversal of Actions	Undo functionality in translation results and editable input fields allow users to recover from mistakes without restarting the task.
Support Internal Locus of Control	Users maintain control through manual language swap, mode selection (Text/Voice/Camera), and toggle-based configuration in settings. The system assists but does not override user intent.
Reduce Short-Term Memory Load	Primary actions are visible above the fold, recent languages are displayed for recognition, and navigation is limited to five items, minimizing reliance on recall.

8 Nielsen's Usability Heuristics

- **Visibility of System Status:** The system continuously communicates processing states through indicators such as "Translating...", animated waveform feedback, "Scanning for text...", confidence percentages (e.g., 92% match), and "Translation complete" messages. These reduce uncertainty and cognitive anxiety during AI processing delays.
- **Match Between System and Real World:** Familiar metaphors such as microphone for voice input, camera for text scanning, flag-based language indicators, and card-based translation outputs align with established user mental models, reducing learning effort.
- **User Control and Freedom:** Language swap controls, undo functionality in translation results, editable input fields, and toggle-based settings (Auto-translate, Dark Mode, Save History) ensure users can reverse actions and customize behavior without system dominance.
- **Error Prevention:** Character limits (54/5000), clearly separated destructive actions (e.g., "Clear History – Cannot be undone"), and structured interaction flows minimize accidental misuse and destructive errors.
- **Recognition Rather Than Recall:** Recent languages, bottom navigation icons, visible mode tabs (Text / Voice / Camera), and direct access to Copy/Share actions reduce dependency on memory retrieval.
- **Consistency and Standards:** Uniform bottom navigation across all screens, consistent color semantics (green = success, orange = primary action), and standardized card layouts maintain interaction predictability.

9 Classical Design Laws Applied

9.1 Miller's 7±2 Rule



Figure 6: Navigation Limitation Supporting Miller's 7±2 Rule

The bottom navigation is limited to five primary options (Home, Voice, Camera, History, Settings), reducing short-term memory load and preventing cognitive overload. By

constraining visible choices, the interface supports efficient decision-making without overwhelming the user.

9.2 Primacy and Recency Effect



Figure 7: Placement of Core Actions Using Primacy–Recency Effect

High-priority actions such as language selection and the primary Translate button are positioned prominently near the top and center of the interface. Frequently accessed navigation items are placed at the bottom, leveraging both primacy and recency effects to enhance recall and task efficiency.

9.3 Fitts' Law

Figure 8: Large Call-to-Action Button Optimized Using Fitts' Law

The large, centrally positioned Translate button and microphone control reduce movement time and increase target accessibility. By increasing button size and minimizing travel distance, the interface optimizes motor efficiency, particularly in one-handed mobile usage contexts.

9.4 Mental Models



Figure 9: Alignment with User Mental Models

The interface follows familiar patterns that users have already experienced in other applications. The microphone icon naturally suggests voice input, the camera icon indicates text scanning, and flag symbols represent language selection. The swap icon () clearly conveys reversing the translation direction. The separation between input and output sections follows the common pattern of entering text and receiving a result below. By using these familiar elements, the system becomes easy to understand without requiring additional learning.

9.5 Inverted Pyramid Principle



Figure 10: Above-the-Fold Prioritization Using Inverted Pyramid Structure

The home screen follows an inverted pyramid structure where the most important interaction elements are placed at the top of the interface. Language selection, text input, and the primary Translate button are positioned above the fold, ensuring they receive immediate user attention. Secondary elements such as recent languages and bottom navigation appear lower on the screen. This hierarchical arrangement guides user focus from essential tasks to supporting features, reducing visual search time and improving task efficiency.

10 Tesler's Law vs Vital Few Balance



Figure 11: Balancing Simplicity (Vital Few) with Managed System Complexity (Tesler's Law)

The primary interface presents only the essential translation actions—Text, Voice, Camera input, language selection, and the central Translate button—ensuring cognitive simplicity and reduced decision complexity. These high-frequency tasks represent the Vital Few features that deliver maximum user value with minimal interaction effort.

Advanced configurations such as auto-translate, dark mode, language detection, history control, and data clearing are intentionally placed within the Settings section. This reflects Tesler's Law, which states that system complexity cannot be eliminated but must

be managed. Instead of exposing algorithmic and configuration complexity in the core workflow, the design relocates it to a secondary layer.

By separating essential actions from advanced options, LinguaLink maintains a clean and focused primary interface while preserving full functional robustness. This balance ensures usability for first-time users and flexibility for experienced users without overwhelming either group.

11 Usability Evaluation

- **Learnability** – Minimal onboarding is required due to familiar iconography (mic, camera, flags) and clear visual hierarchy. First-time users can immediately identify core actions.
- **Efficiency** – Primary translation tasks can be completed in one or two interaction steps, minimizing cognitive and motor effort.
- **Memorability** – Consistent layout, stable bottom navigation, and uniform card structures across modes reduce relearning effort after periods of non-use.
- **Error Handling** – Clear feedback messages, undo functionality, visible character limits, and recovery mechanisms support robustness and fault tolerance.
- **Flexibility** – The system allows the same task (language translation) to be performed through multiple modalities—Text, Voice, and Camera input. This flexibility accommodates different user preferences, environmental constraints, and expertise levels, thereby enhancing efficiency for frequent users.
- **Satisfaction** – Clean visual hierarchy, clear completion states, and responsive feedback contribute to a smooth and cognitively comfortable user experience.

12 Asimov's Interaction Laws Applied

- **The system protects user work:** Translations are automatically saved in History (when enabled), preventing accidental loss of important communication. Undo functionality in the result screen further supports safe interaction.
- **The system minimizes wasted effort:** Auto-detect language, recent language shortcuts, and multiple input modes (Text, Voice, Camera) reduce repeated configuration and speed up task completion in time-critical situations.
- **The interface avoids user blame:** Error states and processing delays are communicated through neutral messages such as "Translating..." or "Scanning for

text. . . ” rather than accusatory prompts. Clear warnings (e.g., “Clear History – Cannot be undone”) inform without blaming the user.

13 Conclusion

LinguaLink demonstrates a deliberate and structured application of Human–Computer Interaction principles in mobile interface design. By prioritizing the Vital Few features, applying classical cognitive laws such as Fitts’ Law and Miller’s Rule, and managing hidden complexity through Tesler’s Law, the system achieves a clear balance between simplicity and functional robustness.

The interface supports real-time use in cognitively demanding contexts through visible system status, reduced memory load, and flexible interaction modes (Text, Voice, and Camera). Overall, the design reflects a human-centered approach where efficiency, clarity, and controlled complexity guide interaction decisions, resulting in a usable and adaptable translation experience..

14 Appendix

The complete interactive prototype of LinguaLink is provided as an accompanying HTML document.

The submitted HTML file contains the full navigable interface, including Text, Voice, Camera, History, and Settings screens with dynamic interaction states.

Please refer to the submitted HTML document for a complete demonstration of the interaction flow and functional behavior of the system.

14.1 Prototype Link

https://claude.ai/public/artifacts/471e721f-d33d-4d82-ac91-e27e9af652c8