Evaluating Feature Attribution Stability Using SHAP Across Multiple Machine Learning Models

Pallav Anand
Credit Karma
pallav.anand@creditkarma.com

Abstract

We train three tree-based models (Random Forest, Gradient Boosting, and XGBoost) on the same tabular datasets and compare their SHAP-based global feature importance and *instance-level* (local) stability. Using three public datasets—California Housing (regression), Adult income (classification), and Titanic (classification)—we compute pairwise Spearman rank correlation of feature importance, top-k overlap (Jaccard index), and per-instance metrics (mean pairwise Spearman per instance, proportion of "stable" instances). We find that SHAP-derived importance rankings are often highly correlated across models (e.g., Spearman $r \approx 0.88$–0.98) but local attributions are less stable; many instances are not Spearman-stable or top-k-stable. We report test-set model performance and conclude that practitioners should not treat a single model's SHAP explanation as unique; checking consistency across models or reporting which model was explained is recommended.

Keywords: SHAP; feature attribution; explainable AI; model comparison; stability; tree ensembles.

1 Introduction

SHAP (SHapley Additive exPlanations) is widely used to explain predictions of machine learning models by attributing importance to each input feature. When multiple models achieve similar predictive performance on the same task, a natural question is whether their explanations agree: do they identify the same features as important, and in the same order?

Prior work has shown that feature attributions can vary with model choice and that different models with comparable accuracy may yield different local explanations. We quantify this phenomenon for *global* SHAP-based feature importance across three popular tree-based models—Random Forest, Gradient Boosting, and XGBoost—on three public datasets. We also address the gap of *instance-level* stability: whether local attributions are stable across models for the same instance, and how to summarize that (e.g., per-instance rank correlation, proportion of "stable" instances). We measure agreement via pairwise Spearman rank correlation and top-k feature set overlap (Jaccard index), and we report model performance metrics so that explanation stability can be interpreted alongside predictive performance.

2 Related Work

Consistency of SHAP within a single model (e.g., tree ensembles) is well studied. The Rashomon set framework addresses explanation variability across models that perform equally well: different models in the set can yield different attributions for the same prediction. SHAP rankings have also been shown to be sensitive to architecture and random initialization in deep learning. We focus on tabular data and tree explainers, and provide a systematic empirical comparison with explicit metrics (Spearman, top-k overlap) that can be replicated.

3 Methods

3.1 Datasets and Labels

We use three public datasets:

- **California Housing**: regression; target is median house value (MedHouseVal). Source: sklearn `fetch_california_housing`.
- **Adult**: classification; target is income > 50K (binary). Source: OpenML adult, version 2. Numeric features only.
- **Titanic**: classification; target is survival (binary). Source: OpenML titanic, version 1.

Data are split 80%/20% train/test with a fixed random seed (42) for reproducibility.

3.2 Models

For each dataset we train three models with default or standard settings ($n_estimators = 100$, fixed `random_state`=42):

- Random Forest (scikit-learn)
- Gradient Boosting (scikit-learn)
- XGBoost

Regression models are used for California Housing; classifiers for Adult and Titanic.

3.3 SHAP and Global Importance

We use TreeExplainer (SHAP) with a small background set (100 samples from the training set) and compute SHAP values for a subsample of the test set (200 samples by default). For each model we define *global* feature importance as the mean absolute SHAP value per feature over this subsample. Features are then ranked by this importance (rank 1 = most important).

3.4 Stability Metrics

- **Spearman rank correlation**: pairwise, between the feature rankings of each pair of models. High r indicates similar ordering of importance.
- **Top-k overlap (Jaccard)**: for each pair of models, the Jaccard index of the sets of top-k feature indices ($k = 5$). Equal to 1 if the same k features are selected (order ignored).

3.5 Instance-level (local) stability

Global metrics (mean |`SHAP`|) do not capture whether *per-instance* attributions agree across models. For each instance in the SHAP subsample we compute: (i) pairwise Spearman correlation of the three models' SHAP vectors (across features), then the mean pairwise ρ over the three pairs; (ii) for each pair, the top-k feature set from that instance's SHAP values, and the Jaccard index between those sets—we take the minimum Jaccard over the three pairs (worst agreement). We summarize across instances by the mean and standard deviation of (i), the *proportion of instances* with mean pairwise $\rho \geq 0.9$ ("Spearman-stable"), the mean of (ii), and the proportion of instances for which all three models have identical top-k sets ("top-k-stable"). This addresses the gap of whether local attributions are stable across models for the same instance.

3.6 Model Performance

We report test-set metrics to contextualize explanation comparison: RMSE and R^2 for regression; accuracy and AUC for classification.

4 Results

All numbers below are from a single run with `random_state=42` and `-shap-sample 200`. Reproduce with: `python shap_stability.py -dataset california` (and `adult`, `titanic`).

Table **??** summarizes model performance. Table **??** gives pairwise Spearman correlation of SHAP feature rankings; Table **??** gives top-5 Jaccard overlap. Table **??** summarizes instance-level stability (mean pairwise Spearman per instance, proportion Spearman-stable, mean min top-5 Jaccard, proportion top-5 identical). Table **??** shows the top-5 features by mean |`SHAP`| per model for California Housing. Figure **??** illustrates global feature importance for one dataset. Rankings are often highly correlated but the top-5 set or order can differ across models (e.g., XGBoost vs. others on California); local stability is generally lower than global, with many instances not Spearman-stable or top-5-stable.

Table 1: Test-set performance (single run, seed 42).

Dataset	Model	Metric 1	Metric 2
California	RF	RMSE 0.505	R^2 0.805
	GBM	RMSE 0.542	R^2 0.776
	XGB	RMSE 0.474	R^2 0.829
Adult	RF	Acc. 0.809	AUC 0.827
	GBM	Acc. 0.844	AUC 0.868
	XGB	Acc. 0.849	AUC 0.874
Titanic	RF	Acc. 0.798	AUC 0.860
	GBM	Acc. 0.782	AUC 0.876
	XGB	Acc. 0.786	AUC 0.865

Table 2: Pairwise Spearman correlation of SHAP feature rankings (single run).

Dataset	Model pair	Spearman r
California	RF–GBM	0.976
	RF–XGB	0.905
	GBM–XGB	0.881
Adult	RF–GBM	0.943
	RF–XGB	0.886
	GBM–XGB	0.943
Titanic	RF–GBM	0.964
	RF–XGB	0.929
	GBM–XGB	0.964

5 Discussion

Even when model performance is similar (e.g., all three classifiers on Titanic around 78–80% accuracy), the ordering or composition of the top SHAP features can differ. This supports the

Table 3: Top-5 feature overlap (Jaccard index) between model pairs.

Dataset	Model pair	Jaccard (top-5)
California	RF–GBM	1.000
	RF–XGB	0.667
	GBM–XGB	0.667
Adult	RF–GBM	0.667
	RF–XGB	0.667
	GBM–XGB	1.000
Titanic	RF–GBM	1.000
	RF–XGB	1.000
	GBM–XGB	1.000

Table 4: Top-5 features by mean |`SHAP`| per model (California Housing).

Model	Top-5 features (most to least important)
RF	MedInc, Latitude, Longitude, AveOccup, HouseAge
GBM	MedInc, Latitude, Longitude, AveOccup, HouseAge
XGB	Latitude, Longitude, MedInc, AveOccup, AveRooms

Table 5: Instance-level (local) stability: per-instance agreement across the three models (single run, 200 instances). Mean ρ = mean over instances of mean pairwise Spearman; Prop. stable = fraction of instances with mean pairwise $\rho \geq 0.9$; Mean min Jaccard = mean over instances of minimum pairwise top-5 Jaccard; Prop. top-5 identical = fraction of instances where all three models have the same top-5 set.

Dataset	Mean ρ (std)	Prop. stable	Mean min Jaccard	Prop. top-5 identical
California	0.79 (0.11)	18%	0.67	16%
Adult	0.71 (0.21)	12%	0.73	18%
Titanic	0.69 (0.18)	2%	0.64	12%



Figure 1: Mean |SHAP| per feature for California Housing (RF, GBM, XGB).

view that a single model's explanation should not be treated as the only valid answer. Reporting which model was explained or checking agreement across several models (e.g., via Spearman or top-k overlap) can make conclusions more reliable.

6 Conclusions

We quantified SHAP-based global feature importance stability across Random Forest, Gradient Boosting, and XGBoost on three tabular datasets (California Housing, Adult, Titanic). We also evaluated *instance-level* stability: whether local attributions agree across models for the same instance (per-instance Spearman and top-k agreement, and proportion of "stable" instances). Pairwise Spearman rank correlations of global feature importance were high (roughly 0.88–0.98) but not perfect; local stability was generally lower, with many instances not Spearman-stable or top-5-stable.

We conclude that a single model's SHAP explanation should not be treated as the only valid answer: which features matter can depend on the model even when predictive performance is similar. Practitioners should report which model was explained or check agreement across models (e.g., via Spearman or top-k overlap) before drawing strong conclusions from SHAP.

Future work could include multiple random seeds for confidence intervals and extension to non-tree models.

Data Availability

Code and instructions to reproduce results are available in the project repository. Datasets are public (California Housing, OpenML adult and titanic).

References

[1] Lundberg, S.M.; Lee, S.-I. A Unified Approach to Interpreting Model Predictions. In Advances in Neural Information Processing Systems 30; NeurIPS: Long Beach, CA, USA, 2017.

[2] Lundberg, S.M. et al. Consistent feature attribution for tree ensembles. arXiv:1706.06060, 2017.