



HttpClient and Observables

.NET

Angular provides a client HTTP API for Angular applications. The HttpClient service class in @angular/common/http provides HTTP communication functionality for Angular Programs.

[HTTPS://ANGULAR.IO/TUTORIAL/TOH-PT4#WHY-SERVICES](https://angular.io/tutorial/toh-pt4#why-services)


HttpClient - Overview

<https://angular.io/guide/http>
<https://angular.io/start/start-data>

Most front-end applications need to communicate with a server over the HTTP protocol, in order to download or upload data and access other back-end services. Angular provides a client HTTP API for Angular applications, the **HttpClient** service class in `@angular/common/http`.

The HTTP client service offers the following major features.

- The ability to request typed response objects.
- Streamlined error handling.
- Testability features.
- Request and response interception.



HttpClient – Set-up

<https://angular.io/guide/http#communicating-with-backend-services-using-http>

1. Import the Angular *HttpClientModule* to **app.module.ts**.
 1. `import { HttpClientModule } from '@angular/common/http';`
2. Add **HttpClientModule** to the imports array of **app.module.ts**.
3. Inject the **HttpClient** service as a dependency of a service class.
 1. `import { HttpClient } from '@angular/common/http';`
 2. `constructor(private http: HttpClient) { }`
4. Import the following into the service class.
 1. `import { Observable, throwError } from 'rxjs';`
 2. `import { catchError, retry } from 'rxjs/operators';`

HttpClient.get<>

<https://angular.io/guide/http#requesting-data-from-a-server>

`HttpClient.get()<>` is asynchronous, sends an HTTP GET request, and returns an **Observable** that emits the requested data when the response is received. The return type varies based on the **observe** and **responseType** values passed to the call.

The `HttpClient.get()<>` takes two arguments; the endpoint URL from which to fetch and an options object that you can use to configure the request.

```
options: {  
  headers?: HttpHeaders | {[header: string]: string | string[]},  
  observe?: 'body' | 'events' | 'response',  
  params?: HttpParams|{[param: string]: string | number | boolean |  
    ReadonlyArray<string | number | boolean>},  
  reportProgress?: boolean,  
  responseType?: 'arraybuffer' | 'blob' | 'json' | 'text',  
  withCredentials?: boolean,  
}
```

```
configUrl = 'assets/config.json';  
  
getConfig() {  
  return this.http.get<Config>(this.configUrl);  
}
```

HttpClient.post<>

<https://angular.io/guide/http#making-a-post-request>

The `HttpClient.post()<>` method is similar to `get()<>` in that it has a type parameter, which you can use to specify that you expect the server to return data of a given type. The method takes 3 parameters.

- a resource URL
- body - The data to POST in the body of the request.
- options - An object containing method options which, in this case, specify required headers.

```
this.heroesService
  .addHero(newHero)
  .subscribe(hero => this.heroes.push(hero));
```

```
/** POST: add a new hero to the database */
addHero(hero: Hero): Observable<Hero> {
  return this.http.post<Hero>(this.heroesUrl, hero, httpOptions)
    .pipe(
      catchError(this.handleError('addHero', hero))
    );
}
```

HttpClient Headers

<https://angular.io/guide/http#adding-headers>

Many servers require extra headers for save operations. For example, a server might require an authorization token or "Content-Type" header to explicitly declare the MIME type of the request body.

```
import { HttpHeaders } from '@angular/common/http';

const httpOptions = {
  headers: new HttpHeaders({
    'Content-Type': 'application/json',
    Authorization: 'my-auth-token'
  })
};
```

Instances of the *HttpHeaders* class are immutable. Use the **.set()** method to change existing headers.

```
httpOptions.headers =
  httpOptions.headers.set('Authorization', 'my-new-auth-token');
```

Observables

<https://angular.io/guide/observables>
