

```
1: // $Id: countwords.cpp,v 1.1 2020-06-27 19:59:24-07 - - $
2:
3: #include <cerrno>
4: #include <cstring>
5: #include <fstream>
6: #include <iostream>
7: #include <map>
8: #include <regex>
9: #include <string>
10: #include <vector>
11: using namespace std;
12:
13: using wordcount_type = map<string,size_t>;
14:
15: void scan (wordcount_type& words, istream& infile) {
16:     static const regex word_rx {"[[:alpha:]]+"};
17:     for (;;) {
18:         string line;
19:         getline (infile, line);
20:         if (infile.eof()) break;
21:         for (auto& chr: line) chr = tolower (chr);
22:         auto itor = sregex_iterator (line.begin(), line.end(), word_rx);
23:         for (; itor != sregex_iterator(); ++itor) {
24:             ++words[itor->str()];
25:         }
26:     }
27: }
28:
29: int main (int argc, char** argv) {
30:     wordcount_type words;
31:     string exec_name {basename (argv[0])};
32:     int exit_status = EXIT_SUCCESS;
33:     vector<string> filenames (&argv[1], &argv[argc]);
34:     if (filenames.size() == 0) filenames.push_back ("-");
35:     for (const auto& filename: filenames) {
36:         if (filename == "-") scan (words, cin);
37:         else {
38:             ifstream infile (filename);
39:             if (infile) scan (words, infile);
40:             else {
41:                 exit_status = EXIT_FAILURE;
42:                 cerr << exec_name << ": " << filename << ": "
43:                     << strerror (errno) << endl;
44:             }
45:         }
46:     }
47:     for (const auto& word: words) {
48:         cout << word.first << " " << word.second << endl;
49:     }
50:     return exit_status;
51: }
```

```
1: # $Id: Makefile,v 1.1 2020-06-27 19:59:24-07 - - $
2:
3:
4: GARN      = -Wall -Wextra -Wpedantic -Wshadow -Wold-style-cast
5: GOPTS     = ${GWARN} -fdiagnostics-color=never
6: GPP       = g++ -std=gnu++2a -g -O0 ${GOPTS}
7: GRIND     = valgrind --leak-check=full --show-reachable=yes
8: NODEPS    = ${filter ci clean spotless tar, ${MAKECMDGOALS}}
9: MKTAR     = gtar --create --verbose --gzip
10:
11: H_FILES   =
12: C_FILES   = countwords.cpp
13: OBJECTS   = ${C_FILES:.cpp=.o}
14: EXECBIN   = countwords
15: SOURCES   = ${H_FILES} ${C_FILES} Makefile
16:
17:
18: all : ${EXECBIN}
19:
20: ${EXECBIN} : ${OBJECTS}
21:             ${GPP} -o $@ $^
22:
23: %.o : %.cpp
24:         - checksource $<
25:         ${GPP} -c $<
26:
27: ci : ${SOURCES}
28:     - checksource $^
29:     cid -is $^
30:
31: clean :
32:     - rm --force ${OBJECTS} test.log test.out test.err
33:
34: lis : ${SOURCES} Makefile.deps
35:     mkpspdf Listing.ps $^
36:
37: spotless : clean
38:     - rm --force ${EXECBIN} Listing.{ps,pdf} Makefile.deps
39:
40: tar : ${SOURCES}
41:     ${MAKE} --no-print-directory spotless
42:     ( DIRNAME=$(basename $(pwd)) \
43:     ; cd .. \
44:     ; ${MKTAR} --exclude=RCS --file=countwords.tar.gz $$DIRNAME \
45:     )
46:
47: test : ${EXECBIN}
48:     ${GRIND} --log-file=test.log \
49:     ${EXECBIN} ${SOURCES} 1>test.out 2>test.err
50:
51: Makefile.deps :
52:     ${GPP} -MM ${C_FILES} >Makefile.deps
53:
54: ifeq (${NODEPS}, )
55: include Makefile.deps
56: endif
57:
```

```
1: countwords.o: countwords.cpp
```