

COMP.SGN.120 Introduction to Audio Processing

Exercise 5

Week 49

In this exercise, you will implement one of the commonly used features in audio signal processing - **MFCC**. There are two questions with 1 point for each summing up to 2 points. Bonus question is optional. The submission should consist of a **report** of your observations and the python **code**. Alternatively, both can be combined in a Jupyter notebook as well.

Question 1 : Mel filterbank (1 point)

(a) Load the given audio file (audio.wav) to get the audio signal and its sampling rate. Hint: `librosa.load('audio.wav')`

(b) Create a mel filterbank with the following settings:

- Sampling rate obtained from (a)
- $N_{\text{fft}} = 512$
- $N_{\text{mel}} = 40$

Hint: `librosa.filters.mel(sr, n_fft, n_mel)`

(c) Plot the mel filterbank and report your observations. Hint: `librosa.display.specshow`

Question 2 : MFCC (1 point)

(a) Pre-emphasis the audio signal (audio.wav) with the given Equation $y(t) = x(t) - \alpha x(t-1)$, $\alpha = 0.97$.

Hint: `np.append(x[0], x[1:] - α * x[:-1])`

(b) In the stft loop you implemented earlier, for each frame, do the following:

- Window each frame (using hamming window) Hint: `signal.hamming`
- Calculate the fft
- Collect the power spectrum (you will get power spectrum)
- Multiply it with mel filterbank you created in Question 1 (you will get mel spectrum)
- Take log operation (you will get logarithmic mel spectrum) Hint: `20 * np.log10`
- DCT (Finally, you will get MFCC) Hint: `from scipy.fftpack import dct`

(c) Plot logarithmic power spectrums, mel spectrums, logarithmic mel spectrums, MFCC.

(d) Implement MFCC using librosa and compare with yours. Report your observations.

Bonus Question : Implement your own mel filterbank with the same setting as Question 1

In Question 1, you used librosa library to get mel filterbank. Now try to implement by yourself!

Hint:

- convert hz to mel using Equation $F_{mel} = 2595 \log_{10}(1 + f/700)$
- uniformly distributed on the mel scale
- convert mel to hz back using the inverse of Equation above
- Mel filter of band m:
 1. starts at 0 amplitude at $F_{mel,c}(m-1)$
 2. has maximum amplitude 1 at $F_{mel,c}(m)$
 3. decays to zero at $F_{mel,c}(m+1)$

You can follow the equation below.

$$H_m(k) = \begin{cases} 0 & k < f(m-1) \\ \frac{k - f(m-1)}{f(m) - f(m-1)} & f(m-1) \leq k < f(m) \\ 1 & k = f(m) \\ \frac{f(m+1) - k}{f(m+1) - f(m)} & f(m) < k \leq f(m+1) \\ 0 & k > f(m+1) \end{cases}$$

- to have a flat spectrum in mel domain for a DFT magnitude spectrum, the mel bands need to be scaled

Plot it and compare with librosa implementation. Report your observations.

Useful material to read:

1. <https://haythamfayek.com/2016/04/21/speech-processing-for-machine-learning.html>
2. <http://practicalcryptography.com/miscellaneous/machine-learning/guide-mel-frequency-cepstral-coefficients-mfccs/>