



Normalization

.NET

Database normalization is the process of structuring a relational database in order to reduce data redundancy and improve data integrity.

[HTTPS://EN.WIKIPEDIA.ORG/WIKI/DATABASE_NORMALIZATION](https://en.wikipedia.org/wiki/Database_normalization)

Normalization Assignment (Pt. 1)

- Create an unnormalized table.
- List the information of at least 5 family members.
- There must be at least 5 attributes to each tuple (row) and at least 5 entities.

Databases – Normalization

https://www.tutorialspoint.com/dbms/database_normalization.htm

<https://www.c-sharpcorner.com/UploadFile/0146e3/database-normalization/>

Normalization is a method to prevent **anomalies** and keep a database in a consistent state. **Fields** and **tables** of a relational DB are organized to minimize redundancy and dependency.

Normalization involves dividing large **tables** into smaller (and less redundant) **tables** and defining relationships among their **atomic** data.

There are many **Normal Forms** but **1NF**, **2NF**, and **3NF** are primarily used.



Databases – Normalization

https://www.tutorialspoint.com/dbms/database_normalization.htm

<https://www.c-sharpcorner.com/UploadFile/0146e3/database-normalization/>

This table is not normalized. All the information is stored in one table.

Title	Name	City	Movies Watched
Mr.	Moore	Crowley	Avengers Endgame, Thor
Miss.	Garza	Monterrey	Ant-Man, Captain Marvel
Mr.	Moore	Dallas	Spider-Man: Homecoming, Doctor Strange, Iron Man 2

Databases – Normalization

https://www.tutorialspoint.com/dbms/database_normalization.htm

<https://www.c-sharpcorner.com/UploadFile/0146e3/database-normalization/>

1st Normal Form (1NF)

- Have a single **Primary Key**.
- Each table cell should contain a single value.
- Each entity needs to be unique.
- The table contains atomic values only.

ID(PK)	Title	Name	City	Movies Watched
1	Mr.	Moore	Crowley	Avengers Endgame
2	Mr.	Moore	Crowley	Thor
3	Miss.	Garza	Monterrey	Ant-Man
4	Miss.	Garza	Monterrey	Captain Marvel
5	Mr.	Moore	Dallas	Spider-Man: Homecoming
6	Mr.	Moore	Dallas	Doctor Strange
7	Mr.	Moore	Dallas	Iron Man 2

Databases – Normalization

https://www.tutorialspoint.com/dbms/database_normalization.htm

<https://www.c-sharpcorner.com/UploadFile/0146e3/database-normalization/>

2nd Normal Form (2NF) –

- First, be in **1NF**.
- Remove subsets of data that apply to multiple rows of a **table** and place them in separate **tables** with **PK** → **FK** relationships among the new tables.
- If the table is in **1NF** and every non-key attribute is dependent on the **Primary Key**, then **2NF** is achieved.

Id(PK)	Title	Name	City	1
1	Mr.	Moore	Crowley	
2	Miss.	Garza	Monterrey	
3	Mr.	Moore	Dallas	

Actions Taken:

- The **1NF** table is divided into two tables.
- Table 1 contains only person information. **Id** is created as the **Primary Key (PK)** for Table 1.
- Table 2 contains the information for each movie. Table 2's new **PK** column is **MovieId**.

MovieId(PK)	Id(FK)	Movie	2
22	1	Avengers Endgame	
4	1	Thor	
12	2	Ant-Man	
21	2	Captain Marvel	
16	3	Spider-Man: Homecoming	
14	3	Doctor Strange	

Databases – Normalization

https://www.tutorialspoint.com/dbms/database_normalization.htm

<https://www.c-sharpcorner.com/UploadFile/0146e3/database-normalization/>

To get to 3rd Normal Form (3NF) -

- There must be no dependencies between fields in a single row.
 - "Given a value for column B, is there only one possible value for column C?"
- If yes, B and C should be put into a new table, with one of them becoming the **Primary Key (PK)**.
- A reference to the new table should be left in the original table and marked as a **Foreign Key**.

Id(PK)	Title	Name	City
1	Mr.	Moore	Crowley
2	Miss.	Garza	Monterrey
3	Mr.	Moore	Dallas

A **Transitive Functional Dependency** occurs when the change of one **Candidate Key** column might cause any other **Candidate Key** column to change. In table 1, changing the non-key column 'Name' may change 'Title'.

Movied(PK)	Id(FK)	Movie
22	1	Avengers Endgame
4	1	Thor
12	2	Ant-Man
21	2	Captain Marvel
16	3	Spider-Man: Homecoming
14	3	Doctor Strange
3	3	Iron Man 2

Databases – Normalization

https://www.tutorialspoint.com/dbms/database_normalization.htm

<https://www.c-sharpcorner.com/UploadFile/0146e3/database-normalization/>

Salutations	
TitleId (PK)	Title
1	Mr.
2	Miss.
3	Mrs.
4	Dr.

Cities	
CityId (PK)	City
76036	Crowley
75201	Dallas
32070	Monterrey
76701	Waco

Movies	
MovieId (PK)	Movie
22	Avengers Endgame
4	Thor
12	Ant-Man
21	Captain Marvel
16	Spider-Man: Homecoming
14	Doctor Strange
3	Iron Man 2

People/Movies Junction Table	
MovieId (FK)	Id (FK)
22	1
4	1
12	2
21	2
16	3
14	3
3	3

People			
Id (PK)	TitleId (FK)	Name	CityId (FK)
1	1	Moore	76036
2	2	Garza	75201
3	1	Moore	32070

Actions Taken:

Table 1 is divided. Two new tables are created to store Title and City. Table 2 is divided to isolate Movie data and a Junction table is created to show the Many-To-Many relationship between movie and person. The database is now in **3NF**.

Assignment (Pt. 2)

- Convert your Pt. 1 table to a 3NF table.