



1. Description

1.1. Project

Project Name	sentinel
Board Name	custom
Generated with:	STM32CubeMX 6.9.1
Date	10/02/2023


1.2. MCU

MCU Series	STM32H7
MCU Line	STM32H750 Value line
MCU name	STM32H750VBTx
MCU Package	LQFP100
MCU Pin number	100

1.3. Core(s) information

Core(s)	ARM Cortex-M7
---------	---------------


2. Pinout Configuration



3. Pins Configuration

Pin Number LQFP100	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
6	VBAT	Power		
10	VSS	Power		
11	VDD	Power		
12	PH0-OSC_IN (PH0)	I/O	RCC_OSC_IN	
13	PH1-OSC_OUT (PH1)	I/O	RCC_OSC_OUT	
14	NRST	Reset		
19	VSSA	Power		
21	VDDA	Power		
26	VSS	Power		
27	VDD	Power		
48	VCAP	Power		
49	VSS	Power		
50	VDD	Power		
72	PA13 (JTMS/SWDIO)	I/O	DEBUG_JTMS-SWDIO	
73	VCAP	Power		
74	VSS	Power		
75	VDD	Power		
76	PA14 (JTCK/SWCLK)	I/O	DEBUG_JTCK-SWCLK	
94	BOOT0	Boot		
99	VSS	Power		
100	VDD	Power		

4. Clock Tree Configuration



5. Software Project

5.1. Project Settings

Name	Value
Project Name	sentinel
Project Folder	X:\Projects\Engineering\ProjectScience\hardware\stm32\sentinel
Toolchain / IDE	STM32CubeIDE
Firmware Package Name and Version	STM32Cube FW_H7 V1.11.1
Application Structure	Advanced
Generate Under Root	Yes
Do not generate the main()	No
Minimum Heap Size	0x200
Minimum Stack Size	0x400

5.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power consumption)	No
Enable Full Assert	No

5.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name
1	SystemClock_Config	RCC
2	MX_GPIO_Init	GPIO

1. Power Consumption Calculator report

1.1. Microcontroller Selection

Series	STM32H7
Line	STM32H750 Value line
MCU	STM32H750VBTx
Datasheet	DS12556_Rev6

1.2. Parameter Selection

Temperature	25
Vdd	3.0

1.3. Battery Selection

Battery	Alkaline(9V)
Capacity	625.0 mAh
Self Discharge	0.3 %/month
Nominal Voltage	9.0 V
Max Cont Current	200.0 mA
Max Pulse Current	0.0 mA
Cells in series	1
Cells in parallel	1


1.4. Sequence

Step	Step1	Step2
Mode	RUN	STOP
Vdd	3.0	3.0
Voltage Source	Battery	Battery
Range	VOS0: Scale0-High	SVOS5: System-Scale5
D1 Mode	DRUN/CRUN	DSTANDBY
D2 Mode	DRUN	DSTANDBY
D3 Mode	DRUN	DSTOP
Fetch Type	ITCM	NA
CPU Frequency	480 MHz	0 Hz
Clock Configuration	HSE BYP PLL	Flash-OFF
Clock Source Frequency	24 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	148 mA	150 μ A
Duration	0.1 ms	0.9 ms
DMIPS	1027.0	0.0
Ta Max	105.02	124.98
Category	In DS Table	In DS Table

1.5. Results

Sequence Time	1 ms	Average Current	14.94 mA
Battery Life	1 day, 17 hours	Average DMIPS	1027.2001 DMIPS

1.6. Chart



2. Peripherals and Middlewares Configuration

2.1. DEBUG

Debug: Serial Wire

2.2. RCC

High Speed Clock (HSE): Crystal/Ceramic Resonator

2.2.1. Parameter Settings:

Power Parameters:

SupplySource	PWR_LDO_SUPPLY
--------------	----------------

RCC Parameters:

TIM Prescaler Selection	Disabled
HSE Startup Timeout Value (ms)	100
LSE Startup Timeout Value (ms)	5000
CSI Calibration Value	16
HSI Calibration Value	32

System Parameters:

VDD voltage (V)	3.3
Flash Latency(WS)	0 WS (1 CPU cycle)
Product revision	rev.Y

PLL range Parameters:

PLL1 clock Input range	Between 4 and 8 MHz
PLL1 clock Output range	Wide VCO range

* User modified value

3. System Configuration

3.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
DEBUG	PA13 (JTMS/SWDIO)	DEBUG_JTMS-SWDIO	n/a	n/a	n/a	
	PA14 (JTCK/SWCLK)	DEBUG_JTCK-SWCLK	n/a	n/a	n/a	
RCC	PH0-OSC_IN (PH0)	RCC_OSC_IN	n/a	n/a	n/a	
	PH1-OSC_OUT (PH1)	RCC_OSC_OUT	n/a	n/a	n/a	

3.2. DMA configuration

nothing configured in DMA service

3.3. BDMA configuration

nothing configured in DMA service

3.4. MDMA configuration

nothing configured in DMA service

3.5. NVIC configuration

3.5.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
Memory management fault	true	0	0
Pre-fetch fault, memory access fault	true	0	0
Undefined instruction or illegal state	true	0	0
System service call via SWI instruction	true	0	0
Debug monitor	true	0	0
Pendable request for system service	true	0	0
System tick timer	true	15	0
PVD and AVD interrupts through EXTI line 16	unused		
Flash global interrupt	unused		
RCC global interrupt	unused		
FPU global interrupt	unused		
HSEM1 global interrupt	unused		

3.5.2. NVIC Code generation

Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Pre-fetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	true	false
Debug monitor	false	true	false
Pendable request for system service	false	true	false
System tick timer	false	true	true

* User modified value

4. System Views

4.1. Category view

4.1.1. Current

4.1.2. Without filters

4.2. Power Domain view

5. Docs & Resources

Type	Link
------	------